

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

Telephone: +86-755-26648640 Fax: +86-755-26648637

Website: <u>www.cqa-cert.com</u>

RF Exposure Evaluation Report

Report No.: CQASZ20180500094E-02

Applicant: Weccan Industrial Limited

Address of Applicant: Room209, 2/F, Building W1-A, No.34 Gaoxin South 4th Street, Hi-tech Industrial

Park, Nanshan District, Shenzhen, China

Manufacturer: Weccan Industrial Limited

Address of Room209, 2/F, Building W1-A, No.34 Gaoxin South 4th Street, Hi-tech Industrial

Manufacturer: Park, Nanshan District, Shenzhen, China

Factory: DongGuan Adoree Industrial Limited

Address of Factory: Building 10, Fuxing Industrial Area, Fucing Road, Xiagang Village, Changan

Town, Dongguang City, Guangdong Province China.

Equipment Under Test (EUT):

Product: 2.4G RC DRONE WITH WIFI CAMERA

Model No.: DRW528

Added Model No.: Please see page 2

Brand Name: N/A

 FCC ID:
 Z3CDRW528F23

 Standards:
 47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2018-05-20 to 2018-05-31

Date of Issue: 2018-05-31

Test Result : PASS*

Tested By:

(Aaron Ma)

Reviewed By: Wen Zhou

Owen Zhou)

Approved By:

(Jack Ai)



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: CQASZ20180500094E-02

2 Version

Revision History Of Report

| Report No. | Version | Description | Issue Date |
|----------------------|---------|----------------|------------|
| CQASZ20180500094E-02 | Rev.01 | Initial report | 2018-05-31 |

All model: DRW528, SG-F23, SG-F1, SG-F2, SG-F3, SG-F4, SG-F5, SG-F6, SG-F7, SG-F8, SG-F9, SG-F10, SG-F11, SG-F12, SG-F13, SG-F14, SG-F15, SG-F16, SG-F17, SG-F18, SG-F19, SG-F20, SG-F21, SG-F22, SG-F33, SG-F24, SG-F25, SG-F26, SG-F27, SG-F28, SG-F29, SG-F30, SG-F31, SG-F32, SG-F34, SG-F35, SG-F36, SG-F37, SG-F38, SG-F39, SG-F40, SG-F41, SG-F42, SG-F43, SG-F44, SG-F45, SG-F46, SG-F47, SG-F48, SG-F49, SG-F50, SG-F51, SG-F52, SG-F53, SG-F54, SG-F55, SG-F56, SG-F57, SG-F58, SG-F59, SG-F60, SG-F61, SG-F62, SG-F63, SG-F64, SG-F65, SG-F66, SG-F67, SG-F68, SG-F69, SG-F70, SG-F71, SG-F72, SG-F73, SG-F74, SG-F75, SG-F76, SG-F77, SG-F78, SG-F79, SG-F80, SG-F81, SG-F82, SG-F83, SG-F84, SG-F85, SG-F86, SG-F87, SG-F88, SG-F89, SG-F90, SG-F91, SG-F92, SG-F93, SG-F94, SG-F95, SG-F96, SG-F97, SG-F98, SG-F99, SG-F

Only the model DRW528 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.





Report No.: CQASZ20180500094E-02

3 Contents

| | | Page |
|---|--|------|
| 1 | COVER PAGE | 1 |
| 2 | VERSION | 2 |
| 2 | CONTENTS | 3 |
| _ | | |
| 4 | GENERAL INFORMATION | 4 |
| | 4.1 CLIENT INFORMATION | 4 |
| | 4.2 GENERAL DESCRIPTION OF EUT | 4 |
| | SAR EVALUATION | |
| | 5.1 RF Exposure Compliance Requirement | 5 |
| | 5.1.1 Standard Requirement | 5 |
| | 5.1.1 Standard Requirement | 5 |
| | 5.1.3 FUT RE Exposure | |



Report No.: CQASZ20180500094E-02

4 General Information

4.1 Client Information

| Applicant: | Weccan Industrial Limited | |
|--------------------------|--|--|
| Address of Applicant: | Rm209,2/F,Building W1-A, No.34 Gaoxin South 4th Street, Hi-Tech Industrial Park, Nanshan District, Shenzhen City,China | |
| Manufacturer: | Weccan Industrial Limited | |
| Address of Manufacturer: | Rm209,2/F,Building W1-A, No.34 Gaoxin South 4th Street, Hi-Tech Industrial Park, Nanshan District, Shenzhen City,China | |
| Factory: | Dongguan Adoree Industrial Limited | |
| Address of Factory: | Idress of Factory: Building 10, Fuxing Industrial Area, Fuxing Road, Xiagang Village, Changan Town, Dongguang City, Guangdong Province, China | |

4.2 General Description of EUT

| Product Name: | 2.4G RC DRONE WITH WIFI CAMERA |
|-----------------------|--------------------------------|
| Model No.: | DRW528 |
| Adding Model No.: | Please see page 3 |
| Trade Mark : | N/A |
| Hardware Version: | V1.0 |
| Software Version: | V1.0 |
| Frequency Range: | 2447 MHz ~ 2477MHz |
| Modulation Type: | GFSK |
| Number of Channels: | 16 (declared by the client) |
| Sample Type: | Portable production |
| Test Software of EUT: | RF test (manufacturer declare) |
| Antenna Type: | Integral antenna |
| Antenna Gain: | 1.3dBi |
| Power Supply: | 4 x AAA battery, DC6V |

Report No.: CQASZ20180500094E-02

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

eirp = pt x gt = $(E \times d)^2/30$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

 $E = electric field strength in V/m, ---10^{((dB\mu V/m)/20)}/10^6$,

d = measurement distance in meters (m)---3m,

So pt = $(E \times d)^2/30 / gt$

The worst case (refer to report CQASZ20180500094E-01) is below:

For 2.4G wireless:

Field strength = 88.98dBµV/m @3m

Ant. gain 1.3dBi; so Ant numeric gain=1.35

So pt= $\{[10^{(88.98/20)}/10^6 x3]^2/30/1.35\}x1000mW = 0.176mW$

So $(0.176 \text{mW/5mm})x \sqrt{2.477 \text{GHz}} = 0.055$,

0.055<3.0 for 1-g SAR

So the SAR report is not required.