

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is an Drone Xtreme Thunderbolt Jet X2 operating at 2.4G Band. The EUT can be powered by DC 3.7V (1 x 3.7V rechargeable battery). And the RF function will be shut down and it can't transmit RF signals while charging. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -1.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -1.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 96.7dB μ V/m at 3m in the frequency 2424MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = 1.47dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 93.9dB μ V/m at 3m in the frequency 2453MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -1.33dBm

which is within the production variation.

The maximum conducted output power specified is 2.0dBm= 1.585mW

The source- based time-averaging conducted output power =1.585mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.453) mW

= 9.58 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.