


Report No.: T210429C13-RP4


Test Mode	IEEE 802.11n 20 MHz / 5500MHz	Temp/Hum	22.6(°C)/ 50%RH
Test Item	Band Edge	Test Date	June 11, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
5460.00	Peak	46.14	8.08	54.22	74.00	-19.78
5460.00	Average	36.48	8.08	44.56	54.00	-9.44
5470.00	Peak	55.37	8.12	63.49	68.20	-4.71

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11n 20 MHz / 5500MHz	Temp/Hum	22.6(°C) / 50%RH
Test Item	Band Edge	Test Date	June 11, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak / Average		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5460.00	Peak	48.07	8.08	56.15	74.00	-17.85
5460.00	Average	36.65	8.08	44.73	54.00	-9.27
5470.00	Peak	55.53	8.12	63.65	68.20	-4.55

Report No.: T210429C13-RP4

Page: 130 / 231

Rev.: 01

Test Mode	IEEE 802.11n 20 MHz / 5700 MHz	Temperature	22.6(°C)/ 50%RH
Test Item	Band Edge	Test Date	June 11, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5725.00	Peak	51.53	9.29	60.82	68.20	-7.38

Report No.: T210429C13-RP4

Page: 131 / 231

Rev.: 01


Test Mode	IEEE 802.11n 20 MHz / 5700 MHz	Temperature	22.6(°C)/ 50%RH
Test Item	Band Edge	Test Date	June 11, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5725.00	Peak	51.85	9.29	61.14	68.20	-7.06

Report No.: T210429C13-RP4


Test Mode	IEEE 802.11n 40 MHz / 5510 MHz	Temp/Hum	22.6(°C) / 50%RH
Test Item	Band Edge	Test Date	June 12, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
5460.00	Peak	49.24	8.08	57.32	74.00	-16.68
5460.00	Average	38.02	8.08	46.10	54.00	-7.90
5470.00	Peak	57.73	8.12	65.85	68.20	-2.35

Report No.: T210429C13-RP4


Test Mode	IEEE 802.11n 40 MHz / 5510 MHz	Temp/Hum	22.6(°C) / 50%RH
Test Item	Band Edge	Test Date	June 12, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak / Average		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5460.00	Peak	49.02	8.08	57.10	74.00	-16.90
5460.00	Average	38.68	8.08	46.76	54.00	-7.24
5470.00	Peak	57.24	8.12	65.36	68.20	-2.84

Report No.: T210429C13-RP4


Test Mode	IEEE 802.11n 40 MHz / 5670 MHz	Temp/Hum	22.6(°C)/ 50%RH
Test Item	Band Edge	Test Date	June 12, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
5725.00	Peak	51.42	9.29	60.71	68.20	-7.49

Report No.: T210429C13-RP4


Test Mode	IEEE 802.11n 40 MHz / 5670 MHz	Temp/Hum	22.6(°C) / 50%RH
Test Item	Band Edge	Test Date	June 12, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5725.00	Peak	48.31	9.29	57.60	68.20	-10.60

Report No.: T210429C13-RP4


Test Mode	IEEE 802.11ac VHT80 / 5530 MHz	Temp/Hum	22.6(°C) / 50%RH
Test Item	Band Edge	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5460.00	Peak	54.06	8.08	62.14	74.00	-11.86
5460.00	Average	45.79	8.08	53.87	54.00	-0.13
5468.70	Peak	59.83	8.12	67.95	68.20	-0.25
5470.00	Peak	53.45	8.12	61.57	68.20	-6.63

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11ac VHT80 / 5530 MHz	Temp/Hum	22.6(°C) / 50%RH
Test Item	Band Edge	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak / Average		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5460.00	Peak	51.64	8.08	59.72	74.00	-14.28
5460.00	Average	45.89	8.08	53.97	54.00	-0.03
5468.60	Peak	60.00	8.12	68.12	68.20	-0.08
5470.00	Peak	54.91	8.12	63.03	68.20	-5.17

Report No.: T210429C13-RP4

Test Data for UNII-3


Test Mode	IEEE 802.11a / 5745 MHz	Temp/Hum	22.6(°C) / 50%RH
Test Item	Band Edge	Test Date	June 11, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
5650.00	Peak	40.19	8.87	49.06	68.20	-19.14
5700.00	Peak	43.40	9.22	52.62	105.20	-52.58
5720.00	Peak	63.62	9.29	72.91	110.80	-37.89
5725.00	Peak	69.29	9.29	78.58	122.20	-43.62

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11a / 5745 MHz	Temp/Hum	22.6(°C) / 50%RH
Test Item	Band Edge	Test Date	June 11, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
5650.00	Peak	39.45	8.87	48.32	68.20	-19.88
5700.00	Peak	41.04	9.22	50.26	105.20	-54.94
5720.00	Peak	57.38	9.29	66.67	110.80	-44.13
5725.00	Peak	64.93	9.29	74.22	122.20	-47.98

Report No.: T210429C13-RP4

Page: 140 / 231

Rev.: 01


Test Mode	IEEE 802.11a / 5825 MHz	Temp/Hum	22.6(°C)/ 50%RH
Test Item	Band Edge	Test Date	June 11, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5850.00	Peak	62.41	9.59	72.00	122.20	-50.20
5855.00	Peak	54.47	9.59	64.06	110.80	-46.74
5875.00	Peak	40.12	9.57	49.69	105.20	-55.51
5925.00	Peak	38.89	9.59	48.48	68.20	-19.72

Report No.: T210429C13-RP4


Test Mode	IEEE 802.11a / 5825 MHz	Temp/Hum	22.6(°C) / 50%RH
Test Item	Band Edge	Test Date	June 11, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
5850.00	Peak	60.41	9.59	70.00	122.20	-52.20
5855.00	Peak	54.05	9.59	63.64	110.80	-47.16
5875.00	Peak	39.91	9.57	49.48	105.20	-55.72
5925.00	Peak	39.44	9.59	49.03	68.20	-19.17

Report No.: T210429C13-RP4


Test Mode	IEEE 802.11n 20 MHz / 5745 MHz	Temp/Hum	22.6(°C)/ 50%RH
Test Item	Band Edge	Test Date	June 11, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5650.00	Peak	42.04	8.87	50.91	68.20	-17.29
5700.00	Peak	56.18	9.22	65.40	105.20	-39.80
5720.00	Peak	71.00	9.29	80.29	110.80	-30.51
5725.00	Peak	76.06	9.29	85.35	122.20	-36.85

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11n 20 MHz / 5745 MHz	Temp/Hum	22.6(°C) / 50%RH
Test Item	Band Edge	Test Date	June 11, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
5650.00	Peak	40.80	8.87	49.67	68.20	-18.53
5700.00	Peak	55.53	9.22	64.75	105.20	-40.45
5720.00	Peak	70.71	9.29	80.00	110.80	-30.80
5725.00	Peak	76.97	9.29	86.26	122.20	-35.94

Report No.: T210429C13-RP4

Page: 144 / 231

Rev.: 01

Test Mode	IEEE 802.11n 20 MHz / 5825 MHz	Temp/Hum	22.6(°C)/ 50%RH
Test Item	Band Edge	Test Date	June 11, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5850.00	Peak	73.02	9.59	82.61	122.20	-39.59
5855.00	Peak	68.63	9.59	78.22	110.80	-32.58
5875.00	Peak	55.63	9.57	65.20	105.20	-40.00
5925.00	Peak	40.29	9.59	49.88	68.20	-18.32

Report No.: T210429C13-RP4

Page: 145 / 231

Rev.: 01


Test Mode	IEEE 802.11n 20 MHz / 5825 MHz	Temp/Hum	22.6(°C) / 50%RH
Test Item	Band Edge	Test Date	June 11, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
5850.00	Peak	71.43	9.59	81.02	122.20	-41.18
5855.00	Peak	67.34	9.59	76.93	110.80	-33.87
5875.00	Peak	52.28	9.57	61.85	105.20	-43.35
5925.00	Peak	38.96	9.59	48.55	68.20	-19.65

Report No.: T210429C13-RP4


Test Mode	IEEE 802.11n 40 MHz/ 5755 MHz	Temp/Hum	22.6(°C)/ 50%RH
Test Item	Band Edge	Test Date	June 12, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
5650.00	Peak	50.88	8.87	59.75	68.20	-8.45
5700.00	Peak	66.29	9.22	75.51	105.20	-29.69
5720.00	Peak	77.99	9.29	87.28	110.80	-23.52
5725.00	Peak	77.95	9.29	87.24	122.20	-34.96

Report No.: T210429C13-RP4


Test Mode	IEEE 802.11n 40 MHz/ 5755 MHz	Temp/Hum	22.6(°C)/ 50%RH
Test Item	Band Edge	Test Date	June 12, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5650.00	Peak	53.71	8.87	62.58	68.20	-5.62
5700.00	Peak	67.25	9.22	76.47	105.20	-28.73
5720.00	Peak	79.30	9.29	88.59	110.80	-22.21
5725.00	Peak	79.13	9.29	88.42	122.20	-33.78

Report No.: T210429C13-RP4


Test Mode	IEEE 802.11n 40 MHz/ 5795 MHz	Temp/Hum	22.6(°C)/ 50%RH
Test Item	Band Edge	Test Date	June 12, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5850.00	Peak	63.77	9.59	73.36	122.20	-48.84
5855.00	Peak	53.43	9.59	63.02	110.80	-47.78
5875.00	Peak	44.83	9.57	54.40	105.20	-50.80
5925.00	Peak	40.17	9.59	49.76	68.20	-18.44

Report No.: T210429C13-RP4


Test Mode	IEEE 802.11n 40 MHz/ 5795 MHz	Temp/Hum	22.6(°C)/ 50%RH
Test Item	Band Edge	Test Date	June 12, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
5850.00	Peak	57.14	9.59	66.73	122.20	-55.47
5855.00	Peak	53.11	9.59	62.70	110.80	-48.10
5875.00	Peak	42.89	9.57	52.46	105.20	-52.74
5925.00	Peak	39.05	9.59	48.64	68.20	-19.56

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11ac VHT80 / 5775 MHz	Temp/Hum	22.6(°C)/ 50%RH
Test Item	Band Edge	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5650.00	Peak	56.02	8.87	64.89	68.20	-3.31
5700.00	Peak	67.71	9.22	76.93	105.20	-28.27
5720.00	Peak	72.40	9.29	81.69	110.80	-29.11
5725.00	Peak	72.44	9.29	81.73	122.20	-40.47

Report No.: T210429C13-RP4

Page: 151 / 231

Rev.: 01

Test Mode	IEEE 802.11ac VHT80 / 5775 MHz	Temp/Hum	22.6(°C) / 50%RH
Test Item	Band Edge	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5650.00	Peak	56.94	8.87	65.81	68.20	-2.39
5700.00	Peak	66.99	9.22	76.21	105.20	-28.99
5720.00	Peak	70.77	9.29	80.06	110.80	-30.74
5725.00	Peak	70.77	9.29	80.06	122.20	-42.14

Report No.: T210429C13-RP4

Page: 152 / 231

Rev.: 01

Test Mode	IEEE 802.11ac VHT80 / 5775 MHz	Temp/Hum	22.6(°C) / 50%RH
Test Item	Band Edge	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5850.00	Peak	66.67	9.59	76.26	122.20	-45.94
5855.00	Peak	66.13	9.59	75.72	110.80	-35.08
5875.00	Peak	61.27	9.57	70.84	105.20	-34.36
5925.00	Peak	49.46	9.59	59.05	68.20	-9.15

Report No.: T210429C13-RP4

Page: 153 / 231

Rev.: 01


Test Mode	IEEE 802.11ac VHT80 / 5775 MHz	Temp/Hum	22.6(°C) / 50%RH
Test Item	Band Edge	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Frequency (MHz)	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
5850.00	Peak	67.16	9.59	76.75	122.20	-45.45
5855.00	Peak	65.83	9.59	75.42	110.80	-35.38
5875.00	Peak	61.11	9.57	70.68	105.20	-34.52
5925.00	Peak	52.22	9.59	61.81	68.20	-6.39

Below 1G Test Data


Test Mode	Mode 1	Temp/Hum	22.9(°C)/ 44%RH
Test Item	30MHz-1GHz	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
47.46	Peak	50.75	-14.32	36.43	40.00	-3.57
148.34	Peak	44.04	-10.33	33.71	43.50	-9.79
250.19	Peak	41.81	-10.82	30.99	46.00	-15.01
542.16	Peak	28.86	-2.40	26.46	46.00	-19.54
849.65	Peak	25.92	2.52	28.44	46.00	-17.56
954.41	Peak	25.35	3.97	29.32	46.00	-16.68

Note: 1. No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)
 2. For below 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	Mode 1	Temp/Hum	22.9(°C)/ 44%RH
Test Item	30MHz-1GHz	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
71.71	Peak	46.67	-14.88	31.79	40.00	-8.21
144.46	Peak	49.54	-10.18	39.36	43.50	-4.14
219.15	Peak	42.76	-11.76	31.00	46.00	-15.00
541.19	Peak	28.68	-2.40	26.28	46.00	-19.72
576.11	Peak	30.72	-2.03	28.69	46.00	-17.31
993.21	Peak	25.12	4.50	29.62	54.00	-24.38

Note: 1. No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)
 2. For below 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Above 1G**Test Data for UNII-1**

Test Mode	IEEE 802.11a / 5180MHZ	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10360.00	Peak	30.95	18.16	49.11	68.20	-19.09
15540.00	Peak	32.22	22.44	54.66	74.00	-19.34
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11a / 5180MHZ	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10360.00	Peak	30.81	18.16	48.97	68.20	-19.23
15540.00	Peak	31.65	22.44	54.09	74.00	-19.91
N/A						

Remark:


1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Page: 158 / 231

Rev.: 01

Test Mode	IEEE 802.11a / 5220 MHz	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonics	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10440.00	Peak	30.37	18.29	48.66	68.20	-19.54
15660.00	Peak	31.50	22.86	54.36	74.00	-19.64
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11a / 5220 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
10440.00	Peak	30.44	18.29	48.73	68.20	-19.47
15660.00	Peak	30.56	22.86	53.42	74.00	-20.58
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11a / 5240MHZ	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10480.00	Peak	30.36	18.28	48.64	68.20	-19.56
15720.00	Peak	31.07	23.15	54.22	74.00	-19.78
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11a / 5240MHZ	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
10480.00	Peak	30.14	18.28	48.42	68.20	-19.78
15720.00	Peak	30.86	23.15	54.01	74.00	-19.99
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11n 20 MHz / 5180MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10360.00	Peak	31.76	18.16	49.92	68.20	-18.28
15540.00	Peak	31.15	22.44	53.59	74.00	-20.41
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 20 MHz/ 5180MHZ	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10360.00	Peak	31.81	18.16	49.97	68.20	-18.23
15540.00	Peak	31.63	22.44	54.07	74.00	-19.93
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11n 20 MHz / 5220MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10440.00	Peak	31.81	18.29	50.10	68.20	-18.10
15660.00	Peak	30.81	22.86	53.67	74.00	-20.33
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 20 MHz / 5220MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10440.00	Peak	30.61	18.29	48.90	68.20	-19.30
15660.00	Peak	31.02	22.86	53.88	74.00	-20.12
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11n 20 MHz / 5240MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10480.00	Peak	29.91	18.28	48.19	68.20	-20.01
15720.00	Peak	30.74	23.15	53.89	74.00	-20.11
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 20 MHz / 5240MHZ	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
10480.00	Peak	30.36	18.28	48.64	68.20	-19.56
15720.00	Peak	31.19	23.15	54.34	74.00	-19.66
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11n 40 MHz / 5190MHZ	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10380.00	Peak	30.76	18.17	48.93	68.20	-19.27
15570.00	Peak	31.38	22.55	53.93	74.00	-20.07
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11n 40 MHz / 5190MHZ	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10380.00	Peak	31.27	18.17	49.44	68.20	-18.76
15570.00	Peak	30.99	22.55	53.54	74.00	-20.46
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11n 40 MHz / 5230MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBuV	Factor dB	Actual FS dBuV/m	Limit @3m dBuV/m	Margin dB
10460.00	Peak	30.41	18.31	48.72	68.20	-19.48
15690.00	Peak	31.23	23.09	54.32	74.00	-19.68
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 40 MHz / 5230MHZ	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10460.00	Peak	30.80	18.31	49.11	68.20	-19.09
15690.00	Peak	31.22	23.09	54.31	74.00	-19.69
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11ac VHT80 / 5210MHZ	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10420.00	Peak	30.83	18.23	49.06	68.20	-19.14
15630.00	Peak	31.55	22.74	54.29	74.00	-19.71
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11ac VHT80 / 5210MHZ	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10420.00	Peak	30.71	18.23	48.94	68.20	-19.26
15630.00	Peak	30.91	22.74	53.65	74.00	-20.35
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Test Data for UNII-2a

Test Mode	IEEE 802.11a / 5260 MHz	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10520.00	Peak	33.16	18.30	51.46	68.20	-16.74
15780.00	Peak	31.27	23.19	54.46	74.00	-19.54
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11a / 5260 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10520.00	Peak	34.19	18.30	52.49	68.20	-15.71
15780.00	Peak	30.93	23.19	54.12	74.00	-19.88
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11a / 5280 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10560.00	Peak	33.91	18.35	52.26	68.20	-15.94
15840.00	Peak	30.51	23.52	54.03	74.00	-19.97
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11a / 5280 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10560.00	Peak	33.32	18.35	51.67	68.20	-16.53
15840.00	Peak	31.06	23.52	54.58	74.00	-19.42
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11a / 5320 MHz	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10600.00	Peak	33.26	18.32	51.58	68.20	-16.62
15900.00	Peak	30.80	24.40	55.20	74.00	-18.80
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11a / 5320 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10600.00	Peak	29.24	18.32	47.56	68.20	-20.64
10600.00	Peak	32.24	18.32	50.56	68.20	-17.64
15900.00	Peak	30.03	24.40	54.43	74.00	-19.57
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11n 20 MHz / 5260 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10520.00	Peak	32.24	18.30	50.54	68.20	-17.66
15780.00	Peak	30.35	23.19	53.54	74.00	-20.46
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 20 MHz / 5260 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10520.00	Peak	33.04	18.30	51.34	68.20	-16.86
15780.00	Peak	31.19	23.19	54.38	74.00	-19.62
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11n 20 MHz / 5280 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10560.00	Peak	30.15	18.35	48.50	68.20	-19.70
15840.00	Peak	30.55	23.52	54.07	74.00	-19.93
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 20 MHz / 5280 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
10560.00	Peak	30.19	18.35	48.54	68.20	-19.66
15840.00	Peak	30.78	23.52	54.30	74.00	-19.70
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11n 20 MHz / 5320 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10600.00	Peak	30.69	18.32	49.01	68.20	-19.19
15900.00	Peak	31.21	24.40	55.61	74.00	-18.39
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 20 MHz / 5320 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10600.00	Peak	29.97	18.32	48.29	68.20	-19.91
15900.00	Peak	31.66	24.40	56.06	74.00	-17.94
N/A						

Remark:


1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Page: 186 / 231

Rev.: 01

Test Mode	IEEE 802.11n 40 MHz / 5270 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10540.00	Peak	30.19	18.34	48.53	68.20	-19.67
15810.00	Peak	31.59	23.31	54.90	74.00	-19.10
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11n 40 MHz / 5270 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10540.00	Peak	30.28	18.34	48.62	68.20	-19.58
15810.00	Peak	31.37	23.31	54.68	74.00	-19.32
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11n 40 MHz / 5310 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
10620.00	Peak	30.35	18.35	48.70	74.00	-25.30
15930.00	Peak	30.26	24.44	54.70	74.00	-19.30
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11n 40 MHz / 5310 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10620.00	Peak	29.85	18.35	48.20	74.00	-25.80
15930.00	Peak	31.28	24.44	55.72	74.00	-18.28
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11ac VHT80 / 5290 MHz	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
10580.00	Peak	30.51	18.34	48.85	68.20	-19.35
15870.00	Peak	30.70	23.91	54.61	74.00	-19.39
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11ac VHT80 / 5290 MHz	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
10580.00	Peak	29.73	18.34	48.07	68.20	-20.13
15870.00	Peak	30.73	23.91	54.64	74.00	-19.36
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Test Data for UNII-2c

Test Mode	IEEE 802.11a / 5500 MHz	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11000.00	Peak	33.26	19.20	52.46	74.00	-21.54
16500.00	Peak	30.13	28.82	58.95	68.20	-9.25
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11a / 5500 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11000.00	Peak	33.07	19.20	52.27	74.00	-21.73
16500.00	Peak	30.53	28.82	59.35	68.20	-8.85
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11a / 5580 MHz	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11160.00	Peak	30.82	19.54	50.36	74.00	-23.64
16740.00	Peak	29.77	30.51	60.28	68.20	-7.92
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11a / 5580 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11160.00	Peak	30.84	19.54	50.38	74.00	-23.62
16740.00	Peak	30.02	30.51	60.53	68.20	-7.67
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Page: 196 / 231

Rev.: 01

Test Mode	IEEE 802.11a / 5700 MHz	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11400.00	Peak	30.00	19.03	49.03	74.00	-24.97
17100.00	Peak	30.30	34.03	64.33	68.20	-3.87
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11a / 5700 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11400.00	Peak	30.69	19.03	49.72	74.00	-24.28
17100.00	Peak	30.75	34.03	64.78	68.20	-3.42
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 20 MHz / 5500 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11000.00	Peak	30.01	19.20	49.21	74.00	-24.79
16500.00	Peak	31.10	28.82	59.92	68.20	-8.28
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11n 20 MHz / 5500 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11000.00	Peak	31.52	19.20	50.72	74.00	-23.28
16500.00	Peak	30.36	28.82	59.18	68.20	-9.02
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11n 20 MHz / 5580 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11160.00	Peak	32.70	19.54	52.24	74.00	-21.76
16740.00	Peak	30.78	30.51	61.29	68.20	-6.91
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 20 MHz / 5580 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11160.00	Peak	32.18	19.54	51.72	74.00	-22.28
16740.00	Peak	30.24	30.51	60.75	68.20	-7.45
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11n 20 MHz / 5700 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 16, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11400.00	Peak	32.81	19.03	51.84	74.00	-22.16
17100.00	Peak	30.19	34.03	64.22	68.20	-3.98
N/A						

Remark:


1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Report No.: T210429C13-RP4

Page: 203 / 231

Rev.: 01

Test Mode	IEEE 802.11n 20 MHz / 5700 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 16, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
11400.00	Peak	31.31	19.03	50.34	74.00	-23.66
17100.00	Peak	30.83	34.03	64.86	68.20	-3.34
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 40 MHz / 5510 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11020.00	Peak	30.58	19.26	49.84	74.00	-24.16
16530.00	Peak	30.39	29.02	59.41	68.20	-8.79
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11n 40 MHz / 5510 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11020.00	Peak	30.28	19.26	49.54	74.00	-24.46
16530.00	Peak	30.77	29.02	59.79	68.20	-8.41
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11n 40 MHz / 5550 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11100.00	Peak	31.81	19.58	51.39	74.00	-22.61
16650.00	Peak	30.50	29.44	59.94	68.20	-8.26
N/A						

Remark:


1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Page: 207 / 231

Rev.: 01

Test Mode	IEEE 802.11n 40 MHz / 5550 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11100.00	Peak	30.47	19.58	50.05	74.00	-23.95
16650.00	Peak	30.25	29.44	59.69	68.20	-8.51
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11n 40 MHz / 5670 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11340.00	Peak	30.23	19.28	49.51	74.00	-24.49
17010.00	Peak	29.61	33.96	63.57	68.20	-4.63
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 40 MHz / 5670 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
11340.00	Peak	30.41	19.28	49.69	74.00	-24.31
17010.00	Peak	30.66	33.96	64.62	68.20	-3.58
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11ac VHT80 / 5530 MHz	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
11060.00	Peak	30.30	19.40	49.70	74.00	-24.30
16590.00	Peak	30.70	29.21	59.91	68.20	-8.29
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11ac VHT80 / 5530 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11060.00	Peak	30.05	19.40	49.45	74.00	-24.55
16590.00	Peak	30.52	29.21	59.73	68.20	-8.47
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11ac VHT80 / 5610 MHz	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
11220.00	Peak	31.55	19.51	51.06	74.00	-22.94
16830.00	Peak	29.78	31.58	61.36	68.20	-6.84
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Page: 213 / 231

Rev.: 01

Test Mode	IEEE 802.11ac VHT80 / 5610 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11220.00	Peak	35.53	19.51	55.04	74.00	-18.96
11220.00	Average	30.20	19.51	49.71	54.00	-4.29
16830.00	Peak	29.21	31.58	60.79	68.20	-7.41
N/A						


Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Report No.: T210429C13-RP4

Test Data for UNII-3

Test Mode	IEEE 802.11a / 5745 MHz	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11490.00	Peak	31.49	19.13	50.62	74.00	-23.38
17235.00	Peak	30.11	33.97	64.08	68.20	-4.12
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11a / 5745 MHz	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11490.00	Peak	30.46	19.13	49.59	74.00	-24.41
17235.00	Peak	30.41	33.97	64.38	68.20	-3.82
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11a / 5785 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11570.00	Peak	29.33	19.04	48.37	74.00	-25.63
17355.00	Peak	30.21	34.47	64.68	68.20	-3.52
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11a / 5785 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
11570.00	Peak	30.86	19.04	49.90	74.00	-24.10
17355.00	Peak	30.13	34.47	64.60	68.20	-3.60
N/A						

Remark:


1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Page: 218 / 231

Rev.: 01

Test Mode	IEEE 802.11a / 5825 MHz	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11650.00	Peak	30.09	19.14	49.23	74.00	-24.77
17475.00	Peak	29.30	34.30	63.60	68.20	-4.60
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11a / 5825 MHz	Temp/Hum	22.9(°C) / 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11650.00	Peak	30.55	19.14	49.69	74.00	-24.31
17475.00	Peak	29.34	34.30	63.64	68.20	-4.56
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 20 MHz / 5745 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 16, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11490.00	Peak	32.01	19.13	51.14	74.00	-22.86
17235.00	Peak	30.16	33.97	64.13	68.20	-4.07
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 20 MHz / 5745 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 16, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11490.00	Peak	30.16	19.13	49.29	74.00	-24.71
17235.00	Peak	29.99	33.97	63.96	68.20	-4.24
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11n 20 MHz/ 5785 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 16, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11570.00	Peak	32.84	19.04	51.88	74.00	-22.12
17355.00	Peak	30.05	34.47	64.52	68.20	-3.68
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 20 MHz/ 5785 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
11570.00	Peak	30.37	19.04	49.41	74.00	-24.59
17355.00	Peak	30.21	34.47	64.68	68.20	-3.52
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11n 20 MHz/ 5825 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 16, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
11650.00	Peak	32.29	19.14	51.43	74.00	-22.57
17475.00	Peak	29.80	34.30	64.10	68.20	-4.10
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 20 MHz/ 5825 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 16, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11650.00	Peak	31.94	19.14	51.08	74.00	-22.92
17475.00	Peak	29.14	34.30	63.44	68.20	-4.76
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11n 40 MHz/ 5755 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11510.00	Peak	30.45	19.13	49.58	74.00	-24.42
17265.00	Peak	30.69	33.98	64.67	68.20	-3.53
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode	IEEE 802.11n 40 MHz/ 5755 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11510.00	Peak	29.99	19.13	49.12	74.00	-24.88
17265.00	Peak	30.38	33.98	64.36	68.20	-3.84
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Test Mode	IEEE 802.11n 40 MHz/ 5795 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11590.00	Peak	29.65	19.00	48.65	74.00	-25.35
17385.00	Peak	30.52	34.60	65.12	68.20	-3.08
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11n 40 MHz/ 5795 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
11590.00	Peak	31.86	19.00	50.86	74.00	-23.14
17385.00	Peak	30.32	34.60	64.92	68.20	-3.28
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

Report No.: T210429C13-RP4

Page: 230 / 231

Rev.: 01

Test Mode	IEEE 802.11ac VHT80/ 5775 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dB μ V	Factor dB	Actual FS dB μ V/m	Limit @3m dB μ V/m	Margin dB
8000.00	Peak	30.25	14.41	44.66	68.20	-23.54
11550.00	Peak	29.63	19.09	48.72	74.00	-25.28
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Report No.: T210429C13-RP4

Test Mode	IEEE 802.11ac VHT80/ 5775 MHz	Temp/Hum	22.9(°C)/ 44%RH
Test Item	Harmonic	Test Date	June 15, 2021
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
8000.00	Peak	29.98	14.41	44.39	68.20	-23.81
11550.00	Peak	30.07	19.09	49.16	74.00	-24.84
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit.

- End of Test Report -