

FCC ID: Z3K-EVOLVE8
Report No.: T210429C13-RP4

IC: 9930A-EVOLVE8

Page: 1 / 231
Rev.: 01

RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART E

INDUSTRY CANADA RSS-247

Test Standard	FCC Part 15.407+ RSS-247 issue 2 and RSS-GEN issue 5
Product name	Evolve Universal 8 inch Headrest Monitor
Brand Name	Ford
Model No.	661182
Test Result	Pass
Statements of Conformity	Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report. The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory)

Approved by:



Kevin Tsai
Deputy Manager

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Report No.: T210429C13-RP4

Page: 2 / 231

Rev.: 01

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	July 20, 2021	Initial Issue	ALL	Doris Chu
01	July 28, 2021	See the following Note Rev. (01)	P.9, P.12, P.148-149, P.212-213	Doris Chu

Rev. (01)

1. Revised calibration table in section 1.6.
2. Revised Operation mode in section 3.1.
3. Added test result 5795 in section 4.4.4.
4. Added test result 5610 in section 4.4.4.

Table of contents

1. GENERAL INFORMATION	4
1.1 EUT INFORMATION	4
1.2 EUT CHANNEL INFORMATION	5
1.3 ANTENNA INFORMATION	6
1.4 MEASUREMENT UNCERTAINTY	6
1.5 FACILITIES AND TEST LOCATION	8
1.6 INSTRUMENT CALIBRATION	8
1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT	10
1.8 TEST METHODOLOGY AND APPLIED STANDARDS	10
2. TEST SUMMARY	11
3. DESCRIPTION OF TEST MODES	12
3.1 THE EUT CHANNEL NUMBER OF OPERATING CONDITION	12
3.2 THE WORST MODE OF MEASUREMENT	13
3.3 EUT DUTY CYCLE	14
4. TEST RESULT	15
4.1 AC POWER LINE CONDUCTED EMISSION	15
4.2 26DB BANDWIDTH, 6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%)	16
4.3 OUTPUT POWER MEASUREMENT	64
4.4 POWER SPECTRAL DENSITY	75
4.5 RADIATION BANDEDGE AND SPURIOUS EMISSION	103
APPENDIX-A TEST PHOTO	A-1
APPENDIX 1 - PHOTOGRAPHS OF EUT	

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	JET OPTOELECTRONICS CO., LTD. 3F., No.300, Yangguang St., Neihu Dist., Taipei City 11491, Taiwan
Manufacturer	JET OPTOELECTRONICS CO., LTD. 3F., No.300, Yangguang St., Neihu Dist., Taipei City 11491, Taiwan
Equipment	Evolve Universal 8 inch Headrest Monitor
Model No.	661182
Model Discrepancy	N/A
Trade Name	Ford
Received Date	April 29, 2021
Date of Test	June 8 ~ 24, 2021
Power Supply	Power from Power Supply: DC 12V
HW Version	20210208 D01
SW Version	95126
EUT Serial #	GA51RW0011030013

Remark:

1. For more details, please refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.
3. The EUT (model: 661182) had been tested under operating condition.

1.2 EUT CHANNEL INFORMATION

Frequency Range	UNII-1	
	IEEE 802.11a	5180 ~ 5240 MHz
	IEEE 802.11n HT 20 MHz	5180 ~ 5240 MHz
	IEEE 802.11n HT 40 MHz	5190 ~ 5230 MHz
	IEEE 802.11ac VHT 80 MHz	5210 MHz
	UNII-2a	
	IEEE 802.11a	5260 ~ 5320 MHz
	IEEE 802.11n HT 20 MHz	5260 ~ 5320 MHz
	IEEE 802.11n HT 40 MHz	5270 ~ 5310 MHz
	IEEE 802.11ac VHT 80 MHz	5290 MHz
	UNII-2c	
	IEEE 802.11a	5500 ~ 5700 MHz
	IEEE 802.11n HT 20 MHz	5500 ~ 5700 MHz
	IEEE 802.11n HT 40 MHz	5510 ~ 5670 MHz
	IEEE 802.11ac VHT 80 MHz	5530, 5610 MHz
	UNII-3	
	IEEE 802.11a	5745 ~ 5825 MHz
	IEEE 802.11n HT 20 MHz	5745 ~ 5825 MHz
	IEEE 802.11n HT 40 MHz	5755 ~ 5795 MHz
	IEEE 802.11ac VHT 80 MHz	5775 MHz
Modulation Type	1. IEEE 802.11a mode: OFDM 2. IEEE 802.11n HT 20 MHz mode: OFDM 3. IEEE 802.11n HT 40 MHz mode: OFDM 4. IEEE 802.11ac VHT 80 MHz mode: OFDM	

Remark:

1. Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 for test channels.
2. For Canada the EUT Frequency Range 5600~5650MHz will be disabled.

Report No.: T210429C13-RP4

Page: 6 / 231

Rev.: 01

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
☐ 1 MHz or less	1	Middle
☐ 1 MHz to 10 MHz	2	1 near top and 1 near bottom
☒ More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

Antenna Type	☒ Ceramic ☐ PCB ☐ Dipole ☐ Coils
Antenna Gain	Chain 0: Gain :2.6 dBi Chain 1: Gain :2.6 dBi Power Directional Gain: 5.61 dBi
Antenna Connector	N/A

Notes:

1. Power Directional Gain = $10 \cdot \log \{ [10^{(Ant1/20)} + 10^{(Ant2/20)} + \dots + 10^{(Ant N /20)}]^2 / N \text{ ANT} \}$ dBi
2. The antenna(s) of the EUT are permanently attached and there are no provisions for connection to an external antenna. So the EUT complies with the requirements of §15.203 and RSS-Gen 6.8.

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 30M~200M	+/- 4.12
3M Semi Anechoic Chamber / 200M~1000M	+/- 4.68
3M Semi Anechoic Chamber / 1G~8G	+/- 5.18
3M Semi Anechoic Chamber / 8G~18G	+/- 5.47
3M Semi Anechoic Chamber / 18G~26G	+/- 3.81
3M Semi Anechoic Chamber / 26G~40G	+/- 3.87

Remark:

- 1.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

Report No.: T210429C13-RP4

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. (R.O.C.)

CAB identifier: TW1309

Test site	Test Engineer	Remark
AC Conduction Room	-	Not applicable, because EUT doesn't connect to AC Main Source direct.
Radiation	Ray Li	-
RF Conducted	Lance Chen	-

Remark: The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC public Access Link (PAL) database, FCC Registration No. :444940, the FCC Designation No.:TW1309

1.6 INSTRUMENT CALIBRATION

3M 966 Chamber Test Site					
Equipment	Manufacturer	Model	Serial Number	Cal Date	Cal Due
Bilog Antenna	Sunol Sciences	JB3	A030105	07/24/2020	07/23/2021
Coaxial Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/24/2021	02/23/2022
Coaxial Cable	EMCI	EMC105	190914+327109/4	09/19/2020	09/18/2021
K Type Cable	Huber+Suhner	SUCOFLEX 102	29406/2	12/09/2020	12/08/2021
K Type Cable	Huber+Suhner	SUCOFLEX 102	22470/2	12/09/2020	12/08/2021
Digital Thermo-Hygro Meter	WISEWIND	1206	D07	01/06/2021	01/05/2022
double Ridged Guide Horn Antenna	ETC	MCTD 1209	DRH13M02003	09/30/2020	09/29/2021
High Pass Filters	MICRO TRONICS	HPM13195	003	02/08/2021	02/07/2022
Horn Antenna	ETS LINDGREN	3116	00026370	12/11/2020	12/10/2021
Loop Ant	COM-POWER	AL-130	121051	04/07/2021	04/06/2022
Pre-Amplifier	EMEC	EM330	060609	02/24/2021	02/23/2022
Pre-Amplifier	HP	8449B	3008A00965	02/25/2021	02/24/2022
Pre-Amplifier	MITEQ	AMF-6F-18004000-37-8P	985646	09/02/2020	09/01/2021
PSA Series Spectrum Analyzer	Agilent	E4446A	MY46180323	07/24/2020	07/23/2021
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180419c				

Remark:

- Each piece of equipment is scheduled for calibration once a year.
- N.C.R. = No Calibration Required.

Report No.: T210429C13-RP4

Page: 9 / 231

Rev.: 01

RF Conducted Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Signal Analyzer	KEYSIGHT	N9010B	MY55460167	09/07/2020	09/06/2021
Coaxial Cable	Woken	WC12	CC003	06/29/2020	06/28/2021
Coaxial Cable	Woken	WC12	CC001	06/29/2020	06/28/2021
Signal Analyzer	R&S	FSV 40	101073	09/17/2020	09/16/2021
Power Meter	Anritsu	ML2487A	6K00003260	05/24/2021	05/23/2022
Power Seneor	Anritsu	MA2490A	032910	05/24/2021	05/23/2022
Software	N/A				

Remark:

1. Each piece of equipment is scheduled for calibration once a year.
2. N.C.R. = No Calibration Required.

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
	N/A				

Support Equipment						
No.	Equipment	Brand	Model	Series No.	FCC ID	IC
1	DC Power Source	Agilent	E3640A	N/A	N/A	N/A
2	DC Power Source	GWINSTEK	SPS-3610	N/A	N/A	N/A
3	NB(J)	TOSHIBA	PT345T-00L002	N/A	PD97260H	1000M-7260H

1.8 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.407, KDB 789033 D02, KDB 905462 D02, RSS-247 Issue 2 and RSS-GEN Issue 5.

2. TEST SUMMARY

FCC Standard Sec.	IC Standard Sec.	Chapter	Test Item	Result
15.203	RSS-Gen (6.8)	1.3	Antenna Requirement	Pass
15.207	RSS-Gen (8.8)	4.1	AC Conducted Emission	Pass
15.403(i)	-	4.2	26dB Bandwidth	Pass
15.407(e)	RSS-247(6.2.4)	4.2	6dB Bandwidth	Pass
15.403(i)	RSS-Gen (6.7)	4.2	Occupied Bandwidth (99%)	Pass
15.407(a)	RSS-247(6.2.1.1) RSS-247(6.2.2.1) RSS-247(6.2.3.1) RSS-247(6.2.4.1)	4.3	Output Power Measurement	Pass
15.407(a)	RSS-247(6.2.1.1) RSS-247(6.2.2.1) RSS-247(6.2.3.1) RSS-247(6.2.4.1)	4.4	Power Spectral Density	Pass
15.407(b)	RSS-247(6.2.1.2) RSS-247(6.2.2.2) RSS-247(6.2.3.2) RSS-247(6.2.4.2)	4.5	Radiation Band Edge	Pass
15.407(b)	RSS-247(6.2.1.2) RSS-247(6.2.2.2) RSS-247(6.2.3.2) RSS-247(6.2.4.2)	4.5	Radiation Spurious Emission	Pass

3. DESCRIPTION OF TEST MODES

3.1 THE EUT CHANNEL NUMBER OF OPERATING CONDITION

Operation mode	1. IEEE 802.11a mode: 6Mbps 2. IEEE 802.11n HT 20 MHz mode: MCS8 3. IEEE 802.11n HT 40 MHz mode: MCS8 4. IEEE 802.11ac VHT 80 MHz mode: MCS0		
Operating Frequency			
	U-NII-1	Mode	Frequency Range (MHz)
		IEEE 802.11a	5180, 5220, 5240
		IEEE 802.11n HT 20 MHz	5180, 5220, 5240
		IEEE 802.11n HT 40 MHz	5190, 5230
	U-NII-2a	IEEE 802.11ac VHT 80 MHz	5210
		IEEE 802.11a	5260, 5280, 5320
		IEEE 802.11n HT 20 MHz	5260, 5280, 5320
		IEEE 802.11n HT 40 MHz	5270, 5310
	U-NII-2c	IEEE 802.11ac VHT 80 MHz	5290
		IEEE 802.11a	5500, 5580, 5700
		IEEE 802.11n HT 20 MHz	5500, 5580, 5700
		IEEE 802.11n HT 40 MHz	5510, 5550, 5670
	U-NII-3	IEEE 802.11ac VHT 80 MHz	5530, 5610
		IEEE 802.11a	5745, 5785, 5825
		IEEE 802.11n HT 20 MHz	5745, 5785, 5825
IEEE 802.11n HT 40 MHz		5755, 5795	
	IEEE 802.11ac VHT 80 MHz	5775	

Remark:

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.
2. For Canada the EUT Frequency Range 5600~5650MHz will be disabled.
3. The system support 802.11a/n HT20/n HT40/ac VHT20/40/80, the VHT20/VHT40 were reduced since the identical parameters with 802.11n HT20 and HT40.
4. The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations. The device supports SISO and MIMO at 802.11n/ac mode, per pre-test, MIMO 2TX mode was the worst and reported.

3.2 THE WORST MODE OF MEASUREMENT

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by Power supply
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☐ Placed in fixed position at X-Plane (E2-Plane) ☐ Placed in fixed position at Y-Plane (E1-Plane) ☒ Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Power supply
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:

- 1. The worst mode was record in this test report.*
- 2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(Z-Plane) were recorded in this report*

Report No.: T210429C13-RP4

3.3 EUT DUTY CYCLE

Temperature: 24.6°C

Humidity:

51.7% RH


Tested by: Lance Chen

Test date:


June 8, 2021

Duty Cycle				
Configuration	Duty Cycle (%)	Duty Factor (dB) =10*log (1/Duty Cycle)	1/T (kHz)	VBW setting (kHz)
802.11a	93.00	0.32	0.72	1.00
802.11n HT20	87.00	0.60	1.49	2.00
802.11n HT40	69.51	1.58	3.24	4.00
802.11ac VHT80	68.13	1.67	3.51	4.00

802.11a




802.11n HT20



802.11n HT40



802.11ac VHT80



4. TEST RESULT

4.1 AC POWER LINE CONDUCTED EMISSION

4.1.1 Test Limit

According to §15.207(a) and RSS-GEN section 8.8,

Frequency Range (MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


* Decreases with the logarithm of the frequency.

4.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-Peak and Average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

4.1.3 Test Setup



4.1.4 Test Result

Not applicable, because EUT doesn't connect to AC Main Source direct.

4.2 26dB BANDWIDTH, 6dB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)

4.2.1 Test Limit

26 dB Bandwidth : For reporting purposes only.

6 dB Bandwidth : Least 500kHz.

Occupied Bandwidth(99%) : For reporting purposes only.

4.2.2 Test Procedure

26dB


1. This measurement setting are specified in section D of KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set RBW: approximately 1% of the emission bandwidth.
3. Set the VBW>RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26dB down from the peak of the emission. Compare this with the RBW setting of the analyser. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

6dB

1. This measurement setting are specified in section D of KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set RBW = 100 kHz.
3. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

99%

1. This measurement setting are specified in section D of KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set center frequency to the nominal EUT channel center frequency.
3. Set span = 1.5 times to 5.0 times the OBW.
4. Set RBW = 1 % to 5% of the OBW.
5. Set VBW $\geq 3 \times \text{RBW}$

4.2.3 Test Setup

4.2.4 Test Result

Temperature: 24.6 ~ 25.1°C **Humidity:** 51.7 ~ 53.9% RH

Tested by: Lance Chen **Test date:** June 8 ~ 9, 2021

Temperature: 23.8°C **Humidity:** 55.2% RH

Tested by: Lance Chen **Test date:** June 24, 2021

UNII-1 5150-5250 MHz					
Test mode: IEEE 802.11a mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5180	23.990	-	19.73	-
Mid	5220	16.437	-	20.04	-
High	5240	16.500	-	25.94	-
Test mode: IEEE 802.11n HT20 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5180	17.530	17.544	19.93	19.85
Mid	5220	17.546	17.531	20.01	19.84
High	5240	17.523	17.570	19.84	19.87
Test mode: IEEE 802.11n HT40 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5190	36.062	36.159	40.29	39.66
High	5230	35.985	36.013	40.56	39.59
Test mode: IEEE 802.11ac VHT80 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Mid	5210	75.829	75.585	89.61	79.32




UNII-2a 5250-5350 MHz					
Test mode: IEEE 802.11a mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5260	21.276	-	38.44	-
Mid	5280	22.871	-	39.76	-
High	5320	22.722	-	37.54	-
Test mode: IEEE 802.11n HT20 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5260	22.177	18.417	24.69	20.32
Mid	5280	17.784	17.794	28.45	28.17
High	5320	18.564	18.697	32.80	26.50
Test mode: IEEE 802.11n HT40 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5270	37.753	36.415	80.07	75.66
High	5310	38.566	36.400	53.48	40.31
Test mode: IEEE 802.11ac VHT80 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Mid	5290	82.605	78.292	80.95	79.68

Report No.: T210429C13-RP4

UNII-2c 5475-5725 MHz					
Test mode: IEEE 802.11a mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5500	21.914	-	32.46	-
Mid	5580	24.135	-	41.41	-
High	5700	20.878	-	33.67	-
Test mode: IEEE 802.11n HT20 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5500	18.119	18.179	26.21	21.64
Mid	5580	17.871	17.651	28.36	26.53
High	5700	17.685	17.715	27.55	26.56
Test mode: IEEE 802.11n HT40 mode					
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5510	37.868	36.665	44.99	40.10
Mid	5550	38.425	36.812	87.95	75.00
High	5670	40.968	36.679	66.79	39.99
Test mode: IEEE 802.11ac VHT80 mode					
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 26dB BW (MHz)	Chain 1 26dB BW (MHz)
Low	5530	77.108	76.220	80.87	79.58
High	5610	83.294	76.841	196.00	186.30

UNII-3 5725-5825MHz						
Test mode: IEEE 802.11a mode						
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)	Limit
Low	5745	21.368	-	14.47	-	>500kHz
Mid	5785	22.237	-	15.48	-	
High	5825	22.721	-	15.97	-	
Test mode: IEEE 802.11n HT20 mode						
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)	Limit
Low	5745	21.732	21.749	14.98	15.59	>500kHz
Mid	5785	21.846	21.671	13.85	15.68	
High	5825	21.888	23.390	15.76	15.04	
Test mode: IEEE 802.11n HT40 mode						
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)	Limit
Low	5755	36.898	37.041	35.04	34.69	>500kHz
High	5795	37.610	38.816	33.86	33.91	
Test mode: IEEE 802.11ac VHT80 mode						
Channel	Frequency (MHz)	Chain 0 OBW(99%) (MHz)	Chain 1 OBW(99%) (MHz)	Chain 0 6dB BW (MHz)	Chain 1 6dB BW (MHz)	Limit
Mid	5775	78.730	80.010	75.11	68.95	>500kHz

Report No.: T210429C13-RP4

Test Data (99% OBW)**Chain 0****UNII-1 IEEE 802.11a mode - Chain 0****Low CH****Mid CH****High CH**


Report No.: T210429C13-RP4

UNII-1 IEEE 802.11n HT20 mode - Chain 0


Low CH



Mid CH




High CH




Report No.: T210429C13-RP4

UNII-1 IEEE 802.11n HT20 mode - Chain 1


Low CH



Mid CH




High CH




Report No.: T210429C13-RP4

UNII-1 IEEE 802.11n HT40 mode- Chain 0

Low CH




High CH




UNII-1 IEEE 802.11n HT40 mode- Chain 1

Low CH




High CH



Report No.: T210429C13-RP4


UNII-1 IEEE 802.11ac VHT80 mode- Chain 0

Low CH




UNII-1 IEEE 802.11ac VHT80 mode- Chain 1

Low CH




Report No.: T210429C13-RP4

Test Data (99% OBW)




Report No.: T210429C13-RP4




UNII-2a IEEE 802.11n HT20 mode- Chain 1


Low CH




Mid CH



High CH




Report No.: T210429C13-RP4



Report No.: T210429C13-RP4


UNII-2a IEEE 802.11ac VHT80 mode- Chain 0

Low CH






UNII-2a IEEE 802.11ac VHT80 mode- Chain 1


Low CH




Report No.: T210429C13-RP4

Test Data (99% OBW)**UNII-2c IEEE 802.11a mode- Chain 0****Low CH****Mid CH****High CH**

Report No.: T210429C13-RP4







Report No.: T210429C13-RP4

UNII-2c IEEE 802.11n HT40 mode- Chain 0

Low CH



Mid CH




High CH




Report No.: T210429C13-RP4

UNII-2c IEEE 802.11n HT40 mode- Chain 1


Low CH



Mid CH




High CH




Report No.: T210429C13-RP4

UNII-2c IEEE 802.11ac VHT80 mode- Chain 0

Low CH




High CH




UNII-2c IEEE 802.11ac VHT80 mode- Chain 1

Low CH




High CH



Report No.: T210429C13-RP4


Test Data (99% OBW)




Report No.: T210429C13-RP4

UNII-3 IEEE 802.11n HT20 mode- Chain 0


Low CH



Mid CH




High CH




Report No.: T210429C13-RP4

UNII-3 IEEE 802.11n HT20 mode- Chain 1


Low CH



Mid CH




High CH




Report No.: T210429C13-RP4

UNII-3 IEEE 802.11n HT40 mode- Chain 0

Low CH




High CH





UNII-3 IEEE 802.11n HT40 mode- Chain 1

Low CH



High CH



UNII-3 IEEE 802.11ac VHT80 mode- Chain 0 Low CH	
	
UNII-3 IEEE 802.11ac VHT80 mode- Chain 1 Low CH	
