4 FCC§15.247(i), §1.1310, § 2.1091 - Maximum Permissible Exposure (MPE)

Report No.: RLK1810008-00A

4.1 Applicable Standard

According to subpart 15.247(i)and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)					
0.3–1.34	614	1.63	*(100)	30					
1.34–30	824/f	2.19/f	*(180/f²)	30					
30–300	27.5	0.073	0.2	30					
300–1500	/	/	f/1500	30					
1500–100,000	/	/	1.0	30					

f = *frequency in MHz*; * = *Plane-wave equivalent power density*;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary: Predication of MPE limit at a given distance

 $S = PG/4\pi R^2 = power density (in appropriate units, e.g. mW/cm2);$

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \leq 1$$

FCC Part 15.247 Page 12 of 69

4.2 RF Exposure Evaluation Result

MPE Evaluation:

Mode	Frequency Range (MHz)	Antenna Gain		Target Power		Evaluation	Power	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)	Distance (cm)	Density (mW/cm²)	(mW/cm ²)
Wi-Fi 2.4G	2412-2462	3.60	2.291	27.00	501.187	25	0.1463	1
BLE	2402-2480	-4.30	0.372	8.00	6.310	25	0.0003	1
BR+EDR	2402-2480	-4.30	0.372	11.00	12.589	25	0.0006	1
Wi-Fi 5G UNII-1	5150-5250	9.44	8.790	23.00	199.526	25	0.2234	1
Wi-Fi 5G UNII-2a	5250-5350	9.44	8.790	21.00	158.489	25	0.1409	1
Wi-Fi 5G UNII-2c	5470-5725	9.78	9.506	19.00	79.433	25	0.0961	1
Wi-Fi 5G UNII-3	5745-5850	9.03	7.999	27.00	501.187	25	0.5107	1

Report No.: RLK1810008-00A

The Wi-Fi 2.4G, BT and Wi-Fi 5G can transmit simultaneously:

 $=S_{2.4G}/S_{limit-2.4G}+S_{BR+EDR}/S_{limit-BR+EDR}+S_{5G~UNII-3}/S_{limit-5G~UNII-3}$

= 0.1463/1 + 0.0006/1 + 0.5107/1 = 0.6576 < 1.0

Result: MPE evaluation meet 25 cm the requirement of standard.

FCC Part 15.247 Page 13 of 69