



Global Product Certification  
EMC-EMF Safety Approvals

**Melbourne**

176 Harrick Road  
Keilor Park, Vic 3042  
Tel: +61 3 9365 1000

**Sydney**

Unit 3/87 Station Road  
Seven Hills, NSW 2147  
Tel: +61 2 9624 2777

Email: [emc-general@emctech.com.au](mailto:emc-general@emctech.com.au)  
Web: [www.emctech.com.au](http://www.emctech.com.au)

# RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES

**REPORT NUMBER: M2112040-5 V1.0**

**STANDARD: FCC KDB 447498 D01**

**CLIENT: MINELAB ELECTRONICS  
PTY LTD**

**DEVICE: PLATYPUS2 METAL  
DETECTOR**

**MODEL: EQUINOX 700, EQUINOX 900**

**DATE OF ISSUE: 5 JULY 2022**

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



Accredited for compliance with ISO/IEC 17020.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

**Except for the Certificate of Compliance, this document must only be reproduced in full.**

## REVISION TABLE

Version	Sec/Para Changed	Change Made	Date
0		Initial issue of document	26/06/2022
1		TCB Comments	05/07/2022

## CONTENTS

1	Introduction.....	5
1.1	Laboratory Overview.....	5
1.2	Test Laboratory/Accreditations.....	5
2	Device Details.....	5
3	SAR TEST EXCLUSION THRESHOLD FOR 100MHz to 6GHz and $\leq 50$ mm.....	7
4	LIMITS for Low Power Consumer Wireless Power Transfer Application.....	9
5	MEASUREMENT METHOD.....	9
5.1	Table 1: Test Equipment List.....	9
5.2	Measurement Procedures.....	9
6	Uncertainty.....	9
7	MEASUREMENT RESULTS.....	10
7.1	Results.....	10
7.2	Bluetooth Module Results.....	10
8	Conclusion.....	10
9	APPENDIX A – Probe Datasheet.....	12
10	APPENDIX B – Measurement Plots.....	13
11	APPENDIX C – Supplied Information.....	21
12	APPENDIX D – Photos.....	22

## RADIOFREQUENCY RADIATION EXPOSURE EVALUATION REPORT - MPE

**Device:** Platypus2 Metal Detector  
**Model Number:** Equinox 700, Equinox 900  
**Serial Number:** Control Unit: 84599366368; Coil: 66259969159

**Manufacturer:** Minelab Electronics Pty Ltd


**Inspected for:** Minelab Electronics Pty Ltd  
**Address:** 2 Second Avenue, Mawson Lakes, SA 5095  
**Phone Number:** 0434481762  
**Contact:** Charles Edwards  
**Email:** charles.edwards@codan.com.au


**Standards:** **447498 D01 General RF Exposure Guidance v06**  
RF exposure procedures and equipment authorization policies for mobile and portable devices.

**Result:** Based on an assessment of the documentation provided and the performed measurements the PLATYPUS2 METAL DETECTOR, model EQUINOX 700, EQUINOX 900 complies with the RF exposure requirements of 447498 D01. Refer to Report M2112040-5 V1.0 for full details

**Assessment Date:** 19 April 2022

**Assessment Engineers:**   
Deborah Olaleye

  
Emad Mansour

**Authorised Signatory:**   
Emad Mansour  
EMR/On-Site Project Manager  
EMC Technologies Pty Ltd

**Issued by:** EMC Technologies Pty. Ltd.,  
176 Harrick Road, Keilor Park, VIC, 3042, Australia.  
**Phone:** +61 3 9365 1000

**E-mail:** [emc-general@emctech.com.au](mailto:emc-general@emctech.com.au)

**Web:** [www.emctech.com.au](http://www.emctech.com.au)

## 1 INTRODUCTION

This report is intended to demonstrate compliance of the Platypus2 Metal Detector model Equinox 700, Equinox 900 with the RF exposure requirements of KDB 447498 D01-v06. Evaluation was performed in accordance with KDB 680106-v03 as per TCP enquiry (Tracking Number 781827)

The test sample was provided by the Client. The conclusion herein is based on the information provided by the client.

### 1.1 Laboratory Overview

EMC Technologies Pty. Ltd. is an independently owned Australian company that is NATA accredited to ISO 17025 for both testing and calibration and ISO 17020 for Inspection. – **Accreditation Number 5292.**

### 1.2 Test Laboratory/Accreditations

Inspection was performed at EMC Technologies' laboratory in Keilor Park, Victoria Australia.

Table 1-1: *Accreditations for Conformity Assessment*

Country/Region	Body	
Australia/New Zealand	NATA	Accreditation Number: 5292
Europe	European Union	Notified Body Number: 0819
USA	FCC	Designation Number: AU0001 (Melb)
Canada	ISED Canada	Company Number: 3569B(Melb)
Japan	VCCI	Company Number: 785
Taiwan	BSMI	Lab Code SL2-IN-E-5001R

## 2 DEVICE DETAILS

(Information supplied by the Client)

Equinox 700 & Equinox 900 (project name: Platypus2) is designed as a high-performance coin & treasure metal detector. The product is designed to detect metal targets buried at varying depths in the ground. The metal detector supports a low-latency wireless audio connection for use with wireless headphones.

Equinox 700 Uses the exact same radio components, PCB and design, and is identical to the tested model Equinox 900. The only differences between these products are model branding, reduced functional features and pack-out of the Equinox 700.

**Manufacturer:** Minelab Electronics Pty Ltd  
**Inspected Sample:** Platypus2 Metal Detector  
**Model Number:** Equinox 700, Equinox 900  
**Serial Number:** Control Unit: 84599366368  
 Coil: 66259969159

Transmit parameters were provided by the customer and are shown below:

Table 2-1: Transmitter Parameters

<b>Transmitter #1</b>	
<b>Radio:</b>	Bluetooth Low Energy (Nordic nRF5340)
<b>Operating Frequency:</b>	2400 – 2483.5 MHz
<b>Output Power:</b>	3 dBm
<b>Antenna:</b>	PCB Trace Antenna TEXAS INSTRUMENTS 2.4-GHz Inverted F Antenna (TI AP #SWRU120D)
<b>Antenna gain:</b>	3.3 dBi
<b>Transmitter #2</b>	
<b>EUT Modulation Type:</b>	Transceiver
<b>Operating Frequency Range:</b>	4kHz to 50kHz

### 3 SAR TEST EXCLUSION THRESHOLD FOR 100MHZ TO 6GHZ AND ≤50MM

Table1: SAR test exclusion threshold 100 MHz- 6GHz

Frequency (MHz)	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
435	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
Frequency (MHz)	30	35	40	45	50	mm
150	232	271	310	349	387	SAR Test Exclusion Threshold (mW)
300	164	192	219	246	274	
450	134	157	179	201	224	
435	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\frac{\text{max. power of channel, including tune – up tolerance (mW)}}{\text{min. test separation distance (mm)}} * \sqrt{f(\text{GHz})} \leq 3.0$$

Where:

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

- The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz.



## 4 LIMITS FOR LOW POWER CONSUMER WIRELESS POWER TRANSFER APPLICATION

The limit as per “680106 D01 RF Exposure Wireless Charging App v03r01”

- 83 V/m for the electric field
- 90 A/m for the magnetic field.

## 5 MEASUREMENT METHOD

### 5.1 Table 1: Test Equipment List

Equipment Type	Make, Model and Serial Number	Calibration due	Calibrated by
EM Field Meter	Asset Number: P-199-1 Manufacturer: Wavecontrol Model Number: SMP2 S/N: 18WP100446/18SN0901	03/2024	Wavecontrol (Manufacturer)
E-Field/ H-Field Probe	Asset Number: P-199-2 Manufacturer: Wavecontrol Model Number: WP400* Freq: 1 Hz to 400 kHz Measurement Type: Selective/Broadband S/N: 18WP100466	03/2024	Wavecontrol (Manufacturer)

\*The WP400 probe is a Realtime isotropic, 3-axis probe with 100 cm<sup>2</sup> sensor (diameter = 5.64 cm), the isotropy of this probe is 5% (0.42 dB).

The Uncertainty of the probe is 0.67 dB (Total, counting isotropy, temperature deviation, resolution, frequency response, linearity, repeatability).

Probe specification sheet attached in appendix.

### 5.2 Measurement Procedures

The measurements were performed at 100 Hz – 400 kHz frequency range; magnetic and electric flux measurements were taken using the WaveControl meter. The levels recorded were then compared against the limits in Section 8.

## 6 UNCERTAINTY

EMC Technologies has evaluated the tools and methods used to perform Radiated Electromagnetic Field predictions.

The Measurement Uncertainties for DC and ELF magnetic field measurements are derived from the manufacturer, Instruments’ stated uncertainty factors and calibration data.

Expanded Uncertainty:

Testing: DC to 400kHz ±2.3 dB

The above expanded uncertainties are based on standard uncertainties multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

## 7 MEASUREMENT RESULTS

### 7.1 Results

Table 7-1: Magnetic Field Result

Survey point #	Measured Magnetic Field (A/m)	Limit (A/m)	% of General Public Limit
1	6.07	90	6.74%
2	3.01	90	3.34%
3	1.76	90	1.95%
4	3.20	90	3.55%
5	27.59	90	30.65%
6	0.68	90	0.76%
7	0.35	90	0.39%

Note: Measurement recorded in  $\mu\text{T}$  and converted to A/m

Table 7-2: E-Field Result

Survey point #	Measured Electric Field (V/m)	Limit (V/m)	% of General Public Limit
1	0.72	83	0.87%
2	0.64	83	0.77%
3	2.98	83	3.59%
4	1.76	83	2.12%
5	1.9	83	2.29%
6	7.3	83	8.80%
7	0.82	83	0.99%

Note 1: For survey point locations refer to appendix D

Note 2: Measurements performed at 0mm spacing (worst case)

An E-Field and H-Field Spatial Averaging measurement performed at survey point # 8, the recorded E-field was 0.62 V/m and 0.70 A/m for magnetic field.

### 7.2 Bluetooth Module Results

The separation distance between the Bluetooth antenna and the user at least 30mm, and the output power 3 dBm (2mW).

The standalone transmitter is exempted from SAR if the below condition satisfied in conjunction with threshold power condition in table 1

$$\frac{\text{max. power of channel, including tune – up tolerance (mW)}}{\text{min. test separation distance (mm)}} * \sqrt{f(\text{GHz})} \leq 3.0$$

Where

Minimum test separation distance (30mm):

The minimum test separation distance is determined by the smallest distance from the antenna (radiating structures) to the outer surface of the device

Maximum power of channel (mW):

Time-averaged maximum conducted output power

$$\frac{\text{max. power of channel, including tune – up tolerance (mW)}}{\text{min. test separation distance (mm)}} * \sqrt{f(\text{GHz})} = \frac{2\text{mW}}{30\text{mm}} * \sqrt{2.45 \text{ GHz}}$$
$$= 0.1 \leq 3.0$$

As the transmitted power is 3 dBm (2 mW) less than 57 mW indicated in table (1) and the result of the above condition is 0.1 (less than 3), hence this transmitter excepted from SAR evaluation

## 8 CONCLUSION

Based on an assessment of the documentation provided and performed measurements the PLATYPUS2 METAL DETECTOR, model EQUINOX 700, EQUINOX 900 complies with the RF exposure requirements of 447498 D01



Accreditation No.5292

Except for the Certificate of Compliance, this document must only be reproduced in full.

## 9 APPENDIX A – PROBE DATASHEET

Probe data sheet



WP400\_Datasheet\_  
EN.pdf



Accreditation No.5292


Except for the Certificate of Compliance, this document must only be reproduced in full.

# WP400 Probe

## 1 Hz - 400 kHz



- Electric & Magnetic field measurement
- Isotropic & True RMS measurement
- Spectrum analysis probe
- Measurements in accordance with International Standards
- 100 cm<sup>2</sup> sensor



### Power grid

Measurement of the exposure to EM fields at transformer stations and high-voltage lines.



### Railway

Measurement of EM fields in trains and in the railway environment with respect to human exposure.



### Industry

Assessment of workers' exposure to EM fields in all kind of manufacturing facilities.



## Technical Specifications

	Electric Field	Magnetic Field
Sensor type	Isotropic patented electrodes	
Frequency range	1 Hz – 400 kHz	1 Hz – 400 kHz
<b>Field Strength Mode</b>		
Measurement range	1 V/m to 100 kV/m	50 nT - 10 mT (100 Hz - 10 kHz) · Upper range increases linearly with decreasing frequency below 100 Hz. · Upper range decreases linearly with increasing frequency above 10 kHz.
Graphical display	RMS, Axis Values, AVG, MAX, MIN, PEAK, RMS time graph	
Peak value	digital realtime	digital realtime
Resolution	< 0.4 mV/m above 8 Hz	< 0.1 nT (at 50 Hz) and < 0.05 nT above 100 Hz
Noise level	< 1 V/m (10 Hz - 400 kHz)	< 50 nT (10 Hz – 400 kHz)
<b>Weigthed Peak Method mode</b>		
Measurement range	200 % (min)	200 % (min)
Graphical display	PEAK (%), AXIS VALUES (%), AVG (%), MAX (%), MIN (%), RMS (%), Time graph	
Standards/Limits	EU Directive 2013/35/EU, FCC/IEEE, ICNIRP, BGV B11. Easy software update to future modifications and to other limits.	



WP400\_EN\_L1904\_V2.2

# WP400 Probe

## 1 Hz - 400 kHz



### Technical Specifications



	Electric Field	Magnetic Field
<b>FFT Mode</b>		
<b>Measurement range</b>	4 mV/m – 100 kV/m	0.5 nT – 10 mT (100 Hz - 10 kHz) · Upper range increases linearly with decreasing frequency below 100 Hz. · Upper range decreases linearly with increasing frequency above 10 kHz.
<b>Graphical display</b>	Frequency analysis, total field and axis	
<b>SPAN (Resolution)</b>	400 Hz (1 Hz) - 4 kHz (10 Hz) - 40 kHz (100 Hz) - 400 kHz (1 kHz)	
<b>Noise level</b>	< 4 mV/m	< 0.5 nT
<b>FFT</b>	1024 point FFT	
<b>General Specifications</b>		
<b>Isotropy</b>	± 5 %	± 4 %
<b>Typical Uncertainty (1)</b>	0.67 dB	0.60 dB
<b>Temperature deviation [typ. at 60 Hz] (referred to 25 °C, 50 % relative humidity)</b>	- 0.005 dB/°C (- 15 °C to 40 °C)	- 0.003 dB/°C (- 15 °C to 25 °C) + 0.003 dB/°C (25 °C to 40 °C)
<b>Damage level</b>	> 200 kV/m	> 2000 mT up to 60 Hz Damage level decreases linearly with increasing frequency above 60 Hz
<b>Linearity</b>	± 1 % (typ.) ± 2 % (max.)	
<b>Weight</b>	220 g	
<b>Probe size</b>	280 mm x 128 mm Ø	


(1) Total, counting isotropy, temperature deviation, resolution, frequency response, linearity, repeatability.




Product specifications and descriptions in this document subject to change without notice


### 10 APPENDIX B – MEASUREMENT PLOTS























## 11 APPENDIX C – SUPPLIED INFORMATION

### *Referenced Documents*

Document	Comments
Tormentor_Form 005 Customer and EUT Information2-20211222	EUT and Transmitter details
SWRU120D	Antenna details
nRF5340_OPS_v0.5.1	Bluetooth Chip Specification



Accreditation No.5292

Except for the Certificate of Compliance, this document must only be reproduced in full.