

FCC Test Report

Report No.: AGC14521230901FR01

FCC ID	:	Z4C-0061
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Wireless Audio Module
BRAND NAME	:	MINELAB
MODEL NAME	:	WM09
APPLICANT	:	Minelab Electronics Pty Ltd
DATE OF ISSUE	:	Sep. 21, 2023
STANDARD(S)	:	FCC Part 15 Subpart C §15.247
REPORT VERSION	:	V1.0







Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Sep. 21, 2023	Valid	Initial Release



Table of Contents

1.	General Information	5
2	Product Information	6
	2.1 Product Technical Description	6
	2.2 Test Frequency List	6
	2.3 Related Submittal(S) / Grant (S)	7
	2.4 Test Methodology	7
	2.5 Special Accessories	7
	2.6 Equipment Modifications	7
	2.7 Antenna Requirement	7
3.	. Test Environment	8
	3.1 Address of the Test Laboratory	8
	3.2 Test Facility	8
	3.3 Environmental Conditions	9
	3.4 Measurement Uncertainty	9
	3.5 List of Equipment Use	
4	System Test Configuration	12
	4.1 EUT Configuration	12
	4.2 EUT Exercise	12
	4.3 Configuration of Tested System	12
	4.4 Equipment Used In Tested System	
	4.5 Summary of Test Results	13
5.	Description of Test Modes	14
6	Duty Cycle Measurement	15
7.	RF Output Power Measurement	16
	7.1 Provisions Applicable	16
	7.2 Measurement Procedure	16
	7.3 Measurement Setup (Block Diagram of Configuration)	16
	7.4 Measurement Result	17
8	. 6dB Bandwidth Measurement	21
	8.1 Provisions Applicable	21
	8.2 Measurement Procedure	21
	8.3 Measurement Setup (Block Diagram of Configuration)	21
	8.4 Measurement Results	22
9.	Power Spectral Density Measurement	29
	9.1 Provisions Applicable	
	9.2 Measurement Procedure	29
	9.3 Measurement Setup (Block Diagram of Configuration)	
	9.4 Measurement Results	30
1(0. Conducted Band Edge And Out-of-Band Emissions	34



10.2 Maggurgement Dragodurg	24
10.2 Measurement Procedure	
10.3 Measurement Setup (Block Diagram of Configuration)	
10.4 Measurement Results	
11. Radiated Spurious Emission	
11.1 Measurement Limits	
11.2 Measurement Procedure	
11.3 Measurement Setup (Block Diagram of Configuration)	
11.4 Measurement Result	
12. AC Power Line Conducted Emission Test	
12.1 Measurement Limits	
12.2 Measurement Setup (Block Diagram of Configuration)	
12.3 Preliminary Procedure of Line Conducted Emission Test	
12.4 Final Procedure of Line Conducted Emission Test	
12.5 Measurement Results	
Appendix I: Photographs of Test Setup	
Appendix II: Photographs of Test EUT	



1. General Information

Applicant	Minelab Electronics Pty Ltd
Address	2 Second Avenue, Mawson Lakes, SA 5095, Australia
Manufacturer	Minelab Electronics Pty Ltd
Address	2 Second Avenue, Mawson Lakes, SA 5095, Australia
Factory	Plexus Manufacturing SDN BHD (Seaside)
Address	Bayan Lepas Free Industrial Zone, Phase IV, Bayan, Lepas, Penang, Malaysia.
Product Designation	Wireless Audio Module
Brand Name	MINELAB
Test Model	WM09
Series Model(s)	N/A
Difference Description	N/A
Date of receipt of test item	Sep. 08, 2023
Date of Test	Sep. 08, 2023 to Sep. 21, 2023
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-BLE-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Thea Huang Prepared By Thea Huang Sep. 21, 2023 (Project Engineer) **Reviewed By** Calvin Liu Sep. 21, 2023 (Reviewer) ax cran Approved By

oved by

Sep. 21, 2023

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Max Zhang

(Authorized Officer)

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com



2. Product Information

2.1 Product Technical Description

Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2402MHz-2480MHz
Bluetooth Version	V5.2
Modulation Type	BLE GFSK 1Mbps GFSK 2Mbps
Number of channels	40
Carrier Frequency of Each Channel	40 Channel (37 hopping + 3 advertising channel)
Channel Separation	2 MHz
Maximum Transmitter Power	BLE GFSK 1Mbps: -2.580dBm (0.552mW) BLE GFSK 2Mbps:-2.613dBm (0.548mW)
Hardware Version	rev 1
Software Version	1.2.0+5
Antenna Designation	PCB Antenna
Antenna Gain	3.3dBi
Power Supply	DC 3.7V by battery or DC 5V by adapter
Adapter Information	N/A

2.2 Test Frequency List

Frequency Band	Channel Number	Frequency			
	0	2402 MHz			
	1	2404 MHz			
	:	:			
2400~2483.5MHz	19	2440MHz			
	:	:			
	38	2478 MHz			
	39	2480 MHz			
Note: $f = 2402 + 2^{k}$ MHz, $k = 0,, 39$ f is the operating frequency (MHz) k is the operating channel.					



2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **Z4C-0061**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

2.5 Special Accessories

Not available for this EUT intended for grant.

2.6 Equipment Modifications

Not available for this EUT intended for grant.

2.7 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 3.3dBi.



3. Test Environment

3.1 Address of the Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories).

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 Environmental Conditions

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 3.7V

3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard

uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$
Uncertainty of Occupied Channel Bandwidth	U _c = ±2 %



3.5 List of Equipment Use

• R	RF Conducted Test System							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2023-06-01	2024-05-31	
	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2023-03-03	2024-03-02	
	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2023-03-03	2024-03-02	
	AGC-EM-A152	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08	
	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A	
	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A	
Radiated Spurious Emission								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	

Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2023-02-18	2024-02-17
\boxtimes	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2023-06-03	2024-06-02
\boxtimes	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2023-06-01	2024-05-31
\boxtimes	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2022-03-12	2024-03-11
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10
\boxtimes	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2023-03-23	2024-03-22
\square	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2021-10-31	2023-10-30
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2022-08-04	2024-08-03
\boxtimes	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2023-06-01	2024-05-31
\square	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08

• A	AC Power Line Conducted Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
\boxtimes	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2023-06-03	2024-06-02	
\boxtimes	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2023-06-03	2024-06-02	
\boxtimes	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2024-06-08	



• Tes	st Software				
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information
	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71
	AGC-EM-S003	RE-Test System	FARA	EZ-EMC	VRA-03A
\boxtimes	AGC-ER-S012	BT/WIFI-Test System	Tonscend	JS1120-2	2.6
\boxtimes	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0



4.System Test Configuration

4.1 EUT Configuration


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:



Conducted Emission Configure:

EUT

4.4 Equipment Used In Tested System

The following peripheral devices and interface cables were connected during the measurement:

☐ Test Accessories Come From The Laboratory

No.	Equipment	Model No.	Specification Information	Note		
1	Control Box	UART	N/A	AE		
I Test Accessories Come From The Manufacturer						
No.	Equipment	Model No.	ID or Specification	Note		
1	Wireless Audio Module	WM09	Z4C-0061	EUT		



4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203&15.247(b)(4)	Antenna Equipment	Pass
2	§15.247 (b)(1)	RF Output Power	Pass
3	§15.247 (a)(1)	6 dB Bandwidth	Pass
4	§15.247 (e)	Power Spectral Density	Pass
4	§15.247 (d)	Conducted Band Edge and Out-of-Band Emissions	Pass
5	§15.209	Radiated Emission& Band Edge	Pass
6	§15.207	AC Power Line Conducted Emission	Not applicable

Note: The BT function cannot transmit when charging.



5. Description of Test Modes

	Summary Table of Test Cases
	Data Rate / Modulation
Test Item	Bluetooth – LE / GFSK
Radiated & Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps(Battery powered) Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps(Battery powered) Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps(Battery powered) Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps(Battery powered) Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps(Battery powered) Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps(Battery powered)
AC Conducted Emission	Not applicable
Note:	
 The battery is full-cha For Radiated Emission 	worst case was recorded in the report, if no other cases. Inged during the test. In, 3axis were chosen for testing for each applicable mode. Nethod, a temporary antenna connector is provided by the manufacture. Software Setting Diagram COM89 - Tera Term VT – – – × File Edit Setup Control Window Help Mart: Start_channel 02 Start channel set to: 2 Mart: Start_channel 02 Start channel set to: 2 Mart: Start to: 2 Mart: Start the RADID TWHER_DEBN Mart: Start the modulated TX carrier Mart: Start the modulated TX carrier




6. Duty Cycle Measurement

The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Peak. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Operating mode	T(µs)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)
BLE_1Mbps	2117	90.74	0.42	0.47
BLE_2Mbps	1050	89.97	0.46	0.95

Remark:

2. The duty cycle of each frequency band mode reflects the determination requirements of the low channel measurement value



The test plots as follows:

^{1.} Duty Cycle factor = 10 * log (1/ Duty cycle)



7. RF Output Power Measurement

7.1 Provisions Applicable

For DTSs employing digital modulation techniques operating in the bands 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W.


7.2 Measurement Procedure

For Peak Power, the testing follows ANSI C63.10 Section 11.9.1.2 Method Integrated band power:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. RBW≥DTS bandwidth
- 3. VBW≥3*RBW.
- 4. SPAN≥VBW.
- 5. Sweep: Auto.
- 6. Detector Function: Peak.
- 7. Trace: Max hold.
- 8. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- For Average power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G:
- 1. The RF output of EUT was connected to the power meter by RF cable and attenuator.
- 2. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power and record the results in the test report.


7.3 Measurement Setup (Block Diagram of Configuration)

⊠For Average power test setup





For peak power test setup




7.4 Measurement Result

	Test Da	ta of Conducted Output	Power	
Test Mode	Test Frequency (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail
	2402	-2.580	≤30	Pass
GFSK_1Mbps	2440	-2.621	≤30	Pass
	2480	-3.049	≤30	Pass
	2402	-2.613	≤30	Pass
GFSK_2Mbps	2440	-2.664	≤30	Pass
	2480	-4.573	≤30	Pass

Test Result of Average Output Power (Reporting Only)


	Test Data of Conducted Output Power							
Test Mode	Test Frequency (MHz)	Average Power (dBm)	Limits (dBm)	Pass or Fail				
	2402	-4.755	≤30	Pass				
GFSK_1Mbps	2440	-4.631	≤30	Pass				
	2480	-5.259	≤30	Pass				
	2402	-4.457	≤30	Pass				
GFSK_2Mbps	2440	-4.854	≤30	Pass				
	2480	-6.629	≤30	Pass				






Test Graphs of Conducted Output Power











8. 6dB Bandwidth Measurement


8.1 Provisions Applicable

The minimum 6 dB bandwidth shall be 500 kHz.

8.2 Measurement Procedure

- 1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) ≥ 3 * RBW.
- 6. Measure and record the results in the test report.

8.3 Measurement Setup (Block Diagram of Configuration)






8.4 Measurement Results


	Test Data of Occupied Bandwidth and DTS Bandwidth								
Test Mode	Test Frequency (MHz)	Occupied Bandwidth (MHz)	DTS BW (MHz)	DTS BW Limits	Pass or Fail				
	2402	1.066	0.696	≥0.5	Pass				
GFSK_1Mbps	2440	1.071	0.714	≥0.5	Pass				
	2480	1.067	0.708	≥0.5	Pass				
	2402	2.108	1.386	≥0.5	Pass				
GFSK_2Mbps	2440	2.140	1.255	≥0.5	Pass				
	2480	2.131	1.315	≥0.5	Pass				

Test Graphs of Occupied Bandwidth






































9. Power Spectral Density Measurement


9.1 Provisions Applicable

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

9.2 Measurement Procedure

- 1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz in order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 6. Measure and record the results in the test report.
- The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

9.3 Measurement Setup (Block Diagram of Configuration)






9.4 Measurement Results

	Test Data of Co	nducted Output Power S	pectral Density	
Test Mode	Test Frequency (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail
	2402	-15.915	≤8	Pass
GFSK_1Mbps	2440	-15.746	≤8	Pass
	2480	-15.490	≤8	Pass
	2402	-18.431	≤8	Pass
GFSK_2Mbps	2440	-17.937	≤8	Pass
	2480	-20.382	≤8	Pass


Test Graphs of Conducted Output Power Spectral Density














📕 Keysight Sp 🛛 R L	ectrum Analyzer - Swe RF 50 Ω		ORREC		ICT. THT			02:25:40.0	10 10, 0000	_	
	req 2.48000	0000 G					ALIGN AUTO e: Log-Pwr : 94/100	TRAC	M Sep 13, 2023 E 1 2 3 4 5 6 E M WWWWWW F P N N N N N	Frec	luency
0 dB/div	Ref 20.00 d	IBm					Mkr1 2		7 4 GHz 82 dBm	A	uto Tun
10.0											nter Fre 00000 GH
0.0											Start Fre 13750 Gi
20.0 30.0	hww.	hallipa		<u>አ</u> ሉባቸካታትሌ	N/41/V4n	mmhayy/	X, May AMA	Maynan	ALVAL MANNA		Stop Fre 86250 GI
										1 <u>Auto</u>	CF Ste 97.250 kł Ma
60.0										Fr	eq Offs 0 F
70.0	4900000 000							Chan-4	072 Mills		
	4800000 GHz 3.0 kHz		#VBW	/ 10 kHz			Sweep 2	08.0 ms (.973 MHz 1000 pts)		
		Test	Graph	LE2N		Г1_248	0_2Mb	ps_PS	SD		





10. Conducted Band Edge And Out-of-Band Emissions

10.1 Provisions Applicable


The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure.

10.2 Measurement Procedure

- Reference level measurement
- 1. Set instrument center frequency to DTS channel center frequency
- 2. Set the span to \geq 1.5 times the DTS bandwidth
- 3. Set the RBW = 100 kHz
- 4. Set the VBW \geq 3 x RBW
- 5. Detector = peak
- 6. Sweep time = auto couple
- 7. Trace mode = max hold
- 8. Allow trace to fully stabilize
- Emission level measurement
- 1. Set the center frequency and span to encompass frequency range to be measured
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep time = auto couple
- 7. The trace was allowed to stabilize

10.3 Measurement Setup (Block Diagram of Configuration)

Spectrum Analyzer






10.4 Measurement Results




Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands











































Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands







11. Radiated Spurious Emission

11.1 Measurement Limits

FCC Part 15.209 Limit in the below table to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

11.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.

Any rep Ashang alternative by provided ther transmitter aloperates a forrial orgen than on the seconds) e Orbin cases in where is the Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

10.In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

Spectrum ParameterSettingStart ~Stop Frequency9KHz~150KHz/RB 200Hz for QPStart ~Stop Frequency150KHz~30MHz/RB 9KHz for QPStart ~Stop Frequency30MHz~1000MHz/RB 120KHz for QPStart ~Stop Frequency1GHz~26.5GHzStart ~Stop Frequency1MHz/3MHz for Peak, 1MHz/3MHz for Average

The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP



• Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize


<u>Average Measurements above 1GHz (Method VB)</u>

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW setting requirements are as follows:
- 4. If the EUT is configured to transmit with duty cycle \ge 98%, set VBW = 10 Hz.
- 5. If the EUT duty cycle is < 98%, set VBW \ge 1/T. T is the minimum transmission duration.
- 6. Detector = Peak
- 7. Sweep time = auto
- 8. Trace mode = max hold
- 8. Trace was allowed to stabilize




11.3 Measurement Setup (Block Diagram of Configuration)






Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com



11.4 Measurement Result

Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

			Radia	ted Emiss	ion Test Res	ults at 30MH	z-1GHz			
EUT Nan	ne	Wireless Audio Module			Model Na	ime	WM09			
Tempera	ture	23.9	°C		Relative Humidity 59.8%					
Pressure	•	960h	nPa			Test Volta	age	Normal Voltage		
Test Mod	e	Mode	e 1			Polarity:			I	
	ľ									
	130				FCC PART 1	5C				
	120 110									
	100									
	90									
[m,	80 70									
Level[dBµV/m]	60									
Level	50									
	40 30						* ³ * ⁴	* ⁵		
	20			*		**************************************	monteresting	where the second states and the second se		
	10			~~	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~					
	-10									
	30M			100M					1G	
		QP Limit	Horizontal PK		Frequency[H	12]				
	*	QP Detector	r							
Final Dat										
	Freq.		Level	Factor	Limit	Margin	Height	Angle		
NO.	[MHz		[dBµV/m]	[dB]	[dBµV/m]	[dB]	[cm]		Polarity	
1	100.8	-	25.00	20.58	43.50	18.50	100	10	Horizonta	
2	233.7	,	22.73	15.76	46.00	23.27	100	310	Horizonta	
3	425.7		31.29	22.14	46.00	14.71	100	170	Horizonta	
4	457.7		32.15	26.38	46.00	13.85	100	40	Horizonta	
5	615.8	8	32.57	27.10	46.00	13.43	100	340	Horizonta	
6	879.72	2	37.07	31.94	46.00	8.93	100	170	Horizonta	



100

100

100

100

100

100

18.68

17.45

17.64

13.57

10.89

8.46

10

150

320

290

220

210

Vertical

Vertical

Vertical

Vertical

Vertical

Vertical

			Radi	ated Emiss	ion Test Res	ults at 30MH	z-1GHz		
EUT Na	ime	Wireless Audio Module Model Name			WM09	WM09			
Temper	rature	23.9	°C		Relative Humidity 59.8%	ve Humidity 59.8%			
Pressu	re	960ł	nPa	Test Voltage			age	Normal Voltage	
Test Mo	de	Mod	e 1			Polarity:		Vertical	
L evel(dBj.Vm)	40 30 20 10 -10 30M	- OP Limit		100M	FCC PART 150				16
Final Da	*	QP Detecto							
NO.	Freq [MHz		Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity

RESULT: Pass

1

2

3

4

5

6

67.83

149.31

423.82

699.3

782.72

845.77

Note: 1. Factor=Antenna Factor + Cable loss, Margin= Limit-Level.

21.32

26.05

28.36

32.43

35.11

37.54

13.43

20.25

20.82

27.86

29.63

31.15

2. All test modes had been pre-tested. The mode 1 is the worst case and recorded in the report.

40.00

43.50

46.00

46.00

46.00

46.00



UT Name		Wireless A			Mode			
emperature		23.9°C			Relative Humidity 59.8% Test Voltage Normal Voltage			
ressure		960hPa					Normal V	oltage
est Mode	est Mode 1				Anter	nna Polarity	Horizontal	
Frequency	Met	er Reading	Factor	Emissio	n Level	Limits	Margin	Value Type
(MHz)		(dBµV)	(dB)	(dBµ\	√/m)	(dBµV/m)	(dB)	value Type
4804.000		46.85	0.08	46.9	93	74	-27.07	peak
4804.000		35.41	0.08	35.4	49	54	-18.51	AVG
7206.000		41.27	2.21	43.4	48	74	-30.52	peak
7206.000		31.69	2.21	33.	.9	54	-20.1	AVG
Remark: Factor = Anter	nna Fa	actor + Cable	e Loss – Pre-	amplifier.				
Factor = Anter	nna Fa	Wireless A	e Loss – Pre- udio Module	amplifier.		I Name	WM09	
⁻ actor = Anter	nna Fa			amplifier.	Relat	I Name ive Humidity /oltage	WM09 59.8% Normal V	oltage
Factor = Anter UT Name emperature	nna Fa	Wireless A 23.9°C		amplifier.	Relat	ive Humidity	59.8%	oltage
Factor = Anter UT Name emperature ressure est Mode		Wireless A 23.9°C 960hPa Mode 1	udio Module		Relat Test V Anter	ive Humidity /oltage nna Polarity	59.8% Normal V Vertical	oltage
Factor = Anter UT Name emperature ressure est Mode Frequency		Wireless A 23.9°C 960hPa Mode 1 er Reading	udio Module	Emissio	Relat Test V Anter	ive Humidity /oltage nna Polarity	59.8% Normal V Vertical Margin	oltage Value Type
Factor = Anter UT Name emperature ressure est Mode Frequency (MHz)		Wireless A 23.9°C 960hPa Mode 1 er Reading (dBµV)	udio Module Factor (dB)	Emissio (dBµ\	Relat Test V Anter n Level	ive Humidity /oltage nna Polarity Limits (dBµV/m)	59.8% Normal V Vertical Margin (dB)	- Value Type
Factor = Anter		Wireless A 23.9°C 960hPa Mode 1 er Reading (dBµV) 46.74	udio Module Factor (dB) 0.08	Emissio (dBµ\ 46.8	Relat Test V Anter n Level V/m) 82	ive Humidity /oltage nna Polarity Limits (dBµV/m) 74	59.8% 59.8% Vormal V Vertical Margin (dB) -27.18	- Value Type peak
Factor = Anter		Wireless A 23.9°C 960hPa Mode 1 er Reading (dBµV) 46.74 35.56	Exactor (dB) 0.08 0.08	Emissio (dBµ\ 46.8 35.6	Relat Test V Anter n Level V/m) 82 64	ive Humidity /oltage nna Polarity Limits (dBµV/m) 74 54	59.8% Normal V Vertical Margin (dB) -27.18 -18.36	- Value Type peak AVG
Factor = Anter		Wireless A 23.9°C 960hPa Mode 1 er Reading (dBµV) 46.74 35.56 41.33	Factor (dB) 0.08 0.08 2.21	Emissio (dBµ\ 46.8 35.6 43.9	Relat Test V Anter n Level V/m) 82 64 54	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54 74	59.8% Normal V Vertical Margin (dB) -27.18 -18.36 -30.46	- Value Type peak AVG peak
Factor = Anter		Wireless A 23.9°C 960hPa Mode 1 er Reading (dBµV) 46.74 35.56	Exactor (dB) 0.08 0.08	Emissio (dBµ\ 46.8 35.6	Relat Test V Anter n Level V/m) 82 64 54	ive Humidity /oltage nna Polarity Limits (dBµV/m) 74 54	59.8% Normal V Vertical Margin (dB) -27.18 -18.36	- Value Type peak AVG

Radiated Emissions Test Results for Above 1 GHz

RESULT: Pass



UT Name		Wireless A		Mod	el Name		WM09			
emperature		23.9°C			Relative Humidity			59.8%		
ressure		960hPa	960hPa Test Voltage Normal		Test Voltage			Normal Voltage		
est Mode		Mode 2			Ante	enna Polarit	у	Horizor	ntal	
Frequency	Me	eter Reading	Factor	Emissior	n Level	Limits		Margin	Value Type	
(MHz)		(dBµV)	(dB)	(dBµ∖	//m)	(dBµV/m)		(dB)	value Type	
4882.000		45.52	0.14	45.6	6	74		-28.34	peak	
4882.000		36.39	0.14	36.5	53	54		-17.47	AVG	
7323.000		41.41	2.36	43.7	77	74		-30.23	peak	
7323.000		34.74	2.36	37.	1	54		-16.9	AVG	
Remark:										
	enna F	actor + Cab	le Loss – Pre	-amplifier.						
Factor = Ante	enna F		le Loss – Pre udio Module	-amplifier.	Mode	el Name		WM09		
Factor = Ante	enna F			-amplifier.		el Name tive Humidi	ity	WM09 59.8%		
Factor = Ante	enna F	Wireless A		-amplifier.	Rela		ity	59.8%	Voltage	
Factor = Ante	enna F	Wireless A 23.9°C		-amplifier.	Rela Test	tive Humid		59.8%	U	
Factor = Ante		Wireless A 23.9°C 960hPa Mode 2	udio Module		Rela Test Ante	tive Humidi Voltage enna Polarit	у	59.8% Normal Vertical		
Factor = Ante	Meter	Wireless A 23.9°C 960hPa Mode 2 Reading	udio Module	Emission Le	Relat Test Ante	tive Humidi Voltage nna Polarit	у Ма	59.8% Normal	U	
Factor = Ante	Meter (c	Wireless A 23.9°C 960hPa Mode 2	udio Module		Relat Test Ante	tive Humidi Voltage enna Polarit Limits (dBµV/m)	у Ма	59.8% Normal Vertical		
Factor = Ante	Meter (c	Wireless A 23.9°C 960hPa Mode 2 Reading iBµV)	udio Module Factor (dB)	Emission Le	Relat Test Ante	tive Humidi Voltage nna Polarit	у Ма ((59.8% Normal Vertical argin dB)	Value Type	
Factor = Ante	Meter (c 4	Wireless A 23.9°C 960hPa Mode 2 Reading IBµV) 5.36	udio Module Factor (dB) 0.14	Emission Le (dBµV/m 45.5	Relat Test Ante	tive Humidi Voltage enna Polarit Limits (dBµV/m) 74	y Ma ((-2	59.8% Normal Vertical urgin 1B) 28.5	Value Type peak	
Factor = Ante	Meter (c 4 3 4	Wireless A 23.9°C 960hPa Mode 2 Reading 1BµV) 15.36 55.74	Factor (dB) 0.14 0.14	Emission Le (dBµV/m 45.5 35.88	Relat Test Ante	tive Humidi Voltage enna Polarit Limits (dBµV/m) 74 54	y Ma ((-2 -1) -3	59.8% Normal Vertical Irgin JB) 88.5 8.12	Value Type peak AVG	
Factor = Ante	Meter (c 4 3 4	Wireless A 23.9°C 960hPa Mode 2 Reading 1BµV) 5.36 5.74 1.41	Exactor (dB) 0.14 0.14 2.36	Emission Le (dBµV/m 45.5 35.88 43.77	Relat Test Ante	tive Humidi Voltage enna Polarit Limits (dBµV/m) 74 54 74	y Ma ((-2 -1) -3	59.8% Normal Vertical Ingin (B) (8.5) (3.12) (0.23)	Value Type peak AVG peak	
Factor = Ante	Meter (c 4 3 4	Wireless A 23.9°C 960hPa Mode 2 Reading 1BµV) 5.36 5.74 1.41	Exactor (dB) 0.14 0.14 2.36	Emission Le (dBµV/m 45.5 35.88 43.77	Relat Test Ante	tive Humidi Voltage enna Polarit Limits (dBµV/m) 74 54 74	y Ma ((-2 -1) -3	59.8% Normal Vertical Ingin (B) (8.5) (3.12) (0.23)	Value Type peak AVG peak	

Radiated Emissions Test Results for Above 1GHz

RESULT: Pass



EUT Name	Wireless Au	Wireless Audio Module		Model	Name	WM09		
Temperature	23.9°C			Relativ	ve Humidity	59.8%	59.8%	
Pressure	960hPa	ıPa			oltage	e Normal Voltage		
Test Mode	Mode 3			Anten	na Polarity	Horizonta	al	
Frequency	Meter Reading	Factor	Emissic	on Level	Limits	Margin		
(MHz)	(dBµV)	(dB)	(dBµ	V/m)	(dBµV/m)	(dB)	Value Type	
4960.000	46.65	0.22	46.	.87	74	-27.13	peak	
4960.000	34.88	0.22	35	.1	54	-18.9	AVG	
7440.000	41.49	2.64	44.	.13	74	-29.87	peak	
7440.000	32.33	2.64	34.	.97	54	-19.03	AVG	
Remark:								
Factor = Ante	nna Factor + Cabl	e Loss – Pre-a	amplifier.					
EUT Name	Wireless Au	dio Module		Model	Name	WM09		
Temperature	23.9°C			Relativ	ve Humiditv	59.8%		

Radiated Emissions Test Results for Above 1GHz

Lot Name		Model Name	111105
Temperature	23.9°C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	- Value Type
4960.000	46.48	0.22	46.7	74	-27.3	peak
4960.000	34.51	0.22	34.73	54	-19.27	AVG
7440.000	41.74	2.64	44.38	74	-29.62	peak
7440.000	32.63	2.64	35.27	54	-18.73	AVG
emark:						

RESULT: Pass


Note:

- 1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.
- 4. All test modes had been tested. The BLE GFSK 1Mbps is the worst case and recorded in the report.




EUT Name	Wireless Audio Module	Model Name	WM09
Temperature	23.9°C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna Polarity	Horizontal

Test Graph for Peak Measurement




Test Graph for Average Measurement




RESULT: Pass



EUT Name	Wireless Audio Module	Model Name	WM09
Temperature	23.9°C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna Polarity	Vertical



Test Graph for Average Measurement




RESULT: Pass



EUT Name	Wireless Audio Module	Model Name	WM09
Temperature	23.9°C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: Pass




EUT Name	Wireless Audio Module	Model Name	WM09
Temperature	23.9°C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: Pass




EUT Name	Wireless Audio Module	Model Name	WM09
Temperature	23.9°C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna Polarity	Horizontal

Test Graph for Peak Measurement




Test Graph for Average Measurement




RESULT: Pass



EUT Name	Wireless Audio Module	Model Name	WM09
Temperature	23.9°C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna Polarity	Vertical



Test Graph for Average Measurement



RESULT: Pass




EUT Name	Wireless Audio Module	Model Name	WM09
Temperature	23.9°C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna Polarity	Horizontal



Test Graph for Peak Measurement

Test Graph for Average Measurement




RESULT: Pass




EUT Name	Wireless Audio Module	Model Name	WM09
Temperature	23.9°C	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: Pass

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



12. AC Power Line Conducted Emission Test

12.1 Measurement Limits


Frequency	Maximum RF Line Voltage		
Frequency	Q.P. (dBµV)	Average (dBµV)	
150kHz~500kHz	66-56	56-46	
500kHz~5MHz	56	46	
5MHz~30MHz	60	50	

Note:

1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

12.2 Measurement Setup (Block Diagram of Configuration)





12.3 Preliminary Procedure of Line Conducted Emission Test

- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


12.4 Final Procedure of Line Conducted Emission Test

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

12.5 Measurement Results

N/A

Note: The BT function cannot transmit when charging





Appendix I: Photographs of Test Setup Refer to the Report No.: AGC14521230901AP02

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC14521230901AP03

-----End of Report-----



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.