


SAR Evaluation Report

Application No.: SZEM1903011713CR
Applicant: Seeed Technology Co., Ltd.
Address of Applicant: 9F, G3 Building, TCL International E City, Zhongshanyuan Road, Nanshan District, Shenzhen, China 518055
Manufacturer: Seeed Technology Co., Ltd.
Address of Manufacturer: 9F, G3 Building, TCL International E City, Zhongshanyuan Road, Nanshan District, Shenzhen, Guangdong Province, P.R.C.
Factory: Seeed Technology Co., Ltd.
Address of Factory: 1F, Tower B, Building 2, Shanshui Building, NanshanYungu Innovation Industry Park, Liuxian Ave, Nanshan District, Shenzhen, Guangdong, P.R.C.
Equipment Under Test (EUT):
EUT Name: Microsoft Sensor Box v3
Model No.: Microsoft Sensor Box v3(915 MHz)
Trade mark: Seeedstudio
FCC ID: Z4T-MSESENSORBOX
Standards: 47 CFR Part 1.1307
 47 CFR Part 1.1310
Date of Receipt: 2019-03-15
Date of Test: 2019-03-19 to 2019-04-15
Date of Issue: 2019-04-25

| | |
|----------------------|--------------|
| Test Result : | PASS* |
|----------------------|--------------|

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu
 EMC Laboratory Manager



2 Version

| <i>Revision Record</i> | | | | |
|------------------------|----------------|-------------|-----------------|---------------|
| <i>Version</i> | <i>Chapter</i> | <i>Date</i> | <i>Modifier</i> | <i>Remark</i> |
| 01 | | 2019-04-25 | | Original |
| | | | | |
| | | | | |

| | | | |
|---------------------------------|--|---|--|
| Authorized for issue by: | | | |
| | |  | |
| | | <hr/> Harry Wu /Project Engineer | |
| | |  | |
| | | <hr/> Eric Fu /Reviewer | |





3 Contents

| | Page |
|---|------|
| 1 COVER PAGE | 1 |
| 2 VERSION | 2 |
| 3 CONTENTS | 3 |
| 4 GENERAL INFORMATION | 4 |
| 4.1 GENERAL DESCRIPTION OF EUT | 4 |
| 4.2 TEST LOCATION | 5 |
| 4.3 TEST FACILITY | 5 |
| 4.4 DEVIATION FROM STANDARDS | 5 |
| 4.5 ABNORMALITIES FROM STANDARD CONDITIONS | 5 |
| 4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER | 5 |
| 5 SAR EVALUATION | 6 |
| 5.1 RF EXPOSURE COMPLIANCE REQUIREMENT | 6 |
| 5.1.1 Limits | 6 |
| 5.1.2 Test Procedure | 6 |
| 5.1.3 EUT RF Exposure Evaluation | 7 |



4 General Information

4.1 General Description of EUT

| | |
|----------------------|--------------------------------------|
| Power supply: | DC 12.0V(8 x 1.5V Size"D" Batteries) |
| BLE | |
| Operation Frequency: | 2402MHz to 2480MHz |
| Bluetooth Version: | V4.0 |
| Modulation Type: | GFSK |
| Number of Channels: | 40 |
| Channel Spacing: | 2MHz |
| Antenna Type: | Integral Antenna |
| Antenna Gain: | 0dBi |
| Lora | |
| Operation Frequency: | 902.3MHz to 914.9MHz |
| Antenna Type: | Integral Antenna |
| Antenna Gain: | 3dBi |



4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.4 Deviation from Standards

None.

4.5 Abnormalities from Standard Conditions

None.

4.6 Other Information Requested by the Customer

None.



5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures | | | | |
| 0.3–3.0 | 614 | 1.63 | *(100) | 6 |
| 3.0–30 | 1842/f | 4.89/f | *(900/f ²) | 6 |
| 30–300 | 61.4 | 0.163 | 1.0 | 6 |
| 300–1500 | | | f/300 | 6 |
| 1500–100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1500 | | | f/1500 | 30 |
| 1500–100,000 | | | 1.0 | 30 |

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

5.1.3 EUT RF Exposure Evaluation

Remark: The Bluetooth and Lora function can't simultaneous transmission.

For BLE:

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

| Channel | Frequency (MHz) | Max Conducted Peak Output Power(including tune-up tolerance) (dBm) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) | Limit | Result |
|---------|-----------------|--|------------------------------|--|-------|--------|
| Middle | 2440 | 0.78 | 1.197 | 0.0002 | 1.0 | PASS |

Note: Refer to report No. SZEM190301171302 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

For Lora:

Antenna Gain: 3dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.00 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

| Channel | Frequency (MHz) | Max Conducted Peak Output Power(including tune-up tolerance) (dBm) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) | Limit | Result |
|---------|-----------------|--|------------------------------|--|-------|--------|
| Middle | 908.7 | 18.875 | 77.18 | 0.0031 | 1.0 | PASS |

Note: Refer to report No. MLTI0045.1 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

- End of the Report -

