

## RF Exposure Evaluation Report

**Product** : LoRaWAN Data Logger  
**Trade mark** : seeed studio  
**Model/Type reference** : S2100  
**Serial Number** : N/A  
**Report Number** : EED32O81631405  
**FCC ID** : Z4T-S2100  
**Date of Issue** : Nov. 25, 2022  
: 47 CFR Part 1.1307  
**Test Standards** : 47 CFR Part 2.1091  
: KDB447498D01 General  
: RF Exposure Guidance v06  
**Test result** : PASS

Prepared for:

**Seed Technology Co., Ltd.**

**9F, G3 Building, TCL International E City, Zhongshanyuan Road,  
Nanshan District, Shenzhen, Guangdong Province, P.R.C**

Prepared by:

**Centre Testing International Group Co., Ltd.  
Hongwei Industrial Zone, Bao'an 70 District,  
Shenzhen, Guangdong, China**

**TEL: +86-755-3368 3668**

**FAX: +86-755-3368 3385**

Compiled by:

*mark.chen.*

Reviewed by:

*Tom Chen*

Mark Chen

Tom Chen

Approved by:

*Aaron Ma*

Date:

Nov. 25, 2022

Aaron Ma

Check No.: 6013171022



## 2 Version

Version No.	Date	Description
00	Nov. 25, 2022	Original

## 3 Contents

	Page
<b>1 COVER PAGE</b> .....	<b>1</b>
<b>2 VERSION</b> .....	<b>2</b>
<b>3 CONTENTS</b> .....	<b>3</b>
<b>4 GENERAL INFORMATION</b> .....	<b>4</b>
4.1 CLIENT INFORMATION .....	4
4.2 GENERAL DESCRIPTION OF EUT .....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD .....	4
4.4 TEST LOCATION .....	5
4.5 DEVIATION FROM STANDARDS .....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS .....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	5
<b>5 RF EXPOSURE EVALUATION</b> .....	<b>6</b>
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	6
5.2 MAXIMUM PERMISSIBLE EXPOSURE .....	7

## 4 General Information

### 4.1 Client Information

Applicant:	Seed Technology Co., Ltd.
Address of Applicant:	9F, G3 Building, TCL International E City, Zhongshanyuan Road, Nanshan District, Shenzhen, Guangdong Province, P.R.C
Manufacturer:	Seed Technology Co., Ltd.
Address of Manufacturer:	9F, G3 Building, TCL International E City, Zhongshanyuan Road, Nanshan District, Shenzhen, Guangdong Province, P.R.C
Factory:	Shenzhen Xinxian Technology Co., Limited
Address of Factory:	F5, Building B17, Hengfeng Industrial City, No. 739 Zhoushi Rd, Baoan District, Shenzhen, Guangdong, P.R.C.

### 4.2 General Description of EUT

Product Name:	LoRaWAN Data Logger
Model No.:	S2100
Trade mark:	seed studio

### 4.3 Product Specification subjective to this standard

Frequency Range:	Bluetooth: 2402MHz to 2480MHz FHSS/DTS LORA: 902MHz~928MHz
Modulation Type:	Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK FHSS/DTS: LORA Chirp Spread Spectrum
Test Power Grade:	Default
Antenna Type	Bluetooth: Chip Antenna LORA: Shrapnel Antenna
Antenna Gain	Bluetooth: 1.32 dBi LORA FHSS/DTS: 1.70 dBi
Power Supply:	DC 3.6V or DC 12V
Max Conducted Peak Output Power:	BLE: -3.53 dBm, BT: -10.08dBm, FHSS: 20.44dBm, DTS: 20.47dBm The Max Conducted Peak Output Power data refer to the report EED32O81631401, EED32O81631402, EED32O81631403, EED32O81631404.
Sample Received Date:	Oct. 17, 2022
Sample tested Date:	Oct. 17, 2022 to Oct. 31, 2022
<p>Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified. The product has three different sensors,its model is:</p> <ol style="list-style-type: none"> <li>1.LoRaWAN EC Sensor</li> <li>2.LoRaWAN pH Sensor</li> <li>3.SenseCAP S2110 Grove to MODBUS RS485 Converter</li> </ol> <p>the report only shows the worst mode.</p>	

## 4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

## 4.5 Deviation from Standards

None.

## 4.6 Abnormalities from Standard Conditions

None.

## 4.7 Other Information Requested by the Customer

None.

## 5 RF Exposure Evaluation

### 5.1 RF Exposure Compliance Requirement

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \text{ \& } S = \frac{E^2}{377}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm<sup>2</sup>



## 5.2 Maximum Permissible Exposure

Substituting the MPE safe distance using  $d = 20$  cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where  $P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power density in mW / cm<sup>2</sup>

**TABLE 1 TO §1.1310(E)(1)—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(i) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
<b>(ii) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

### 1) For BLE

#### Measurement Data:

BLE:

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-3.53	-4±0.5	-3.5	0.447
Middle(2440MHz)	-3.83	-4±0.5	-3.5	0.447
Highest(2480MHz)	-4.32	-4±0.5	-3.5	0.447

BT Classic:

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-10.16	-11±0.5	-10.5	0.089
Middle(2441MHz)	-10.75	-11±0.5	-10.5	0.089
Highest(2480MHz)	-11.18	-11±0.5	-10.5	0.089

$\pi/4$ DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-10.12	-11±1	-10	0.100
Middle(2441MHz)	-10.72	-11±1	-10	0.100
Highest(2480MHz)	-11.85	-11±1	-10	0.100

8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-10.08	-11±0.5	-10.5	0.089
Middle(2441MHz)	-10.71	-11±0.5	-10.5	0.089
Highest(2480MHz)	-11.16	-11±0.5	-10.5	0.089

FHSS:

LORA mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(902.3MHz)	20.44	20±0.5	20.5	112.202
Middle(908.5MHz)	20.41	20±0.5	20.5	112.202
Highest(914.9MHz)	20.37	20±0.5	20.5	112.202



DTS: 500K

LORA mode(Worst)				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(903MHz)	20.43	20±0.5	20.5	112.202
Middle(907.8MHz)	20.47	20±0.5	20.5	112.202
Highest(914.2MHz)	20.41	20±0.5	20.5	112.202

**BLE:**

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
0	2402	0.444	1.355	20	0.00012	1

**BT Classic:**

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
0	2402	0.098	1.355	20	0.00003	1

**LORA FHSS:**

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
1	902.3	110.662	1.479	20	0.0326	0.6

**LORA DTS:**

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm <sup>2</sup> )
4	907.8	111.429	1.479	20	0.0328	0.6

Note: 1. Refer to report No. EED32O81002001, EED32O81002002, EED32O81002003, EED32O81002004.

2. BLE and LoRa that simultaneous transmission is not possible.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

\*\*\* End of Report \*\*\*