

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057

Telephone:	+86 (0) 755 2601 2053
Fax:	+86 (0) 755 2671 0594
Email:	ee.shenzhen@sgs.com

Report No.: SZEM151000664402 Page: 1 of 48

FCC REPORT

Application No:	SZEM1510006644CR
Applicant:	Seeed Technology Co., Ltd
Manufacturer/Factory:	Seeed Technology Co., Ltd
Product Name:	Rephone Kit Create (Xadow GSM + BLE)
Model No.(EUT):	Xadow GSM + BLE v1.0
Add Model No.:	Xadow GSM + BLE v1.1
Trade Mark:	Seeedstudio
FCC ID:	Z4TXADOW-GSMBTV10
Standards:	47 CFR Part 15, Subpart C (2014)
Date of Receipt:	2015-11-23
Date of Test:	2015-11-25 to 2016-01-06
Date of Issue:	2016-01-12
Test Result:	PASS *

^{*} In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEM151000664402 Page: 2 of 48

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2016-01-12		Original

Authorized for issue by:		
	Gebin Sun	2016-01-06
Tested By	(Gebin Sun) /Project Engineer	Date
	Jade Chen	2016-01-12
Prepared By	(Jade Chen) /Clerk	Date
	Eric Fu	2016-01-12
Checked By	(Eric Fu) /Reviewer	Date

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151000664402 Page: 3 of 48

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS

Remark:

Model No.: Xadow GSM + BLE v1.0, Xadow GSM + BLE v1.1

Only the model Xadow GSM + BLE v1.0 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being of sick-screen.



Report No.: SZEM151000664402 Page: 4 of 48

4 Contents

			i ugo
1	CC	OVER PAGE	1
2	VE	RSION	2
3		ST SUMMARY	
			-
4		DNTENTS	
5	GE	ENERAL INFORMATION	5
	5.1	CLIENT INFORMATION	5
	5.2	GENERAL DESCRIPTION OF EUT	
	5.3	TEST ENVIRONMENT	
	5.4	DESCRIPTION OF SUPPORT UNITS	
	5.5		
	5.6	Test Facility	
	5.7 5.8	DEVIATION FROM STANDARDS	
	5.8 5.9	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
	5.10	EQUIPMENT LIST.	
6	TE	ST RESULTS AND MEASUREMENT DATA	
Ū			
	6.1 6.2	ANTENNA REQUIREMENT CONDUCTED PEAK OUTPUT POWER	
	6.3	6DB Occupy Bandwidth	
	6.4	POWER SPECTRAL DENSITY	
	6.5	BAND-EDGE FOR RF CONDUCTED EMISSIONS	
	6.6	SPURIOUS RF CONDUCTED EMISSIONS	23
	6.7	RADIATED SPURIOUS EMISSION	
	6.7		
	6.8	RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	
7	PH	IOTOGRAPHS - EUT TEST SETUP	47
	7.1	RADIATED EMISSION	
	7.2	RADIATED SPURIOUS EMISSION	48
8	PH	IOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	48



Report No.: SZEM151000664402 Page: 5 of 48

5 General Information

5.1 Client Information

Applicant:	Seeed Technology Co., Ltd		
Address of Applicant:	F5, Building 8, Shiling Industrial Park, Xinwei, Number32, Tongsha Road Xili Town, Nanshan District, Shenzhen, China. P.R.C		
Manufacturer:	Seeed Technology Co., Ltd		
Address of Manufacturer:	F5, Building 8, Shiling Industrial Park, Xinwei, Number32, Tongsha Road Xili Town, Nanshan District, Shenzhen, China. P.R.C		
Factory:	Seeed Technology Co., Ltd		
Address of Factory:	F5, Building 8, Shiling Industrial Park, Xinwei, Number32, Tongsha Road Xili Town, Nanshan District, Shenzhen, China. P.R.C		

5.2 General Description of EUT

Product Name:	Rephone Kit Create (Xadow GSM + BLE)	
Model No.:	Xadow GSM + BLE v1.0	
Trade Mark:	Seeedstudio	
Operation Frequency:	2402MHz~2480MHz	
Bluetooth Version:	BT4.0 Dual mode	
Modulation Type:	GFSK	
Number of Channel:	40	
Sample Type:	Mobile device	
Antenna Type:	Integral	
Antenna Gain:	0.5dBi	
Power Supply:	3.7V DC (1 x 3.7V Rechargeable Battery) 520mAh	
	Battery: Charge by DC 5V	

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151000664402 Page: 6 of 48

Operation I	Operation Frequency each of channel						
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel (CH0)	2402MHz
The middle channel (CH19)	2440MHz
The highest channel (CH39)	2480MHz

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151000664402 Page: 7 of 48

5.3 Test Environment

Operating Environment:	
Temperature:	25.0 °C
Humidity:	53 % RH
Atmospheric Pressure:	1010mbar

5.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description Adapter	Manufacturer Apple	Model No. A1357W010A051
Laptop	Lenovo	T430u
Test board	Supplied by client	V1.0.1

The laptop and test board is used only for engineering mode configuration before testing.

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594 No tests were sub-contracted.

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151000664402 Page: 8 of 48

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

· CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

The 3m Semi-anechoic chambers and the 10m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-2, 4620C-3.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.



Report No.: SZEM151000664402 Page: 9 of 48

5.10Equipment List

	RE in Chamber					
ltem	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-05-13	2016-05-13
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16	2016-09-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2014-11-15	2017-11-15
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2015-10-17	2016-10-17
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2014-11-24	2017-11-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-13	2016-05-13
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2015-10-17	2016-10-17
9	Coaxial cable	SGS	N/A	SEL0027	2015-05-13	2016-05-13
10	Coaxial cable	SGS	N/A	SEL0189	2015-05-13	2016-05-13
11	Coaxial cable	SGS	N/A	SEL0121	2015-05-13	2016-05-13
12	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13
13	Band filter	Amindeon	82346	SEL0094	2015-05-13	2016-05-13
14	Barometer	Chang Chun	DYM3	SEL0088	2015-05-13	2016-05-13
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-09	2016-10-09
16	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2015-10-24	2016-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-13	2016-05-13
18	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-05-13	2016-05-13



Report No.: SZEM151000664402 Page: 10 of 48

RF connected test								
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)		
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-09	2016-10-09		
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2015-10-24	2016-10-24		
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2015-10-17	2016-10-17		
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13		
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-13	2016-05-13		
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-13	2016-05-13		
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-04-25	2016-04-25		
8	POWER METER	R & S	NRVS	SEL0144	2015-10-09	2016-10-09		
9	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-04-25	2016-04-25		

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151000664402 Page: 11 of 48

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0.5dBi.





Report No.: SZEM151000664402 Page: 12 of 48

6.2 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)		
Test Method:	ANSI C63.10 2013		
Test Setup:	Spectrum Analyzer Image: Image		
Limit:	30dBm		
Test Mode:	Transmitting with GFSK modulation.		
Instruments Used:	Refer to section 5.10 for details.		
Test Results:	Pass		


Measurement Data


GFSK mode							
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result				
Lowest	5.39	30.00	Pass				
Middle	5.37	30.00	Pass				
Highest	5.12	30.00	Pass				

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM151000664402 Page: 13 of 48







Report No.: SZEM151000664402 Page: 14 of 48





Report No.: SZEM151000664402 Page: 15 of 48

Test Requirement: 47 CFR Part 15C Section 15.247 (a)(2) Test Method: ANSI C63.10 2013 Test Setup: Spectrum Analyzer E.U.T G Non-Conducted Table **Ground Reference Plane** Limit: ≥ 500 kHz Transmitting with GFSK modulation. Test Mode: Instruments Used: Refer to section 5.10 for details. **Test Results:** Pass

6.3 6dB Occupy Bandwidth


Measurement Data

GFSK mode						
Test channel	6dB Occupy Bandwidth (KHz)	Limit (kHz)	Result			
Lowest	720.000	≥500	Pass			
Middle	717.000	≥500	Pass			
Highest	729.000	≥500	Pass			

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM151000664402 Page: 16 of 48





Report No.: SZEM151000664402 Page: 17 of 48





Report No.: SZEM151000664402 Page: 18 of 48

Test Requirement: 47 CFR Part 15C Section 15.247 (e) Test Method: ANSI C63.10 2013 Test Setup: Spectrum Analyzer E.U.T Non-Conducted Table **Ground Reference Plane** Limit: ≤8.00dBm/3kHz Test Mode: Transmitting with GFSK modulation. Instruments Used: Refer to section 5.10 for details. Test Results: Pass

6.4 Power Spectral Density


Measurement Data

GFSK mode						
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result			
Lowest	-10.16	≤8.00	Pass			
Middle	-9.91	≤8.00	Pass			
Highest	-10.12	≤8.00	Pass			

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM151000664402 Page: 19 of 48





Report No.: SZEM151000664402 Page: 20 of 48





Report No.: SZEM151000664402 Page: 21 of 48


6.5 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)				
Test Method:	ANSI C63.10 2013				
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.				
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.				
Test Mode:	Transmitting with GFSK modulation.				
Instruments Used:	Refer to section 5.10 for details.				
Test Results:	Pass				





Report No.: SZEM151000664402 Page: 22 of 48





Report No.: SZEM151000664402 Page: 23 of 48


6.6 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2013
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Transmitting with GFSK modulation.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM151000664402 Page: 24 of 48






Report No.: SZEM151000664402 Page: 25 of 48






Report No.: SZEM151000664402 Page: 26 of 48






Report No.: SZEM151000664402 Page: 27 of 48






Report No.: SZEM151000664402 Page: 28 of 48






Report No.: SZEM151000664402 Page: 29 of 48



[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM151000664402 Page: 30 of 48






Report No.: SZEM151000664402 Page: 31 of 48







Report No.: SZEM151000664402 Page: 32 of 48



Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.



Report No.: SZEM151000664402 Page: 33 of 48


6.7 Radiated Spurious Emission

6.7.1 Spurious Emiss	ions							
Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205							
Test Method:	ANSI C63.10 2013							
Test Site:	Measurement Distance	: 3m	n (Semi-Anecl	noic Cham	ber)			
Receiver Setup:	Frequency		Detector	RBW	VBW	Remark		
	0.009MHz-0.090MH	Z	Peak	10kHz	2 30kHz	Peak		
	0.009MHz-0.090MH	Z	Average	10kHz	z 30kHz	Average		
	0.090MHz-0.110MH	Z	Quasi-peak	10kHz	z 30kHz	Quasi-peak		
	0.110MHz-0.490MH	Z	Peak	10kHz	2 30kHz	Peak		
	0.110MHz-0.490MH	Z	Average	10kHz	2 30kHz	Average		
	0.490MHz -30MHz		Quasi-peak	10kHz	2 30kHz	Quasi-peak		
	30MHz-1GHz Quasi-peak Above 1GHz		100 kH	z 300kHz	z Quasi-peak			
			Peak	1MHz	3MHz	Peak		
			Peak	1MHz	10Hz	Average		
Limit:	Frequency	Frequency Field strer (microvolt/n		Limit (dBuV/m)	Remark	Measurement distance (m)		
	0.009MHz-0.490MHz	2	400/F(kHz)	-	-	300		
	0.490MHz-1.705MHz	24	1000/F(kHz)	-	-	30		
	1.705MHz-30MHz		30	-	-	30		
	30MHz-88MHz		100	40.0	Quasi-pea	ık 3		
	88MHz-216MHz		150	43.5	Quasi-pea	ık 3		
	216MHz-960MHz		200	46.0	Quasi-pea	ık 3		
	960MHz-1GHz500Above 1GHz500		54.0	Quasi-pea	ık 3			
			54.0	Average	3			
	Note: 15.35(b), frequency emissions is limit applicable to the e peak emission level rad	20c quip	B above the oment under t	maximum est. This p	permitted a	verage emission		

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151000664402 Page: 34 of 48



[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151000664402 Page: 35 of 48


	 limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. h. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz) i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. j. Repeat above procedures until all frequencies measured was complete.
Exploratory Test	Transmitting with GFSK modulation.
Mode:	Transmitting mode
Final Test Mode:	Transmitting with GFSK modulation.
	For below 1GHz part, through pre-scan, the worst case is the lowest channel.
	Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151000664402 Page: 36 of 48

Radiated Emission below 1GHz						
30MHz~1GHz (QP)						
Test mode:	Transmitting mode	Vertical				




Condition: 47 CFR PART 15.209 3m 3142C Vertical Job No. : 6644CR Test mode: TX

		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	34.88	0.60	15.96	27.34	23.57	12.79	40.00	-27.21
2	92.14	1.12	8.87	27.21	23.70	6.48	43.50	-37.02
3	214.51	1.49	10.91	26.65	24.19	9.94	43.50	-33.56
4	369.40	2.12	15.81	26.93	23.02	14.02	46.00	-31.98
5	568.61	2.67	19.00	27.59	23.79	17.87	46.00	-28.13
6	706.70	2.92	21.67	27.41	24.29	21.47	46.00	-24.53



Report No.: SZEM151000664402 Page: 37 of 48

Test mode:	Transmitting mode	Horizontal



Condition: 47 CFR PART 15.209 3m 3142C Horizontal Job No. : 6644CR Test mode: TX

	Freq			Preamp Factor				Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 3 4 5	33.92 40.70 139.85 333.69 537.59	0.62 1.30 2.01 2.64	12.86 8.39 15.05 18.71	27.34 27.32 26.96 26.66 27.63	24.00 23.68 22.82 25.17	10.16 6.41 13.22 18.89	40.00 43.50 46.00 46.00	-29.84 -37.09 -32.78 -27.11
6	744.87	3.04	21.60	27.36	24.22	21.50	46.00	-24.50



Report No.: SZEM151000664402 Page: 38 of 48

Transmitte	r Emissi	on above	1GHz						
Test mode:	G	FSK	Test	channel:	Lowest Rema		Rema	rk:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit L (dBuV/		Over Limit (dB)	Polarization
3870.000	-31.30	33.30	0.00	40.00	42.00	74		-32.00	Vertical
4804.000	-30.40	34.30	0.00	51.60	55.50	74		-18.50	Vertical
5925.000	-29.10	34.70	0.00	39.50	45.10	74		-28.90	Vertical
7206.000	-27.90	35.80	0.00	37.20	45.10	74		-28.90	Vertical
9608.000	-25.10	37.20	0.00	35.40	47.50	74		-26.50	Vertical
12315.000	-22.50	37.90	0.00	33.50	48.90	74		-25.10	Vertical
3750.000	-31.10	32.90	0.00	41.90	43.70	74		-30.30	Horizontal
4804.000	-30.40	34.30	0.00	48.10	52.00	74		-22.00	Horizontal
6000.000	-28.80	34.90	0.00	41.30	47.40	74		-26.60	Horizontal
7206.000	-27.90	35.80	0.00	37.90	45.80	74		-28.20	Horizontal
9608.000	-25.10	37.20	0.00	35.10	47.20	74		-26.80	Horizontal
12645.000	-23.10	38.10	0.00	34.40	49.40	74		-24.60	Horizontal

Test mode: GFSK		Test	channel:	Lowest	Rema	ark:	Average	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.000	-30.40	34.30	0.00	38.50	42.40	54	-11.60	Vertical

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151000664402 Page: 39 of 48

Test mode:		GFSK	Test	t channel:	Middle	Rer	nark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3765.000	-31.10	32.90	0.00	42.20	44.00	74	-30.00	Vertical
4880.000	-30.40	34.50	0.00	53.00	57.10	74	-16.90	Vertical
5880.000	-29.30	34.50	0.00	39.00	44.20	74	-29.80	Vertical
7320.000	-27.90	35.70	0.00	37.50	45.30	74	-28.70	Vertical
9760.000	-24.90	37.30	0.00	35.00	47.40	74	-26.60	Vertical
12300.000	-22.50	37.90	0.00	34.30	49.70	74	-24.30	Vertical
3750.000	-31.10	32.90	0.00	41.90	43.70	74	-30.30	Horizontal
4880.000	-30.40	34.50	0.00	49.70	53.80	74	-20.20	Horizontal
5790.000	-29.10	34.30	0.00	39.60	44.80	74	-29.20	Horizontal
7320.000	-27.90	35.70	0.00	37.40	45.20	74	-28.80	Horizontal
9760.000	-24.90	37.30	0.00	35.70	48.10	74	-25.90	Horizontal
12645.000	-23.10	38.10	0.00	35.10	50.10	74	-23.90	Horizontal

Test mode:		GFSK		t channel:	Middle	Rem	nark:	Average
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4880.000	-30.40	34.50	0.00	38.80	42.90	54	-11.10	Vertical
4880.000	-30.40	34.50	0.00	36.30	40.40	54	-13.60	Horizontal

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151000664402 Page: 40 of 48

Test mode:		GFSK	Tes	t channel:	Highest	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3915.000	-31.20	33.20	0.00	40.20	42.20	74	-31.80	Vertical
4960.000	-30.30	34.60	0.00	47.80	52.10	74	-21.90	Vertical
6030.000	-28.90	34.90	0.00	39.60	45.60	74	-28.40	Vertical
7440.000	-27.90	35.80	0.00	37.70	45.60	74	-28.40	Vertical
9920.000	-23.90	37.30	0.00	35.80	49.20	74	-24.80	Vertical
12525.000	-22.90	38.00	0.00	34.90	50.00	74	-24.00	Vertical
3645.000	-31.20	32.50	0.00	40.30	41.60	74	-32.40	Horizontal
4960.000	-30.30	34.60	0.00	51.60	55.90	74	-18.10	Horizontal
5985.000	-28.90	34.80	0.00	39.70	45.60	74	-28.40	Horizontal
7440.000	-27.90	35.80	0.00	38.20	46.10	74	-27.90	Horizontal
9920.000	-23.90	37.30	0.00	35.00	48.40	74	-25.60	Horizontal
12345.000	-22.70	37.90	0.00	34.30	49.50	74	-24.50	Horizontal

Test mode:		GFSK		Test channel:		Highest	Rer	nark:	Average
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Prea Fac (dE	tor	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.000	-30.30	34.60	0.0	00	37.30	41.60	54	-12.40	Horizontal

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the above measurement data were shown in the report.



Report No.: SZEM151000664402 Page: 41 of 48

6.8 Restricted bands around fundamental frequency

6.8 Restricted ba	nds around fundame	ental frequency								
Test Requirement:	47 CFR Part 15C Section 15	5.209 and 15.205								
Test Method:	ANSI C63.10 2013									
Test Site:	Measurement Distance: 3m	(Semi-Anechoic Chambe	r)							
Limit:	Frequency	Limit (dBuV/m @3m)	Remark							
	30MHz-88MHz	40.0	Quasi-peak Value							
	88MHz-216MHz	43.5	Quasi-peak Value							
	216MHz-960MHz	46.0	Quasi-peak Value							
	960MHz-1GHz	54.0	Quasi-peak Value							
	90010112-10112		· · · · · · · · · · · · · · · · · · ·							
	Above 1GHz	54.0	Average Value							
		74.0	Peak Value							
Test Setup:										
Figure 1. 30MHz to 1GHz Figure 1. 30MHz to 1GHz Figure 1. 30MHz to 1GHz Figure 2. Above 1 GHz Test Procedure: a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. c. The EUT was set 3 meters away from the interference-receiving antenn which was mounted on the top of a variable-height antenna tower. d. The antenna height is varied from one meter to four meters above the grount to determine the maximum value of the field strength. Both horizontal ar vertical polarizations of the antenna are set to make the measurement. e. For each suspected emission, the EUT was arranged to its worst case and the rotatable form 1 meters to 4 meters and the rotatable form 1 meters of the network.										
i.	 Bandwidth with Maximum H Place a marker at the en frequency to show complian bands. Save the spectru modulation for lowest and hit. Test the EUT in the lowest of 	table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel Test the EUT in the lowest channel , the Highest channel The radiation measurements are performed in X, Y, Z axis positioning for								




Report No.: SZEM151000664402 Page: 42 of 48

	Transmitting mode, and found the X axis positioning which it is the worst case. j. Repeat above procedures until all frequencies measured was complete.
Exploratory Test	Transmitting with GFSK modulation.
Mode:	Transmitting mode
Final Test Mode:	Transmitting with GFSK modulation.
	Only the worst case is recorded in the report.
Instruments	Refer to section 5.10 for details.
Used:	
Test Results:	Pass



Report No.: SZEM151000664402 Page: 43 of 48


Test plot as follows:



Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)	Ant.F.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak:								
1	2390	51.2	74.0	22.8	32.5	0.0	-19.3	Н
2 F	2401.960	90.3	74.0	-16.3	32.6	0.0	-19.3	Н
Avg								
1	2390	38.6	54.0	15.4	32.5	0.0	-19.3	Н
2 F	2401.960	75.1	54.0	-21.1	32.6	0.0	-19.3	Н




Report No.: SZEM151000664402 Page: 44 of 48



Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)	Ant.F.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak:								
1	2390	50.8	74.0	23.2	32.5	0.0	-19.3	V
2 F	2401.960	89.8	74.0	-15.8	32.6	0.0	-19.3	V
Avg								
1	2390	37.6	54.0	16.4	32.5	0.0	-19.3	V
2 F	2401.960	73.6	54.0	-19.6	32.6	0.0	-19.3	V




Report No.: SZEM151000664402 Page: 45 of 48



Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)	Ant.F.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak:								
1 F	2479.900	90.4	74.0	-16.4	32.5	0.0	-19.1	Н
2	2483.5	64.7	74.0	9.3	32.5	0.0	-19.1	Н
Avg								
1 F	2479.900	76.3	54.0	-22.3	32.5	0.0	-19.1	Н
2	2483.5	49.6	54.0	4.4	32.5	0.0	-19.1	Н



Report No.: SZEM151000664402 Page: 46 of 48



Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)	Ant.F.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak:								
1 F	2479.700	87.9	74.0	-13.9	32.5	0.0	-19.1	V
2	2483.5	63.7	74.0	10.3	32.5	0.0	-19.1	V
Avg								
1 F	2479.700	73.1	54.0	-19.1	32.5	0.0	-19.1	V
2	2483.5	48.6	54.0	5.4	32.5	0.0	-19.1	V

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM151000664402 Page: 47 of 48

7 Photographs - EUT Test Setup

Test model No.: Xadow GSM + BLE v1.0

7.1 Radiated Emission








Report No.: SZEM151000664402 Page: 48 of 48

7.2 Radiated Spurious Emission



8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1510006644CR.