

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: Z52-NASIR02W0

EUT Specification

| | |
|-----------------------------------|--|
| EUT | Smart IR |
| Frequency band (Operating) | <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Others: 433.92MHz |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____ |
| Exposure classification | <input type="checkbox"/> Occupational/Controlled exposure ($S = 5\text{mW/cm}^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ($S=1\text{mW/cm}^2$) |
| Antenna diversity | <input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity |
| Max. output power | 14.88 dBm (0.0308W) |
| Antenna gain (Max) | 0 dBi |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation |

Limits for Maximum Permissible Exposure(MPE)

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm^2) | Average Time |
|--|------------------------------|------------------------------|-----------------------------------|--------------|
| (A) Limits for Occupational/Control Exposures | | | | |
| 300-1500 | -- | -- | F/300 | 6 |
| 1500-100000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/Uncontrol Exposures | | | | |
| 300-1500 | -- | -- | F/1500 | 6 |
| 1500-100000 | -- | -- | 1 | 30 |

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm^2

P_{out} =output power to antenna in Mw

G = gain of antenna in linear scale

$\pi=3.1416$

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm^2 . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

| Operating Mode | Channel Frequency (MHz) | Measured Power (dBm) | Tune up tolerance (dBm) | Max. Tune up Power (dBm) | Antenna Gain (dBi) | Power density at 20cm (mW/cm^2) | Power density Limits (mW/cm^2) |
|----------------|-------------------------|----------------------|-------------------------|--------------------------|--------------------|--|---|
| 802.11b | 2412 | 13.43 | 13.43±1 | 14.43 | 0 | 0.0055 | 1 |
| | 2437 | 13.34 | 13.34±1 | 14.34 | 0 | 0.0054 | 1 |
| | 2462 | 13.13 | 13.13±1 | 14.13 | 0 | 0.0051 | 1 |
| 802.11g | 2412 | 14.43 | 14.43±1 | 15.43 | 0 | 0.0069 | 1 |
| | 2437 | 14.88 | 14.88±1 | 15.88 | 0 | 0.0077 | 1 |
| | 2462 | 14.05 | 14.05±1 | 15.05 | 0 | 0.0064 | 1 |
| 802.11n (HT20) | 2412 | 14.48 | 14.48±1 | 15.48 | 0 | 0.0070 | 1 |
| | 2437 | 14.80 | 14.80±1 | 15.80 | 0 | 0.0076 | 1 |
| | 2462 | 14.02 | 14.02±1 | 15.02 | 0 | 0.0063 | 1 |