

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: Z52-NASRP01Z1U

EUT Specification

EUT	Repeater
Frequency band (Operating)	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input checked="" type="checkbox"/> Others: 908.4MHz & 916MHz
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas Tx <input type="checkbox"/> diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	908.4 MHz: -35.6 dBm (0.00028mW)&916MHz: -34.78 dBm (0.00033mW)
Antenna gain (Max)	0 dBi
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

908.4 MHz

Channel Frequency (MHz)	Antenna Gain (dBi)	Max Output power (dBuV/m)	Max Output power (dBm)	Power density at 20cm(mW/cm ²)	Power density Limits (mW/cm ²)
908.4	0	59.66	-35.60	5.3e-05	1

13.56MHz

Channel Frequency (MHz)	Antenna Gain (dBi)	Max Output power (dBuV/m)	Max Output power (dBm)	Power density at 20cm(mW/cm ²)	Power density Limits (mW/cm ²)
916	0	60.48	-34.78	6.4e-05	1

MPE Calculation Method

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

R = Separation distance between radiator and human body (m)=0.2m The formula can be changed to

$P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

$EIRP = E - 104.8 + 20 \log D = 59.66 - 104.8 + 20 \log 3 = -35.60 \text{ dBm}$

The SAR measurement is not necessary.