

# FCC&IC Radio Test Report

**FCC ID: Z5Y-SB210**


**IC: 10828A-SB210**

This report concerns (check one):  Original Grant  Class I Change  Class II Change

**Project No.** : 1608C157  
**Equipment** : Bluetooth Sound Bar with Built-in Subwoofer  
**Model Name** : SB210  
**Applicant** : Compupal (Group) Corporation  
**Address** : No.1555 Jiashan Avenue, Zhejiang, China

**Date of Receipt** : Aug. 16, 2016  
**Date of Test** : Aug. 16, 2016 ~ Aug. 31, 2016  
**Issued Date** : Sep. 01, 2016  
**Tested by** : BTL Inc.


**Testing Engineer** :

  
\_\_\_\_\_  
(Shawn Xiao)

**Technical Manager** :

  
\_\_\_\_\_  
(David Mao)

**Authorized Signatory** :

  
\_\_\_\_\_  
(Steven Lu)

## **B T L I N C .**

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,  
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

### **Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

**BTL's** report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

### **Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents	Page
<b>1 . CERTIFICATION</b>	<b>7</b>
<b>2 . SUMMARY OF TEST RESULTS</b>	<b>8</b>
2.1 TEST FACILITY	9
2.2 MEASUREMENT UNCERTAINTY	9
<b>3 . GENERAL INFORMATION</b>	<b>10</b>
3.1 GENERAL DESCRIPTION OF EUT	10
3.2 DESCRIPTION OF TEST MODES	12
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	12
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
3.5 DESCRIPTION OF SUPPORT UNITS	13
<b>4 . EMC EMISSION TEST</b>	<b>14</b>
4.1 CONDUCTED EMISSION MEASUREMENT	14
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
4.1.2 TEST PROCEDURE	14
4.1.3 DEVIATION FROM TEST STANDARD	14
4.1.4 TEST SETUP	15
4.1.5 EUT OPERATING CONDITIONS	15
4.1.6 EUT TEST CONDITIONS	15
4.1.7 TEST RESULTS	15
4.2 RADIATED EMISSION MEASUREMENT	16
4.2.1 RADIATED EMISSION LIMITS	16
4.2.2 TEST PROCEDURE	17
4.2.3 DEVIATION FROM TEST STANDARD	17
4.2.4 TEST SETUP	18
4.2.5 EUT OPERATING CONDITIONS	19
4.2.6 EUT TEST CONDITIONS	19
4.2.7 TEST RESULTS (9KHZ TO 30MHZ)	19
4.2.8 TEST RESULTS (30MHZ TO 1000 MHZ)	20
4.2.9 TEST RESULTS (ABOVE 1000 MHZ)	20
<b>5 . NUMBER OF HOPPING CHANNEL</b>	<b>21</b>
5.1 APPLIED PROCEDURES	21
5.1.1 TEST PROCEDURE	21
5.1.2 DEVIATION FROM STANDARD	21
5.1.3 TEST SETUP	21
5.1.4 EUT OPERATION CONDITIONS	21
5.1.5 EUT TEST CONDITIONS	21
5.1.6 TEST RESULTS	21

Table of Contents	Page
<b>6 . AVERAGE TIME OF OCCUPANCY</b>	<b>22</b>
<b>6.1 APPLIED PROCEDURES / LIMIT</b>	<b>22</b>
6.1.1 TEST PROCEDURE	22
6.1.2 DEVIATION FROM STANDARD	22
6.1.3 TEST SETUP	22
6.1.4 EUT OPERATION CONDITIONS	23
6.1.5 EUT TEST CONDITIONS	23
6.1.6 TEST RESULTS	23
<b>7 . HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>24</b>
<b>7.1 APPLIED PROCEDURES / LIMIT</b>	<b>24</b>
7.1.1 TEST PROCEDURE	24
7.1.2 DEVIATION FROM STANDARD	24
7.1.3 TEST SETUP	24
7.1.4 EUT TEST CONDITIONS	24
7.1.5 TEST RESULTS	24
<b>8 . BANDWIDTH TEST</b>	<b>25</b>
<b>8.1 APPLIED PROCEDURES</b>	<b>25</b>
8.1.1 TEST PROCEDURE	25
8.1.2 DEVIATION FROM STANDARD	25
8.1.3 TEST SETUP	25
8.1.4 EUT OPERATION CONDITIONS	25
8.1.5 EUT TEST CONDITIONS	25
8.1.6 TEST RESULTS	25
<b>9 . PEAK OUTPUT POWER TEST</b>	<b>26</b>
<b>9.1 APPLIED PROCEDURES / LIMIT</b>	<b>26</b>
9.1.1 TEST PROCEDURE	26
9.1.2 DEVIATION FROM STANDARD	26
9.1.3 TEST SETUP	26
9.1.4 EUT OPERATION CONDITIONS	26
9.1.5 EUT TEST CONDITIONS	26
9.1.6 TEST RESULTS	26
<b>10 . ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>27</b>
<b>10.1 APPLIED PROCEDURES / LIMIT</b>	<b>27</b>
10.1.1 TEST PROCEDURE	27
10.1.2 DEVIATION FROM STANDARD	27
10.1.3 TEST SETUP	27
10.1.4 EUT OPERATION CONDITIONS	27
10.1.5 EUT TEST CONDITIONS	27
10.1.6 TEST RESULTS	27
<b>11 . MEASUREMENT INSTRUMENTS LIST</b>	<b>28</b>

<b>Table of Contents</b>	<b>Page</b>
<b>12 . EUT TEST PHOTO</b>	<b>30</b>
<b>ATTACHMENT A - CONDUCTED EMISSION</b>	<b>34</b>
<b>ATTACHMENT B - RADIATED EMISSION (9KHZ-30MHZ)</b>	<b>37</b>
<b>ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)</b>	<b>39</b>
<b>ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)</b>	<b>46</b>
<b>ATTACHMENT E - NUMBER OF HOPPING CHANNEL</b>	<b>71</b>
<b>ATTACHMENT F - AVERAGE TIME OF OCCUPANCY</b>	<b>73</b>
<b>ATTACHMENT G - HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>86</b>
<b>ATTACHMENT H - BANDWIDTH</b>	<b>91</b>
<b>ATTACHMENT I - PEAK OUTPUT POWER</b>	<b>96</b>
<b>ATTACHMENT J - ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>101</b>

### REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FICP-1-1608C157	Original Issue.	Sep. 01, 2016

## 1. CERTIFICATION

Equipment : Bluetooth Sound Bar with Built-in Subwoofer  
Brand Name : amazonbasics, compupal  
Model Name : SB210  
Applicant : Compupal (Group) Corporation  
Manufacturer : Compupal (Group) Corporation  
Address : No.1555 Jiashan Avenue, Zhejiang, China  
Factory : Compupal (Group) Corporation  
Address : No.1555 Jiashan Avenue, Zhejiang, China  
Date of Test : Aug. 16, 2016 ~ Aug. 31, 2016  
Test Sample : Engineering Sample  
Standard(s) : FCC Part15, Subpart C (15.247)  
ANSI C63.10-2013  
RSS-247 Issue 1, May 2015  
RSS-GEN Issue 4, Nov 2014

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FICP-1-1608C157) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): 47 CFR Part 15, Subpart C; RSS-247 Issue 1, May 2015; RSS-GEN Issue 4, Nov				
Standard(s) Section		Test Item	Judgment	Remark
FCC	IC			
15.207	RSS-GEN 8.8	Conducted Emission	PASS	
15.247(d)	RSS-247 5.5	Antenna conducted Spurious Emission	PASS	
15.247 (a)(1)	RSS-247 5.1 (2)	Hopping Channel Separation	PASS	
15.247(a)(1)	RSS-247 5.1 (1)	Bandwidth	PASS	
15.247 (b)(1)	RSS-247 5.4 (2)	Peak Output Power	PASS	
15.247(d) 15.209	RSS-247 5.5	Radiated Spurious Emission	PASS	
15.247 (a)(1)(iii)	RSS-247 5.1 (4)	Number of Hopping Frequency	PASS	
15.247 (a)(1)(iii)	RSS-247 5.1 (4)	Dwell Time	PASS	
15.205	RSS-GEN 8.10	Restricted Bands	PASS	
15.203	-	Antenna Requirement	PASS	

Note:

(1) "N/A" denotes test is not applicable in this test report



## 2.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

BTL's test firm number for FCC: 319330

BTL's test firm number for IC: 4428B-1

## 2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2.

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %**.

### A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)
DG-C02	CISPR	150 KHz ~ 30MHz	2.32

### B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
DG-CB03	CISPR	9KHz~30MHz	V	3.79
		9KHz~30MHz	H	3.57
		30MHz ~ 200MHz	V	3.82
		30MHz ~ 200MHz	H	3.78
		200MHz ~ 1,000MHz	V	4.10
		200MHz ~ 1,000MHz	H	4.06
		1GHz~18GHz	V	3.12
		1GHz~18GHz	H	3.68
		18GHz~40GHz	V	4.15
		18GHz~40GHz	H	4.14

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

Equipment	Bluetooth Sound Bar with Built-in Subwoofer	
Brand Name	amazonbasics, compupal	
Model Name	SB210	
Model Difference	N/A	
Output Power (Max.)	Operation Frequency	2402~2480 MHz
	Modulation Technology	GFSK(1Mbps) $\pi/4$ -DQPSK(2Mbps)
	Bit Rate of Transmitter	8-DPSK(3Mbps)
	Output Power Max.	1.48 dBm(1Mbps) 1.45 dBm(3Mbps)
Power Source	DC voltage supplied from AC/DC adapter	
Power Rating	I/P: 100V~240Vac50Hz/60Hz 1.5A O/P: DC: 22V, 2.5A	

**Note:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3 Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	PIFA	N/A	-1

### 3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode <b>Note (1)</b>

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Emission	
Final Test Mode	Description
Mode 1	TX Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode <b>Note (1)</b>

**Note:**


- (1) The measurements are performed at the high, middle, low available channels.
- (2) The measurements for Hopping Channel Separation, Bandwidth and Peak Output Power were tested during 1Mbps, 2Mbps and 3Mbps, the worst case are 1Mbps and 3Mbps, only worst case was documented.

### 3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test Software Version	HC_Date_test		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1Mbps)	13	13	13
Parameters(3Mbps)	13	13	13

**3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED**



■ Ferrite core

**3.5 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
-	-	-	-	-	-

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	YES	1.5m	DC Main Cable
2	NO	NO	1.6m	AC Main Cable

## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 -0.50	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

- (1) The limit of " \* " decreases with the logarithm of the frequency
- (2) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)  
 Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz


#### 4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

#### 4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting/receiving data or hopping on mode.

#### 4.1.6 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 4.1.7 TEST RESULTS

Please refer to the Attachment A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform in this case, a "\*" marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.

## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9KHz -1000MHz)

In case the emission fall within the restricted band specified on 15.205(a) & RSS-247 5.5, then the 15.209(a) & RSS-Gen limit in the table below has to be followed.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C&RSS-247.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m) =20log Emission level (uV/m).
- (4) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)  
 Margin Level = Measurement Value - Limit Value

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average



Spectrum Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz ~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz ~110KHz for QP detector
Start ~ Stop Frequency	110KHz ~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz ~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

**4.2.2 TEST PROCEDURE**


- a. The measuring distance of at 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of at 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting conducted emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

**4.2.3 DEVIATION FROM TEST STANDARD**


No deviation

**4.2.4 TEST SETUP**


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For Radiated Emissions Below 30MHz



**4.2.5 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing

**4.2.6 EUT TEST CONDITIONS**

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

**4.2.7 TEST RESULTS (9KHZ TO 30MHZ)**

Please refer to the Attachment B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

#### 4.2.8 TEST RESULTS (30MHZ TO 1000 MHZ)

Please refer to the Attachment C.

Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (3) Measuring frequency range from 30MHz to 1000MHz.
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.

#### 4.2.9 TEST RESULTS (ABOVE 1000 MHZ)

Please refer to the Attachment D.

Remark:

- (1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (2) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (3) EUT Orthogonal Axis:  
"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand
- (4) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (5) No limit: This is fundamental signal, the judgment is not applicable.  
For fundamental signal judgment was referred to Peak output test.

## 5. NUMBER OF HOPPING CHANNEL

### 5.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C/ RSS-GEN and RSS-247			
Section	Test Item	Frequency Range (MHz)	Result
15.247(a)(1)(iii) RSS-247 5.1 (4)	Number of Hopping Channel	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RBW	100 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 5.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW=100KHz, VBW=100KHz, Sweep time = Auto.

#### 5.1.2 DEVIATION FROM STANDARD

No deviation.

#### 5.1.3 TEST SETUP



#### 5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 5.1.5 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 5.1.6 TEST RESULTS

Please refer to the Attachment E

## 6. AVERAGE TIME OF OCCUPANCY

### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C/ RSS-GEN and RSS-247				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(1)(iii) RSS-247 5.1 (4)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS


#### 6.1.1 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- i. DH5 Packet permit maximum  $1600 / 79 / 6 = 3.37$  hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $3.37 \times 31.6 = 106.6$  within 31.6 seconds.
- j. DH3 Packet permit maximum  $1600 / 79 / 4 = 5.06$  hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $5.06 \times 31.6 = 160$  within 31.6 seconds.
- k. DH1 Packet permit maximum  $1600 / 79 / 2 = 10.12$  hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $10.12 \times 31.6 = 320$  within 31.6 seconds.

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### **6.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### **6.1.5 EUT TEST CONDITIONS**

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### **6.1.6 TEST RESULTS**

Please refer to the Attachment F

## 7. HOPPING CHANNEL SEPARATION MEASUREMENT

### 7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 KHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 7.1.1 TEST PROCEDURE

- a. The EUT must have its hopping function enabled
- b. Span = wide enough to capture the peaks of two adjacent channels
  - Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span
  - Video (or Average) Bandwidth (VBW)  $\geq$  RBW
  - Sweep = Auto
  - Detector function = Peak
  - Trace = Max Hold

#### 7.1.2 DEVIATION FROM STANDARD

No deviation.

#### 7.1.3 TEST SETUP



#### 7.1.4 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 7.1.5 TEST RESULTS

Please refer to the Attachment G



## 8. BANDWIDTH TEST

### 8.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C/ RSS-GEN and RSS-247		
Section	Test Item	Frequency Range (MHz)
15.247(a)(2) RSS-GEN 6.6 RSS-247 5.1 (1)	Bandwidth	2400-2483.5

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz (20dB Bandwidth) / 30 KHz (Channel Separation)
VBW	100 KHz (20dB Bandwidth) / 100 KHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 8.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep Time = Auto.

#### 8.1.2 DEVIATION FROM STANDARD

No deviation.

#### 8.1.3 TEST SETUP



#### 8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 8.1.5 EUT TEST CONDITIONS

Temperature: 25°C  
Relative Humidity: 55%  
Test Voltage: AC 120V/60Hz

#### 8.1.6 TEST RESULTS

Please refer to the Attachment H

## 9. PEAK OUTPUT POWER TEST

### 9.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C/ RSS-247				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(1) RSS-247 5.4 (2)	Peak Output Power	1 Watt or 30dBm ( hopping channel >75) 0.125Watt or 21dBm (hopping channel <75)	2400-2483.5	PASS

#### 9.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 1MHz/3MHz, VBW= 1MHz/3MHz, Sweep time = Auto.

#### 9.1.2 DEVIATION FROM STANDARD

No deviation.

#### 9.1.3 TEST SETUP



#### 9.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 9.1.5 EUT TEST CONDITIONS

Temperature: 25°C  
Relative Humidity: 55%  
Test Voltage: AC 120V/60Hz

#### 9.1.6 TEST RESULTS

Please refer to the Attachment I

## 10. ANTENNA CONDUCTED SPURIOUS EMISSION

### 10.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.

#### 10.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.
- c. Offset=antenna gain+cable loss

#### 10.1.2 DEVIATION FROM STANDARD

No deviation.

#### 10.1.3 TEST SETUP



#### 10.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 10.1.5 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 10.1.6 TEST RESULTS

Please refer to the Attachment J

## 11. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	EMCO	3816/2	0052765	Mar. 27, 2017
2	LISN	R&S	ENV216	101447	Mar. 27, 2017
3	Test Cable	emci	RG223(9KHz-30 MHz)	C_17	Mar. 10, 2017
4	EMI Test Receiver	R&S	ESCI	100382	Mar. 27, 2017
5	50Ω Terminator	SHX	TF2-3G-A	08122901	Mar. 27, 2017
6	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarbeck	VULB9160	9160-3232	Mar. 27, 2017
2	Amplifier	HP	8447D	2944A09673	Nov. 09, 2016
3	Receiver	AGILENT	N9038A	MY52130039	Oct. 11, 2016
4	Test Cable	emci	LMR-400(30MHz-1GHz)	C-01	Jun. 26, 2017
5	Control	CT	SC100	N/A	N/A
6	Position Control	MF	MF-7802	MF780208416	N/A
7	Antenna	ETS	3115	00075789	Mar. 27, 2017
8	Amplifier	Agilent	8449B	3008A02274	Nov. 01, 2016
9	Receiver	AGILENT	N9038A	MY52130039	Oct. 11, 2016
10	Test Cable	emci	EMC104-SM-S M-10000(1GHz-26.5GHz)	C-68	Jun. 26, 2017
11	Controller	CT	SC100	N/A	N/A
12	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Apr. 23, 2017
13	Microwave Pre-amplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Mar. 27, 2017
14	Active Loop Antenna	R&S	HFH2-Z2	830749/020	Sep. 07, 2016
15	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Number of Hopping Channel					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Oct. 11, 2016

Average Time of Occupancy					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Oct. 11, 2016

Hopping Channel Separation Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Oct. 11, 2016

Bandwidth					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Oct. 11, 2016

Peak Output Power					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Oct. 11, 2016

Antenna Conducted Spurious Emission					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Oct. 11, 2016

Remark: "N/A" denotes no model name, serial no. or calibration specified.  
 All calibration period of equipment list is one year.

**12. EUT TEST PHOTO**

**Conducted Measurement Photos**



## Radiated Measurement Photos

9KHz to 30MHz





**Radiated Measurement Photos**



**30MHz to 1000MHz**





**Radiated Measurement Photos**


**Above 1000MHz**



# ATTACHMENT A - CONDUCTED EMISSION

Test Mode: TX Mode


Line



No.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1620	37.27	9.52	46.79	65.36	-18.57	Peak	
2	0.4700	38.56	9.61	48.17	56.51	-8.34	Peak	
3 *	0.4700	29.80	9.61	39.41	46.51	-7.10	AVG	
4	0.8340	34.59	9.75	44.34	56.00	-11.66	Peak	
5	0.8340	25.40	9.75	35.15	46.00	10.85	AVG	
6	1.3099	30.74	9.81	40.55	56.00	-15.45	Peak	
7	4.9780	29.47	9.99	39.46	56.00	-16.54	Peak	
8	10.7340	30.52	10.23	40.75	60.00	-19.25	Peak	

Test Mode: TX Mode

### Neutral



No.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1580	36.44	9.48	45.92	65.57	-19.65	Peak	
2	0.4580	38.47	9.44	47.91	56.73	-8.82	Peak	
3 *	0.4580	29.90	9.44	39.34	46.73	-7.39	AVG	
4	0.8420	34.91	9.59	44.50	56.00	-11.50	Peak	
5	0.8420	27.10	9.59	36.69	46.00	-9.31	AVG	
6	1.2780	30.49	9.67	40.16	56.00	-15.84	Peak	
7	4.8780	29.57	9.98	39.55	56.00	-16.45	Peak	
8	10.8540	30.88	10.32	41.20	60.00	-18.80	Peak	

**ATTACHMENT B - RADIATED EMISSION (9KHZ-30MHZ)**

Test Mode:	TX Mode
------------	---------


Frequency (MHz)	Ant 0°/90°	Read level dBuV/m	Factor (dB)	Measured(FS) (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Note
0.0092	0°	13.41	24.9840	38.3940	128.3285	-89.9345	AVG
0.0092	0°	14.28	24.9840	39.2640	148.3285	-109.0645	PEAK
0.0271	0°	6.73	23.8503	30.5803	118.9448	-88.3645	AVG
0.0271	0°	8.12	23.8503	31.9703	138.9448	-106.9745	PEAK
0.0364	0°	3.17	23.2613	26.4313	116.3822	-89.9509	AVG
0.0364	0°	5.58	23.2613	28.8413	136.3822	-107.5409	PEAK
0.0578	0°	1.16	22.2440	23.4040	112.3657	-88.9617	AVG
0.0578	0°	2.53	22.2440	24.7740	132.3657	-107.5917	PEAK
0.5023	0°	19.36	19.8074	39.1674	73.5850	-34.4176	QP
1.9547	0°	23.71	19.5045	43.2145	69.5400	-26.3255	QP

Frequency (MHz)	Ant 0°/90°	Read level dBuV/m	Factor (dB)	Measured(FS) (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Note
0.0119	90°	13.16	24.3000	37.4600	126.0933	-88.6333	AVG
0.0119	90°	14.89	24.3000	39.1900	146.0933	-106.9033	PEAK
0.0201	90°	7.28	24.2937	31.5737	121.5403	-89.9666	AVG
0.0201	90°	8.94	24.2937	33.2337	141.5403	-108.3066	PEAK
0.0422	90°	5.23	22.8940	28.1240	115.0980	-86.9740	AVG
0.0422	90°	6.19	22.8940	29.0840	135.0980	-106.0140	PEAK
0.0576	90°	1.54	22.2480	23.7880	112.3958	-88.6078	AVG
0.0576	90°	2.86	22.2480	25.1080	132.3958	-107.2878	PEAK
0.6224	90°	22.17	20.1917	42.3617	71.7228	-29.3612	QP
2.0587	90°	24.56	19.4648	44.0248	69.5400	-25.5152	QP

**ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)**

Test Mode: TX 2402MHz\_CH00\_1Mbps

**Vertical**




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	*	159.9800	41.69	-12.15	29.54	43.50	-13.96	peak	
2		233.7000	43.83	-13.51	30.32	46.00	-15.68	peak	
3		257.9500	42.11	-14.20	27.91	46.00	-18.09	peak	
4		307.4200	37.22	-10.32	26.90	46.00	-19.10	peak	
5		442.2500	32.98	-7.97	25.01	46.00	-20.99	peak	
6		528.5800	32.39	-6.76	25.63	46.00	-20.37	peak	



Test Mode: TX 2402MHz\_CH00\_1Mbps


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		159.9800	44.80	-12.15	32.65	43.50	-10.85	peak	
2		233.7000	49.78	-13.51	36.27	46.00	-9.73	peak	
3	*	307.4200	48.58	-10.32	38.26	46.00	-7.74	peak	
4		331.6700	47.96	-10.83	37.13	46.00	-8.87	peak	
5		442.2500	38.97	-7.97	31.00	46.00	-15.00	peak	
6		552.8300	32.93	-4.68	28.25	46.00	-17.75	peak	

Test Mode: TX 2441MHz \_CH39\_1Mbps


**Vertical**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	*	159.9800	41.94	-12.15	29.79	43.50	-13.71	peak	
2		233.7000	43.77	-13.51	30.26	46.00	-15.74	peak	
3		257.9500	42.11	-14.20	27.91	46.00	-18.09	peak	
4		307.4200	37.24	-10.32	26.92	46.00	-19.08	peak	
5		331.6700	35.85	-10.83	25.02	46.00	-20.98	peak	
6		431.5800	34.11	-7.92	26.19	46.00	-19.81	peak	

Test Mode: TX 2441MHz\_CH39\_1Mbps


**Horizontal**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		159.9800	43.27	-12.15	31.12	43.50	-12.38	peak	
2		184.2300	44.66	-13.30	31.36	43.50	-12.14	peak	
3		233.7000	50.00	-13.51	36.49	46.00	-9.51	peak	
4	*	307.4200	48.24	-10.32	37.92	46.00	-8.08	peak	
5		355.9200	44.53	-10.82	33.71	46.00	-12.29	peak	
6		442.2500	38.19	-7.97	30.22	46.00	-15.78	peak	

Test Mode: TX 2480MHz \_CH78\_1Mbps


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	*	171.6200	42.27	-12.33	29.94	43.50	-13.56	peak	
2		233.7000	43.05	-13.51	29.54	46.00	-16.46	peak	
3		307.4200	37.88	-10.32	27.56	46.00	-18.44	peak	
4		431.5800	33.22	-7.92	25.30	46.00	-20.70	peak	
5		528.5800	32.45	-6.76	25.69	46.00	-20.31	peak	
6		720.6400	30.45	-2.04	28.41	46.00	-17.59	peak	

Test Mode: TX 2480MHz\_CH78\_1Mbps

### Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		159.9800	45.05	-12.15	32.90	43.50	-10.60	peak	
2		233.7000	49.96	-13.51	36.45	46.00	-9.55	peak	
3		257.9500	49.45	-14.20	35.25	46.00	-10.75	peak	
4		294.8100	47.36	-10.72	36.64	46.00	-9.36	peak	
5	*	307.4200	48.43	-10.32	38.11	46.00	-7.89	peak	
6		331.6700	47.99	-10.83	37.16	46.00	-8.84	peak	

**ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)**

Test Mode : TX 2402MHz\_CH00\_1Mbps


**Vertical**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		2390.000	24.49	33.87	58.36	74.00	-15.64	peak	
2		2390.000	12.22	33.87	46.09	54.00	-7.91	AVG	
3	X	2401.850	70.29	33.95	104.24	74.00	30.24	peak	No Limit
4	*	2401.875	59.56	33.95	93.51	54.00	39.51	AVG	No Limit

Test Mode : TX 2402MHz \_CH00\_1Mbps

Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		4803.705	45.64	4.77	50.41	74.00	-23.59	peak	
2		4803.725	34.79	4.77	39.56	54.00	-14.44	AVG	
3		7205.460	49.61	11.16	60.77	74.00	-13.23	peak	
4	*	7205.560	38.35	11.16	49.51	54.00	-4.49	AVG	



Test Mode : TX 2402MHz \_CH00\_1Mbps


**Horizontal**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		2390.000	24.77	33.87	58.64	74.00	-15.36	peak	
2		2390.000	12.04	33.87	45.91	54.00	-8.09	AVG	
3	X	2401.850	66.10	33.95	100.05	74.00	26.05	peak	No Limit
4	*	2401.875	55.37	33.95	89.32	54.00	35.32	AVG	No Limit

Test Mode : TX 2402MHz \_CH00\_1Mbps


**Horizontal**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4803.7350	45.08	4.77	49.85	74.00	-24.15	Peak	
2	4803.7450	33.99	4.77	38.76	54.00	-15.24	AVG	
3	7205.4850	44.63	11.16	55.79	74.00	-18.21	Peak	
4 *	7205.5550	33.30	11.16	44.46	54.00	-9.54	AVG	

Test Mode : TX 2441MHz \_CH39\_ 1Mbps


**Vertical**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2440.9000	71.17	34.17	105.34	74.00	31.34	Peak	No Limit
2 *	2440.9000	60.47	34.17	94.64	54.00	40.64	AVG	No Limit

Test Mode : TX 2441MHz \_CH39\_1Mbps


**Vertical**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4881.7450	45.99	5.10	51.09	74.00	-22.91	Peak	
2	4881.7550	35.29	5.10	40.39	54.00	-13.61	AVG	
3	7322.3950	46.11	11.39	57.50	74.00	-16.50	Peak	
4 *	7322.5650	34.65	11.40	46.05	54.00	-7.95	AVG	

Test Mode : TX 2441MHz \_CH39\_1Mbps


**Horizontal**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2440.8750	57.00	34.17	91.17	54.00	37.17	AVG	No Limit
2	2440.9000	67.69	34.17	101.86	74.00	27.86	Peak	No Limit

Test Mode : TX 2441MHz \_CH39\_1Mbps


Horizontal



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4881.6800	45.77	5.10	50.87	74.00	-23.13	Peak	
2	4881.7000	34.97	5.10	40.07	54.00	-13.93	AVG	
3	7322.4850	44.06	11.39	55.45	74.00	-18.55	Peak	
4 *	7322.5400	32.46	11.40	43.86	54.00	-10.14	AVG	

Test Mode : TX 2480MHz \_CH78\_1Mbps


**Vertical**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2479.8750	70.54	34.39	104.93	74.00	30.93	Peak	No Limit
2 *	2479.8750	58.85	34.39	93.24	54.00	39.24	AVG	No Limit
3	2483.5000	27.26	34.41	61.67	74.00	-12.33	Peak	
4	2483.5000	14.01	34.41	48.42	54.00	-5.58	AVG	

Test Mode : TX 2480MHz \_CH78\_1Mbps

**Vertical**




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4959.7450	34.17	5.43	39.60	54.00	-14.40	AVG	
2	4959.7500	45.27	5.43	50.70	74.00	-23.30	Peak	
3	7439.3650	44.11	11.63	55.74	74.00	-18.26	Peak	
4 *	7439.5600	31.73	11.63	43.36	54.00	-10.64	AVG	



Test Mode : TX 2480MHz \_CH78\_1Mbps


**Horizontal**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2479.8500	65.93	34.39	100.32	74.00	26.32	Peak	No Limit
2 *	2479.8750	55.19	34.39	89.58	54.00	35.58	AVG	No Limit
3	2483.5000	24.50	34.41	58.91	74.00	-15.09	Peak	
4	2483.5000	13.17	34.41	47.58	54.00	-6.42	AVG	

Test Mode : TX 2480MHz \_CH78\_1Mbps

**Horizontal**




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4959.6850	46.51	5.43	51.94	74.00	-22.06	Peak	
2	4959.7450	35.54	5.43	40.97	54.00	-13.03	AVG	
3 *	7439.5200	30.63	11.63	42.26	54.00	-11.74	AVG	
4	7439.5450	42.75	11.63	54.38	74.00	-19.62	Peak	

Test Mode : TX 2402MHz \_CH00\_3Mbps

**Vertical**


110 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	22.84	33.88	56.72	74.00	-17.28	Peak	
2	2390.0000	12.05	33.88	45.93	54.00	-8.07	AVG	
3 *	2402.0000	56.09	33.95	90.04	54.00	36.04	AVG	No Limit
4	2402.2000	69.17	33.95	103.12	74.00	29.12	Peak	No Limit

Test Mode : TX 2402MHz \_CH00\_3Mbps


**Vertical**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	7205.9650	50.89	11.16	62.05	74.00	-11.95	Peak	
2 *	7205.9900	39.31	11.16	50.47	54.00	-3.53	AVG	
3	4804.5000	38.22	4.77	42.99	54.00	-11.01	AVG	
4	4803.0000	49.78	4.76	54.54	74.00	-19.46	Peak	

Test Mode : TX 2402MHz \_CH00\_3Mbps


**Horizontal**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	11.98	33.88	45.86	54.00	-8.14	AVG	
2	2390.0000	21.58	33.88	55.46	74.00	-18.54	Peak	
3	2401.8500	66.06	33.94	100.00	74.00	26.00	Peak	No Limit
4 *	2402.0000	52.51	33.95	86.46	54.00	32.46	AVG	No Limit

Test Mode : TX 2402MHz \_CH00\_3Mbps


**Horizontal**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4803.9950	33.58	4.77	38.35	54.00	-15.65	AVG	
2	4804.0150	44.83	4.77	49.60	74.00	-24.40	Peak	
3	7205.9300	46.95	11.16	58.11	74.00	-15.89	Peak	
4 *	7205.9850	35.37	11.16	46.53	54.00	-7.47	AVG	

Test Mode : TX 2441MHz \_CH39\_3Mbps


**Vertical**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2441.0000	56.35	34.17	90.52	54.00	36.52	AVG	No Limit
2	2441.0000	69.35	34.17	103.52	74.00	29.52	Peak	No Limit

Test Mode : TX 2441MHz \_CH39\_3Mbps

Vertical




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4881.9900	35.04	5.10	40.14	54.00	-13.86	AVG	
2	4882.2450	46.37	5.10	51.47	74.00	-22.53	Peak	
3	7322.9650	46.48	11.40	57.88	74.00	-16.12	Peak	
4 *	7322.9900	34.37	11.40	45.77	54.00	-8.23	AVG	



Test Mode : TX 2441MHz \_CH39\_3Mbps


**Horizontal**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2441.0000	53.96	34.17	88.13	54.00	34.13	AVG	No Limit
2	2440.8500	67.59	34.17	101.76	74.00	27.76	Peak	No Limit

Test Mode : TX 2441MHz \_CH39\_3Mbps

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4881.6500	46.36	5.10	51.46	74.00	-22.54	Peak	
2	4881.9700	35.55	5.10	40.65	54.00	-13.35	AVG	
3	7322.9200	45.66	11.40	57.06	74.00	-16.94	Peak	
4 *	7323.0000	33.51	11.40	44.91	54.00	-9.09	AVG	

Test Mode : TX 2480MHz \_CH78\_3Mbps

**Vertical**


110 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2479.8250	69.47	34.39	103.86	74.00	29.86	Peak	No Limit
2 *	2480.0000	56.39	34.39	90.78	54.00	36.78	AVG	No Limit
3	2483.5000	27.02	34.41	61.43	74.00	-12.57	Peak	
4	2483.5000	13.45	34.41	47.86	54.00	-6.14	AVG	

Test Mode : TX 2480MHz \_CH78\_3Mbps


**Vertical**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4959.5700	44.94	5.43	50.37	74.00	-23.63	Peak	
2	4959.9850	33.75	5.43	39.18	54.00	-14.82	AVG	
3 *	7439.9750	33.38	11.63	45.01	54.00	-8.99	AVG	
4	7440.0600	45.40	11.63	57.03	74.00	-16.97	Peak	

Test Mode : TX 2480MHz \_CH78\_3Mbps


**Horizontal**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2479.8500	65.63	34.39	100.02	74.00	26.02	Peak	No Limit
2 *	2480.0000	52.06	34.39	86.45	54.00	32.45	AVG	No Limit
3	2483.5000	24.05	34.41	58.46	74.00	-15.54	Peak	
4	2483.5000	12.80	34.41	47.21	54.00	-6.79	AVG	

Test Mode : TX 2480MHz \_CH78\_3Mbps

**Horizontal**




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4959.7250	45.03	5.43	50.46	74.00	-23.54	Peak	
2	4959.9950	33.87	5.43	39.30	54.00	-14.70	AVG	
3 *	7439.9900	33.05	11.63	44.68	54.00	-9.32	AVG	
4	7440.0800	44.78	11.63	56.41	74.00	-17.59	Peak	

# ATTACHMENT E - NUMBER OF HOPPING CHANNEL

**Test Mode**      **Hopping Mode\_1Mbps**


Number of Hopping Channel      79



Date: 22.AUG.2016 18:02:41

**Test Mode**      **Hopping Mode\_3Mbps**

Number of Hopping Channel      79



Date: 22.AUG.2016 18:11:14




## ATTACHMENT F - AVERAGE TIME OF OCCUPANCY

Test Mode :	TX Mode_1Mbps
-------------	---------------


Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
DH5	2402	2.9600	0.3157	0.4000	Pass
DH3	2402	1.6800	0.1792	0.4000	Pass
DH1	2402	0.3950	0.0421	0.4000	Pass
DH5	2441	2.9200	0.3115	0.4000	Pass
DH3	2441	1.6800	0.1792	0.4000	Pass
DH1	2441	0.4000	0.0427	0.4000	Pass
DH5	2480	2.9200	0.3115	0.4000	Pass
DH3	2480	1.6800	0.1792	0.4000	Pass
DH1	2480	0.3950	0.0421	0.4000	Pass

### CH00-DH1




Date: 22.AUG.2016 17:57:13

### CH00-DH3




Date: 22.AUG.2016 18:04:22

### CH00-DH5




Date: 22.AUG.2016 18:05:10

### CH39-DH1




Date: 22.AUG.2016 17:57:19

### CH39-DH3




Date: 22.AUG.2016 18:04:35

### CH39-DH5




Date: 22.AUG.2016 18:05:17

### CH78-DH1




Date: 22.AUG.2016 17:57:31

### CH78-DH3



Date: 22.AUG.2016 18:04:50

### CH78-DH5




Date: 22.AUG.2016 18:05:21

Test Mode :	TX Mode_3Mbps
-------------	---------------

Data Packet	Frequency	Pulse Duration(ms)	Dwell Time(s)	Limits(s)	Test Result
DH5	2402	2.8800	0.3072	0.4000	Pass
DH3	2402	1.6600	0.1771	0.4000	Pass
DH1	2402	0.3850	0.0411	0.4000	Pass
DH5	2441	2.9200	0.3115	0.4000	Pass
DH3	2441	1.6400	0.1749	0.4000	Pass
DH1	2441	0.3850	0.0411	0.4000	Pass
DH5	2480	2.9200	0.3115	0.4000	Pass
DH3	2480	1.6400	0.1749	0.4000	Pass
DH1	2480	0.3850	0.0411	0.4000	Pass




**CH00-DH1**




Date: 22.AUG.2016 18:05:52

**CH00-DH3**




Date: 22.AUG.2016 18:18:38

### CH00-DH5




Date: 22.AUG.2016 18:19:11

### CH39-DH1




Date: 22.AUG.2016 18:06:06

### CH39-DH3




Date: 22.AUG.2016 18:18:47

### CH39-DH5




Date: 22.AUG.2016 18:19:16

### CH78-DH1




Date: 22.AUG.2016 18:06:12

### CH78-DH3



Date: 22.AUG.2016 18:18:53

### CH78-DH5




Date: 22.AUG.2016 18:19:20

**ATTACHMENT G - HOPPING CHANNEL SEPARATION  
MEASUREMENT**


Test Mode : Hopping on \_1Mbps

Frequency (MHz)	Channel Separation (MHz)	2/3 of 20dB Bandwidth (MHz)	Test Result
2402	1.004	0.539	Pass
2441	1.002	0.498	Pass
2480	1.004	0.528	Pass




Date: 22.AUG.2016 17:58:40

### CH39



Date: 22.AUG.2016 17:59:44

### CH78




Date: 22.AUG.2016 18:00:52




Test Mode : Hopping on \_3Mbps

Frequency (MHz)	Channel Separation (MHz)	2/3 of 20dB Bandwidth (MHz)	Test Result
2402	1.020	0.732	Pass
2441	0.996	0.747	Pass
2480	0.840	0.753	Pass




Date: 22.AUG.2016 18:07:17

### CH39



Date: 22.AUG.2016 18:08:21

### CH78




Date: 22.AUG.2016 18:09:25

## ATTACHMENT H - BANDWIDTH


Test Mode : TX Mode \_1Mbps

Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	0.808	0.816	Pass
2441	0.747	0.812	Pass
2480	0.792	0.808	Pass




Date: 22.AUG.2016 17:45:04

**CH39**



Date: 22.AUG.2016 17:47:17


**CH78**



Date: 22.AUG.2016 17:48:07


Test Mode : TX Mode\_3Mbps

Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	1.098	1.060	Pass
2441	1.120	1.068	Pass
2480	1.130	1.072	Pass




Date: 22.AUG.2016 17:50:59

**CH39**



Date: 22.AUG.2016 17:52:36

**CH78**




Date: 22.AUG.2016 17:53:21

# ATTACHMENT I - PEAK OUTPUT POWER




Test Mode : TX Mode \_1Mbps

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	1.45	0.0014	30.00	1.00	Pass
2441	1.39	0.0014	30.00	1.00	Pass
2480	1.48	0.0014	30.00	1.00	Pass




Date: 22.AUG.2016 16:59:21

### CH39



Date: 22.AUG.2016 17:00:43


### CH78



Date: 22.AUG.2016 17:01:05


Test Mode : TX Mode \_3Mbps

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	1.36	0.0014	30.00	1.00	Pass
2441	1.35	0.0014	30.00	1.00	Pass
2480	1.45	0.0014	30.00	1.00	Pass




Date: 22.AUG.2016 17:23:54

### CH39



Date: 22.AUG.2016 17:24:09


### CH78



Date: 22.AUG.2016 17:24:27


**ATTACHMENT J - ANTENNA CONDUCTED SPURIOUS EMISSION**

### CH00 (Lower)\_1Mbps




Date: 22.AUG.2016 17:44:29

### CH78 (Upper)\_1Mbps




Date: 22.AUG.2016 17:47:38

### CH00 Hopping on mode (Lower)\_1Mbps




Date: 22.AUG.2016 18:03:16

### CH78 Hopping on mode (Upper)\_1Mbps




Date: 22.AUG.2016 18:03:51

### CH00 (10 Harmonic of the frequency) \_1Mbps




Date: 22.AUG.2016 17:45:18




Date: 22.AUG.2016 17:45:26






Date: 22.AUG.2016 17:45:35


### CH39 (10 Harmonic of the frequency) \_1Mbps



Date: 22.AUG.2016 17:46:29




Date: 22.AUG.2016 17:46:37




Date: 22.AUG.2016 17:46:45


### CH78 (10 Harmonic of the frequency) \_1Mbps



Date: 22.AUG.2016 17:48:21




Date: 22.AUG.2016 17:48:29




Date: 22.AUG.2016 17:48:38

### CH00 (Lower) \_3Mbps




Date: 22.AUG.2016 17:50:33

### CH78 (Upper) \_3Mbps




Date: 22.AUG.2016 17:52:58

### CH00 Hopping on mode (Lower)\_3Mbps




Date: 22.AUG.2016 18:11:49

### CH78 Hopping on mode (Upper)\_3Mbps




Date: 22.AUG.2016 18:12:24


### CH00 (10 Harmonic of the frequency) \_3Mbps



Date: 22.AUG.2016 17:51:12




Date: 22.AUG.2016 17:51:21




Date: 22.AUG.2016 17:51:29

### CH39 (10 Harmonic of the frequency) \_3Mbps




Date: 22.AUG.2016 17:51:54






Date: 22.AUG.2016 17:52:03




Date: 22.AUG.2016 17:52:11


### CH78 (10 Harmonic of the frequency) \_3Mbps



Date: 22.AUG.2016 17:53:35



Date: 22.AUG.2016 17:53:44



Date: 22.AUG.2016 17:53:52