

SAR Evaluation Report

RF Exposure Compliance Requirement

1. Standard Requirement

15.247(b)(4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.

2. Limits

According to KDB447498 General RF Exposure Guidance v05

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
MHz	30	35	40	45	50	
150	232	271	310	349	387	SAR Test Exclusion Threshold (mW)
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

Note: 10-g Extremity SAR Test Exclusion Power Thresholds are 2.5 times higher than the 1-g SAR Test Exclusion Thresholds indicated above. These thresholds do not apply, by extrapolation or other means, to occupational exposure limits.

Shenzhen Laker Testing Technology Co.,Ltd

4D, Block 1, Sunshine Huayi Building, Nanhai West Road, Nanshan, Shenzhen, China

TEL: 0755-86307736

FAX: 0755-86307356

3. EUT RF Exposure

The Max Conducted Peak Output Power is -0.56dBm(0.88mW) in lowest channel, and the Max Conducted Average Output Power is less than 0.88mW.

The best case gain of the antenna is 0dBi.

0 dBi logarithmic terms convert to numeric result is nearly 1.

According to the formula. calculate the EIRP test result:

$$\text{EIRP} < P \times G = 0.88\text{mW} \times 1 = 0.88\text{mW} \text{ ①}$$

SAR requirement:

$$\text{Limit} = 10\text{mW} @ 5\text{mm} \text{ ②} ;$$

$$\text{①} < \text{②}.$$

So the SAR report is not required.