

Maximum Permissible Exposure Evaluation

FCC ID: Z63-AUSDOM002

1. Client Information

Applicant	:	ShenZhen Aoni Electronic Industry Co., Ltd.
Address	:	HongHui Industrial Park,2nd Liuxian Road, Xin'An streets, District 68, Bao'an District, Shenzhen, China
Manufacturer	:	ShenZhen Aoni Electronic Industry Co., Ltd.
Address	:	HongHui Industrial Park,2nd Liuxian Road, Xin'An streets, District 68, Bao'an District, Shenzhen, China

2. General Description of EUT

EUT Name	:	Baby Monitor	
Models No.	:	E95A	
Model Different	:	N/A	
Sample ID	:	20210115-04-1#&20210115-04-2#	
Product Description	:	Operation Frequency:	2406MHz~2475MHz
		RF Output Power:	18.155dBm
		Antenna Gain:	2dBi FPC Antenna
		Modulation Type:	GFSK (4Mbps)
Power Rating	:	DC 5V from Adapter(SAN-05015) Input: 100-240V~, 50/60Hz, 0.35A Max. Output: DC 5V 1.5A	
Software Version	:	XM530_BMS50X20-WVGA_16M_20200622	
Hardware Version	:	BM-ETH V2.01 0308195962	
Remark	:	The adapter and antenna gain provided by the applicant, the verified for the RF conduction test provided by TOBY test lab.	

MPE Calculations for WIFI

1. Antenna Gain:

FPC Antenna: 2dBi.

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Test Result:

Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
2406	18.155	18±1	19	2	20	0.0250
2442	17.935	18±1	19	2	20	0.0250
2475	17.868	18±1	19	2	20	0.0250

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For GFSK:2406~2475 MHz

MPE limit S: 1mW/ cm²

The MPE is calculated as $0.0250\text{mW} / \text{cm}^2 < \text{limit } 1\text{mW} / \text{cm}^2$. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

Note

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----