

INTERTEK TESTING SERVICES

RF Exposure

The Equipment under Test (EUT) is a receiver unit for the DRONE DX 5INCH STUNT operating at 2.4GHz band. It is powered by DC 3.7V (1 x 3.7V Rechargeable battery). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -15.0dBm (tolerance: +/- 3dB).

The normal conducted output power is: -15.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 80.8dB μ V/m at 3m in the frequency 2434MHz

The EIRP = [(FS*D) ^2 / 30] mW = -14.43dBm

which is within the production variation.

The maximum conducted output power specified is -12dBm = 0.063mW

The source- based time-averaging conducted output power
= 0.063* Duty cycle mW <0.063 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt(2.434) mW

= 9.61 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 8.1159 ms

Effective period of the cycle = 2.1739 ms

DC = 2.1739ms / 8.1159 ms = 0.2679 or 26.79%

FCC ID: Z6QDFX12524G