



198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technological Development District, Guangzhou, China 510663
Telephone: +86 (0) 20 82155555
Fax: +86 (0) 20 82075059
Email: ee.guangzhou@sgs.com

Report No.: GZEM130300106501
Page: 1 of 27
FCC ID: Z6QFX061FL0001

TEST REPORT

Application No.:	GZEM1303001065RF
Applicant:	GUANGDONG FEILUN TECHNOLOGY INDUSTRIAL CO., LTD.
FCC ID:	Z6QFX061FL0001
Product Name:	Remote-control planes
Product Description:	Wireless remote control with 2.4 GHz as carrier.
Model No.:	FX034, FX051, FX052, FX056, FX059, FX060, FX061, FX066, FX069, FX072, FX076, FX077, FX078, FX079, FX080, FX081, FX082, FX083, FX084, FX085, FX086, FX087, FX088, FX089, FX090, FX091, FX092, FX093, FX094, FX095, FX096, FX097, FX098, FX099, FX100, FX101, FX102, FX103, FX104, FX105 ♣
♣	Please refer to section 3 of this report for details
Standards:	47 CFR PART 15 Subpart C: 2012 section 15.249
Date of Receipt:	2013-03-22
Date of Test:	2013-03-25 to 2013-04-16
Date of Issue:	2013-05-02
Test Result :	Pass*

* In the configuration tested, the EUT complied with the standards specified above.

Richard Li
Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2013-05-02		Original

Authorized for issue by:				
Tested By		 <hr/> (Storm Shu) / Project Engineer		2013-03-25 to 2013-04-16 <hr/> Date
Prepared By		 <hr/> (Storm Shu) / Clerk		2013-04-18 <hr/> Date
Checked By		 <hr/> (Jeffrey Chen) / Reviewer		2013-05-02 <hr/> Date



3 Test Summary

TEST	TEST REQUIREMENT	TEST METHOD	RESULT
Field Strength of Fundamental	FCC PART 15 C section 15.249 (a)	ANSI C63.10: Clause 6.6	PASS
Field Strength of Unwanted Emissions	FCC PART 15 C section 15.249 (a) section 15.249 (d)	ANSI C63.10: Clause 6.4, 6.6 and 6.7	PASS
Band Edges	FCC PART 15 C section 15.249 (d)	ANSI C63.10: Clause 6.9.2	PASS
Occupied Bandwidth	FCC PART 15 C section 15.215(c)	ANSI C63.10: Clause 6.9.1	PASS

Remark:

EUT: In this whole report EUT means Equipment Under Test.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radio Frequency.

ANSI C63.10: the detail version is ANSI C63.10:2009 in the whole report.

♣Model No.: FX034, FX051, FX052, FX056, FX059, FX060, **FX061**, FX066, FX069, FX072, FX076, FX077, FX078, FX079, FX080, FX081, FX082, FX083, FX084, FX085, FX086, FX087, FX088, FX089, FX090, FX091, FX092, FX093, FX094, FX095, FX096, FX097, FX098, FX099, FX100, FX101, FX102, FX103, FX104, FX105

According to the confirmation from the applicant, since the electrical circuit design, layout, components used and internal wiring were identical for the above items, only difference being the model numbers.

Therefore only one item **FX061** was tested in this report.



4 Contents

1 COVER PAGE 1

2 VERSION..... 2

3 TEST SUMMARY 3

4 CONTENTS..... 4

5 GENERAL INFORMATION 5

5.1 Client Information 5

5.2 General Description of E.U.T. 5

5.3 Details of E.U.T. 5

5.4 Description of Support Units 5

5.5 Other Information Requested by the Customer 5

5.6 Deviation from Standards 5

5.7 Test Location 5

6 EQUIPMENT USED DURING TEST 7

7 TEST RESULTS 8

7.1 E.U.T. Operation..... 8

7.2 Antenna Requirement 10

7.3 Field Strength of Fundamental& Field Strength of Unwanted Emissions& Band Edge 11

7.4 Occupied Bandwidth 26



5 General Information

5.1 Client Information

Applicant: GUANGDONG FEILUN TECHNOLOGY INDUSTRIAL CO., LTD.
Address of Applicant: Haisheng Road, Laimei Industrial District, Fengxiang Chenghai, Shantou
Guangdong China

5.2 General Description of E.U.T.

Product Name: Remote-control planes
Model No.: FX061

5.3 Details of E.U.T.

Operating Frequency: 2402 MHz to 2480 MHz
Type of Modulation: FSK
Number of Channels: 79
Antenna Type: Integral Antenna
Antenna gain: 0 dBi
Function: The EUT is a set of equipment with FHSS technology; the EUT will hop between 2402 MHz and 2479 MHz with 78 channels to transfer data.
Power Supply: DC 9.0 V size "AA" batteries x 6
Power cord: N/A

5.4 Description of Support Units

None.

5.5 Other Information Requested by the Customer

None.

5.6 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.

5.7 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory,
198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.



6 Equipment Used during Test

RE in Chamber						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date	Calibration Interval
					(YYYY-MM-DD)	
EMC0525	Compact Semi-Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	2014-08-30	2Y
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2013-06-29	1Y
EMC0056	EMI Test Receiver	Rohde & Schwarz	ESCI	100236	2014-03-04	1Y
EMC0528	RI High frequency Cable	SGS	20 m	N/A	2013-06-01	1Y
EMC2025	Trilog Broadband Antenna 30-3000MHz	SCHWARZBECK MESS-ELEKTRONIK	VULB 9163	9163-450	2013-12-17	2Y
EMC0524	Bi-log Type Antenna	Schaffner -Chase	CBL6112B	2966	2013-11-27	2Y
EMC0519	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	2014-06-02	2Y
EMC2026	Horn Antenna 1-18GHz	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	9120D-841	2013-11-28	2Y
EMC0518	Horn Antenna	Rohde & Schwarz	HF906	100096	2014-07-01	2Y
EMC0521	1-26.5 GHz Pre-Amplifier	Agilent	8449B	3008A01649	2014-03-04	1Y
EMC2065	Amplifier	HP	8447F	N/A	2013-11-7	1Y
EMC2063	1-26GHz Pre Amplifier	Compliance Direction System Inc.	PAP-1G26-48	6279.628	2013-7-29	1Y
EMC0075	310N Amplifier	Sonoma	310N	272683	2014-03-04	1Y
EMC0523	Active Loop Antenna	EMCO	6502	42963	2014-04-07	2Y
EMC2041	Broad-Band Horn Antenna (14)15-26.5(40)GHz	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9170	9170-375	2014-06-01	3Y
EMC0530	10m Semi-Anechoic Chamber	ETS	N/A	N/A	2014-04-27	2Y

General used equipment						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date	Calibration Interval
					(YYYY-MM-DD)	
EMC0006	DMM	Fluke	73	70681569	2013-11-5	1Y
EMC0007	DMM	Fluke	73	70671122	2013-11-5	1Y



7 Test Results

7.1 E.U.T. Operation

Test Voltage: DC 9.0V by “AA” batteries x 6

Temperature: 20.0 -25.0 °C

Humidity: 38-50 % RH

Atmospheric Pressure: 1000 -1010 mbar

Test frequencies and frequency range: According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:

Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified



EUT channels and frequencies list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	11	2413	22	2424
1	2403	12	2414	23	2425
2	2404	13	2415	24	2426
3	2405	14	2416	25	2427
4	2406	15	2417	26	2428
5	2407	16	2418	27	2429
6	2408	17	2419	28	2430
7	2409	18	2420	29	2431
8	2410	19	2421	30	2432
9	2411	20	2422	31	2433
10	2412	21	2423	32	2434
33	2435	49	2451	65	2467
34	2436	50	2452	66	2468
35	2437	51	2453	67	2469
36	2438	52	2454	68	2470
37	2439	53	2455	69	2471
38	2440	54	2456	70	2472
39	2441	55	2457	71	2473
40	2442	56	2458	72	2474
41	2443	57	2459	73	2475
42	2444	58	2460	74	2476
43	2445	59	2461	75	2477
44	2446	60	2462	76	2478
45	2447	61	2463	77	2479
46	2448	62	2464	78	2480
47	2449	63	2465	/	/
48	2450	64	2466	/	/

Test frequencies are the lowest channel: 0 channel (2402MHz), middle channel: 39 channel (2441MHz) and highest channel: 78 channel (2480MHz).

7.2 Antenna Requirement

Standard requirement

15.203 requirement:

For intentional device. According to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

EUT Antenna

The antenna is an ISM Band Planar Chip Antenna integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0 dBi.



Test result: The unit does meet the FCC requirements.



7.3 Field Strength of Fundamental& Field Strength of Unwanted Emissions& Band Edge

Test Requirement: FCC Part15 C section 15.249

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (dBµV/m @ 3m)	Field Strength of Harmonics (dBµV/m @ 3m)
902 to 928	94.0	54.0
2400 to 2483.5	94.0	54.0
5725 to 5875	94.0	54.0
24000 to 24250	108.0	68.0

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Limits: The fundamental frequency rang is in the frequency band of the EUT is 2402MHz ~ 2480MHz.

The limit for Average field strength dBµV/m for the fundamental frequency = 94.0 dBµV/m.

The limit for Peak field strength dBµV/m for the fundamental frequency = 114.0 dBµV/m.

No fundamental is allowed in the restricted bands.

The limit for average field strength dBµV/m for the harmonics = 54.0 dBµV/m.

The limit for peak field strength dBµV/m for the harmonics = 74.0 dBµV/m.

Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or 54.0 dBµV/m in 15.209. Here the limit for the other emission is 54.0 dBµV/m.

Test Method: ANSI C63.10: Clause 6.4, 6.6 and 6.7 for Field Strength of Fundamental& Field Strength of Unwanted Emissions

ANSI C63.10: Clause 6.9.2 for Band Edge

Status Pre-test the EUT in continuous transmitting mode with setup as stand-alone in X, Y, Z threes axes, found the worst case is X axes and report the data.

Measurement Distance: 3m (Semi-Anechoic Chamber)

Frequency range 9 kHz – 25 GHz for transmitting mode.

Test instrumentation resolution bandwidth

9 kHz (9 kHz - 30 MHz), 120 kHz (30 MHz - 1000 MHz), 1 MHz (1000 MHz – 25 GHz)

Test Procedure:

1) 9 kHz to 30 MHz emissions:

For testing performed with the loop antenna, testing was performed in accordance to ANSI C63.10. The centre of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT, During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

2) 30 MHz to 1 GHz emissions:

For testing performed with the bi-log type antenna, testing was performed in accordance to ANSI C63.10. The measurement is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.


3) 1 GHz to 25 GHz emissions:

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2007 was used to perform radiated emission test above 1 GHz.


For testing performed with the horn antenna, testing was performed in accordance to ANSI C63.10. The measurement is performed with the EUT rotated 360°, the antenna height scan between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

Test Configuration:


1) 9 kHz to 30 MHz emissions:



2) 30 MHz to 1 GHz emissions:



3) 1 GHz to 25 GHz emissions:



The field strength is calculated by adding the Antenna Factor, Cable Loss & Pre-amplifier. The basic equation with a sample calculation is as follows:

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Preamplifier Factor}$$



Test at low Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement


The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

Vertical:

Peak scan

Level (dB μ V/m)




Quasi-peak measurement

Freq MHz	ReadAntenna Level dB μ V	Antenna Factor dB/m	Cable Loss dB	Preamplifier Gain dB	Level dB μ V/m	Over Limit dB	Limit dB μ V/m	Remark
70.874	34.54	4.69	0.81	27.79	12.25	-27.75	40.00	QP
143.320	30.06	10.41	1.18	27.45	14.20	-29.30	43.50	QP
321.250	28.34	13.52	1.87	27.24	16.49	-29.51	46.00	QP
532.960	27.82	18.02	2.47	28.16	20.15	-25.85	46.00	QP
635.520	28.98	18.80	2.67	28.19	22.26	-23.74	46.00	QP
873.320	27.20	20.73	3.39	26.97	24.35	-21.65	46.00	QP



Horizontal:

Peak scan
 Level (dBµV/m)



Quasi-peak measurement

Freq	ReadAntenna	Cable	Preamp	Over	Limit	Limit	Line	Remark
MHz	Level	Factor	Loss	Factor	Level	Limit	dBµV/m	
	dBµV	dB/m	dB	dB	dBµV/m	dB	dBµV/m	
73.250	33.70	5.01	0.84	27.78	11.77	-28.23	40.00	QP
160.960	31.05	8.90	1.23	27.38	13.80	-29.70	43.50	QP
348.020	26.43	14.29	1.95	27.43	15.24	-30.76	46.00	QP
521.440	29.56	17.50	2.45	28.12	21.39	-24.61	46.00	QP
685.023	29.50	18.65	2.77	27.95	22.97	-23.03	46.00	QP
836.520	28.42	20.47	3.25	27.30	24.84	-21.16	46.00	QP



1~25 GHz Field Strength of Fundamental & Field Strength of Unwanted Emissions.

Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2402.000	27.58	6.56	49.44	92.33	77.03	114.00	V
4804.000	31.53	11.11	49.30	64.34	57.68	74.00	V
7206.000	36.47	12.90	49.69	62.42	62.10	74.00	V
9608.000	38.08	15.16	49.88	56.52	59.88	74.00	V
2402.000	27.58	6.56	49.44	97.35	82.05	114.00	H
4804.000	31.53	11.11	49.30	62.74	56.08	74.00	H
7206.000	36.47	12.90	49.69	62.87	62.55	74.00	H
9608.000	38.08	15.16	49.88	57.13	60.49	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2402.000	27.58	6.56	49.44	83.33	68.03	94.00	V
4804.000	31.53	11.11	49.30	57.34	50.68	54.00	V
7206.000	36.47	12.90	49.69	47.42	47.10	54.00	V
9608.000	38.08	15.16	49.88	43.52	46.88	54.00	V
2402.000	27.58	6.56	49.44	89.35	74.05	94.00	H
4804.000	31.53	11.11	49.30	56.74	50.08	54.00	H
7206.000	36.47	12.90	49.69	46.87	46.55	54.00	H
9608.000	38.08	15.16	49.88	44.13	47.49	54.00	H



Band Edge:

Peak Measurement:							
Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2400.00	27.58	6.56	49.44	55.51	40.21	74.00	V
2483.50	27.55	6.99	49.42	56.57	41.69	74.00	V
2400.00	27.58	6.56	49.44	55.32	40.02	74.00	H
2483.50	27.55	6.99	49.42	55.12	40.24	74.00	H

Average Measurement:							
Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2400.00	27.58	6.56	49.44	47.93	32.63	54.00	V
2483.50	27.55	6.99	49.42	48.57	33.69	54.00	V
2400.00	27.58	6.56	49.44	46.51	31.21	54.00	H
2483.50	27.55	6.99	49.42	47.80	32.92	54.00	H



Test at middle Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement


The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

Vertical:

Peak scan

Level (dBμV/m)




Quasi-peak measurement

Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Over Limit	Limit Line	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dB	dBuV/m	
66.860	41.46	4.54	0.77	27.80	18.97	-21.03	40.00	QP
108.570	28.07	11.81	1.04	27.63	13.29	-30.21	43.50	QP
373.380	26.25	15.31	2.02	27.60	15.98	-30.02	46.00	QP
528.580	27.11	17.82	2.46	28.14	19.25	-26.75	46.00	QP
666.320	27.18	18.45	2.73	28.04	20.32	-25.68	46.00	QP
793.390	27.70	19.97	3.07	27.64	23.10	-22.90	46.00	QP



Horizontal:

Peak scan
 Level (dBμV/m)



Quasi-peak measurement

Freq	ReadAntenna	Cable	Preamp	Over	Limit	Line	Remark
MHz	Level	Factor	Loss	Factor	Level	Limit	
	dBuV	dB/m	dB	dB	dBuV/m	dB	dBuV/m
129.910	26.65	12.00	1.13	27.51	12.27	-31.23	43.50 QP
349.130	26.77	14.34	1.95	27.44	15.62	-30.38	46.00 QP
573.200	26.84	18.42	2.55	28.30	19.51	-26.49	46.00 QP
671.170	25.70	18.30	2.74	28.02	18.72	-27.28	46.00 QP
778.840	26.36	19.80	3.03	27.68	21.51	-24.49	46.00 QP
863.230	27.47	20.57	3.36	27.06	24.34	-21.66	46.00 QP



1~25 GHz Field Strength of Fundamental & Field Strength of Unwanted Emissions.

Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2441.000	27.57	6.81	49.43	103.04	87.99	114.00	V
4882.000	31.58	11.26	49.30	63.91	57.45	74.00	V
7323.000	36.50	13.28	49.71	61.43	61.50	74.00	V
9764.000	38.46	15.05	49.89	56.99	60.61	74.00	V
2441.000	27.57	6.81	49.43	94.54	79.49	114.00	H
4882.000	31.58	11.26	49.30	64.57	58.11	74.00	H
7323.000	36.50	13.28	49.71	63.37	63.44	74.00	H
9764.000	38.46	15.05	49.89	59.19	62.81	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2441.000	27.57	6.81	49.43	94.04	78.99	94.00	V
4882.000	31.58	11.26	49.30	56.91	50.45	54.00	V
7323.000	36.50	13.28	49.71	47.43	47.50	54.00	V
9764.000	38.46	15.05	49.89	42.99	46.61	54.00	V
2441.000	27.57	6.81	49.43	87.54	72.49	94.00	H
4882.000	31.58	11.26	49.30	56.57	50.11	54.00	H
7323.000	36.50	13.28	49.71	46.37	46.44	54.00	H
9764.000	38.46	15.05	49.89	43.19	46.81	54.00	H



Band Edge:

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2400.00	27.58	6.56	49.44	55.83	40.53	74.00	V
2483.50	27.55	6.99	49.42	56.10	41.22	74.00	V
2400.00	27.58	6.56	49.44	55.54	40.24	74.00	H
2483.50	27.55	6.99	49.42	56.22	41.34	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB μ V)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2400.00	27.58	6.56	49.44	47.83	32.53	54.00	V
2483.50	27.55	6.99	49.42	48.57	33.69	54.00	V
2400.00	27.58	6.56	49.44	46.81	31.51	54.00	H
2483.50	27.55	6.99	49.42	47.02	32.14	54.00	H



Test at high Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement


The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

Vertical:

Peak scan

Level (dBμV/m)




Quasi-peak measurement

Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Gain	Level	Over Limit	Limit	Line	Remark
MHz	dBμV	dB/m	dB	dB	dBμV/m	dB	dBμV/m		
71.690	34.52	4.79	0.82	27.78	12.35	-27.65	40.00		QP
145.700	29.18	10.06	1.18	27.44	12.98	-30.52	43.50		QP
325.201	28.35	13.61	1.88	27.27	16.57	-29.43	46.00		QP
533.750	27.72	18.02	2.47	28.17	20.04	-25.96	46.00		QP
633.520	29.00	18.80	2.66	28.20	22.26	-23.74	46.00		QP
876.970	28.19	20.77	3.41	26.94	25.43	-20.57	46.00		QP



Horizontal:

Peak scan
 Level (dBμV/m)



Quasi-peak measurement

Freq MHz	ReadAntenna Level dBuV	Cable Factor dB/m	Preamp Loss dB	Preamp Factor dB	Level dBuV/m	Over Limit dB	Limit dBuV/m	Remark
73.360	35.70	5.01	0.84	27.78	13.77	-26.23	40.00	QP
160.920	30.06	8.90	1.22	27.38	12.80	-30.70	43.50	QP
350.740	25.44	14.40	1.95	27.45	14.34	-31.66	46.00	QP
523.300	27.44	17.58	2.45	28.12	19.35	-26.65	46.00	QP
685.201	26.50	18.65	2.77	27.95	19.97	-26.03	46.00	QP
833.690	25.43	20.53	3.22	27.30	21.88	-24.12	46.00	QP



1~25 GHz Field Strength of Fundamental & Field Strength of Unwanted Emissions.

Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2480.00	27.56	6.98	49.42	96.46	81.58	114.00	V
4960.00	31.70	11.39	49.30	64.44	58.23	74.00	V
7440.00	36.60	13.60	49.72	59.22	59.70	74.00	V
9920.00	38.65	14.92	49.90	57.68	61.35	74.00	V
2480.00	27.56	6.98	49.42	88.36	73.48	114.00	H
4960.00	31.70	11.39	49.30	64.01	57.8	74.00	H
7440.00	36.60	13.60	49.72	60.91	61.39	74.00	H
9920.00	38.65	14.92	49.90	60.15	63.82	74.00	H

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2480.00	27.56	6.98	49.42	89.46	74.58	94.00	V
4960.00	31.70	11.39	49.30	56.85	50.64	54.00	V
7440.00	36.60	13.60	49.72	45.22	45.70	54.00	V
9920.00	38.65	14.92	49.90	42.68	46.35	54.00	V
2480.00	27.56	6.98	49.42	81.36	66.48	94.00	H
4960.00	31.70	11.39	49.30	56.59	50.38	54.00	H
7440.00	36.60	13.60	49.72	44.91	45.39	54.00	H
9920.00	38.65	14.92	49.90	41.15	44.82	54.00	H



Band Edge:

Peak Measurement:							
Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2400.00	27.58	6.56	49.44	55.83	40.53	74.00	V
2483.50	27.55	6.99	49.42	56.57	41.69	74.00	V
2400.00	27.58	6.56	49.44	55.54	40.24	74.00	H
2483.50	27.55	6.99	49.42	57.80	42.92	74.00	H

Average Measurement:							
Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2400.00	27.58	6.56	49.44	47.83	32.53	54.00	V
2483.50	27.55	6.99	49.42	48.50	33.62	54.00	V
2400.00	27.58	6.56	49.44	45.56	30.26	54.00	H
2483.50	27.55	6.99	49.42	47.82	32.94	54.00	H

Remark:

- 1). The field strength is calculated by adding the Antenna Factor. Cable Factor & Pre-amplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Loss – Pre-amplifier Factor.
- 2). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

Test result: The unit does meet the FCC requirements.

7.4 Occupied Bandwidth

Test Requirement: FCC Part 15 C section 15.249


(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Test Method: ANSI C63.10: Clause 6.9.1


Operation within the band 2.400 to 2.4835 GHz

Method of measurement: A small sample of the transmitter output was fed into the Spectrum Analyzer and the attached plot was taken.


1. Test in the lowest frequency 2.402 GHz



2. Test in the middle frequency 2.441 GHz



3. Test in the highest frequency 2.480 GHz



The results: The unit does meet the FCC requirements.

--End of the report--