

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is a Drone DX 5inch Stunt operating at 2.4G Band. The EUT can be powered by DC 9.0V (6X 1.5V AA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

Modulation Type: GFSK.

The normal radiated output power (e.i.r.p) is: 1.0dBm (tolerance: +/- 3dB).

The normal conducted output power is 1.0dBm (tolerance: +/- 3dB).

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 95.3dB $\mu$ V/m at 3m in the frequency 2445MHz

The EIRP = [(FS\*D) ^2 / 30] mW = 0.07dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 94.6dB $\mu$ V/m at 3m in the frequency 2475MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -0.63dBm

which is within the production variation.

The maximum conducted output power specified is 4.0dBm =2.51 mW

The source- based time-averaging conducted output power

= 2.51 \* Duty cycle mW <2.51mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 \* 5 / sqrt (2.475) mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 5.9420ms

Effective period of the cycle = 0.4348ms

DC =0.4348ms / 5.9420ms= 0.0732 or 7.32%