

FCC 47 CFR MPE REPORT

Jiangmen Dascom Computer Peripherals Co., Ltd.

Thermal desktop label printer

Model Number: DL-820

Additional Model: DL-820a, DL-820b, DL-830

FCC ID: Z7ODL8300

Prepared for:	Jiangmen Dascom Computer Peripherals Co., Ltd.
	No.399, Jin Xing Road, Jiang Hai District, Jiangmen City,
	Guang Dong Province, P.R.China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2109273.
Date of Test:	Jun. 18~Sep. 18, 2021
Date of Report:	Sep. 22, 2021



Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: Pd (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11 b	2412	16.26	42.2669	16±1	2	1.585
	2442	17.56	57.0164	17±1	2	1.585
	2462	16.50	44.6684	16±1	2	1.585
IEEE 802.11 g	2412	19.53	89.7429	19±1	2	1.585
	2442	20.54	113.2400	20±1	2	1.585
	2462	19.74	94.1890	19±1	2	1.585
IEEE 802.11 n HT20	2412	19.14	82.0352	19±1	2	1.585
	2442	20.25	105.9254	20±1	2	1.585
	2462	19.05	80.3526	19±1	2	1.585
IEEE 802.11 n HT40	2422	19.81	95.7194	19±1	2	1.585
	2437	19.52	89.5365	19±1	2	1.585
	2452	19.53	89.7429	19±1	2	1.585

3. Calculated Result and Limit

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
2.4G Band						
IEEE 802.11 b	18	2	1.585	0.0199	1	Complies
IEEE 802.11 g	21	2	1.585	0.0397	1	Complies
IEEE 802.11 n HT20	21	2	1.585	0.0397	1	Complies
IEEE 802.11 n HT40	20	2	1.585	0.0315	1	Complies

End of Test Report