

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

Portable Receipt and Label Printer

Model No.: FP-530, FP-530L

FCC ID: Z7OFP530L

Trademark: PRINTEK

Report No.: ES180516009E

Issue Date: May 22, 2018

Prepared for

**Jiangmen Dascom Computer Peripherals Co., Ltd.
No 399, Jin Xing Road, Jiang Hai District, Jiangmen City Guang Dong
Province, China**

Prepared by

EMTEK(SHENZHEN) CO., LTD.

**Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China.**

TEL: 86-755-26954280

FAX: 86-755-26954282

**This report shall not be reproduced, except in full, without the written approval of
EMTEK(SHENZHEN) CO., LTD.**

VERIFICATION OF COMPLIANCE

Applicant:	Jiangmen Dascom Computer Peripherals Co., Ltd. No 399, Jin Xing Road, Jiang Hai District, Jiangmen City Guang Dong Province, China
Manufacturer:	Jiangmen Dascom Computer Peripherals Co., Ltd. No 399, Jin Xing Road, Jiang Hai District, Jiangmen City Guang Dong Province, China
Product Description:	Portable Receipt and Label Printer
Model Number:	FP-530, FP-530L (Note: These models are same except model number and appearance, here FP-530 was selected for full test.)
Input Rating:	DC 19V, 3.42A

We hereby certify that:

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2017).

Date of Test : May 16, 2018 to May 22, 2018

Yaping Shen

Prepared by : Yaping Shen/Editor

Joe Xia

Reviewer : Joe Xia/Supervisor

[Signature]

Approved & Authorized Signer : Lisa Wang/Manager

Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	ES180516009E

Table of Contents

1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION	6
2. SYSTEM TEST CONFIGURATION	7
2.1 EUT CONFIGURATION	7
2.2 EUT EXERCISE	7
2.3 TEST PROCEDURE.....	7
2.4 CONFIGURATION OF TESTED SYSTEM.....	7
3. DESCRIPTION OF TEST MODES	8
4. SUMMARY OF TEST RESULTS.....	9
5. TEST METHODOLOGY.....	9
6. TEST FACILITY.....	10
7. TEST SYSTEM UNCERTAINTY	11
8. CONDUCTED EMISSIONS TEST	12
8.1 MEASUREMENT PROCEDURE.....	12
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	12
8.3 MEASUREMENT EQUIPMENT USED	12
8.4 CONDUCTED EMISSION LIMIT	12
8.5 MEASUREMENT RESULT	12
9. RADIATED EMISSION TEST.....	15
9.1 MEASUREMENT PROCEDURE.....	15
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	16
9.3 MEASUREMENT EQUIPMENT USED	17
9.4 RADIATED EMISSION LIMIT.....	18
9.5 MEASUREMENT RESULT	19
10. 6DB BANDWIDTH TEST.....	24
10.1 MEASUREMENT PROCEDURE.....	24
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	24
10.3 MEASUREMENT EQUIPMENT USED	24
10.4 MEASUREMENT RESULTS	24
11. MAXIMUM PEAK OUTPUT POWER TEST.....	29
11.1 MEASUREMENT PROCEDURE.....	29
11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	29
11.3 MEASUREMENT EQUIPMENT USED	29
11.4 PEAK POWER OUTPUT LIMIT	29
11.5 MEASUREMENT RESULTS	29
12. BAND EDGE TEST.....	30
12.1 MEASUREMENT PROCEDURE.....	30
12.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	31
12.3 MEASUREMENT EQUIPMENT USED	31
12.4 MEASUREMENT RESULTS	31
13. MAXIMUM POWER SPECTRAL DENSITY.....	35
13.1 TEST EQUIPMENT	35
13.2 MEASURING INSTRUMENTS AND SETTING	35
13.3 TEST PROCEDURES.....	35
13.4 BLOCK DIAGRAM OF TEST SETUP.....	35
13.5 LIMIT	35

13.6	TEST RESULT	36
14.	ANTENNA PORT EMISSION.....	40
14.1	TEST EQUIPMENT	40
14.2	MEASURING INSTRUMENTS AND SETTING	40
14.3	TEST PROCEDURES.....	40
14.4	BLOCK DIAGRAM OF TEST SETUP	40
14.5	TEST RESULT	40
15.	ANTENNA APPLICATION.....	45
15.1	ANTENNA REQUIREMENT	45
15.2	RESULT	45

1. General Information

1.1 Product Description

Characteristics	Description
Product Name	Portable Receipt and Label Printer
Model number	FP-530, FP-530L
Power Supply	DC 19V, 3.42A
Modulation	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11n(HT40)
Operating Frequency Range	2412-2462MHz for 802.11b 2422-2452MHz for 802.11n(HT40)
Number of Channels	11 Channels for 802.11b 7 Channels for 802.11n(HT40)
Transmit Power Max	802.11b: 8.43dBm 802.11n(HT40): 8.41dBm
Antenna Type	Internal chip antenna
Antenna Gain	0.5dBi

Note: for more details, please refer to the User's manual of the EUT.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. Emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Trademark	Model No.	FCC ID	Note
1.	Portable Receipt and Label Printer	PRINTEK	FP-530	Z7OFP530L	EUT

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11n (HT40) : MCS0) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11 b

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Frequency and Channel list for 802.11 n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	8	2447
4	2427	6	2437	9	2452
		7	2442		

Test Frequency and Channel for 802.11 b

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

Test Frequency and channel for 802.11 n (HT40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452

4. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.247(a)(2)	6dB bandwidth	Pass
§15.247(b)(3)	Max Peak output Power test	Pass
§15.247(e)	Power density	Pass
§15.247(d)	Band edge test	Pass
§15.207	AC Power Conducted Emission	Pass
§15.247(d), §15.209	Radiated Emission	Pass
§15.247(d)	Antenna Port Emission	Pass
§15.247(b)&§15.203	Antenna Application	Pass

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: Z7OFP530L filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

The system is compliance with Subpart B is authorized under a DOC procedure

5. Test Methodology

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

FCC KDB 558074 DTS D01 Meas. Guidance v04

FCC KDB 662911 D01 Multiple Transmitter Output v01

FCC KDB 662911 D02 MIMO With Cross Polarized Antenna V01

6. Test Facility

Site Description

EMC Lab : Accredited by CNAS, 2016.10.24
The certificate is valid until 2022.10.28
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)
The Certificate Registration Number is L2291.

Accredited by TUV Rheinland Shenzhen 2016.5.19
The Laboratory has been assessed according to the requirements ISO/IEC 17025.

Accredited by FCC, August 03, 2017
Designation Number: CN1204
Test Firm Registration Number: 882943

Accredited by Industry Canada, November 24, 2015
The Certificate Registration Number is 4480A.

Accredited by A2LA, July 31, 2017
The Certificate Number is 4321.01.

Name of Firm : EMTEK(SHENZHEN) CO., LTD.
Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China.

7. TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Power Density	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$


Measurement Uncertainty for a level of Confidence of 95%

8. Conducted Emissions Test

8.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Last Cal.	Due date
Test Receiver	Rohde & Schwarz	ESCS30	100018	05/16/2018	05/15/2019
L.I.S.N	Rohde & Schwarz	ENV216	100017	05/16/2018	05/15/2019
RF Switching Unit	CDS	RSU-M2	38401	05/16/2018	05/15/2019
Coaxial Cable	CDS	79254	46107086	05/16/2018	05/15/2019


8.4 Conducted Emission Limit

Conducted Emission Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

- Note:**
1. The lower limit shall apply at the transition frequencies
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.5 Measurement Result

Conducted emission at both 120V & 240V, and emission at 120V represents the worst case. All the modulation modes were tested the data of the worst mode (TX 802.11b 2412MHz) are recorded in the following pages and the others modulation methods do not exceed the limits. Please refer to following pages.



Site site #1 Phase: **N** Temperature: 24
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
 Mode: WIFI(TX2412)
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.4065	37.33	0.00	37.33	57.72	-20.39	QP	
2		0.4065	33.52	0.00	33.52	47.72	-14.20	AVG	
3		0.5144	38.87	0.00	38.87	56.00	-17.13	QP	
4	*	0.5144	34.94	0.00	34.94	46.00	-11.06	AVG	
5		0.8070	38.26	0.00	38.26	56.00	-17.74	QP	
6		0.8070	30.44	0.00	30.44	46.00	-15.56	AVG	
7		0.9195	38.81	0.00	38.81	56.00	-17.19	QP	
8		0.9195	33.09	0.00	33.09	46.00	-12.91	AVG	
9		19.6250	42.80	0.00	42.80	60.00	-17.20	QP	
10		19.6250	34.43	0.00	34.43	50.00	-15.57	AVG	
11		28.4250	44.92	0.00	44.92	60.00	-15.08	QP	
12		28.4250	35.70	0.00	35.70	50.00	-14.30	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver.

9. Radiated Emission Test

9.1 Measurement Procedure

1. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane, And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured was complete.

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RBW	120KHz
VBW	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:


EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	10Hz
Detector	Peak
Trace	Max hold

9.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



9.3 Measurement Equipment Used

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI	1166.5950.03	05/16/2018	1 Year
2.	Bilog Antenna	Schwarzbeck	VULB9163	000141	05/16/2018	1 Year
3.	Power Amplifier	CDS	RSU-M352	818	05/16/2018	1 Year
4.	Power Amplifier	HP	8447F	OPT H64	05/16/2018	1 Year
5.	Color Monitor	SUNSPPO	SP-140A	N/A	05/16/2018	1 Year
6.	Single Line Filter	JIANLI	XL-3	N/A	05/16/2018	1 Year
7.	Single Phase Power Line Filter	JIANLI	DL-2X100B	N/A	05/16/2018	1 Year
8.	3 Phase Power Line Filter	JIANLI	DL-4X100B	N/A	05/16/2018	1 Year
9.	DC Power Filter	JIANLI	DL-2X50B	N/A	05/16/2018	1 Year
10.	Cable	Schwarzbeck	PLF-100	549489	05/16/2018	1 Year
11.	Cable	Rosenberger	CIL02	A0783566	05/16/2018	1 Year
12.	Cable	Rosenberger	RG 233/U	525178	05/16/2018	1 Year
13.	Signal Analyzer	Rohde & Schwarz	FSV30	103040	05/16/2018	1 Year
14.	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1272	05/16/2018	1 Year
15.	Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	05/16/2018	1 Year
16.	Cable	H+S	CBL-26	N/A	05/16/2018	1 Year
17.	Cable	H+S	CBL-26	N/A	05/16/2018	1 Year
18.	Cable	H+S	CBL-26	N/A	05/16/2018	1 Year

9.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (microrvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

Remark 1. Emission level in dBuV/m=20 log (uV/m)

: 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

9.5 Measurement Result

Below 30MHz:

All the modulation modes were tested the data of the test mode are recorded in the following pages.

Operation Mode:	TX Mode	Test Date :	May 21, 2018
Frequency Range:	9KHz~30MHz	Temperature :	28°C
Test Result:	PASS	Humidity :	60 %
Measured Distance:	3m	Test By:	John

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor.

Below 1000MHz:

All the modulation modes were tested the data of the worst mode (TX 802.11b 2412MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following test plots:




Site site #1 Polarization: **Horizontal** Temperature: 24
 Limit: (RE)FCC PART 15 class B 3m Power: AC 120V/60Hz Humidity: 55 %
 Mode: WIFI (TX2412)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		43.6584	43.84	-13.36	30.48	40.00	-9.52	QP	0	
2	*	65.8900	55.17	-21.07	34.10	40.00	-5.90	QP	0	
3		77.5300	49.67	-22.60	27.07	40.00	-12.93	QP	0	
4		231.7600	49.78	-15.93	33.85	46.00	-12.15	QP	0	
5		307.4200	50.24	-13.85	36.39	46.00	-9.61	QP	0	
6		480.0800	48.57	-10.54	38.03	46.00	-7.97	QP	0	

*:Maximum data x:Over limit l:over margin

Operator:



Site site #1 Polarization: **Vertical** Temperature: 24
 Limit: (RE)FCC PART 15 class B 3m Power: AC 120V/60Hz Humidity: 55 %
 Mode:WIFI (TX2412)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		38.7300	45.34	-13.77	31.57	40.00	-8.43	QP	0	
2		78.5000	52.14	-22.55	29.59	40.00	-10.41	QP	0	
3		92.0800	56.34	-20.52	35.82	43.50	-7.68	QP	0	
4		104.6900	53.48	-18.26	35.22	43.50	-8.28	QP	0	
5		150.5377	54.71	-17.79	36.92	43.50	-6.58	QP	0	
6	*	526.6400	49.67	-9.86	39.81	46.00	-6.19	QP	0	

*:Maximum data x:Over limit l:over margin

Operator:

Above 1000MHz:

Operation Mode: 802.11b Lowest Test Date : May 21, 2018
 Test Voltage: AC 120V/60Hz Test by: John

Freq. (MHz)	Ant. Pol. H/V	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4824	V	96.49	77.42	-32.3	64.19	45.12	74	54	-9.81	-8.88
7236	V	100.68	81.98	-37.2	63.48	44.78	74	54	-10.52	-9.22
9648	V	102.19	83.09	-39.8	62.39	43.29	74	54	-11.61	-10.71
12060	V	101.99	83.08	-40.5	61.49	42.58	74	54	-12.51	-11.42
14472	V	102.28	83.01	-41.7	60.58	41.31	74	54	-13.42	-12.69
16884	V	99.67	80.67	-40	59.67	40.67	74	54	-14.33	-13.33
4824	H	96.84	76.66	-31.6	65.24	45.06	74	54	-8.76	-8.94
7236	H	99.88	79.71	-35.5	64.38	44.21	74	54	-9.62	-9.79
9648	H	101.51	82.17	-38.3	63.21	43.87	74	54	-10.79	-10.13
12060	H	101.38	81.29	-39	62.38	42.29	74	54	-11.62	-11.71
14472	H	103.98	83.37	-42	61.98	41.37	74	54	-12.02	-12.63
16884	H	99.69	79.69	-39.3	60.39	40.39	74	54	-13.61	-13.61

Operation Mode: 802.11b Middle Test Date : May 21, 2018
 Test Voltage: AC 120V/60Hz Test by: Andy

Freq. (MHz)	Ant. Pol. H/V	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4874	V	96.56	78.11	-32.3	64.26	45.81	74	54	-9.74	-8.19
7311	V	100.65	81.78	-37.2	63.45	44.58	74	54	-10.55	-9.42
9688	V	102.48	83.43	-39.8	62.68	43.63	74	54	-11.32	-10.37
12185	V	101.87	83.15	-40.5	61.37	42.65	74	54	-12.63	-11.35
14622	V	101.54	82.49	-41	60.54	41.49	74	54	-13.46	-12.51
17059	V	100.96	81.38	-41.1	59.86	40.28	74	54	-14.14	-13.72
4874	H	96.96	78.37	-31.6	65.36	46.77	74	54	-8.64	-7.23
7311	H	100.28	81.19	-35.5	64.78	45.69	74	54	-9.22	-8.31
9688	H	101.89	83.17	-38.3	63.59	44.87	74	54	-10.41	-9.13
12185	H	101.58	82.19	-39	62.58	43.19	74	54	-11.42	-10.81
14622	H	103.98	84.98	-42	61.98	42.98	74	54	-12.02	-11.02
17059	H	102.29	83.29	-41.5	60.79	41.79	74	54	-13.21	-12.21

Operation Mode: 802.11b Highest

Test Date : May 21, 2018

Test Voltage: AC 120V/60Hz

Test by: Andy

Freq. (MHz)	Ant. Pol. H/V	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4924	V	95.85	77.59	-32.3	63.55	45.29	74	54	-10.45	-8.71
7386	V	99.65	81.58	-37.2	62.45	44.38	74	54	-11.55	-9.62
9848	V	101.29	82.95	-39.8	61.49	43.15	74	54	-12.51	-10.85
12310	V	100.87	83.08	-40.5	60.37	42.58	74	54	-13.63	-11.42
14772	V	100.68	82.68	-41	59.68	41.68	74	54	-14.32	-12.32
17234	V	99.77	81.39	-41.1	58.67	40.29	74	54	-15.33	-13.71
4924	H	98.53	76.01	-31.6	66.93	44.41	74	54	-7.07	-9.59
7386	H	100.89	79.07	-35.5	65.39	43.57	74	54	-8.61	-10.43
9848	H	102.68	80.97	-38.3	64.38	42.67	74	54	-9.62	-11.33
12310	H	102.19	80.79	-39	63.19	41.79	74	54	-10.81	-12.21
14772	H	104.54	82.49	-42	62.54	40.49	74	54	-11.46	-13.51
17234	H	103.45	81.28	-41.5	61.95	39.78	74	54	-12.05	-14.22

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ – ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


10. 6dB Bandwidth Test

10.1 Measurement Procedure

The EUT was operating in IEEE 802.11b, 802.11n(HT40) mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

1. Set resolution bandwidth (RBW) = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequency) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

10.2 Test SET-UP (Block Diagram of Configuration)



10.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	05/16/2018	05/15/2019

10.4 Measurement Results


6 Bandwidth Test Data Chart:



Refer to attached data chart.

Spectrum Detector: PK
 Test By: Yaping Shen
 Humidity : 60%


Test Date : May 21, 2018
 Temperature : 28°C



IEEE 802.11b			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	10056	>500	Pass
2437	10056	>500	
2462	10056	>500	





IEEE 802.11n (HT40)			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2422	35728	>500	Pass
2437	35500	>500	
2452	35399	>500	





11. Maximum Peak Output Power Test

11.1 Measurement Procedure

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

11.2 Test SET-UP (Block Diagram of Configuration)



11.3 Measurement Equipment Used

EQUIPMENT TYPE	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Power meter	ML2495A	0824006	05/16/2018	05/15/2019
Power sensor	MA2411B	0738172	05/16/2018	05/15/2019

11.4 Peak Power output limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

11.5 Measurement Results

Spectrum Detector: PK Test Date : May 21, 2018
 Test By: Andy Temperature : 28°C
 Test Result: PASS Humidity : 60%

Test Channel	Peak Output Power (dBm)		Limit(dBm)	Result
	802.11b	802.11n(HT40)		
Lowest	7.89	7.05	30	Pass
Middle	8.26	8.41		
Highest	8.43	7.62		

12. Band Edge Test

12.1 Measurement Procedure

For Conducted Test

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

For Radiated emission Test

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Repeat above procedures until all frequency measured were complete.


When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz.

EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz.

EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	10Hz
Detector	Peak
Trace	Max hold

12.2 Test SET-UP (Block Diagram of Configuration)




12.3 Measurement Equipment Used


EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	05/16/2018	05/15/2019

12.4 Measurement Results


1. Conducted Test


Test Mode: IEEE 802.11b





Test Mode: IEEE 802.11n(HT40)





2. Radiated emission Test

Spectrum Detector: PK/AV Test Date : May 21, 2018
 Test By: Andy Temperature : 28 °C
 Humidity : 65 %

IEEE 802.11b										
Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
<2400	H	88.78	71.82	-26.3	62.48	45.52	74	54	-11.52	-8.48
<2400	V	84.4	66.25	-26.1	58.3	40.15	74	54	-15.7	-13.85
>2483.5	H	89.34	70.66	-26.3	63.04	44.36	74	54	-10.96	-9.64
>2483.5	V	86.69	65.35	-26.1	60.59	39.25	74	54	-13.41	-14.75

IEEE 802.11n(HT40)										
Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
<2400	H	89.56	70.31	-26.3	63.26	44.01	74	54	-10.74	-9.99
<2400	V	86.35	66.46	-26.1	60.25	40.36	74	54	-13.75	-13.64
>2483.5	H	90.45	71.56	-26.3	64.15	45.26	74	54	-9.85	-8.74
>2483.5	V	85.45	64.85	-26.1	59.35	38.75	74	54	-14.65	-15.25

13. Maximum Power Spectral Density

13.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	05/16/2018	05/15/2019

13.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS bandwidth.
RBW	3KHz
VBW	10KHz
Detector	Peak
Trace	Max hold
Sweep Time	Automatic

13.3 Test Procedures

- a. The transmitter output (antenna port) was connected to the spectrum analyzer.
- b. Set analyzer center frequency to DTS channel center frequency.
- c. Set the analyzer span to a minimum of 1.5 times the DTS bandwidth.
- d. Set the RBW=3KHz. Set the VBW=10KHz
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level.

13.4 Block Diagram of Test Setup



13.5 Limit


The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3 kHz bandwidth.



13.6 Test Result

Spectrum Detector: PK
 Test By: Andy
 Humidity : 60%


Test Date : May 21,2018
 Temperature : 28°C



IEEE 802.11b			
Channel frequency (MHz)	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
2412	-3.93	8	Pass
2437	-3.83		
2462	-3.63		





IEEE 802.11n(HT40)			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
2422	-14.99	8	Pass
2437	-15.20		
2452	-12.34		





14. Antenna Port Emission

14.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	05/16/2018	05/15/2019

14.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
RBW	100kHz
VBW	300kHz
Detector	Peak
Trace	Max hold

14.3 Test Procedures

The conducted spurious emissions were measured conducted using a spectrum analyzer at low, Middle, and high channels, the limit was determined by attenuation 20dB of the RF peak power output.

14.4 Block Diagram of Test setup




14.5 Test Result

PASS.


Please refer to the following pages.

Test Mode: IEEE 802.11b


Lowest Channel



Middel Channel




Highest Channel




Test Mode: IEEE802.11n(HT40)


Lowest Channel



Middle Channel



Highest Channel



15. Antenna Application

15.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

15.2 Result

The EUT'S antenna, permanent attached antenna, is internal antenna. The antenna's gain is 0.5dBi and meets the requirement.

APPENDIX I (PHOTOS OF EUT)



