FCC ID: Z7RKSNYPWHS Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] *

 $[\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation:

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT DSS:

Transmit Frequency (GHz)	Mode	EIRP (dBm)	tune up maximum power	Result calculation	1-g SAR
2.402	GFSK	0.964	0 dBm to 2 dBm	0.49	3.0
2.441	GFSK	1.403	0 dBm to 2 dBm	0.49	3.0
2.480	GFSK	2.589	1 dBm to 3 dBm	0.63	3.0
2.402	π /4 -DQPSK	-1.055	-2 dBm to 0dBm	0.31	3.0
2.441	π /4-DQPSK	-0.240	-2 dBm to 0dBm	0.31	3.0
2.480	π /4-DQPSK	0.826	0 dBm to 2 dBm	0.50	3.0
2.402	8DPSK	-0.797	0 dBm to 2 dBm	0.49	3.0
2.441	8DPSK	0.108	0 dBm to 2 dBm	0.49	3.0
2.480	8DPSK	1.258	0 dBm to 2 dBm	0.50	3.0

Conclusion:

For the max result : $0.63 \le 3.0$ for 1-g SAR extremity SAR, No SAR is required.

Signature: And La

Date: 2016-7-7

NAME AND TITLE (Please print or type): David Lee/Manager COMPANY (Please print or type): Shenzhen EMTEK Co., Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China