



166 South Carter, Genoa City, WI 53128

Company:	Cambium Networks
Model Tested:	C024900P021A & C024900P031A
Report Number:	19738
DLS Project:	6334

Code of Federal Regulations 47 Part 15 – Radio Frequency Devices

Subpart C – Intentional Radiators

Section 15.247

Operation within the bands 902 - 928 MHz,
2400 - 2483.5 MHz, 5725 - 5875 MHz,
and 24.0 - 24.25 GHz.

PART 2 - Sections B7.0 to B12.0

THE FOLLOWING **MEETS** THE ABOVE TEST SPECIFICATION

Formal Name:	EPMP Station 2.4 GHz OFDM MIMO Radio
Kind of Equipment:	Point-to-Point or Point-to-Multipoint Digital Transmission Transceiver
Frequency Range:	2412 to 2462 MHz (20 MHz bandwidth) 2427 to 2452 MHz (40 MHz bandwidth) <i>Please see the Users' Manual for the channel specifications for use with the Dish antenna.</i>
Test Configuration:	Stand-alone
Model Number(s):	Connectorized: C024900P021A, C024900A021A Integrated: C024900P031A, C024900C031A
Model(s) Tested:	Connectorized: C024900P021A Integrated: C024900P031A
Serial Number(s):	Connectorized: MAC Address: 000456C2CE92 Integrated: MAC Address: 000456C2CE05
Date of Tests:	January to March, 2014 (non-consecutive days)
Test Conducted For:	Cambium Networks 3800 Golf Road, Suite 360 Rolling Meadows, IL 60008, USA

NOTICE: “This test report relates only to the items tested and must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government”. Please see the "Description of Test Sample" page listed inside of this report.

© Copyright 1983 – 2014, D.L.S. Electronic Systems, Inc.

COPYRIGHT NOTICE

This report must not be reproduced (except in full), without the approval of D.L.S. Electronic Systems, Inc.



166 South Carter, Genoa City, WI 53128

Company:
Model Tested:
Report Number:
DLS Project:

Cambium Networks
C024900P021A & C024900P031A
19738
6334

SIGNATURE PAGE

Tested By:

A handwritten signature in black ink that reads "Craig Brandt". The signature is fluid and cursive, with a long horizontal stroke at the end.

Craig Brandt
Senior Test Engineer

Reviewed By:

A handwritten signature in black ink that reads "William Stumpf". The signature is cursive and somewhat stylized, with a prominent vertical stroke at the end.

William Stumpf
OATS Manager

Approved By:

A handwritten signature in black ink that reads "Brian J. Mattson". The signature is cursive and includes a middle initial "J.". There is a horizontal line under the signature.

Brian Mattson
General Manager



166 South Carter, Genoa City, WI 53128

Company:

Model Tested:

Report Number:

DLS Project:

Cambium Networks

C024900P021A & C024900P031A

19738

6334

Table of Contents

i. Cover Page.....	1
ii. Signature Page.....	2
iii. Table of Contents	3
iv. NVLAP Certificate of Accreditation.....	5
1.0 Summary of Test Report	6
2.0 Introduction	7
3.0 Test Facilities	7
4.0 Description of Test Sample	7
5.0 Test Equipment.....	9
6.0 Test Arrangements	10
7.0 Test Conditions.....	10
8.0 Modifications Made To EUT for Compliance	11
9.0 Additional Descriptions.....	11
10.0 Results	11
11.0 Conclusion.....	11
Appendix A – Test Photos.....	12
Appendix B – Measurement Data	17
B1.0 DTS Bandwidth – 6 dB bandwidth - Conducted	17
B1.0a - with Omni Antenna	18
B1.0b - w-Integral Patch using power settings from radiated output power measurements	24
B2.0 Fundamental Emission Output Power - Conducted.....	30
B2.0a - with Omni Antenna	31
B2.0b - with Integral Patch Antenna	37
B2.0c - with Sector Antenna	51
B2.0d - with Panel Antenna.....	58
B2.0e - with Dish Antenna	64
B3.0 Fundamental Emission Output Power - Radiated with 12 dBi integral Patch antenna	70
B3.0a – with Integral Patch Antenna only	71
B4.0 Maximum Power Spectral Density – Conducted.....	85
B4.0a – for Omni, Sector, Panel & Dish Antennas	86
B4.0b – for Integral Patch Antenna	92
B5.0 Maximum Unwanted Emission Levels (not in restricted bands) – Conducted	98
B5.0a – with Omni Antenna, 20MHz Channel BW	99



166 South Carter, Genoa City, WI 53128

Company: Cambium Networks
Model Tested: C024900P021A & C024900P031A
Report Number: 19738
DLS Project: 6334

B5.0b – with Omni Antenna, 40MHz Channel BW	114
B5.0c – with Integral Patch Antenna, 20MHz Channel BW	129
B5.0d – with Integral Patch Antenna, 40MHz Channel BW	149
B5.0e – with Sector Antenna, 20MHz Channel BW	164
B5.0f – with Sector Antenna, 40MHz Channel BW	184
B5.0g – with Panel Antenna, 20MHz Channel BW	199
B5.0h – with Panel Antenna, 40MHz Channel BW	214
B5.0i – with Dish Antenna, 20MHz Channel BW	229
B5.0j – with Dish Antenna, 40MHz Channel BW	244
B6.0 Maximum Unwanted Emission Levels – Conducted Operating Band-Edge	259
B6.0a – with Omni Antenna	260
B6.0b – with Integral Patch Antenna	266
B6.0c – with Sector Antenna	274
B6.0d – with Panel Antenna	280
B6.0e – with Dish Antenna	286
B7.0 Maximum Unwanted Emission Levels into Restricted Frequency Bands - Radiated	292
B7.0a – with Integrated Patch, 30 to 1000 MHz	293
B7.0b – with Integrated Patch, 1 to 4.5 GHz, 20MHz Channel BW	299
B7.0c – with Integrated Patch, 1 to 4.5 GHz, 40MHz Channel BW	315
B7.0d – with Integrated Patch, 4.5 to 25 GHz	327
B8.0 Conducted Measurements for Radiated Restricted Band-Edge Compliance - for	328
Sector, Panel, and Dish antennas	328
B8.0a – with Omni Antenna, 20 MHz Channel BW	329
B8.0b – with Omni Antenna, 40 MHz Channel BW	356
B8.0c – with Sector Antenna, 20 MHz Channel BW	383
B8.0d – with Sector Antenna, 40 MHz Channel BW	423
B8.0e – with Panel Antenna	454
B8.0f – with Dish Antenna	458
B9.0 Radiated Restricted Band-Edge Compliance - radiated with Omni & Patch Antennas	460
B9.0a – with Omni Antenna	461
B9.0b – with Integral Patch Antenna	485
B10.0 Conducted Measurements for Radiated Restricted Band-Edge Compliance - for Sector, Panel, and Dish Antennas	509
B10.0a – with Sector Antenna	510
B10.0b – with Panel Antenna	542
B10.0c – with Dish Antenna	574
B11.0 Duty Cycle of Test Unit	606
B12.0 AC Line Conducted Emissions	609



166 South Carter, Genoa City, WI 53128

Company:	Cambium Networks
Model Tested:	C024900P021A & C024900P031A
Report Number:	19738
DLS Project:	6334

Appendix B – Measurement Data

B7.0 Maximum Unwanted Emission Levels into Restricted Frequency Bands - Radiated

Rule Section: FCC 15.205

Test Procedure: FCC KDB 558074 D01 DTS Meas Guidance v03r01 – *Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247*

12.0 Emissions in restricted frequency bands
12.1 Radiated emission measurements

Description: This test applies to harmonics/spurs that fall in the restricted bands listed in Section 15.205.

Measurements were taken for OFDM MCS15 with 20 MHz and 40 MHz channel bandwidths at the low, middle and high channels of operation. EUT was set to transmit continuously with a 100% duty cycle.

Limit: FCC Part 15.209

Results: Passed

Note: Tested with the 12 dBi integral Patch antenna.
Both transmit chains were active at maximum power during this test.
The Ethernet cable was unplugged from the remote computer in order to pass radiated emissions below 1 GHz.

FCC Part 15.209 Class B

Electric Field Strength

EUT: Cambium Networks
Manufacturer: EPMP 2.4 GHz STA with 12 dBi Integral antenna
Operating Condition: 66 deg. F; 17% R.H.
Test Site: DLS O.F. Site 2
Operator: Craig B
Test Specification: Low, Mid, & High channels
Comment: Continuous Tx 20 & 40 MHz channel BW's; Power setting 27
Date: 01-28-2014


TEXT: "Horz 3 meters"

Short Description: Test Set-up

Test Set-up: EUT Measured at 3 Meters with HORIZONTAL Antenna Polarization

Equations: $\text{Total Level(dB}\mu\text{V/m)} = \text{Level(dB}\mu\text{V)} + \text{System Loss(dB)} + \text{Antenna Factor(dB}\mu\text{V/m)}$
 $\text{Margin(dB)} = \text{Limit(dB}\mu\text{V/m)} - \text{Total Level(dB}\mu\text{V/m)}$

Graph Markers: + Frequency marker (Level of marker not related to final level)
| Final maximized level using Quasi-Peak detector
X Final maximized level using Average detector
Final maximized level using Peak detector



MEASUREMENT RESULT: "A1274_F1H_Final"

1/28/2014 1:46PM

Frequency	Level	Antenna Factor	System Loss	Total Level	Limit	Margin	Height Ant. m	EuT Angle deg	Final Detector	Comment
MHz	dBμV	dBμV/m	dB	dBμV/m	dBμV/m	dB				
115.025000	33.01	12.31	-23.0	22.3	43.5	21.2	3.00	80	QUASI-PEAK	None
255.400000	28.84	12.72	-22.0	19.5	46.0	26.5	1.00	90	QUASI-PEAK	None
330.000000	23.85	14.60	-21.6	16.8	46.0	29.2	1.20	90	QUASI-PEAK	None

FCC Part 15.209 Class B

Electric Field Strength

EUT: Cambium Networks
Manufacturer: EPMP 2.4 GHz STA with 12 dBi Integral antenna
Operating Condition: 66 deg. F; 17% R.H.
Test Site: DLS O.F. Site 2
Operator: Craig B
Test Specification: Low, Mid, & High channels
Comment: Continuous Tx 20 & 40 MHz channel BW's; Power setting 27
Date: 01-28-2014

TEXT: "Vert 3 meters"


Short Description: Test Set-up

Test Set-up: EUT Measured at 3 Meters with VERTICAL Antenna Polarization

Sample Equations:
$$\begin{array}{rclclcl} \text{Total Level(dB}\mu\text{V/m)} & = & \text{Level(dB}\mu\text{V)} & + & \text{System Loss(dB)} & + & \text{Antenna Factor(dB}\mu\text{V/m)} \\ 24.6 & & = & 35.51 & + & (-22.1) & + & 11.20 \end{array}$$

$$\begin{array}{rclcl} \text{Margin(dB)} & = & \text{Limit(dB}\mu\text{V/m)} & - & \text{Total Level(dB}\mu\text{V/m)} \\ 15.4 & = & 40 & - & 24.6 \end{array}$$

Graph Markers: + Frequency marker (Level of marker not related to final level)
| Final maximized level using Quasi-Peak detector
X Final maximized level using Average detector
Final maximized level using Peak detector




MEASUREMENT RESULT: "A1274_F1V_Final"

1/28/2014 1:17PM


Frequency	Level	Antenna	System	Total	Limit	Margin	Height	EuT	Final	Comment
MHz	dBμV	Factor	Loss	Level			Ant.	Angle	Detector	
		dBμV/m	dB	dBμV/m	dBμV/m	dB	m	deg		
36.305000	44.05	11.50	-24.1	31.4	40.0	8.6	1.00	0	QUASI-PEAK	None
30.130000	43.99	11.46	-24.3	31.2	40.0	8.8	1.00	0	QUASI-PEAK	None
49.275000	41.30	11.80	-23.9	29.2	40.0	10.8	1.00	225	QUASI-PEAK	None
84.000000	42.23	6.80	-23.4	25.6	40.0	14.4	1.00	170	QUASI-PEAK	None
115.405000	34.04	12.38	-23.0	23.4	43.5	20.1	1.00	225	QUASI-PEAK	None
198.595000	26.18	17.54	-22.5	21.2	43.5	22.3	1.00	170	QUASI-PEAK	None
203.110000	29.87	12.01	-22.5	19.4	43.5	24.1	1.00	150	QUASI-PEAK	None
239.980000	30.71	12.00	-22.0	20.7	46.0	25.3	1.00	225	QUASI-PEAK	None
296.420000	27.35	14.19	-21.8	19.8	46.0	26.2	1.00	100	QUASI-PEAK	None

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold **Low Channel Transmit = 2412 MHz**
POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Peak limit: 74 dBμV/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 09:15:55

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold **Low Channel Transmit = 2412 MHz**
POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Average limit: 54 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 09:17:19

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold **Low Channel Transmit = 2412 MHz**
POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Peak limit: 74 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 09:11:34

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold **Low Channel Transmit = 2412 MHz**
POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Average limit: 54 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 09:10:23

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold **Mid Channel Transmit = 2437 MHz**
POINT-TO-POINT OPERATION
 Output Power Setting 27 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Peak limit: 74 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 09:59:02

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold **Mid Channel Transmit = 2437 MHz**
POINT-TO-POINT OPERATION
 Output Power Setting 27 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Average limit: 54 dB μ V/m at 3 meters




Date: 29.JAN.2014 10:01:31

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold **Mid Channel Transmit = 2437 MHz**
POINT-TO-POINT OPERATION
 Output Power Setting 27 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Peak limit: 74 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 10:36:21

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold **Mid Channel Transmit = 2437 MHz**
POINT-TO-POINT OPERATION
 Output Power Setting 27 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Average limit: 54 dB μ V/m at 3 meters




Date: 29.JAN.2014 10:34:51

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold **Mid Channel Transmit = 2437 MHz**
POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 24.5 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Peak limit: 74 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 10:06:40

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold **Mid Channel Transmit = 2437 MHz**
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 24.5 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Average limit: 54 dB μ V/m at 3 meters




Date: 29.JAN.2014 10:04:50

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold **Mid Channel Transmit = 2437 MHz**
POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 24.5 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Peak limit: 74 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 10:29:21

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold **Mid Channel Transmit = 2437 MHz**
POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 24.5 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Average limit: 54 dB μ V/m at 3 meters




Date: 29.JAN.2014 10:30:30

Test Date: 01-24-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 17 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Peak limit: 74 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 24.JAN.2014 13:18:44

Test Date: 01-24-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 17 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Average limit: 54 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 24.JAN.2014 13:17:29

Test Date: 01-24-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 17 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Peak limit: 74 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 24.JAN.2014 13:26:22

Test Date: 01-24-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 17 Channel bandwidth: 20 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Average limit: 54 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 24.JAN.2014 13:27:19

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold **Low Channel Transmit = 2427 MHz**
 POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 12.5 Channel bandwidth: 40 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Peak limit: 74 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 11:25:48

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold **Low Channel Transmit = 2427 MHz**
POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 12.5 Channel bandwidth: 40 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Average limit: 54 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 11:26:56

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold **Low Channel Transmit = 2427 MHz**
POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 12.5 Channel bandwidth: 40 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Peak limit: 74 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 11:38:13

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold **Low Channel Transmit = 2427 MHz**
POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 12.5 Channel bandwidth: 40 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Average limit: 54 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 11:39:13

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold **Mid Channel Transmit = 2437 MHz**
 POINT-TO-POINT 7 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 17 Channel bandwidth: 40 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Peak limit: 74 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 11:11:57

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold **Mid Channel Transmit = 2437 MHz**
 POINT-TO-POINT 7 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 17 Channel bandwidth: 40 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Average limit: 54 dB μ V/m at 3 meters




Date: 29.JAN.2014 11:09:31

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold **Mid Channel Transmit = 2437 MHz**
POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 17 Channel bandwidth: 40 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Peak limit: 74 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 10:49:39

Test Date: 01-29-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold **Mid Channel Transmit = 2437 MHz**
POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 17 Channel bandwidth: 40 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Average limit: 54 dB μ V/m at 3 meters




Date: 29.JAN.2014 10:50:44

Test Date: 01-24-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 13.5 Channel bandwidth: 40 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Peak limit: 74 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 13:13:01

Test Date: 01-24-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 13.5 Channel bandwidth: 40 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Average limit: 54 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz




Date: 29.JAN.2014 13:14:02

Test Date: 01-24-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 13.5 Channel bandwidth: 40 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Peak limit: 74 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz



Date: 29.JAN.2014 11:45:12

Test Date: 01-24-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C2CE05
 Test: Maximum Unwanted Emission Levels - **RADIATED**
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 POINT-TO-POINT & POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 13.5 Channel bandwidth: 40 MHz
 Both output chains active OFDM MCS15
Emission Level Measurement
 Average limit: 54 dB μ V/m at 3 meters
 Frequency Range: 1 – 4.5 GHz



Date: 29.JAN.2014 11:43:55

**Maximum Unwanted Emission Levels
into Restricted Frequency Bands -
Radiated**

with 12 dBi Integral Patch Antenna

**No measurable emissions were detected
from the EUT from
4.5 to 25 GHz.**

Software power setting 27



166 South Carter, Genoa City, WI 53128

Company:	Cambium Networks
Model Tested:	C024900P021A & C024900P031A
Report Number:	19738
DLS Project:	6334

Appendix B – Measurement Data

B8.0 Conducted Measurements for Radiated Restricted Band-Edge Compliance - for Sector, Panel, and Dish antennas

Rule Section: FCC 15.205

Test Procedure: FCC KDB 558074 D01 DTS Meas Guidance v03r01 – *Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247*

12.1 Emissions in restricted frequency bands

12.2.2 General Procedure for conducted measurements in restricted bands

Description: Measure the conducted output power (in dBm) using the detector specified (section 12.2.4 used for peak, and 12.2.5.1 used for average).
Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level.
For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (*e.g.*, Watts, mW).
Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

Compare the resultant electric field strength level to the applicable limit.



Limit: Average Limit = 54dBuV/m @ 3 meters
Peak Limit = 74dBuV/m @ 3 meters

Results: Passed

Notes: Measurements were taken for OFDM MCS15 with 20 MHz and 40 MHz channel bandwidths at the low, middle and high channels of operation. EUT was set to transmit continuously with a 100% duty cycle.


Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: Receiver detector bandwidth 120 kHz
 Low Channel Transmit = 2412 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Conducted limits:
 30-88 MHz: = $40 \text{ dB}\mu\text{V/m} + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} - 4.7 \text{ dB (maximum ground reflection)} = -70.96 \text{ dBm}$
 88-216 MHz ($43.5 \text{ dB}\mu\text{V/m}$): = -67.46 dBm
 216-960 MHz ($46 \text{ dB}\mu\text{V/m}$): = -64.96 dBm
 960-1000 MHz ($54 \text{ dB}\mu\text{V/m}$): = -56.96 dBm

Frequency range: 30 – 1000 MHz




Date: 7.MAR.2014 13:47:21

Test Date: 03-11-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -52.26 dBm




Date: 11.MAR.2014 13:01:41

Test Date: 03-11-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 11.MAR.2014 13:02:33

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 7.MAR.2014 14:16:57

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 7.MAR.2014 14:18:42

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 7.MAR.2014 14:42:14

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -32.26 dBm




Date: 7.MAR.2014 14:43:34

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$



Date: 7.MAR.2014 15:16:08



Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -32.26 dBm



Date: 7.MAR.2014 15:17:10


Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: Receiver detector bandwidth 120 kHz
 Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 26.5 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Conducted limits:
 30-88 MHz: = 40 dBμV/m + 20log (3 meters) – 104.8 – 8 dBi antenna
 gain – 3 dB (MIMO operation) -4.7 dB (maximum ground
 reflection = -70.96 dBm
 88-216 MHz (43.5 dBμV/m): = -67.46 dBm
 216-960 MHz (46 dBμV/m): = -64.96 dBm
 960-1000 MHz (54 dBμV/m): = -56.96 dBm

Frequency range: 30 – 1000 MHz




Date: 7.MAR.2014 13:29:11

Test Date: 03-11-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 26.5 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 11.MAR.2014 12:55:01

Test Date: 03-11-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 26.5 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 11.MAR.2014 12:56:36

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 26.5 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 7.MAR.2014 11:18:05

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 26.5 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 7.MAR.2014 11:21:47

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 26.5 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 7.MAR.2014 11:30:21

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 26.5 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 7.MAR.2014 11:29:16

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 26.5 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$



Date: 7.MAR.2014 12:45:39



Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 26.5 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$



Date: 7.MAR.2014 12:46:53


Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: Receiver detector bandwidth 120 kHz
 High Channel Transmit = 2462 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Conducted limits:
 30-88 MHz: = $40 \text{ dB}\mu\text{V/m} + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} - 4.7 \text{ dB (maximum ground reflection)} = -70.96 \text{ dBm}$
 88-216 MHz ($43.5 \text{ dB}\mu\text{V/m}$): = -67.46 dBm
 216-960 MHz ($46 \text{ dB}\mu\text{V/m}$): = -64.96 dBm
 960-1000 MHz ($54 \text{ dB}\mu\text{V/m}$): = -56.96 dBm

Frequency range: 30 – 1000 MHz




Date: 7.MAR.2014 13:52:08

Test Date: 03-11-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 11.MAR.2014 13:07:07

Test Date: 03-11-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -32.26 dBm




Date: 11.MAR.2014 13:05:58

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 7.MAR.2014 14:21:14

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 7.MAR.2014 14:22:51

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 7.MAR.2014 14:46:27

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 7.MAR.2014 14:47:49

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$



Date: 7.MAR.2014 15:19:41


Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 7.MAR.2014 15:20:54

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: Receiver detector bandwidth 120 kHz
 Low Channel Transmit = 2427 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Conducted limits:
 30-88 MHz: = 40 dBμV/m + 20log (3 meters) – 104.8 – 8 dBi antenna
 gain – 3 dB (MIMO operation) -4.7 dB (maximum ground
 reflection = -70.96 dBm
 88-216 MHz (43.5 dBμV/m): = -67.46 dBm
 216-960 MHz (46 dBμV/m): = -64.96 dBm
 960-1000 MHz (54 dBμV/m): = -56.96 dBm

Frequency range: 30 – 1000 MHz




Test Date: 03-11-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2427 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 11.MAR.2014 13:15:12

Test Date: 03-11-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2427 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 11.MAR.2014 13:14:14

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2427 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 7.MAR.2014 14:30:46

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2427 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 7.MAR.2014 14:32:13

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2427 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 7.MAR.2014 14:54:47

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2427 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 7.MAR.2014 14:56:08

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2427 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$



Date: 7.MAR.2014 15:27:53


Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2427 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -32.26 dBm




Date: 7.MAR.2014 15:29:16

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: Receiver detector bandwidth 120 kHz
 Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Conducted limits:
 30-88 MHz: = 40 dBμV/m + 20log (3 meters) – 104.8 – 8 dBi antenna
 gain – 3 dB (MIMO operation) -4.7 dB (maximum ground
 reflection = -70.96 dBm
 88-216 MHz (43.5 dBμV/m): = -67.46 dBm
 216-960 MHz (46 dBμV/m): = -64.96 dBm
 960-1000 MHz (54 dBμV/m): = -56.96 dBm

Frequency range: 30 – 1000 MHz




Test Date: 03-11-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 11.MAR.2014 13:11:02

Test Date: 03-11-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 11.MAR.2014 13:12:01

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 7.MAR.2014 14:25:34

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 7.MAR.2014 14:26:49

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = 54 + 20log (3 meters) – 104.8 – 8 dBi antenna gain – 3 dB (MIMO operation) = -52.26 dBm




Date: 7.MAR.2014 14:50:41

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 7.MAR.2014 14:52:05

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$



Date: 7.MAR.2014 15:23:58


Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 18 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$



Date: 7.MAR.2014 15:25:19


Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: Receiver detector bandwidth 120 kHz
 High Channel Transmit = 2452 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Conducted limits:
 30-88 MHz: = 40 dBμV/m + 20log (3 meters) – 104.8 – 8 dBi antenna
 gain – 3 dB (MIMO operation) -4.7 dB (maximum ground
 reflection = -70.96 dBm
 88-216 MHz (43.5 dBμV/m): = -67.46 dBm
 216-960 MHz (46 dBμV/m): = -64.96 dBm
 960-1000 MHz (54 dBμV/m): = -56.96 dBm

Frequency range: 30 – 1000 MHz




Date: 7.MAR.2014 14:06:14

Test Date: 03-11-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 11.MAR.2014 13:17:34

Test Date: 03-11-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 11.MAR.2014 13:18:28

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 7.MAR.2014 14:36:59

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 7.MAR.2014 14:38:49

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 7.MAR.2014 14:58:33

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -32.26 \text{ dBm}$




Date: 7.MAR.2014 14:59:48

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -52.26 \text{ dBm}$




Date: 7.MAR.2014 15:31:47

Test Date: 03-07-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 POINT-TO-MULTIPOINT OPERATION
 Output Power Setting 15.5 Antenna gain: 8 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 8 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -32.26 dBm




Date: 7.MAR.2014 15:33:02

Frequency range: 30 – 335.4 MHz



Date: 13.MAR.2014 12:27:56


Frequency range: 399.9 – 1000 MHz



Date: 13.MAR.2014 12:55:01

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average
 Trace = Max Hold **Low Channel Transmit = 2412 MHz**
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 1 – 4.2 GHz



Date: 13.MAR.2014 14:20:08

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 1 – 4.2 GHz



Date: 13.MAR.2014 14:21:10

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -69.26 dBm


Frequency range: 4.2 – 10 GHz



Date: 13.MAR.2014 15:19:30

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 4.2 – 10 GHz



Date: 13.MAR.2014 15:20:36

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 10 – 18 GHz



Date: 14.MAR.2014 09:03:35

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 10 – 18 GHz



Date: 14.MAR.2014 09:04:54

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 18 – 25 GHz



Date: 14.MAR.2014 09:41:55

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2412 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm

Frequency range: 18 – 25 GHz



Date: 14.MAR.2014 09:43:06

Mid Channel Transmit = 2437 MHz

Output Power Setting 20.5 (used for 17 dBi antenna)

Antenna gain: 17, 19, or 25 dBi

Channel bandwidth: 20 MHz

Output port: 1 OFDM MCS15

Conducted limits: (calculated using worst case antenna gain of 25 dBi)

$$30\text{-}88\text{ MHz:} = 40\text{ dB}\mu\text{V/m} + 20\log(3\text{ meters}) - 104.8 - 25\text{ dBi antenna}$$

gain – 3 dB (MIMO operation) -4.7 dB (maximum ground

reflection = -87.96 dBm

88-216 MHz (43.5 dB μ V/m): = -84.46 dBm

216-960 MHz (46 dB μ V/m): = -81.96 dBm

960-1000 MHz (54 dB μ V/m): = -73.96 dBm




Att 10 dB AUTO
INPUT 1

Det	MA/QP	Trd	ES-K1
ResBW	120 kHz		
Meas T	100 ms	Unit	dBm


```

FREQUENCY      335.2100000  MHz
LEVEL    PK+    -78.22      dBm
          QPK    -82.42      dBm

```



```
Marker 1 [T2]
          -86.24 dBm
          335.21000000 MHz
```



Date: 13.MAR.2014 12:23:27

Mid Channel Transmit = 2437 MHz

Output Power Setting 20.5 (used for 17 dBi antenna)

Antenna gain: 17, 19, or 25 dBi

Output port: 1

OFDM MCS15

Conducted limits: (calculated using worst case antenna gain of 25 dBi)

$$30\text{-}88 \text{ MHz:} = 40 \text{ dB}\mu\text{V/m} + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna}$$

gain – 3 dB (MIMO operation) -4.7 dB (maximum ground

reflection = -87.96 dBm

88-216 MHz (43.5 dB μ V/m): = -84.46 dBm

216-960 MHz (46 dB μ V/m): = -81.96 dBm

960-1000 MHz (54 dB μ V/m): = -73.96 dBm



Det	MA/QP
ResBW	120 kHz
Meas T	100 ms

Trd
Unit


ES-K1

d Bm

Country	Number of People (Millions)
United States	81
United Kingdom	77


Date: 13.MAR.2014 12:48:24

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Point operation
 Output Power Setting 20.5 Antenna gain: 17 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = 54 + 20log (3 meters) – 104.8 – 17 dBi antenna gain – 3 dB (MIMO operation) = -61.26 dBm



Date: 13.MAR.2014 13:55:47


Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Point operation
 Output Power Setting 20.5 Antenna gain: 17 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 17 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -41.26 \text{ dBm}$



Date: 13.MAR.2014 13:54:17

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Point operation
 Output Power Setting 20.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 4.2 – 10 GHz



Date: 13.MAR.2014 15:09:02

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Point operation
 Output Power Setting 20.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 4.2 – 10 GHz



Date: 13.MAR.2014 15:08:13


Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Point operation
 Output Power Setting 20.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm

Frequency range: 10 – 18 GHz



Date: 14.MAR.2014 08:46:58


Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Point operation
 Output Power Setting 20.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm



Date: 14.MAR.2014 08:48:29

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Point operation
 Output Power Setting 20.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 18 – 25 GHz



Date: 14.MAR.2014 09:34:13


Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Point operation
 Output Power Setting 20.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm

Frequency range: 18 – 25 GHz




Date: 14.MAR.2014 09:35:30

Frequency range: 30 – 335.4 MHz




Date: 13.MAR.2014 12:43:01

Frequency range: 399.9 – 1000 MHz




Date: 13.MAR.2014 12:52:13

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Multipoint operation
 Output Power Setting 18 Antenna gain: 17 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 17 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -61.26 \text{ dBm}$



Date: 13.MAR.2014 13:58:10


Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Multipoint operation
 Output Power Setting 18 Antenna gain: 17 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 17 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -41.26 \text{ dBm}$



Date: 13.MAR.2014 13:59:20

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Multipoint operation
 Output Power Setting 18 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 4.2 – 10 GHz



Date: 13.MAR.2014 15:14:44

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Multipoint operation
 Output Power Setting 18 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 74 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -49.26 dBm


Frequency range: 4.2 – 10 GHz



Date: 13.MAR.2014 15:15:40

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Multipoint operation
 Output Power Setting 18 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 10 – 18 GHz



Date: 14.MAR.2014 08:52:22

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Multipoint operation
 Output Power Setting 18 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 10 – 18 GHz



Date: 14.MAR.2014 08:51:32

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Multipoint operation
 Output Power Setting 18 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 18 – 25 GHz



Date: 14.MAR.2014 09:38:52


Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Multipoint operation
 Output Power Setting 18 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm

Frequency range: 18 – 25 GHz




Date: 14.MAR.2014 09:37:56

Frequency range: 30 – 335.4 MHz



Date: 13.MAR.2014 12:30:40


Frequency range: 399.9 – 1000 MHz



Date: 13.MAR.2014 12:58:01

Test Date: 03-13-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Unwanted Emission Levels in Restricted Bands- Conducted
Operator: Craig B
Comment: RBW = 1 MHz VBW = 3 MHz
Detector = Average
Trace = Max Hold High Channel Transmit = 2462 MHz
Point-to-Point & Point-to-Multipoint operation
Output Power Setting 10 (used for 17 dBi antenna gain)
Antenna gain: 17, 19, or 25 dBi
Channel bandwidth: 20 MHz
Output port: 1 OFDM MCS15
Average limit = 54 dBμV/m at 3 meters
Conducted limit (calculated using worst case antenna gain of 25 dBi)
= 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
operation) = -69.26 dBm


Frequency range: 1 – 4.2 GHz



Date: 13.MAR.2014 14:24:08

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak
 Trace = Max Hold High Channel Transmit = 2462 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 1 – 4.2 GHz



Date: 13.MAR.2014 14:27:25

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 4.2 – 10 GHz



Date: 13.MAR.2014 15:24:15

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 4.2 – 10 GHz



Date: 13.MAR.2014 15:23:28

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 10 – 18 GHz



Date: 14.MAR.2014 09:09:41

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 10 – 18 GHz



Date: 14.MAR.2014 09:08:55

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -69.26 dBm


Frequency range: 18 – 25 GHz



Date: 14.MAR.2014 09:47:21


Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2462 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm

Frequency range: 18 – 25 GHz




Date: 14.MAR.2014 09:46:14

Frequency range: 30 – 335.4 MHz



Date: 13.MAR.2014 12:37:16


Frequency range: 399.9 – 1000 MHz



Date: 13.MAR.2014 13:03:21

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average
 Trace = Max Hold **Low Channel Transmit = 2427 MHz**
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 1 – 4.2 GHz



Date: 13.MAR.2014 14:39:32

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak
 Trace = Max Hold **Low Channel Transmit = 2427 MHz**
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 1 – 4.2 GHz



Date: 13.MAR.2014 14:40:24

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2427 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -69.26 dBm


Frequency range: 4.2 – 10 GHz



Date: 13.MAR.2014 15:34:03

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2427 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 4.2 – 10 GHz



Date: 13.MAR.2014 15:32:53

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2427 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 10 – 18 GHz



Date: 14.MAR.2014 09:18:54

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2427 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 10 – 18 GHz



Date: 14.MAR.2014 09:18:05

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2427 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 18 – 25 GHz



Date: 14.MAR.2014 09:55:29

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Low Channel Transmit = 2427 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 10 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm

Frequency range: 18 – 25 GHz



Date: 14.MAR.2014 09:54:31

Mid Channel Transmit = 2437 MHz

Output Power Setting 11.5 (used for 17 dBi antenna)

Antenna gain: 17, 19, or 25 dBi

Output port: 1 OFDM MCS15

Conducted limits: (calculated using worst case antenna gain of 25 dBi)

30-88 MHz: = 40 dBμV/m + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO operation) -4.7 dB (maximum ground reflection) = -87.96 dBm



88-216 MHz (43.5 dB μ V/m): = -84.46 dBm

216-960 MHz (46 dB μ V/m): = -81.96 dBm

960-1000 MHz (54 dB μ V/m): = -73.96 dBm



Det	MA/QP	Trd	ES-K1
ResBW	120 kHz		
Meas T	100 ms	Unit	dBm




Date: 13.MAR.2014 12:33:33




Att 10 dB AUTO
INPUT 1

Det MA/QP Trd ES-K1
ResBW 120 kHz
Meas T 100 ms Unit dBm

FREQUENCY 32.8100000 MHz
LEVEL PK+ -86.95 dBm
QPK -91.94 dBm




Marker 1 [T2]
-94.77 dBm
32.8100000 MHz



Date: 13.MAR.2014 12:34:17


Frequency range: 399.9 – 1000 MHz



Date: 13.MAR.2014 13:00:54

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average
 Trace = Max Hold **Mid Channel Transmit = 2437 MHz**
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 1 – 4.2 GHz



Date: 13.MAR.2014 14:35:08

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak
 Trace = Max Hold
 Mid Channel Transmit = 2437 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 1 – 4.2 GHz



Date: 13.MAR.2014 14:36:13

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -69.26 dBm


Frequency range: 4.2 – 10 GHz



Date: 13.MAR.2014 15:27:44

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 4.2 – 10 GHz



Date: 13.MAR.2014 15:28:46

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 10 – 18 GHz



Date: 14.MAR.2014 09:13:08

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 10 – 18 GHz



Date: 14.MAR.2014 09:15:05

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -69.26 dBm


Frequency range: 18 – 25 GHz



Date: 14.MAR.2014 09:50:49


Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold Mid Channel Transmit = 2437 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 11.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm

Frequency range: 18 – 25 GHz



Date: 14.MAR.2014 09:51:55

Frequency range: 30 – 335.4 MHz




Date: 13.MAR.2014 12:39:48

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: Receiver detector bandwidth 120 kHz
 High Channel Transmit = 2452 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 6.5 (used for 17 dBi antenna)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Conducted limits: (calculated using worst case antenna gain of 25 dBi)
 30-88 MHz: = 40 dBμV/m + 20log (3 meters) – 104.8 – 25 dBi antenna
 gain – 3 dB (MIMO operation) -4.7 dB (maximum ground
 reflection = -87.96 dBm
 88-216 MHz (43.5 dBμV/m): = -84.46 dBm
 216-960 MHz (46 dBμV/m): = -81.96 dBm
 960-1000 MHz (54 dBμV/m): = -73.96 dBm


Frequency range: 399.9 – 1000 MHz

	Att 10 dB AUTO	Det	MA/QP	Trd	ES-K1
	INPUT 1	ResBW	120 kHz		
		Meas T	100 ms	Unit	dBm

FREQUENCY	405.7900000 MHz		
LEVEL	PK+	-78.82	dBm
	QPK	-83.84	dBm




Marker 1 [T2]
 -87.22 dBm
 405.7900000 MHz



Date: 13.MAR.2014 13:07:33

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average
 Trace = Max Hold High Channel Transmit = 2452 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 6.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 1 – 4.2 GHz



Date: 13.MAR.2014 14:43:31

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak
 Trace = Max Hold High Channel Transmit = 2452 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 6.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 1 – 4.2 GHz



Date: 13.MAR.2014 14:44:47

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 6.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 4.2 – 10 GHz



Date: 13.MAR.2014 15:37:02

Test Date: 03-13-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 6.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 4.2 – 10 GHz



Date: 13.MAR.2014 15:38:04

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 6.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 10 – 18 GHz



Date: 14.MAR.2014 09:21:36

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 6.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm


Frequency range: 10 – 18 GHz



Date: 14.MAR.2014 09:22:38

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 6.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 54 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -69.26 dBm


Frequency range: 18 – 25 GHz



Date: 14.MAR.2014 10:00:31

Test Date: 03-14-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak Sweep = Auto Couple
 Trace = Max Hold High Channel Transmit = 2452 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 6.5 (used for 17 dBi antenna gain)
 Antenna gain: 17, 19, or 25 dBi
 Channel bandwidth: 40 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $74 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)}$ = -49.26 dBm

Frequency range: 18 – 25 GHz



Date: 14.MAR.2014 10:01:44


**Conducted Measurements for Radiated
Restricted Band Compliance
- 19 dBi Panel Antenna**

**for 20MHz Channel Bandwidth
Low & High Channel data**

**See the notes with the
20MHz Channel Bandwidth
Low & High Channel data
for the
17 dBi Sector Antenna**

Test Date: 03-15-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Average
 Trace = Max Hold **Mid Channel Transmit = 2437 MHz**
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 15 (used for 19 dBi antenna gain)
 Antenna gain: 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Average limit = 54 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = $54 + 20\log(3 \text{ meters}) - 104.8 - 25 \text{ dBi antenna gain} - 3 \text{ dB (MIMO operation)} = -69.26 \text{ dBm}$


Frequency range: 1 – 4.2 GHz



Date: 15.MAR.2014 12:48:30

Test Date: 03-15-2014
 Company: Cambium Networks
 EUT: EPMP 2.4 GHz STA MAC: 000456C69680
 Test: Unwanted Emission Levels in Restricted Bands- Conducted
 Operator: Craig B
 Comment: RBW = 1 MHz VBW = 3 MHz
 Detector = Peak
 Trace = Max Hold
 Mid Channel Transmit = 2437 MHz
 Point-to-Point & Point-to-Multipoint operation
 Output Power Setting 15 (used for 19 dBi antenna gain)
 Antenna gain: 19, or 25 dBi
 Channel bandwidth: 20 MHz
 Output port: 1 OFDM MCS15
 Peak limit = 74 dBμV/m at 3 meters
 Conducted limit (calculated using worst case antenna gain of 25 dBi)
 = 74 + 20log (3 meters) – 104.8 – 25 dBi antenna gain – 3 dB (MIMO
 operation) = -49.26 dBm

Frequency range: 1 – 4.2 GHz



Date: 15.MAR.2014 12:51:27

**Conducted Measurements for Radiated
Restricted Band Compliance
- 19 dBi Panel Antenna**

**for 20MHz Channel Bandwidth
Mid Channel data,
30 to 1000 MHz
&
4.2 to 25 GHz**

**See the notes with the
20MHz Channel Bandwidth
Mid Channel data
for the
17 dBi Sector Antenna,
30 to 1000 MHz
&
4.2 to 25 GHz**

**Conducted Measurements for Radiated
Restricted Band Compliance
- 25 dBi Dish Antenna**

**for 20MHz Channel Bandwidth
Low & High Channel data:**

See the notes with the 20MHz Channel
Bandwidth Low & High Channel data for the
17 dBi Sector Antenna

**for 20MHz Channel Bandwidth
Mid Channel data:**

See the notes with the 20MHz Channel
Bandwidth Mid Channel data for the
19 dBi Panel Antenna

**Conducted Measurements for Radiated
Restricted Band Compliance
- 25 dBi Dish Antenna**

for 40MHz Channel Bandwidth

**See the notes with the
40MHz Channel Bandwidth data
for the
17 dBi Sector Antenna**



166 South Carter, Genoa City, WI 53128

Company:	Cambium Networks
Model Tested:	C024900P021A & C024900P031A
Report Number:	19738
DLS Project:	6334

Appendix B – Measurement Data

B9.0 Radiated Restricted Band-Edge Compliance - radiated with Omni & Patch Antennas

Rule Section: FCC 15.205

Test Procedure: FCC KDB 558074 D01 DTS Meas Guidance v03r01 – *Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247*

12.0 Emissions in restricted frequency bands
12.1 Radiated emission measurements

Description: This test applies to harmonics/spurs that fall in the restricted bands listed in Section 15.205.

Measurements were taken for OFDM MCS15 with 20 MHz and 40 MHz channel bandwidths at the low, middle and high channels of operation. EUT was set to transmit continuously with a 100% duty cycle.


Limit: FCC Part 15.209

Results: Passed

Notes: Tested while transmitting from antennas. Both transmit chains were active during this test.

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Average
Trace mode = max hold
Low Channel Transmit = 2.412 GHz
Test software power setting: 18
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 13:59:59

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from 8 dBi Omni antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.412 GHz
Test software power setting: 18
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 14:01:07

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Average
Trace mode = max hold
Low Channel Transmit = 2.412 GHz
Test software power setting: 18
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 12:57:05

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from 8 dBi Omni antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.412 GHz
Test software power setting: 18
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 12:59:17

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Average
Trace mode = max hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 26.5
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 14:10:46

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from 8 dBi Omni antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 26.5
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 14:11:48

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Average
Trace mode = max hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 26.5
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 12:47:52

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from 8 dBi Omni antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 26.5
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 12:50:29

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Average
Trace mode = max hold
High Channel Transmit = 2.462 GHz
Test software power setting: 18
20 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 13:55:07

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from 8 dBi Omni antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.462 GHz
Test software power setting: 18
20 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 13:56:10

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Average
Trace mode = max hold
High Channel Transmit = 2.462 GHz
Test software power setting: 18
20 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 13:22:53

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from 8 dBi Omni antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.462 GHz
Test software power setting: 18
20 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 13:24:32

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Average
Trace mode = max hold
Low Channel Transmit = 2.427 GHz
Test software power setting: 15.5
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 14:03:23

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from 8 dBi Omni antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.427 GHz
Test software power setting: 15.5
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 14:04:18

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Average
Trace mode = max hold
Low Channel Transmit = 2.427 GHz
Test software power setting: 15.5
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 13:07:34

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from 8 dBi Omni antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.427 GHz
Test software power setting: 15.5
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 13:09:18

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Average
Trace mode = max hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 18
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 13:32:14

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from 8 dBi Omni antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 18
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 13:33:34

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Average
Trace mode = max hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 18
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 12:33:57

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from 8 dBi Omni antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 18
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 12:36:01

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Average
Trace mode = max hold
High Channel Transmit = 2.452 GHz
Test software power setting: 15.5
40 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 13:43:11

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from 8 dBi Omni antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.452 GHz
Test software power setting: 15.5
40 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 13:44:28

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Average
Trace mode = max hold
High Channel Transmit = 2.452 GHz
Test software power setting: 15.5
40 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 13:16:25

Test Date: 03-04-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – Radiated from 8 dBi Omni antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.452 GHz
Test software power setting: 15.5
40 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 4.MAR.2014 13:17:27

Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.412 GHz
Test software setting: 15 (used to get 14 dBm output)
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 09:27:23

Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.412 GHz
Test software setting: 15 (used to get 14 dBm output)
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 09:28:50

Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.412 GHz
Test software setting: 15 (used to get 14 dBm output)
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 08:58:47

Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.412 GHz
Test software setting: 15 (used to get 14 dBm output)
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 09:00:03

Test Date: 01-17-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software setting: 27 (used to get 26 dBm output)
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 17.JAN.2014 15:19:17

Test Date: 01-17-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software setting: 27 (used to get 26 dBm output)
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 17.JAN.2014 15:21:38

Test Date: 01-17-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software setting: 27 (used to get 26 dBm output)
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 17.JAN.2014 15:05:29

Test Date: 01-17-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software setting: 27 (used to get 26 dBm output)
20 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 17.JAN.2014 15:04:10

Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.462 GHz
Test software setting: 17 (used to get 16 dBm output)
20 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 09:50:22

Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.462 GHz
Test software setting: 17 (used to get 16 dBm output)
20 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 09:52:42

Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.462 GHz
Test software setting: 17 (used to get 16 dBm output)
20 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 10:12:52

Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.462 GHz
Test software setting: 17 (used to get 16 dBm output)
20 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 10:15:09

Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.422 GHz
Test software setting: 12.5 (used to get 11.5 dBm output)
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 11:24:50

Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.422 GHz
Test software setting: 12.5 (used to get 11.5 dBm output)
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 11:27:15

Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.422 GHz
Test software setting: 12.5 (used to get 11.5 dBm output)
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 11:40:52

Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.422 GHz
Test software setting: 12.5 (used to get 11.5 dBm output)
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 11:42:28

Test Date: 01-17-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software setting: **17** (used to get 16 dBm output)
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 17.JAN.2014 15:45:38

Test Date: 01-17-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software setting: 17 (used to get 16 dBm output)
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 17.JAN.2014 15:49:01

Test Date: 01-17-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software setting: 17 (used to get 16 dBm output)
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 17.JAN.2014 16:09:23

Test Date: 01-17-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software setting: **17** (used to get 16 dBm output)
40 MHz CH BW Both chains 0 and 1 active
Lower Restricted Band-Edge Frequency = 2.390 GHz
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 17.JAN.2014 16:08:24


Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.452 GHz
Test software setting: 13.5 (used to get 12.5 dBm output)
40 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.452 GHz
Test software setting: 13.5 (used to get 12.5 dBm output)
40 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 10:56:25

Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.452 GHz
Test software setting: 13.5 (used to get 12.5 dBm output)
40 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 10:37:08

Test Date: 01-20-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C1A853
Test: Band-Edge Measurements – Radiated from integral antenna
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.452 GHz
Test software setting: 13.5 (used to get 12.5 dBm output)
40 MHz CH BW Both chains 0 and 1 active
Upper Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 20.JAN.2014 10:51:27



166 South Carter, Genoa City, WI 53128

Company:	Cambium Networks
Model Tested:	C024900P021A & C024900P031A
Report Number:	19738
DLS Project:	6334

Appendix B – Measurement Data

B10.0 Conducted Measurements for Radiated Restricted Band-Edge Compliance - for Sector, Panel, and Dish Antennas

Rule Section: FCC 15.205

Test Procedure: FCC KDB 558074 D01 DTS Meas Guidance v03r01 – *Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247*

12.1 Emissions in restricted frequency bands

12.2.2 General Procedure for conducted measurements in restricted bands

Description: Measure the conducted output power (in dBm) using the detector specified (section 12.2.4 used for peak, and 12.2.5.1 used for average).
Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level.
For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (*e.g.*, Watts, mW).
Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

Compare the resultant electric field strength level to the applicable limit.


Limit: Average Limit = 54dBuV/m @ 3 meters
Peak Limit = 74dBuV/m @ 3 meters

Results: Passed

Notes: Measurements were taken for OFDM MCS15 with 20 MHz and 40 MHz channel bandwidths at the low, middle and high channels of operation. EUT was set to transmit continuously with a 100% duty cycle.

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.412 GHz
Test software power setting: 11.5
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 13:49:50

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.412 GHz
Test software power setting: 11.5
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 13:52:05

$$-61.14 \text{ dBm} = 0.000000769 \text{ mW}$$

$$-61.66 \text{ dBm} = 0.000000682 \text{ mW}$$

$$\text{Total} = 0.000000769 + 0.000000682 = 0.000001451 \text{ mW} = -58.38 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -58.38 \text{ dBm} + 17 \text{ dBi} - 20 \log 3 + 104.8 = 53.88 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 0.12 \text{ (for Average limit of } 54 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.412 GHz
Test software power setting: 11.5
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 13:58:03

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.412 GHz
Test software power setting: 11.5
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



$$-42.29 \text{ dBm} = 0.000059020 \text{ mW}$$

$$-44.09 \text{ dBm} = 0.000038994 \text{ mW}$$

$$\text{Total} = 0.000059020 + 0.000038994 = 0.000098014 \text{ mW} = -40.08 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -40.08 \text{ dBm} + 17 \text{ dBi} - 20 \log 3 + 104.8 = 72.18 \text{ dB}\mu\text{V/m}$$

Margin = 1.82 dB (for Peak limit of 74 dBuV/m)

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 20.5
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 08:42:22

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 20.5
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



$$-64.16 \text{ dBm} = 0.000000384 \text{ mW}$$

$$-62.72 \text{ dBm} = 0.000000535 \text{ mW}$$

$$\text{Total} = 0.000000384 + 0.000000535 = 0.000000919 \text{ mW} = -60.36 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -60.36 \text{ dBm} + 17 \text{ dBi} - 20 \log 3 + 104.8 = 51.90 \text{ dB}\mu\text{V/m}$$

Margin = 2.10 dB (for Average limit of 54 dB μ V/m)

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 20.5
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 08:38:06

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW ≥ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 20.5
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



$$-49.94 \text{ dBm} = 0.000010139 \text{ mW}$$

$$-48.15 \text{ dBm} = 0.000015311 \text{ mW}$$

$$\text{Total} = 0.000010139 + 0.000015311 = 0.00002545 \text{ mW} = -45.94 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -45.94 \text{ dBm} + 17 \text{ dBi} - 20 \log 3 + 104.8 = 66.32 \text{ dB}\mu\text{V/m}$$

Margin = 7.68 dB (for Peak limit of 74 dB μ V/m)

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 20.5
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 08:21:18

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 20.5
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



$$-61.07 \text{ dBm} = 0.000000782 \text{ mW}$$

$$-62.09 \text{ dBm} = 0.000000618 \text{ mW}$$

$$\text{Total} = 0.000000782 + 0.000000618 = 0.000001400 \text{ mW} = -58.53 \text{ dBm}$$


$$E = \text{EIRP} - 20\log D + 104.8$$

$$= -58.53 \text{ dBm} + 17 \text{ dBi} - 20\log 3 + 104.8 = 53.23 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = \mathbf{0.77 \text{ dB}}$$
 (for Average limit of 54 dBuV/m)

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 20.5
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 08:26:48

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 20.5
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 08:29:23

$$-47.18 \text{ dBm} = 0.000019143 \text{ mW}$$

$$-46.65 \text{ dBm} = 0.000021627 \text{ mW}$$

$$\text{Total} = 0.000019143 + 0.000021627 = 0.00004077 \text{ mW} = -43.89 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -43.89 \text{ dBm} + 17 \text{ dBi} - 20 \log 3 + 104.8 = 68.37 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 5.63 \text{ dB (for Peak limit of } 74 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.462 GHz
Test software power setting: 10
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 13:32:15

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.462 GHz
Test software power setting: 10
20 MHz CH BW Output port: 1
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



$$-61.58 \text{ dBm} = 0.000000695 \text{ mW}$$

$$-61.71 \text{ dBm} = 0.000000675 \text{ mW}$$

$$\text{Total} = 0.000000695 + 0.000000675 = 0.000001370 \text{ mW} = -58.63 \text{ dBm}$$


$$E = \text{EIRP} - 20\log D + 104.8$$

$$= -58.63 \text{ dBm} + 17 \text{ dBi} - 20\log 3 + 104.8 = 53.63 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 0.37 \text{ dB (for Average limit of } 54 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.462 GHz
Test software power setting: 10
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 13:40:57

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.462 GHz
Test software power setting: 10
20 MHz CH BW Output port: 1
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 13:38:31

$$-48.01 \text{ dBm} = 0.000015812 \text{ mW}$$

$$-45.87 \text{ dBm} = 0.000025882 \text{ mW}$$

$$\text{Total} = 0.000015812 + 0.000025882 = 0.000041694 \text{ mW} = -43.79 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -43.79 \text{ dBm} + 17 \text{ dBi} - 20 \log 3 + 104.8 = 68.47 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 5.53 \text{ dB (for Peak limit of } 74 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.427 GHz
Test software power setting: 10
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 14:13:54

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.427 GHz
Test software power setting: 10
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 14:11:51

-62.12 dBm = 0.000000614 mW

-60.61 dBm = 0.000000869 mW

Total = 0.000000614 + 0.000000869 = 0.000001483 mW = -58.28 dBm


$E = \text{EIRP} - 20\log D + 104.8$

$= -58.28 \text{ dBm} + 17 \text{ dBi} - 20\log 3 + 104.8 = 53.98 \text{ dB}\mu\text{V/m}$

Margin = 0.02 (for Average limit of 54 dB μ V/m)

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.427 GHz
Test software power setting: 10
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 14:18:44

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.427 GHz
Test software power setting: 10
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



$$-46.91 \text{ dBm} = 0.000020370 \text{ mW}$$

$$-44.91 \text{ dBm} = 0.000032285 \text{ mW}$$

$$\text{Total} = 0.000020370 + 0.000032285 = 0.000052655 \text{ mW} = -42.78 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -42.78 \text{ dBm} + 17 \text{ dBi} - 20 \log 3 + 104.8 = 69.48 \text{ dB}\mu\text{V/m}$$

Margin = 4.52 dB (for Peak limit of 74 dB μ V/m)

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 11.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 09:42:50

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 11.5
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 09:38:07

$$-64.05 \text{ dBm} = 0.000000394 \text{ mW}$$

$$-59.96 \text{ dBm} = 0.000001009 \text{ mW}$$

$$\text{Total} = 0.000000394 + 0.000001009 = 0.000001403 \text{ mW} = -58.53 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -58.53 \text{ dBm} + 17 \text{ dBi} - 20 \log 3 + 104.8 = 53.73 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = \mathbf{0.27 \text{ dB}}$$
 (for Average limit of 54 dBuV/m)

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 11.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 09:47:15

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 11.5
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



$$-49.79 \text{ dBm} = 0.000010495 \text{ mW}$$

$$-41.12 \text{ dBm} = 0.000077268 \text{ mW}$$

$$\text{Total} = 0.000010495 + 0.000077268 = 0.000087763 \text{ mW} = -40.56 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -40.56 \text{ dBm} + 17 \text{ dBi} - 20 \log 3 + 104.8 = 71.70 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 2.30 \text{ dB (for Peak limit of } 74 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 11.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 09:10:05

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 11.5
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



$$-62.01 \text{ dBm} = 0.000000630 \text{ mW}$$

$$-60.95 \text{ dBm} = 0.000000804 \text{ mW}$$

$$\text{Total} = 0.000000630 + 0.000000804 = 0.000001434 \text{ mW} = -58.43 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -58.43 \text{ dBm} + 17 \text{ dBi} - 20 \log 3 + 104.8 = 53.83 \text{ dB}\mu\text{V/m}$$

Margin = 0.17 dB (for Average limit of 54 dB μ V/m)

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 11.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 09:14:39

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 11.5
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



$$-49.75 \text{ dBm} = 0.000010593 \text{ mW}$$

$$-45.66 \text{ dBm} = 0.000027164 \text{ mW}$$

$$\text{Total} = 0.000010593 + 0.000027164 = 0.000037757 \text{ mW} = -44.23 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -44.23 \text{ dBm} + 17 \text{ dBi} - 20 \log 3 + 104.8 = 68.03 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 5.97 \text{ dB (for Peak limit of } 74 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.452 GHz
Test software power setting: 6.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 10:21:53

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1 MHz
VBW $\geq$ 3 MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.452 GHz
Test software power setting: 6.5
40 MHz CH BW Output port: 1
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 10:23:25

$$-62.36 \text{ dBm} = 0.000000581 \text{ mW}$$

$$-60.90 \text{ dBm} = 0.000000813 \text{ mW}$$

$$\text{Total} = 0.000000581 + 0.000000813 = 0.000001394 \text{ mW} = -58.55 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -58.55 \text{ dBm} + 17 \text{ dBi} - 20 \log 3 + 104.8 = 53.71 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 0.29 \text{ dB (for Average limit of } 54 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.452 GHz
Test software power setting: 6.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 12.MAR.2014 10:31:03

Test Date: 03-12-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1 MHz
VBW $\geq$ 3 MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.452 GHz
Test software power setting: 6.5
40 MHz CH BW Output port: 1
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



$$-44.91 \text{ dBm} = 0.000032285 \text{ mW}$$

$$-45.84 \text{ dBm} = 0.000026062 \text{ mW}$$

$$\text{Total} = 0.000032285 + 0.000026062 = 0.000058347 \text{ mW} = -42.33 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -42.33 \text{ dBm} + 17 \text{ dBi} - 20 \log 3 + 104.8 = 69.93 \text{ dB}\mu\text{V/m}$$

Margin = 4.07 dB (for Peak limit of 74 dB μ V/m)

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.412 GHz
Test software power setting: 10.5
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 13:52:54

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.412 GHz
Test software power setting: 10.5
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 13:55:50

$$-63.86 \text{ dBm} = 0.000000411 \text{ mW}$$

$$-64.61 \text{ dBm} = 0.000000346 \text{ mW}$$

$$\text{Total} = 0.000000411 + 0.000000346 = 0.000000757 \text{ mW} = -61.20 \text{ dBm}$$


$$E = \text{EIRP} - 20\log D + 104.8$$

$$= -61.20 \text{ dBm} + 19 \text{ dBi} - 20\log 3 + 104.8 = 53.06 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 0.94 \text{ (for Average limit of } 54 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.412 GHz
Test software power setting: 10.5
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 14:10:42

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.412 GHz
Test software power setting: 10.5
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



-44.82 dBm = 0.000032961 mW

-47.07 dBm = 0.000019634 mW

Total = 0.000032961 + 0.000019634 = 0.000052595 mW = -42.79 dBm


$E = \text{EIRP} - 20\log D + 104.8$

$= -42.79 \text{ dBm} + 19 \text{ dBi} - 20\log 3 + 104.8 = 71.47 \text{ dB}\mu\text{V/m}$

Margin = 2.53 dB (for Peak limit of 74 dB μ V/m)

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 15
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 13:03:09

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 15
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



$$-67.79 \text{ dBm} = 0.000000166 \text{ mW}$$

$$-65.84 \text{ dBm} = 0.000000261 \text{ mW}$$

$$\text{Total} = 0.000000166 + 0.000000261 = 0.000000427 \text{ mW} = -63.69 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -63.69 \text{ dBm} + 19 \text{ dBi} - 20 \log 3 + 104.8 = 50.57 \text{ dB}\mu\text{V/m}$$

Margin = 3.43 dB (for Average limit of 54 dBuV/m)

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 15
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 13:12:38

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 15
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



$$-54.96 \text{ dBm} = 0.000003192 \text{ mW}$$

$$-53.56 \text{ dBm} = 0.000004406 \text{ mW}$$

$$\text{Total} = 0.000003192 + 0.000004406 = 0.000007598 \text{ mW} = -51.19 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -51.19 \text{ dBm} + 19 \text{ dBi} - 20 \log 3 + 104.8 = 63.07 \text{ dB}\mu\text{V/m}$$

Margin = 10.93 dB (for Peak limit of 74 dB μ V/m)

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 15
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 12:39:48

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 15
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



$$-62.98 \text{ dBm} = 0.000000504 \text{ mW}$$

$$-64.16 \text{ dBm} = 0.000000384 \text{ mW}$$

$$\text{Total} = 0.000000504 + 0.000000384 = 0.000000888 \text{ mW} = -60.51 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -60.51 \text{ dBm} + 19 \text{ dBi} - 20 \log 3 + 104.8 = 53.75 \text{ dB}\mu\text{V/m}$$

Margin = 0.25 dB (for Average limit of 54 dB μ V/m)

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 15
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 12:51:57

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW ≥ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 15
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 12:48:40

-50.64 dBm = 0.000008630 mW

-53.15 dBm = 0.000004842 mW

Total = 0.000008630 + 0.000004842 = 0.000013472 mW = -48.70 dBm


$E = \text{EIRP} - 20\log D + 104.8$

$= -48.70 \text{ dBm} + 19 \text{ dBi} - 20\log 3 + 104.8 = 65.56 \text{ dB}\mu\text{V/m}$

Margin = 8.44 dB (for Peak limit of 74 dB μ V/m)

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.462 GHz
Test software power setting: 9
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 13:33:57

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.462 GHz
Test software power setting: 9
20 MHz CH BW Output port: 1
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



-63.42 dBm = 0.000000455 mW

-63.28 dBm = 0.000000470 mW

Total = 0.000000455 + 0.000000470 = 0.000000925 mW = -60.33 dBm


$E = \text{EIRP} - 20\log D + 104.8$

$= -60.33 \text{ dBm} + 19 \text{ dBi} - 20\log 3 + 104.8 = 53.93 \text{ dB}\mu\text{V/m}$

Margin = 0.07 dB (for Average limit of 54 dBuV/m)

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.462 GHz
Test software power setting: 9
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 13:45:12

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.462 GHz
Test software power setting: 9
20 MHz CH BW Output port: 1
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 13:41:44

$$-48.38 \text{ dBm} = 0.000014521 \text{ mW}$$

$$-47.70 \text{ dBm} = 0.000016982 \text{ mW}$$

$$\text{Total} = 0.000014521 + 0.000016982 = 0.000031503 \text{ mW} = -45.01 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -45.01 \text{ dBm} + 19 \text{ dBi} - 20 \log 3 + 104.8 = 69.25 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 4.75 \text{ dB (for Peak limit of } 74 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.427 GHz
Test software power setting: 9
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 15:51:55

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.427 GHz
Test software power setting: 9
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



$$-64.85 \text{ dBm} = 0.000000327 \text{ mW}$$

$$-62.77 \text{ dBm} = 0.000000528 \text{ mW}$$

$$\text{Total} = 0.000000327 + 0.000000528 = 0.000000855 \text{ mW} = -60.67 \text{ dBm}$$


$$E = \text{EIRP} - 20\log D + 104.8$$

$$= -60.67 \text{ dBm} + 19 \text{ dBi} - 20\log 3 + 104.8 = 53.59 \text{ dB}\mu\text{V/m}$$

Margin = 0.41 (for Average limit of 54 dBuV/m)

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.427 GHz
Test software power setting: 9
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 16:07:28

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.427 GHz
Test software power setting: 9
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



$$-50.22 \text{ dBm} = 0.000009506 \text{ mW}$$

$$-47.26 \text{ dBm} = 0.000018793 \text{ mW}$$

$$\text{Total} = 0.000009506 + 0.000018793 = 0.000028299 \text{ mW} = -45.48 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -45.48 \text{ dBm} + 19 \text{ dBi} - 20 \log 3 + 104.8 = 68.78 \text{ dB}\mu\text{V/m}$$

Margin = 5.22 dB (for Peak limit of 74 dBuV/m)

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 10
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 15:32:30

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 10
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



$$-69.61 \text{ dBm} = 0.000000109 \text{ mW}$$

$$-65.43 \text{ dBm} = 0.000000286 \text{ mW}$$

$$\text{Total} = 0.000000109 + 0.000000286 = 0.000000395 \text{ mW} = -64.02 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -64.02 \text{ dBm} + 19 \text{ dBi} - 20 \log 3 + 104.8 = 50.24 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 3.76 \text{ dB (for Average limit of } 54 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 10
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 15:43:55

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 10
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 15:39:32

$$-56.49 \text{ dBm} = 0.000002244 \text{ mW}$$

$$-49.84 \text{ dBm} = 0.000010375 \text{ mW}$$

$$\text{Total} = 0.000002244 + 0.000010375 = 0.000012619 \text{ mW} = -48.98 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -48.98 \text{ dBm} + 19 \text{ dBi} - 20 \log 3 + 104.8 = 65.28 \text{ dB}\mu\text{V/m}$$

Margin = 8.72 dB (for Peak limit of 74 dB μ V/m)

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 10
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 14:30:00

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 10
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



-64.00 dBm = 0.000000398 mW

-63.09 dBm = 0.000000491 mW

Total = 0.000000398 + 0.000000491 = 0.000000889 mW = -60.51 dBm


$E = \text{EIRP} - 20\log D + 104.8$

$= -60.51 \text{ dBm} + 19 \text{ dBi} - 20\log 3 + 104.8 = 53.75 \text{ dB}\mu\text{V/m}$

Margin = 0.25 dB (for Average limit of 54 dB μ V/m)

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 10
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 14:41:01

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1 MHz
VBW $\geq$ 3 MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 10
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



$$-51.97 \text{ dBm} = 0.000006353 \text{ mW}$$

$$-48.25 \text{ dBm} = 0.000014962 \text{ mW}$$

$$\text{Total} = 0.000006353 + 0.000014962 = 0.000021315 \text{ mW} = -46.71 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -46.71 \text{ dBm} + 19 \text{ dBi} - 20 \log 3 + 104.8 = 67.55 \text{ dB}\mu\text{V/m}$$

Margin = 6.45 dB (for Peak limit of 74 dBuV/m)

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.452 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 15:12:38

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.452 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: 1
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



$$-63.73 \text{ dBm} = 0.000000424 \text{ mW}$$

$$-62.99 \text{ dBm} = 0.000000502 \text{ mW}$$

$$\text{Total} = 0.000000424 + 0.000000502 = 0.000000926 \text{ mW} = -60.33 \text{ dBm}$$


$$E = \text{EIRP} - 20\log D + 104.8$$

$$= -60.33 \text{ dBm} + 19 \text{ dBi} - 20\log 3 + 104.8 = 53.93 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 0.07 \text{ dB (for Average limit of } 54 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.452 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 15:25:26

Test Date: 03-14-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1 MHz
VBW $\geq$ 3 MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.452 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: 1
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 14.MAR.2014 15:18:27

$$-45.72 \text{ dBm} = 0.000026792 \text{ mW}$$

$$-45.30 \text{ dBm} = 0.000029512 \text{ mW}$$

$$\text{Total} = 0.000026792 + 0.000029512 = 0.000056304 \text{ mW} = -42.49 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -42.49 \text{ dBm} + 19 \text{ dBi} - 20 \log 3 + 104.8 = 71.77 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 2.23 \text{ dB (for Peak limit of } 74 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.412 GHz
Test software power setting: 7
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 17:39:58

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.412 GHz
Test software power setting: 7
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 17:37:42

$$-69.65 \text{ dBm} = 0.000000108 \text{ mW}$$

$$-69.59 \text{ dBm} = 0.000000110 \text{ mW}$$

$$\text{Total} = 0.000000108 + 0.000000110 = 0.000000218 \text{ mW} = -66.60 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -66.60 \text{ dBm} + 25 \text{ dBi} - 20 \log 3 + 104.8 = 53.66 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 0.34 \text{ (for Average limit of } 54 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.412 GHz
Test software power setting: 7
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 17:44:23

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.412 GHz
Test software power setting: 7
20 MHz CH BW Output port: 1
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



$$-53.73 \text{ dBm} = 0.000004236 \text{ mW}$$

$$-53.47 \text{ dBm} = 0.000004498 \text{ mW}$$

$$\text{Total} = 0.000004236 + 0.000004498 = 0.000008734 \text{ mW} = -50.58 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -50.58 \text{ dBm} + 25 \text{ dBi} - 20 \log 3 + 104.8 = 69.68 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 4.32 \text{ dB (for Peak limit of } 74 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 7
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 15:14:09

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 7
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



$$-73.53 \text{ dBm} = 0.000000044 \text{ mW}$$

$$-71.25 \text{ dBm} = 0.000000075 \text{ mW}$$

$$\text{Total} = 0.000000044 + 0.000000075 = 0.000000119 \text{ mW} = -69.24 \text{ dBm}$$


$$E = \text{EIRP} - 20\log D + 104.8$$

$$= -69.24 \text{ dBm} + 25 \text{ dBi} - 20\log 3 + 104.8 = 51.02 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = \mathbf{2.98 \text{ dB}}$$
 (for Average limit of 54 dB μ V/m)

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 7
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 15:23:20

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 7
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



$$-60.88 \text{ dBm} = 0.000000817 \text{ mW}$$

$$-59.19 \text{ dBm} = 0.000001205 \text{ mW}$$

$$\text{Total} = 0.000000817 + 0.000001205 = 0.000002022 \text{ mW} = -56.94 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -56.94 \text{ dBm} + 25 \text{ dBi} - 20 \log 3 + 104.8 = 63.32 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = \mathbf{10.68 \text{ dB}}$$
 (for Peak limit of 74 dB μ V/m)

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 7
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 14:50:30

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 7
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



$$-69.66 \text{ dBm} = 0.000000108 \text{ mW}$$

$$-69.97 \text{ dBm} = 0.000000101 \text{ mW}$$

$$\text{Total} = 0.000000108 + 0.000000101 = 0.000000209 \text{ mW} = -66.80 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -66.80 \text{ dBm} + 25 \text{ dBi} - 20 \log 3 + 104.8 = 53.46 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 0.54 \text{ dB (for Average limit of } 54 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 7
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 15:08:59

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 7
20 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15




-58.18 dBm = 0.000001521 mW
-59.42 dBm = 0.000001143 mW
Total = 0.000001521 + 0.000001143 = 0.000002664 mW = -55.74 dBm

$E = \text{EIRP} - 20\log D + 104.8$
 $= -55.74 \text{ dBm} + 25 \text{ dBi} - 20\log 3 + 104.8 = 64.52 \text{ dB}\mu\text{V/m}$
Margin = 9.48 dB (for Peak limit of 74 dB μ V/m)

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.462 GHz
Test software power setting: 2.5
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 16:24:10

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.462 GHz
Test software power setting: 2.5
20 MHz CH BW Output port: 1
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



$$-70.66 \text{ dBm} = 0.000000086 \text{ mW}$$

$$-70.86 \text{ dBm} = 0.000000082 \text{ mW}$$

$$\text{Total} = 0.000000086 + 0.000000082 = 0.000000168 \text{ mW} = -67.74 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -67.74 \text{ dBm} + 25 \text{ dBi} - 20 \log 3 + 104.8 = 52.52 \text{ dB}\mu\text{V/m}$$

Margin = 1.48 dB (for Average limit of 54 dB μ V/m)

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.462 GHz
Test software power setting: 2.5
20 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 16:32:41

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.462 GHz
Test software power setting: 2.5
20 MHz CH BW Output port: 1
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 16:29:46

$$-57.83 \text{ dBm} = 0.000001648 \text{ mW}$$

$$-58.55 \text{ dBm} = 0.000001396 \text{ mW}$$

$$\text{Total} = 0.000001648 + 0.000001396 = 0.000003044 \text{ mW} = -55.16 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -55.16 \text{ dBm} + 25 \text{ dBi} - 20 \log 3 + 104.8 = 65.10 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 8.90 \text{ dB (for Peak limit of } 74 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.427 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 17:14:16

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Low Channel Transmit = 2.427 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 17:15:56

$$-70.04 \text{ dBm} = 0.000000099 \text{ mW}$$

$$-68.84 \text{ dBm} = 0.000000131 \text{ mW}$$

$$\text{Total} = 0.000000099 + 0.000000131 = 0.000000230 \text{ mW} = -66.38 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -66.38 \text{ dBm} + 25 \text{ dBi} - 20 \log 3 + 104.8 = 53.88 \text{ dB}\mu\text{V/m}$$

$$\text{Margin} = 0.12 \text{ (for Average limit of } 54 \text{ dB}\mu\text{V/m)}$$

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.427 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 17:23:12

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Low Channel Transmit = 2.427 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: 1
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



$$-56.86 \text{ dBm} = 0.000002061 \text{ mW}$$

$$-55.17 \text{ dBm} = 0.000003041 \text{ mW}$$

$$\text{Total} = 0.000002061 + 0.000003041 = 0.000005102 \text{ mW} = -52.92 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -52.92 \text{ dBm} + 25 \text{ dBi} - 20 \log 3 + 104.8 = 67.34 \text{ dB}\mu\text{V/m}$$

Margin = 6.66 dB (for Peak limit of 74 dB μ V/m)

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 15:59:08

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



-73.79 dBm = 0.000000042 mW

-71.48 dBm = 0.000000071 mW

Total = 0.000000042 + 0.000000071 = 0.000000113 mW = -69.47 dBm


$E = \text{EIRP} - 20\log D + 104.8$

$= -69.47 \text{ dBm} + 25 \text{ dBi} - 20\log 3 + 104.8 = 50.79 \text{ dB}\mu\text{V/m}$

Margin = 3.21 dB (for Average limit of 54 dB μ V/m)

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 16:02:44

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.390 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



$$-61.28 \text{ dBm} = 0.000000745 \text{ mW}$$

$$-59.90 \text{ dBm} = 0.000001023 \text{ mW}$$

$$\text{Total} = 0.000000745 + 0.000001023 = 0.000001768 \text{ mW} = -57.52 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -57.52 \text{ dBm} + 25 \text{ dBi} - 20 \log 3 + 104.8 = 62.74 \text{ dB}\mu\text{V/m}$$

Margin = 11.26 dB (for Peak limit of 74 dB μ V/m)

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 15:44:02

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
Mid Channel Transmit = 2.437 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



-69.25 dBm = 0.000000119 mW

-69.44 dBm = 0.000000114 mW

Total = 0.000000119 + 0.000000114 = 0.000000233 mW = -66.32 dBm


$E = \text{EIRP} - 20\log D + 104.8$

$= -66.32 \text{ dBm} + 25 \text{ dBi} - 20\log 3 + 104.8 = 53.94 \text{ dB}\mu\text{V/m}$

Margin = 0.06 dB (for Average limit of 54 dBuV/m)

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 15:47:21

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
Mid Channel Transmit = 2.437 GHz
Test software power setting: 4.5
40 MHz CH BW Output port: **1**
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



$$-57.96 \text{ dBm} = 0.000001600 \text{ mW}$$

$$-57.05 \text{ dBm} = 0.000001972 \text{ mW}$$

$$\text{Total} = 0.000001600 + 0.000001972 = 0.000003572 \text{ mW} = -54.47 \text{ dBm}$$


$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -54.47 \text{ dBm} + 25 \text{ dBi} - 20 \log 3 + 104.8 = 65.79 \text{ dB}\mu\text{V/m}$$

Margin = 8.21 dB (for Peak limit of 74 dBuV/m)

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.447 GHz
Test software power setting: 2.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 16:53:57

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = RMS
Trace mode = Average 200 traces
High Channel Transmit = 2.447 GHz
Test software power setting: 2.5
40 MHz CH BW Output port: 1
Restricted Band-Edge Frequency = 2.4835 GHz
Average Limit = 54 dBuV/m
Modulation Type: OFDM MCS15



-69.90 dBm = 0.000000102 mW

-69.59 dBm = 0.000000110 mW

Total = 0.000000102 + 0.000000110 = 0.000000212 mW = -66.72 dBm


$E = \text{EIRP} - 20\log D + 104.8$

$= -66.72 \text{ dBm} + 25 \text{ dBi} - 20\log 3 + 104.8 = 53.54 \text{ dB}\mu\text{V/m}$

Margin = 0.46 dB (for Average limit of 54 dBuV/m)

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B


Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.447 GHz
Test software power setting: 2.5
40 MHz CH BW Output port: 0
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 16:57:55

Test Date: 03-15-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Band-Edge Measurements – RF Conducted
Operator: Craig B

Comment: RBW = 1MHz
VBW $\geq$ 3MHz
Detector = Peak
Trace = Max Hold
High Channel Transmit = 2.447 GHz
Test software power setting: 2.5
40 MHz CH BW Output port: 1
Restricted Band-Edge Frequency = 2.4835 GHz
Peak Limit = 74 dBuV/m
Modulation Type: OFDM MCS15



Date: 15.MAR.2014 17:01:14

$$-55.75 \text{ dBm} = 0.000002661 \text{ mW}$$

$$-55.72 \text{ dBm} = 0.000002679 \text{ mW}$$

$$\text{Total} = 0.000002661 + 0.000002679 = 0.000005340 \text{ mW} = -52.72 \text{ dBm}$$

$$E = \text{EIRP} - 20 \log D + 104.8$$

$$= -52.72 \text{ dBm} + 25 \text{ dBi} - 20 \log 3 + 104.8 = 67.54 \text{ dB}\mu\text{V/m}$$

Margin = 6.46 dB (for Peak limit of 74 dB μ V/m)



166 South Carter, Genoa City, WI 53128

Company:
Model Tested:
Report Number:
DLS Project:

Cambium Networks
C024900P021A & C024900P031A
19738
6334

Appendix B – Measurement Data

B11.0 Duty Cycle of Test Unit

Rule Part: FCC Section 15.35(c)

Test Procedure: ANSI C63.10-2009 Section 7.5



Limits: Informative

Results: EUT is continuously transmitting (duty cycle = 100%).

Sample Equations: None



Notes: No duty cycle correction factor was applied to measurements for this device.

Test Date: 03-05-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Duty Cycle during testing
Operator: Craig B
20 MHz channel bandwidth; OFDM MCS15
Comment: Duty cycle = 100%



Date: 5.MAR.2014 13:45:00

Test Date: 03-05-2014
Company: Cambium Networks
EUT: EPMP 2.4 GHz STA MAC: 000456C69680
Test: Duty Cycle during testing
Operator: Craig B
40 MHz channel bandwidth; OFDM MCS15
Comment: Duty cycle = 100%



Date: 5.MAR.2014 13:46:17



166 South Carter, Genoa City, WI 53128

Company:
Model Tested:
Report Number:
DLS Project:

Cambium Networks
C024900P021A & C024900P031A
19738
6334

Appendix B – Measurement Data

B12.0 AC Line Conducted Emissions

Rule Part: FCC Part 15.207

Test Procedure: ANSI C63.10-2009
Section 6.2

Limit: FCC Part 15.207(a)

Results: Compliant

Notes: This was an AC Conducted emissions measurement.
The EUT was powered from a representative AC Adapter with an input of
120 VAC 60 Hz.


FCC Part 15.207

Voltage Mains Test

EUT: EPMP 2.4 GHz STA
Manufacturer: Cambium Networks
Operating Condition: 72 deg. F, 21% R.H.
Test Site: DLS O.F. Screen Room
Operator: Craig B
Test Specification: 120 V 60 Hz
Comment: Line 1; continuous Tx
Date: 01-24-2014

SCAN TABLE: "Line Cond SR Final"

Short Description:			Line Conducted Emissions				
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer	
Frequency 150.0 kHz	Frequency 30.0 MHz	Step Width 4.0 kHz	QuasiPeak CISPR AV	3.0 s	9 kHz	LISN DLS#128	



MEASUREMENT RESULT: "124bL1_fin"

1/24/2014 3:59PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector
0.153200	45.00	13.7	66	20.8	QP
0.161400	45.70	13.5	65	19.7	QP
0.183400	52.60	13.0	64	11.7	QP
0.184400	53.00	13.0	64	11.3	QP
0.202200	45.70	12.8	64	17.8	QP
0.378800	46.20	11.6	58	12.1	QP
0.900000	38.60	10.8	56	17.4	QP
1.436000	39.50	10.6	56	16.5	QP
2.100000	39.30	10.6	56	16.7	QP
3.072000	39.30	10.7	56	16.7	QP
3.672000	36.60	10.7	56	19.4	QP
3.752000	36.50	10.7	56	19.5	QP
5.801000	33.60	10.7	60	26.4	QP
26.609000	38.40	11.6	60	21.6	QP
27.158000	38.70	11.6	60	21.3	QP
29.237000	40.20	11.6	60	19.8	QP
29.966000	39.10	11.6	60	20.9	QP

MEASUREMENT RESULT: "124bL1_fin2"

1/24/2014 3:59PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector
0.183200	40.00	13.0	54	14.3	CAV
0.186200	41.50	13.0	54	12.7	CAV
0.250800	34.20	12.2	52	17.5	CAV
0.311000	34.80	11.9	50	15.1	CAV
0.376400	38.90	11.6	48	9.5	CAV
0.493200	28.10	11.2	46	18.0	CAV
0.680000	30.90	10.9	46	15.1	CAV
0.924000	31.00	10.8	46	15.0	CAV
1.428000	30.80	10.6	46	15.2	CAV
1.668000	31.20	10.7	46	14.8	CAV
3.232000	30.70	10.7	46	15.3	CAV
3.420000	30.00	10.7	46	16.0	CAV
18.365000	35.80	11.3	50	14.2	CAV
26.609000	35.40	11.6	50	14.6	CAV
27.158000	35.40	11.6	50	14.6	CAV
29.237000	36.50	11.6	50	13.5	CAV
29.786000	33.60	11.6	50	16.4	CAV
29.966000	35.20	11.6	50	14.8	CAV


FCC Part 15.207

Voltage Mains Test

EUT: EPMP 2.4 GHz STA
Manufacturer: Cambium Networks
Operating Condition: 72 deg. F, 21% R.H.
Test Site: DLS O.F. Screen Room
Operator: Craig B
Test Specification: 120 V 60 Hz
Comment: Line 2; continuous Tx
Date: 01-24-2014

SCAN TABLE: "Line Cond SR Final"

Short Description:			Line Conducted Emissions				
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer	
Frequency 150.0 kHz	Frequency 30.0 MHz	Width 4.0 kHz	QuasiPeak CISPR AV	3.0 s	9 kHz	LISN DLS#128	



MEASUREMENT RESULT: "124aL2_fin"

1/24/2014 3:52PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector
0.182600	53.10	13.0	64	11.3	QP
0.185600	54.80	13.0	64	9.4	QP
0.201000	48.70	12.8	64	14.9	QP
0.204200	46.00	12.8	63	17.4	QP
0.204800	45.50	12.8	63	17.9	QP
0.384000	46.70	11.6	58	11.5	QP
0.900000	40.30	10.8	56	15.7	QP
1.184000	40.40	10.7	56	15.6	QP
1.408000	40.70	10.6	56	15.3	QP
1.608000	40.70	10.7	56	15.3	QP
1.968000	39.70	10.6	56	16.3	QP
3.248000	39.10	10.7	56	16.9	QP
5.657000	34.10	10.7	60	25.9	QP
18.239000	37.00	11.3	60	23.0	QP
18.302000	38.80	11.3	60	21.2	QP
26.546000	37.30	11.6	60	22.7	QP
27.158000	39.20	11.6	60	20.8	QP
29.480000	37.20	11.6	60	22.8	QP

MEASUREMENT RESULT: "124aL2_fin2"

1/24/2014 3:52PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector
0.184200	40.50	13.0	54	13.8	CAV
0.190600	42.30	12.9	54	11.7	CAV
0.251800	34.80	12.2	52	16.9	CAV
0.311800	33.70	11.8	50	16.2	CAV
0.383400	38.00	11.6	48	10.2	CAV
0.455800	27.80	11.3	47	19.0	CAV
0.680000	30.40	10.9	46	15.6	CAV
0.924000	30.30	10.8	46	15.7	CAV
1.172000	30.60	10.7	46	15.4	CAV
1.924000	30.20	10.6	46	15.8	CAV
3.260000	30.70	10.7	46	15.3	CAV
3.416000	29.50	10.7	46	16.5	CAV
18.302000	36.40	11.3	50	13.6	CAV
18.914000	34.20	11.3	50	15.8	CAV
26.609000	35.60	11.6	50	14.4	CAV
27.158000	35.70	11.6	50	14.3	CAV
29.237000	36.70	11.6	50	13.3	CAV



166 South Carter, Genoa City, WI 53128

Company:	Cambium Networks
Model Tested:	C024900P021A & C024900P031A
Report Number:	19738
DLS Project:	6334

END OF REPORT

Revision #	Date	Comments	By
1.0	03-18-2014	Preliminary Release	JS