

# Radio Exposure Evaluation Report

**FCC ID** : Z8H89FT0071  
**Equipment** : e410 Indoor Wi-Fi access point, 802.11ac wave 2, 2x2  
**Brand Name** :  Cambium Networks  
**Model Name** : e410YYYYYYY(Y can be 0-9, a-z, A-Z, blank, "+" or "-" or "#")  
**Applicant** : Cambium Networks Inc.  
3800 Golf Road, Suite 360 Rolling Meadows, IL 60008,  
USA  
**Manufacturer** : Cambium Networks Ltd.  
Unit B2 Linhay Business Park Eastern Rd Ashburton,  
Devon TQ13 7UP United Kingdom  
**Standard** : 47 CFR Part 2.1091

The product was received on Jan. 04, 2021, and testing was started from Jan. 08, 2021 and completed on Feb. 10, 2021. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

**HISTORY OF THIS TEST REPORT .....3**

**1 GENERAL DESCRIPTION .....5**

1.1 EUT General Information .....5

1.2 Table for Multiple Listing .....5

1.3 Table for Permissive Change .....5

1.4 Testing Location .....5

**2 MAXIMUM PERMISSIBLE EXPOSURE .....6**

2.1 Limit of Maximum Permissible Exposure .....6

2.2 MPE Calculation Method .....6

2.3 Calculated Result and Limit.....7

### Photographs of EUT V01





### Summary of Test Result

| Report Clause | Ref Std. Clause | Test Items          | Result (PASS/FAIL) | Remark |
|---------------|-----------------|---------------------|--------------------|--------|
| 2             | -               | Exposure evaluation | PASS               | -      |

|  |
|--|
| <b>Declaration of Conformity:</b>  |
| The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. |
| <b>Comments and Explanations:</b>  |
| None.  |

Reviewed by: Ben Tseng

Report Producer: Amber Chiu

# 1 General Description

## 1.1 EUT General Information

| RF General Information |  |  |   |
|------------------------|--|--|---|
| Evaluation Mode        | Frequency Range (MHz)                            | Operating Frequency (MHz)                        | Modulation Type   |
| 2.4GHz WLAN            | 2400-2483.5                                      | 2412-2462  | 802.11b: DSSS (DBPSK, DQPSK, CCK)<br>802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)                 |
| 5GHz WLAN              | 5150-5250<br>5250-5350<br>5470-5725<br>5725-5850 | 5180-5240<br>5260-5320<br>5500-5700<br>5745-5825 | 802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)<br>802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) |

## 1.2 Table for Multiple Listing

The model names in the following table are all refer to the identical product.

| Model Name  | Description   |
|---|---|
| e410YYYYYYY(Y can be 0-9, a-z, A-Z, blank, "+" or "-" or "#") | All the models are identical, the difference model for as marketing strategy. |

## 1.3 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FA0D3123.

Below is the table for the change of the product with respect to the original one.

| Modifications                                    | Performance Checking |
|--|----------------------|
| Frequency bands U-NII-2A and U-NII-2C was added. | MPE                  |

## 1.4 Testing Location

| Testing Location                           |        |  |                      |
|--|--------|--|----------------------|
| <input checked="" type="checkbox"/>        | HWA YA | ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)    |                      |
|  |        | TEL : 886-3-327-3456   | FAX : 886-3-327-0973 |
| Test site Designation No. TW1190 with FCC. |        |  |                      |
| <input type="checkbox"/>                   | JHUBEI | ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.) |                      |
|  |        | TEL : 886-3-656-9065   | FAX : 886-3-656-9085 |
| Test site Designation No. TW0006 with FCC. |        |  |                      |

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                   | 6  |
| 3.0-30                | 1842 / f                          | 4.89 / f                          | (900 / f <sup>2</sup> )*                 | 6  |
| 30-300                | 61.4                              | 0.163                             | 1.0                                      | 6  |
| 300-1500              | -                                 | -                                 | F/300                                    | 6  |
| 1500-100,000          | -                                 | -                                 | 5  | 6  |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                   | 30   |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f <sup>2</sup> )*                   | 30   |
| 30-300                | 27.5                              | 0.073                             | 0.2                                      | 30   |
| 300-1500              | -                                 | -                                 | F/1500                                   | 30   |
| 1500-100,000          | -                                 | -                                 | 1.0                                      | 30   |

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



### 2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

WLAN 2.4GHz+WLAN 5GHz

| Mode     | DG (dBi) | Power (dBm) | EIRP (dBm) | Tolerance (dB) | Tune-up EIRP (dBm) | Tune-up EIRP (W) | Distance (cm) | S (mW/cm <sup>2</sup> ) | S Limit (mW/cm <sup>2</sup> ) | Ratio (S/Limit) |
|----------|----------|-------------|------------|----------------|--------------------|------------------|---------------|-------------------------|-------------------------------|-----------------|
| 2.4G;G1D | 4.5      | 25.69       | 30.19      | 0.50           | 30.69              | 1.17220          | 20            | 0.23320                 | 1.00000                       | 0.23320         |
| 5.8G;D1D | 8.71     | 26.41       | 35.12      | 0.50           | 35.62              | 3.64754          | 20            | 0.72565                 | 1.00000                       | 0.72565         |
|          |          |             |            |                |                    |                  |               |                         | Sum Ratio                     | 0.95885         |
|          |          |             |            |                |                    |                  |               |                         | Ratio Limit                   | 1               |

—————THE END—————