



# RADIO EXPOSURE TEST REPORT

**FCC ID** : Z8H89FT0078

**Equipment** : XV2-21X Indoor Wi-Fi 6 Access Point

**Brand Name** : Cambium Networks

**Model Name** : XV2-21X


**Applicant** : Cambium Networks Inc.  
3800 Golf Road, Suite 360 Rolling Meadows, IL 60008, USA

**Manufacturer** : Cambium Networks, Ltd.  
Ashburton, TQ13 7UP, UK

**Standard** : 47 CFR Part 2.1091

The product was received on Jun. 10, 2022, and testing was started from Jun. 13, 2022 and completed on Nov. 11, 2022. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.



Approved by: Sam Chen

**Sporton International Inc. Hsinchu Laboratory**  
No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



## Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
<b>1 General Description .....</b>	<b>5</b>
1.1 EUT General Information .....	5
1.2 Antenna Information .....	5
1.3 Table for EUT supports functions.....	7
1.4 Table for Permissive Change .....	7
1.5 Accessories .....	7
1.6 Applicable Standards .....	7
1.7 Testing Location .....	7
<b>2 Maximum Permissible Exposure .....</b>	<b>8</b>
2.1 Limit of Maximum Permissible Exposure .....	8
2.2 MPE Calculation Method.....	8
2.3 MPE Exemption.....	9
2.4 Calculated Result and Limit.....	10

### Photographs of EUT v01





## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Note: Reference to Sporton Project No.: 261015-01.

### Declaration of Conformity:

1. The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.
2. The measurement uncertainty please refer to report "Measurement Uncertainty".

### Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: **Sam Chen**

Report Producer: **Sophia Shiung**



# 1 General Description

## 1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850 5725-5895	5180-5250 5250-5320 5500-5700 5745-5825 5815-5885	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)

## 1.2 Antenna Information

Ant.	Port		Brand	Model Name	Antenna Type	Connector	Gain (dBi)
	WLAN 2.4GHz	WLAN 5GHz					
1	1	-	Gemtek	WRTQ-369AX	PIFA	MHF	Note1
2	2	-	Gemtek	WRTQ-369AX	PIFA	MHF	
3	-	2	Gemtek	WRTQ-369AX	PIFA	MHF	
4	-	1	Gemtek	WRTQ-369AX	PIFA	MHF	

Note1:

Ant.	Antenna Gain (dBi)						Cable Loss (dB)					
	WLAN 2.4GHz	WLAN 5GHz UNII 1	WLAN 5GHz UNII 2A	WLAN 5GHz UNII 2C	WLAN 5GHz UNII 3	WLAN 5GHz UNII 4	WLAN 2.4GHz	WLAN 5GHz UNII 1	WLAN 5GHz UNII 2A	WLAN 5GHz UNII 2C	WLAN 5GHz UNII 3	WLAN 5GHz UNII 4
1	5.65	-	-	-	-	-	0.6	-	-	-	-	-
2	5	-	-	-	-	-	0.35	-	-	-	-	-
3	-	6.32	7.2	7.76	7.79	7.79	-	0.9	0.9	0.9	0.9	0.9
4	-	6.92	6.89	8.16	8.15	7.48	-	0.4	0.4	0.4	0.4	0.4



Ant.	Net Gain (dBi)					
	WLAN 2.4GHz	WLAN 5GHz UNII 1	WLAN 5GHz UNII 2A	WLAN 5GHz UNII 2C	WLAN 5GHz UNII 3	WLAN 5GHz UNII 4
1	5.05	-	-	-	-	-
2	4.65	-	-	-	-	-
3	-	5.42	6.3	6.86	6.89	6.89
4	-	6.52	6.49	7.76	7.75	7.08

Note2: The above information was declared by manufacturer.

Note3: Directional gain information

Type	Maximum Output Power	Power Spectral Density
Non-BF	Directional gain = Max.gain + array gain. For power measurements on IEEE 802.11 devices Array Gain = 0 dB (i.e., no array gain) for N ANT ≤ 4	$Directional\ IGain = 10 \cdot \log \left[ \frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$
BF	$Directional\ IGain = 10 \cdot \log \left[ \frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$	$Directional\ IGain = 10 \cdot \log \left[ \frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$

Ex.

Directional Gain (NSS1) formula :

$$Directional\ IGain = 10 \cdot \log \left[ \frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

NSS1(g1,1) = 10<sup>G1/20</sup> ; NSS1(g1,2)= 10<sup>G2/20</sup> ;

g<sub>j,k</sub>=(Nss1(g1,1) + Nss1(g1,2) )<sup>2</sup>

DG = 10 log[(Nss1(g1,1) + Nss1(g1,2) )<sup>2</sup> / N<sub>ANT</sub>] => 10 log[(10<sup>G1/20</sup> + 10<sup>G2/20</sup> )<sup>2</sup> / N<sub>ANT</sub>]

Where ;

G1 = 10 ; G2 = 10 ;

2.4G G1 = 5.05 dBi; G2 = 4.65 dBi ; DG = 7.86 dBi

5G UNII 1 G1 = 5.42 dBi; G2 = 6.52 dBi; DG = 9.00 dBi

5G UNII 2A G1 = 6.3 dBi; G2 = 6.49 dBi; DG = 9.41 dBi

5G UNII 2C G1 = 6.86 dBi; G2 = 7.76 dBi; DG = 10.33 dBi

5G UNII 3 G1 = 6.89 dBi; G2 = 7.75 dBi; DG = 10.34 dBi

5G UNII 4 G1 = 6.89 dBi; G2 = 7.08 dBi; DG = 10.00 dBi

Note4: **For 2.4GHz function:**

**For IEEE 802.11 b/g/n/VHT/ax (2TX/2RX):**

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

**For 5GHz function:**

**For IEEE 802.11a/n/ac/ax (2TX/2RX):**

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.



### 1.3 Table for EUT supports functions

Function	Support Type	Support Band
AP	Master	Support 2.4GHz / 5GHz full band
Mesh	Slave without radar detection	Support 5GHz UNII 2A / UNII 2C

Note: The above information was declared by manufacturer.

### 1.4 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FA261015-03.

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
<ol style="list-style-type: none"> <li>1. Removing the Bridge mode.</li> <li>2. Removing the Mesh mode (master mode).</li> <li>3. Adding the Mesh mode (slave without radar) in UNII 2A and UNII 2C bands..</li> </ol>	After evaluation, it does not need to re-test.
<ol style="list-style-type: none"> <li>4. Adding the UNII 2A and UNII 2C bands.</li> </ol>	Maximum Permissible Exposure

Note: RF Exposure Evaluation of 5GHz UNII 1/ UNII 3 / UNII 4 and 2.4GHz Band are based on original test report.

### 1.5 Accessories

Wall-mounted rack\*1, Iron sheet for rack\*1

### 1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2.1091
  - ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01
- The following reference test guidance is not within the scope of accreditation of TAF.
- ♦ 47 CFR Part 1.1307
  - ♦ 47 CFR Part 1.1310

### 1.7 Testing Location

Testing Location Information	
Test Lab. : Sporton International Inc. Hsinchu Laboratory	
Hsinchu	ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)
(TAF: 3787)	TEL: 886-3-656-9065      FAX: 886-3-656-9085
	Test site Designation No. TW3787 with FCC.
	Conformity Assessment Body Identifier (CABID) TW3787 with ISED.



## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	*(100)	<6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1500	-	-	f/300	<6
1500-100,000	-	-	5	<6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1500	-	-	f/1500	<30
1500-100,000	-	-	1.0	<30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 51 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$





### 2.3 MPE Exemption

Option (A): 1.1307(b)(3)(i)(A): Available maximum time-averaged power is < 1 mW

Option (B): 1.1307(b)(3)(i)(B): Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, <= Pth.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

*d* = the separation distance (cm);

Option (C): 1.1307(b)(3)(i)(C): ERP is below a threshold calculated based on the distance

R between the person and the antenna / radiating structure, where  $R > \lambda / 2 \pi$ .

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R <sup>2</sup> .
1.34-30	3,450 R <sup>2</sup> /f <sup>2</sup> .
30-300	3.83 R <sup>2</sup> .
300-1,500	0.0128 R <sup>2</sup> f.
1,500-100,000	19.2R <sup>2</sup> .
Note: R is in meters, f is in MHz.	



## 2.4 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
2.4G;D1D	7.86	27.99	35.85	0.14	35.99	3.97192	51	0.12152	1.00000
5.2G;D1D	9.00	26.83	35.83	0.16	35.99	3.97192	51	0.12152	1.00000
5.3G;D1D	6.49	23.05	29.54	0.45	29.99	0.99770	51	0.03052	1.00000
5.6G;D1D	7.76	22.17	29.93	0.06	29.99	0.99770	51	0.03052	1.00000
5.8G;D1D	7.75	28.22	35.97	0.02	35.99	3.97192	51	0.12152	1.00000
5.81G;D1D	10.00	25.59	35.59	0.40	35.99	3.97192	51	0.12152	1.00000

MPE Exemption Option C							
Frequency (MHz)	$\lambda/2\pi$ (m)	R (m)	Tune-up EIRP (dBm)	Tune-up ERP (dBm)	Tune-up ERP (W)	ERP Threshold (W)	MPE Exemption
2437	0.0196	0.51	35.99	33.84	2.421	4.994	Complies
5745	0.0083		35.99	33.84	2.421	4.994	Complies

Simultaneous Transmission Analysis Mode: WLAN 2.4GHz + WLAN 5GHz

Simultaneous Transmissions Option C							
Frequency (MHz)	R (m)	Tune-up EIRP (dBm)	Tune-up ERP (dBm)	Tune-up ERP (W)	ERP Threshold (W)	Simultaneous Transmissions	Simultaneous Transmissions Limit
2437	0.51	35.99	33.84	2.421	4.994	0.97	<= 1
5745		35.99	33.84	2.421	4.994		

————THE END————