

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Fax: +86 (0) 755 2671 0594 Page: 1 of 6

RF Exposure Evaluation Report

Application No.: SZEM1204002106RF

Applicant: Edifier International Limited

Manufacturer:Beijing Edifier technology Co., Ltd.FactoryDongguan Edifier technology Co., Ltd.

Product Name: Multimedia Speaker

Model No.(EUT): iF600BT

Add Model No.: Breathe Bluetooth

FCC ID: Z9G-EDF06

Standards: FCC CFR Title 47 Part 1.1307

FCC CFR Title 47 Part 1.1310

Date of Receipt: 2012-04-27

Date of Test: 2012-05-07 to 2012-05-16

Date of Issue: 2012-05-21

Test Result : PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM120400210602

Page: 2 of 6

2 Contents

		Pa	ge
1	С	OVER PAGE	1
_			
2	С	ONTENTS	2
3	G	ENERAL INFORMATION	3
3	3.1		
_	3.2	GENERAL DESCRIPTION OF EUT.	3
3	3.3	TEST LOCATION	4
3	3.4	TEST FACILITY	4
3	3.5	DEVIATION FROM STANDARDS	4
3	3.6	ABNORMALITIES FROM STANDARD CONDITIONS	4
3	3.7		4
4	R	F EXPOSURE EVALUATION	5
1	1	RF Exposure Compliance Requirement	_
4	⊦. I 1	.1.1 Limits	د د
	4. 1	.1.2 Test Procedure	ر 2
4		B EUT RF Exposure Evaluation.	



Report No.: SZEM120400210602

Page: 3 of 6

3 General Information

3.1 Client Information

Applicant:	Edifier International Limited		
Address of Applicant:	Room 2207-9,Tower Two, Lippo Centre 89 Queensway, HongKong		
Manufacturer:	Beijing Edifier technology Co., Ltd.		
Address of Manufacturer:	8th floor, ZuoAn Building, NO.68 BeiSiHuanXiLu, Haidian District,		
	Beijing 100080, CHINA		
Factory:	Dongguan Edifier technology Co., Ltd.		
Address of Factory:	No.2 Gongyedong Road, Songshan Lake Sci & Tech Industry Park,		
	Dongguan, Guangdong 523808, PR. China		

3.2 General Description of EUT

Name: Multimedia Speaker Model No. iF600BT, Breathe Bluetooth Trade Mark: EDIFIER Operation Frequency: 2402MHz~2480MHz Bluetooth Version: 2.1+EDR Modulation Technique: Frequency Hopping Spread Spectrum(FHSS) Modulation Type: GFSK, π/4DQPSK, 8DPSK Number of Channel: 79 Hopping Channel Type: Adaptive Frequency Hopping systems Sample Type: fixed production Test Power Grade: 255(manufacturer declare) Test Software of EUT: CSR blue suite (manufacturer declare) Antenna Type and Gain: Type: Integral Gain: 2.5dBi
Trade Mark: Operation Frequency: 2402MHz~2480MHz Bluetooth Version: 2.1+EDR Modulation Technique: Frequency Hopping Spread Spectrum(FHSS) Modulation Type: GFSK, π/4DQPSK, 8DPSK Number of Channel: 79 Hopping Channel Type: Adaptive Frequency Hopping systems Sample Type: fixed production Test Power Grade: 255(manufacturer declare) Test Software of EUT: CSR blue suite (manufacturer declare) Type: Integral Gain: 2.5dBi
Operation Frequency: 2402MHz~2480MHz Bluetooth Version: 2.1+EDR Modulation Technique: Frequency Hopping Spread Spectrum(FHSS) Modulation Type: GFSK, π/4DQPSK, 8DPSK Number of Channel: 79 Hopping Channel Type: Adaptive Frequency Hopping systems Sample Type: fixed production Test Power Grade: 255(manufacturer declare) Test Software of EUT: CSR blue suite (manufacturer declare) Antenna Type and Gain: Type: Integral Gain: 2.5dBi
Bluetooth Version: 2.1+EDR Modulation Technique: Frequency Hopping Spread Spectrum(FHSS) Modulation Type: GFSK, π/4DQPSK, 8DPSK Number of Channel: 79 Hopping Channel Type: Adaptive Frequency Hopping systems Sample Type: fixed production Test Power Grade: 255(manufacturer declare) Test Software of EUT: CSR blue suite (manufacturer declare) Antenna Type and Gain: Type: Integral Gain: 2.5dBi
Modulation Technique: Frequency Hopping Spread Spectrum(FHSS) Modulation Type: GFSK, π/4DQPSK, 8DPSK Number of Channel: 79 Hopping Channel Type: Adaptive Frequency Hopping systems Sample Type: fixed production Test Power Grade: 255(manufacturer declare) Test Software of EUT: CSR blue suite (manufacturer declare) Antenna Type and Gain: Type: Integral Gain: 2.5dBi
Modulation Type: GFSK, π/4DQPSK, 8DPSK Number of Channel: 79 Hopping Channel Type: Adaptive Frequency Hopping systems Sample Type: fixed production Test Power Grade: 255(manufacturer declare) Test Software of EUT: CSR blue suite (manufacturer declare) Antenna Type and Gain: Type: Integral Gain: 2.5dBi
Number of Channel: 79 Hopping Channel Type: Adaptive Frequency Hopping systems Sample Type: fixed production Test Power Grade: 255(manufacturer declare) Test Software of EUT: CSR blue suite (manufacturer declare) Antenna Type and Gain: Type: Integral Gain: 2.5dBi
Hopping Channel Type: Adaptive Frequency Hopping systems Sample Type: fixed production Test Power Grade: 255(manufacturer declare) Test Software of EUT: CSR blue suite (manufacturer declare) Antenna Type and Gain: Type: Integral Gain: 2.5dBi
Sample Type: fixed production Test Power Grade: 255(manufacturer declare) Test Software of EUT: CSR blue suite (manufacturer declare) Antenna Type and Gain: Type: Integral Gain: 2.5dBi
Test Power Grade: 255(manufacturer declare) Test Software of EUT: CSR blue suite (manufacturer declare) Antenna Type and Gain: Type: Integral Gain: 2.5dBi
Test Software of EUT: CSR blue suite (manufacturer declare) Antenna Type and Gain: Type: Integral Gain: 2.5dBi
Antenna Type and Gain: Type: Integral Gain: 2.5dBi
Gain: 2.5dBi
AC Adapter: MODEL NO:ADT-60200
INPUT: 100-240V~ 50/60Hz 1.5A
OUTPUT:20V == 2.75A
Test Voltage: AC 230V
AUX in Line: <3m
RCA Line: <3m
DC Line: <3m

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM120400210602

Page: 4 of 6

3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab
No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

VCCI

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1.

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.

3.7 Other Information Requested by the Customer

None.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a ransaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM120400210602

Page: 5 of 6

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Table 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)					
(A) Limits for Occupational/Controlled Exposures									
0.3–3.0 3.0–30 30–300 30–1500 1500–100,000	614 1842/f 61.4	1.63 4.89/f 0.163	*(100) *(900/f²) 1.0 f/300 5	6 6 6 6					
(B) Limits for General Population/Uncontrolled Exposure									
0.3–1.34 1.34–30 30–300 300–1500 1500–100,000	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/f²) 0.2 f/1500 1.0	30 30 30 30 30					

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4*Pi*R2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2 . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms-e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM120400210602

Page: 6 of 6

4.1.3 EUT RF Exposure Evaluation

Antenna Gain: 2.5dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.778in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency	Max Conducted	Output Power	Power Density	Limit	Result
	(MHz)	Peak Output	to Antenna	at R = 20 cm		
		Power (dBm)	(mW)	(mW/cm ²)		
Lowest	2402	2.92	1.9588	0.000693	1.0	PASS

Note: Refer to report No. SZEM120400210601 for EUT test EIRP value.

The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.