



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

Test Report

Report No. : CQASZ20210300370E-01
Applicant: Edifier International Limited
Address of Applicant: P.O. Box 6264 General Post Office Hong Kong
Equipment Under Test (EUT):
Product: True Wireless Gaming Earbuds
Model No.: GM4
Brand Name: EDIFIER,HECATE
FCC ID: Z9G-EDF108
Standards: 47 CFR Part 15, Subpart C
Date of Test: 2021-3-29 to 2021-4-12
Date of Issue: 2021-4-12
Test Result : **PASS***

Tested By: _____
Jun Li

(Jun Li)

Reviewed By: _____
Ares Liu

(Ares Liu)

Approved By: _____
Sheek Luo

(Sheek luo)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20210300370E-01	Rev.01	Initial report	2021-4-12

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2013)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2013)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2013)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2013)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS

Note: When the EUT charging, BT will not work.

3 Contents

	Page
COVER PAGE.....	1
1 VERSION.....	2
2 TEST SUMMARY.....	3
3 CONTENTS.....	4
4 GENERAL INFORMATION.....	5
4.1 CLIENT INFORMATION.....	5
4.2 GENERAL DESCRIPTION OF EUT.....	5
4.3 ADDITIONAL INSTRUCTIONS.....	7
4.4 TEST ENVIRONMENT.....	8
4.5 DESCRIPTION OF SUPPORT UNITS.....	8
4.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	9
4.7 TEST LOCATION.....	10
4.8 TEST FACILITY.....	10
4.9 ABNORMALITIES FROM STANDARD CONDITIONS.....	10
4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	10
4.11 EQUIPMENT LIST.....	11
5 TEST RESULTS AND MEASUREMENT DATA.....	12
5.1 ANTENNA REQUIREMENT.....	12
5.2 CONDUCTED EMISSIONS.....	13
5.3 CONDUCTED PEAK OUTPUT POWER.....	19
5.4 20dB OCCUPY BANDWIDTH.....	32
5.5 CARRIER FREQUENCIES SEPARATION.....	43
5.6 HOPPING CHANNEL NUMBER.....	56
5.7 DWELL TIME.....	61
5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS.....	92
5.9 SPURIOUS RF CONDUCTED EMISSIONS.....	107
5.10 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM.....	144
5.11 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS.....	146
5.11.1 Radiated Emission below 1GHz.....	149
5.11.2 Transmitter Emission above 1GHz.....	153
6 PHOTOGRAPHS - EUT TEST SETUP.....	159
6.1 RADIATED EMISSION.....	159
LEFT EAR:.....	159
RIGHT EAR:.....	161
6.2 CONDUCTED EMISSION.....	162
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS.....	163

4 General Information

4.1 Client Information

Applicant:	Edifier International Limited
Address of Applicant:	P.O. Box 6264 General Post Office Hong Kong
Manufacturer:	Dongguan Edifier Esports Technology Co., Ltd
Address of Manufacturer:	5th floor, Office Building in the 1st district, No. 2, East Industry Road, Songshan Lake Science & Technology Industrial Park, Dongguan, 523808, CHINA
Factory:	Dongguan Edifier Technology Co., Ltd.
Address of Factory:	No.2 Gongyedong Road, Songshan Lake Sci&Tech Industry Park, Dongguan,Guangdong 523808, PR.China

4.2 General Description of EUT

Product Name:	True Wireless Gaming Earbuds
Model No.:	GM4
Trade Mark:	EDIFIER,HECATE
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	AWRDLAB_R_1_0_4_173
Antenna Type:	FPC antenna
Antenna Gain:	1.96 dBi
Power Supply:	lithium battery: DC3.7V,50mAh/60mAh, Charge by DC5.0V

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

Note:


In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz

4.3 Additional Instructions

EUT Test Software Settings:		
Mode:	<input checked="" type="checkbox"/> Special software is used. <input type="checkbox"/> Through engineering command into the engineering mode. engineering command: ###3646633###	
EUT Power level:	Class2 (Power level is built-in set parameters and cannot be changed and selected)	
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.		
Mode	Channel	Frequency(MHz)
DH1/DH3/DH5	CH0	2402
	CH39	2441
	CH78	2480
2DH1/2DH3/2DH5	CH0	2402
	CH39	2441
	CH78	2480
3DH1/3DH3/3DH5	CH0	2402
	CH39	2441
	CH78	2480

Run Software:



4.4 Test Environment

Operating Environment:	
Temperature:	25.5 °C
Humidity:	53 % RH
Atmospheric Pressure:	1009mbar
Test Mode:	Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	FCC certification
Adapter	XIAOMI	MDY-08-EF	/	FCC

4.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	±5.12dB	(1)
2	Radiated Emission (Above 1GHz)	±4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	±3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8°C	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	time	0.6 %.	(1)
14	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.7 Test Location

Shenzhen Huaxia Testing Technology Co., Ltd,

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

4.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 22984-1

The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

The test facility is recognized, certified, or accredited by the following organizations:

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.9 Abnormalities from Standard Conditions

None.

4.10 Other Information Requested by the Customer

None.

4.11 Equipment List



Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2020/9/26	2021/9/25
Spectrum analyzer	R&S	FSU26	CQA-038	2020/10/28	2021/10/27
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2020/9/26	2021/9/25
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2020/11/2	2021/11/1
Loop antenna	Schwarzbeck	FMZB1516	CQA-087	2019/10/28	2021/10/27
Bilog Antenna	R&S	HL562	CQA-011	2019/9/26	2021/9/25
Horn Antenna	R&S	HF906	CQA-012	2019/9/26	2021/9/25
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2019/9/26	2021/9/25
Coaxial Cable (Above 1GHz)	CQA	N/A	C019	2020/9/26	2021/9/25
Coaxial Cable (Below 1GHz)	CQA	N/A	C020	2020/9/26	2021/9/25
Antenna Connector	CQA	RFC-01	CQA-080	2020/9/26	2021/9/25
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2020/9/26	2021/9/25
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2020/9/26	2021/9/25
EMI Test Receiver	R&S	ESPI3	CQA-013	2020/9/26	2021/9/25
LISN	R&S	ENV216	CQA-003	2020/11/5	2021/11/4
Coaxial cable	CQA	N/A	CQA-C009	2020/9/26	2021/9/25

Note:


The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>	
EUT Antenna:Left ear	
EUT Antenna:Right ear	
<p>The antenna is integral antenna. The best case gain of the antenna is 1.96 dBi.</p>	

5.2 Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	* Decreases with the logarithm of the frequency.		
Test Procedure:	<ol style="list-style-type: none"> 1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 		
Test Setup:			

Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type at the lowest, middle, high channel.
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation at the lowest channel is the worst case. Only the worst case is recorded in the report.
Test Voltage:	AC 120V/60Hz
Test Results:	Pass

Measurement Data

Left ear

Live line:




	Read Freq	Read Level	Factor	Limit Level	Over Limit	Remark	Pol/Phase	
	MHz	dBuV	dB	dBuV	dB			
1	0.220	21.43	9.49	30.92	52.82	-21.90	Average	Line
2	0.220	26.56	9.49	36.05	62.82	-26.77	QP	Line
3	0.605	19.79	9.71	29.50	46.00	-16.50	Average	Line
4	0.605	25.40	9.71	35.11	56.00	-20.89	QP	Line
5	1.330	19.39	9.53	28.92	46.00	-17.08	Average	Line
6	1.330	24.42	9.53	33.95	56.00	-22.05	QP	Line
7	2.675	12.98	9.58	22.56	46.00	-23.44	Average	Line
8	2.675	19.28	9.58	28.86	56.00	-27.14	QP	Line
9	3.900	10.48	9.67	20.15	46.00	-25.85	Average	Line
10	3.900	18.43	9.67	28.10	56.00	-27.90	QP	Line
11	12.185	11.37	9.85	21.22	50.00	-28.78	Average	Line
12	12.185	21.51	9.85	31.36	60.00	-28.64	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.180	21.25	9.48	30.73	54.49	-23.76	Average	Neutral
2	0.180	27.04	9.48	36.52	64.49	-27.97	QP	Neutral
3	0.460	18.88	9.57	28.45	46.69	-18.24	Average	Neutral
4	0.460	24.23	9.57	33.80	56.69	-22.89	QP	Neutral
5	1.240	19.18	9.71	28.89	46.00	-17.11	Average	Neutral
6	1.240	24.12	9.71	33.83	56.00	-22.17	QP	Neutral
7	PP 1.565	20.26	9.72	29.98	46.00	-16.02	Average	Neutral
8	QP 1.565	25.25	9.72	34.97	56.00	-21.03	QP	Neutral
9	2.710	11.94	9.74	21.68	46.00	-24.32	Average	Neutral
10	2.710	17.53	9.74	27.27	56.00	-28.73	QP	Neutral
11	12.130	8.90	9.94	18.84	50.00	-31.16	Average	Neutral
12	12.130	17.09	9.94	27.03	60.00	-32.97	QP	Neutral

Measurement Data

Right ear

Live line:




	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.220	21.43	9.49	30.92	52.82	-21.90	Average	Line
2	0.220	26.56	9.49	36.05	62.82	-26.77	QP	Line
3 PP	0.605	19.79	9.71	29.50	46.00	-16.50	Average	Line
4 QP	0.605	25.40	9.71	35.11	56.00	-20.89	QP	Line
5	1.330	19.39	9.53	28.92	46.00	-17.08	Average	Line
6	1.330	24.42	9.53	33.95	56.00	-22.05	QP	Line
7	2.675	12.98	9.58	22.56	46.00	-23.44	Average	Line
8	2.675	19.28	9.58	28.86	56.00	-27.14	QP	Line
9	3.900	10.48	9.67	20.15	46.00	-25.85	Average	Line
10	3.900	18.43	9.67	28.10	56.00	-27.90	QP	Line
11	12.185	11.37	9.85	21.22	50.00	-28.78	Average	Line
12	12.185	21.51	9.85	31.36	60.00	-28.64	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.180	21.25	9.48	30.73	54.49	-23.76	Average	Neutral
2	0.180	27.04	9.48	36.52	64.49	-27.97	QP	Neutral
3	0.460	18.88	9.57	28.45	46.69	-18.24	Average	Neutral
4	0.460	24.23	9.57	33.80	56.69	-22.89	QP	Neutral
5	1.240	19.18	9.71	28.89	46.00	-17.11	Average	Neutral
6	1.240	24.12	9.71	33.83	56.00	-22.17	QP	Neutral
7 PP	1.565	20.26	9.72	29.98	46.00	-16.02	Average	Neutral
8 QP	1.565	25.25	9.72	34.97	56.00	-21.03	QP	Neutral
9	2.710	11.94	9.74	21.68	46.00	-24.32	Average	Neutral
10	2.710	17.53	9.74	27.27	56.00	-28.73	QP	Neutral
11	12.130	8.90	9.94	18.84	50.00	-31.16	Average	Neutral
12	12.130	17.09	9.94	27.03	60.00	-32.97	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.


5.3 Conducted Peak Output Power


Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p style="text-align: center;"><i>Remark: Offset=Cable loss+ attenuation factor.</i></p>
Limit:	21dBm
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data: Left ear

GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	4.090	21.00	Pass
Middle	4.930	21.00	Pass
Highest	4.690	21.00	Pass
$\pi/4$ DQPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	3.050	21.00	Pass
Middle	3.790	21.00	Pass
Highest	3.460	21.00	Pass
8DPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	3.360	21.00	Pass
Middle	4.140	21.00	Pass
Highest	3.900	21.00	Pass

Test plot as follows:










8DPSK/HCH





Date: 6.APR.2021 13:27:13

Measurement Data: Right ear

GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	3.620	21.00	Pass
Middle	4.380	21.00	Pass
Highest	4.180	21.00	Pass
$\pi/4$ DQPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	2.350	21.00	Pass
Middle	3.080	21.00	Pass
Highest	2.730	21.00	Pass
8DPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	2.760	21.00	Pass
Middle	3.510	21.00	Pass
Highest	3.180	21.00	Pass


Test plot as follows:








8DPSK/LCH




Date: 6.APR.2021 15:38:26

8DPSK/MCH




Date: 6.APR.2021 15:41:59

8DPSK/HCH



Date: 6.APR.2021 15:45:04


5.4 20dB Occupy Bandwidth



Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Limit:	NA
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass


Measurement Data: Left ear



Test channel	20dB Occupy Bandwidth (MHz)		
	GFSK	$\pi/4$ DQPSK	8DPSK
Lowest	0.954	1.294	1.302
Middle	0.956	1.292	1.306
Highest	0.956	1.294	1.306


Test plot as follows:
















Measurement Data: Right ear


Test channel	20dB Occupy Bandwidth (MHz)		
	GFSK	$\pi/4$ DQPSK	8DPSK
Lowest	0.954	1.294	1.302
Middle	0.956	1.294	1.306
Highest	0.956	1.294	1.300


Test plot as follows:












5.5 Carrier Frequencies Separation


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Limit:	2/3 of the 20dB bandwidth Remark: the transmission power is less than 0.125W.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass



Measurement Data: Left ear



GFSK mode			
Test channel	Carrier Frequencies Separation (MHz)	Limit (MHz)	Result
Lowest	1.010	≥ 0.637	Pass
Middle	1.010	≥ 0.637	Pass
Highest	1.005	≥ 0.637	Pass
$\pi/4$ DQPSK mode			
Test channel	Carrier Frequencies Separation (MHz)	Limit (MHz)	Result
Lowest	0.990	≥ 0.863	Pass
Middle	1.005	≥ 0.863	Pass
Highest	1.000	≥ 0.863	Pass
8DPSK mode			
Test channel	Carrier Frequencies Separation (MHz)	Limit (MHz)	Result
Lowest	0.995	≥ 0.871	Pass
Middle	0.995	≥ 0.871	Pass
Highest	1.000	≥ 0.871	Pass


Mode	20dB bandwidth (MHz) (worse case)	Limit (MHz) (Carrier Frequencies Separation)
GFSK	0.956	0.637
$\pi/4$ DQPSK	1.924	0.863
8DPSK	1.306	0.871

Test plot as follows:














Measurement Data: Right ear



GFSK mode			
Test channel	Carrier Frequencies Separation (MHz)	Limit (MHz)	Result
Lowest	1.005	≥ 0.736	Pass
Middle	0.995	≥ 0.736	Pass
Highest	1.014	≥ 0.736	Pass
$\pi/4$ DQPSK mode			
Test channel	Carrier Frequencies Separation (MHz)	Limit (MHz)	Result
Lowest	1.000	≥ 0.929	Pass
Middle	0.995	≥ 0.929	Pass
Highest	1.010	≥ 0.929	Pass
8DPSK mode			
Test channel	Carrier Frequencies Separation (MHz)	Limit (MHz)	Result
Lowest	1.000	≥ 0.931	Pass
Middle	1.000	≥ 0.931	Pass
Highest	1.010	≥ 0.931	Pass


Mode	20dB bandwidth (MHz) (worse case)	Limit (MHz) (Carrier Frequencies Separation)
GFSK	0.956	0.638
$\pi/4$ DQPSK	1.294	0.863
8DPSK	1.306	0.871

Test plot as follows:












5.6 Hopping Channel Number


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p style="text-align: center;"><i>Remark: Offset=Cable loss+ attenuation factor.</i></p>
Limit:	At least 15 channels
Exploratory Test Mode:	hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data: Left ear

Mode	Hopping channel numbers	Limit
GFSK	79	≥ 15
$\pi/4$ DQPSK	79	≥ 15
8DPSK	79	≥ 15

Test plot as follows:






Measurement Data: Right ear


Mode	Hopping channel numbers	Limit
GFSK	79	≥15
$\pi/4$ DQPSK	79	≥15
8DPSK	79	≥15

Test plot as follows:





5.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer</p> <p style="text-align: center;">E.U.T</p> <p style="text-align: center;">Non-Conducted Table</p> <p style="text-align: center;">Ground Reference Plane</p> <p><i>Remark: Offset=Cable loss+ attenuation factor.</i></p>
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Limit:	0.4 Second
Test Results:	Pass

Measurement Data: Left ear

Mode	Packet	Channel	Burst Width [ms/hop/ch]	Dwell Time[s]	Limit (second)
GFSK	DH1	LCH	0.39	0.125	≤0.4
GFSK	DH1	MCH	0.4	0.128	≤0.4
GFSK	DH1	HCH	0.4	0.128	≤0.4
π/4DQPSK	2DH1	LCH	0.41	0.131	≤0.4
π/4DQPSK	2DH1	MCH	0.42	0.134	≤0.4
π/4DQPSK	2DH1	HCH	0.42	0.134	≤0.4
8DPSK	3DH1	LCH	0.41	0.131	≤0.4
8DPSK	3DH1	MCH	0.42	0.134	≤0.4
8DPSK	3DH1	HCH	0.42	0.134	≤0.4
GFSK	DH3	LCH	1.67	0.267	≤0.4
GFSK	DH3	MCH	1.67	0.267	≤0.4
GFSK	DH3	HCH	1.67	0.267	≤0.4
π/4DQPSK	2DH3	LCH	1.69	0.27	≤0.4
π/4DQPSK	2DH3	MCH	1.69	0.27	≤0.4
π/4DQPSK	2DH3	HCH	1.69	0.27	≤0.4
8DPSK	3DH3	LCH	1.69	0.27	≤0.4
8DPSK	3DH3	MCH	1.69	0.27	≤0.4
8DPSK	3DH3	HCH	1.69	0.27	≤0.4
GFSK	DH5	LCH	2.89	0.308	≤0.4
GFSK	DH5	MCH	2.89	0.308	≤0.4
GFSK	DH5	HCH	2.89	0.308	≤0.4
π/4DQPSK	2DH5	LCH	2.91	0.31	≤0.4
π/4DQPSK	2DH5	MCH	2.91	0.31	≤0.4
π/4DQPSK	2DH5	HCH	2.91	0.31	≤0.4
8DPSK	3DH5	LCH	2.91	0.31	≤0.4
8DPSK	3DH5	MCH	2.91	0.31	≤0.4
8DPSK	3DH5	HCH	2.91	0.31	≤0.4

Remark:


The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

DH1/2DH1/3DH1 Dwell time = Burst Width(ms)*(1600/(2*79))*31.6


DH3/2DH3/3DH3 Dwell time = Burst Width (ms)*(1600/(4*79))*31.6

DH5/2DH5/3DH5 Dwell time = Burst Width (ms)*(1600/(6*79))*31.6

Test plot as follows:




GFSK_DH1/HCH







Date: 6.APR.2021 14:45:30



π /4DQPSK
 _2DH1/LCH




Date: 6.APR.2021 14:49:49








GFSK_DH3/MCH




Date: 6.APR.2021 14:46:38

GFSK_DH3/HCH




Date: 6.APR.2021 14:47:19

$\pi/4$ DQPSK
 _2DH3/LCH







Date: 6.APR.2021 14:51:43

$\pi/4$ DQPSK
 _2DH3/MCH




Date: 6.APR.2021 14:52:27






GFSK_DH5/LCH




Date: 6.APR.2021 14:47:57

GFSK_DH5/MCH




Date: 6.APR.2021 14:48:33

GFSK_DH5/HCH







Date: 6.APR.2021 14:49:04

$\pi/4$ DQPSK
_2DH5/LCH




Date: 6.APR.2021 14:53:50





8DPSK_3DH5/HCH



Date: 6.APR.2021 15:03:23

Measurement Data: Right ear

Mode	Packet	Channel	Burst Width [ms/hop/ch]	Dwell Time[s]	Limit (second)
GFSK	DH1	LCH	0.01	0.003	≤0.4
GFSK	DH1	MCH	0.4	0.128	≤0.4
GFSK	DH1	HCH	0.4	0.128	≤0.4
π/4DQPSK	2DH1	LCH	0.41	0.131	≤0.4
π/4DQPSK	2DH1	MCH	0.41	0.131	≤0.4
π/4DQPSK	2DH1	HCH	0.41	0.131	≤0.4
8DPSK	3DH1	LCH	0.41	0.131	≤0.4
8DPSK	3DH1	MCH	0.41	0.131	≤0.4
8DPSK	3DH1	HCH	0.42	0.134	≤0.4
GFSK	DH3	LCH	1.67	0.267	≤0.4
GFSK	DH3	MCH	1.67	0.267	≤0.4
GFSK	DH3	HCH	1.67	0.267	≤0.4
π/4DQPSK	2DH3	LCH	1.69	0.27	≤0.4
π/4DQPSK	2DH3	MCH	1.69	0.27	≤0.4
π/4DQPSK	2DH3	HCH	1.69	0.27	≤0.4
8DPSK	3DH3	LCH	1.69	0.27	≤0.4
8DPSK	3DH3	MCH	1.69	0.27	≤0.4
8DPSK	3DH3	HCH	1.69	0.27	≤0.4
GFSK	DH5	LCH	2.89	0.308	≤0.4
GFSK	DH5	MCH	2.89	0.308	≤0.4
GFSK	DH5	HCH	2.89	0.308	≤0.4
π/4DQPSK	2DH5	LCH	2.91	0.31	≤0.4
π/4DQPSK	2DH5	MCH	2.91	0.31	≤0.4
π/4DQPSK	2DH5	HCH	2.91	0.31	≤0.4
8DPSK	3DH5	LCH	2.91	0.31	≤0.4
8DPSK	3DH5	MCH	2.91	0.31	≤0.4
8DPSK	3DH5	HCH	2.91	0.31	≤0.4

Remark:


The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

DH1/2DH1/3DH1 Dwell time = Burst Width(ms)*(1600/(2*79))*31.6


DH3/2DH3/3DH3 Dwell time = Burst Width (ms)*(1600/(4*79))*31.6

DH5/2DH5/3DH5 Dwell time = Burst Width (ms)*(1600/(6*79))*31.6

Test plot as follows:




GFSK_DH1/HCH





Date: 7.APR.2021 08:17:07


π /4DQPSK
 _2DH1/LCH



Date: 7.APR.2021 08:25:43




8DPSK_3DH1/LCH





Date: 7.APR.2021 08:33:17


8DPSK_3DH1/MCH



Date: 7.APR.2021 08:33:58




GFSK_DH3/MCH




Date: 7.APR.2021 08:19:28

GFSK_DH3/HCH




Date: 7.APR.2021 08:21:13

$\pi/4$ DQPSK
 _2DH3/LCH




Date: 7.APR.2021 08:27:56

$\pi/4$ DQPSK
 _2DH3/MCH




Date: 7.APR.2021 08:28:37

$\pi/4$ DQPSK
 _2DH3/HCH





Date: 7.APR.2021 08:29:50


8DPSK _3DH3/LCH



Date: 7.APR.2021 08:35:29




GFSK_DH5/LCH




Date: 7.APR.2021 08:22:08

GFSK_DH5/MCH




Date: 7.APR.2021 08:23:14

GFSK_DH5/HCH





Date: 7.APR.2021 08:23:56


$\pi/4$ DQPSK
_2DH5/LCH



Date: 7.APR.2021 08:30:34




8DPSK_3DH5/LCH




Date: 7.APR.2021 08:37:41

8DPSK_3DH5/MCH




Date: 7.APR.2021 08:39:08

8DPSK_3DH5/HCH



Date: 7.APR.2021 08:39:39


5.8 Band-edge for RF Conducted Emissions



Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p style="text-align: center;"><i>Remark: Offset=cable loss+ attenuation factor.</i></p>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass



Left ear:



Mode	Test Channel	Frequency [MHz]	Frequency Hopping	Emission Level [dBm]	Limit [dBm]	Result
GFSK	LCH	2400	Off	-48.460	-16.33	PASS
			On	-45.690	-14.79	PASS
GFSK	HCH	2483.5	Off	-48.740	-15.71	PASS
			On	-46.510	-15.46	PASS
$\pi/4$ DQPSK	LCH	2400	Off	-36.260	-19.25	PASS
			On	-46.300	-17.86	PASS
$\pi/4$ DQPSK	HCH	2483.5	Off	-49.310	-18.49	PASS
			On	-46.390	-18.45	PASS
8DPSK	LCH	2400	Off	-46.710	-19.49	PASS
			On	-43.490	-17.74	PASS
8DPSK	HCH	2483.5	Off	-48.220	-19.3	PASS
			On	-45.890	-18.31	PASS



Test plot as follows:



















Right ear:


Mode	Test Channel	Frequency [MHz]	Frequency Hopping	Emission Level [dBm]	Limit [dBm]	Result
GFSK	LCH	2400	Off	-49.450	-17.12	PASS
			On	-46.160	-15.69	PASS
GFSK	HCH	2483.5	Off	-49.390	-16.07	PASS
			On	-44.910	-15.93	PASS
$\pi/4$ DQPSK	LCH	2400	Off	-37.120	-20.07	PASS
			On	-47.080	-18.48	PASS
$\pi/4$ DQPSK	HCH	2483.5	Off	-47.730	-19.36	PASS
			On	-45.710	-19.19	PASS
8DPSK	LCH	2400	Off	-47.630	-19.86	PASS
			On	-45.810	-18.59	PASS
8DPSK	HCH	2483.5	Off	-47.610	-19.9	PASS
			On	-45.810	-19.24	PASS



Test plot as follows:


















5.9 Spurious RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 <p style="text-align: center;"><i>Remark: Offset=cable loss+ attenuation factor.</i></p>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Test Results:	Pass

Left ear:






Date: 6.APR.2021 09:40:39



Date: 6.APR.2021 09:40:52


GFSK_MCH_Graphs

Pref




Date: 6.APR.2021 09:43:35


Puw



Date: 6.APR.2021 09:43:48




Date: 6.APR.2021 09:43:59



Date: 6.APR.2021 09:44:12


GFSK_HCH_Graphs

Pref




Date: 6.APR.2021 09:47:04


Puw



Date: 6.APR.2021 09:47:17






Date: 6.APR.2021 09:47:27




Date: 6.APR.2021 09:47:40

$\pi/4$ DQPSK LCH_Graphs






Date: 6.APR.2021 09:51:08



Date: 6.APR.2021 09:51:20


$\pi/4$ DQPSK_MCH_Graphs

Pref




Date: 6.APR.2021 09:53:52


Puw



Date: 6.APR.2021 09:54:05




Date: 6.APR.2021 09:54:16



Date: 6.APR.2021 09:54:28


$\pi/4$ DQPSK_HCH_Graphs

Pref




Date: 6.APR.2021 09:57:12


Puw



Date: 6.APR.2021 09:57:25




Date: 6.APR.2021 09:57:36



Date: 6.APR.2021 09:57:49


8DPSK_LCH_Graphs

Pref




Date: 6.APR.2021 10:02:00


Puw



Date: 6.APR.2021 10:02:13




Date: 6.APR.2021 10:02:24



Date: 6.APR.2021 10:02:37


8DPSK_MCH_Graphs

Pref




Date: 6.APR.2021 10:04:59


Puw



Date: 6.APR.2021 10:05:12




Date: 6.APR.2021 10:05:22



Date: 6.APR.2021 10:05:35


8DPSK_HCH_Graphs

Pref




Date: 6.APR.2021 13:28:09


Puw



Date: 6.APR.2021 13:28:22





Date: 6.APR.2021 13:28:33




Date: 6.APR.2021 13:28:45

Right ear:





Date: 6.APR.2021 15:12:07




Date: 6.APR.2021 15:12:19

#imgtxdh51chnnpuw4

#imgtxdh51chnnpuw5


GFSK_MCH_Graphs

Pref




Date: 6.APR.2021 15:14:44


Puw



Date: 6.APR.2021 15:14:57




Date: 6.APR.2021 15:15:08




Date: 6.APR.2021 15:15:20


#imgtxdh51mchnnpuw4

#imgtxdh51mchnnpuw5





Date: 6.APR.2021 15:18:33




Date: 6.APR.2021 15:18:46

#imgtxdh51hchnpuw4

#imgtxdh51hchnpuw5


$\pi/4$ DQPSK LCH_Graphs

Pref




Date: 6.APR.2021 15:21:44


Puw



Date: 6.APR.2021 15:21:57



Date: 6.APR.2021 15:22:07




Date: 6.APR.2021 15:22:20

#imgtx2dh51lchnpuw4

#imgtx2dh51lchnpuw5


$\pi/4$ DQPSK_MCH_Graphs

Pref




Date: 6.APR.2021 15:24:45


Puw



Date: 6.APR.2021 15:24:58



Date: 6.APR.2021 15:25:09




Date: 6.APR.2021 15:25:22

#imgtx2dh51mchnnpuw4

#imgtx2dh51mchnnpuw5


$\pi/4$ DQPSK_HCH_Graphs

Pref




Date: 6.APR.2021 15:35:54


Puw



Date: 6.APR.2021 15:36:07



Date: 6.APR.2021 15:36:17






Date: 6.APR.2021 15:36:30

#imgtx2dh51hchnnpw4


#imgtx2dh51hchnnpw5

8DPSK_LCH_Graphs





Date: 6.APR.2021 15:39:49




Date: 6.APR.2021 15:40:02

#imgtx3dh51lchnpuw4

#imgtx3dh51lchnpuw5


8DPSK_MCH_Graphs

Pref




Date: 6.APR.2021 15:42:27


Puw



Date: 6.APR.2021 15:42:40



Date: 6.APR.2021 15:42:51




Date: 6.APR.2021 15:43:03

#imgtx3dh51mchnnpuw4

#imgtx3dh51mchnnpuw5


8DPSK_HCH_Graphs

Pref




Date: 6.APR.2021 15:46:00


Puw



Date: 6.APR.2021 15:46:13



Date: 6.APR.2021 15:46:24



Date: 6.APR.2021 15:46:36



#imgtx3dh51hchnnpw4

#imgtx3dh51hchnnpw5

Remark:

Pre test 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.10 Other requirements Frequency Hopping Spread Spectrum System

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:
<p>The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.</p> <p>Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.</p> <p>The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.</p>	
Compliance for section 15.247(a)(1)	
<p>According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.</p> <ul style="list-style-type: none"> • Number of shift register stages: 9 • Length of pseudo-random sequence: $2^9 - 1 = 511$ bits • Longest sequence of zeros: 8 (non-inverted signal) <div style="text-align: center;">  <p><i>Linear Feedback Shift Register for Generation of the PRBS sequence</i></p> </div> <p>An example of Pseudorandom Frequency Hopping Sequence as follow:</p> <div style="text-align: center;">  </div> <p>Each frequency used equally on the average by each transmitter.</p> <p>According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.</p>	
Compliance for section 15.247(g)	
<p>According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.</p>	

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

5.11 Radiated Spurious Emission & Restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Peak	100 kHz	300kHz	Peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
<p>Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.</p>					

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz


Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:
 Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

	<p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz)</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p>
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case.
Test Results:	Pass

5.11.1 Radiated Emission below 1GHz

30MHz~1GHz		
Test mode:	Transmitting	Vertical
Left ear:		



	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	44.28	10.38	10.79	21.17	40.00	-18.83	Peak	VERTICAL
2	112.52	9.43	10.31	19.74	43.50	-23.76	Peak	VERTICAL
3	278.07	8.78	13.01	21.79	46.00	-24.21	Peak	VERTICAL
4	501.18	12.53	18.29	30.82	46.00	-15.18	Peak	VERTICAL
5	694.42	9.89	20.99	30.88	46.00	-15.12	Peak	VERTICAL
6 pp	869.13	9.05	23.97	33.02	46.00	-12.98	Peak	VERTICAL

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Test mode:	Transmitting	Horizontal
------------	--------------	------------



	Read Freq	Read Level	Factor	Limit Level	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	39.85	9.05	12.85	21.90	40.00	-18.10	Peak HORIZONTAL
2	71.83	8.72	8.45	17.17	40.00	-22.83	Peak HORIZONTAL
3	117.36	7.88	10.56	18.44	43.50	-25.06	Peak HORIZONTAL
4	244.23	8.53	11.87	20.40	46.00	-25.60	Peak HORIZONTAL
5	370.70	9.41	15.31	24.72	46.00	-21.28	Peak HORIZONTAL
6 pp	570.61	9.31	19.01	28.32	46.00	-17.68	Peak HORIZONTAL

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

30MHz~1GHz		
Test mode:	Transmitting	Vertical
Right ear:		



	Read Freq	Read Level	Factor	Limit Level	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	31.95	7.92	15.41	23.33	40.00	-16.67	Peak VERTICAL
2	54.07	9.79	7.24	17.03	40.00	-22.97	Peak VERTICAL
3	112.52	9.43	10.31	19.74	43.50	-23.76	Peak VERTICAL
4	255.62	8.72	12.26	20.98	46.00	-25.02	Peak VERTICAL
5	425.03	8.60	15.95	24.55	46.00	-21.45	Peak VERTICAL
6 pp	501.18	12.53	18.29	30.82	46.00	-15.18	Peak VERTICAL

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Test mode:	Transmitting	Horizontal
------------	--------------	------------



	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	40.56	8.32	12.54	20.86	40.00	-19.14	Peak	HORIZONTAL
2	119.02	7.57	10.65	18.22	43.50	-25.28	Peak	HORIZONTAL
3	260.14	9.12	12.41	21.53	46.00	-24.47	Peak	HORIZONTAL
4	472.18	8.88	17.41	26.29	46.00	-19.71	Peak	HORIZONTAL
5	714.17	10.63	21.19	31.82	46.00	-14.18	Peak	HORIZONTAL
6 pp	851.04	9.58	24.04	33.62	46.00	-12.38	Peak	HORIZONTAL

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

5.11.2 Transmitter Emission above 1GHz

Left ear:

Worse case mode:		GFSK(DH5)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2390	55.53	-9.2	46.33	74	-27.67	Peak	H
2400	56.88	-9.39	47.49	74	-26.51	Peak	H
4804	52.51	-4.33	48.18	74	-25.82	Peak	H
7206	49.57	1.01	50.58	74	-23.42	Peak	H
2390	54.40	-9.2	45.20	74	-28.80	Peak	V
2400	56.40	-9.39	47.01	74	-26.99	Peak	V
4804	53.23	-4.33	48.90	74	-25.10	Peak	V
7206	49.36	1.01	50.37	74	-23.63	Peak	V

Worse case mode:		GFSK(DH5)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
4882	50.86	-4.11	46.75	74	-27.25	peak	H
7323	48.35	1.51	49.86	74	-24.14	peak	H
4882	51.48	-4.11	47.37	74	-26.63	peak	V
7323	51.02	1.51	52.53	74	-21.47	peak	V

Worse case mode:		GFSK(DH5)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2483.5	54.70	-9.29	45.41	74	-28.59	Peak	H
4960	50.60	-4.04	46.56	74	-27.44	Peak	H
7440	48.64	1.57	50.21	74	-23.79	Peak	H
2483.5	55.71	-9.29	46.42	74	-27.58	Peak	V
4960	50.68	-4.04	46.64	74	-27.36	Peak	V
7440	48.84	1.57	50.41	74	-23.59	Peak	V

Worse case mode:		4DQPSK(2DH5)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2390	54.77	-9.2	45.57	74	-28.43	Peak	H
2400	54.70	-9.39	45.31	74	-28.69	Peak	H
4804	54.08	-4.33	49.75	74	-24.25	Peak	H
7206	49.80	1.01	50.81	74	-23.19	Peak	H
2390	54.14	-9.2	44.94	74	-29.06	Peak	V
2400	55.25	-9.39	45.86	74	-28.14	Peak	V
4804	54.10	-4.33	49.77	74	-24.23	Peak	V
7206	48.33	1.01	49.34	74	-24.66	Peak	V

Worse case mode:		4DQPSK(2DH5)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
4882	52.60	-4.11	48.49	74	-25.51	peak	H
7323	49.17	1.51	50.68	74	-23.32	peak	H
4882	52.53	-4.11	48.42	74	-25.58	peak	V
7323	49.34	1.51	50.85	74	-23.15	peak	V

Worse case mode:		4DQPSK(2DH5)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2483.5	54.36	-9.29	45.07	74	-28.93	Peak	H
4960	50.79	-4.04	46.75	74	-27.25	Peak	H
7440	50.42	1.57	51.99	74	-22.01	Peak	H
2483.5	53.67	-9.29	44.38	74	-29.62	Peak	V
4960	49.66	-4.04	45.62	74	-28.38	Peak	V
7440	50.24	1.57	51.81	74	-22.19	Peak	V

Worse case mode:		8DPSK(3DH5)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2390	55.30	-9.2	46.10	74	-27.90	Peak	H
2400	55.12	-9.39	45.73	74	-28.27	Peak	H
4804	51.24	-4.33	46.91	74	-27.09	Peak	H
7206	49.69	1.01	50.70	74	-23.30	Peak	H
2390	55.29	-9.2	46.09	74	-27.91	Peak	V
2400	54.30	-9.39	44.91	74	-29.09	Peak	V
4804	53.98	-4.33	49.65	74	-24.35	Peak	V
7206	50.00	1.01	51.01	74	-22.99	Peak	V

Worse case mode:		8DPSK(3DH5)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
4882	53.01	-4.11	48.90	74	-25.10	peak	H
7323	49.00	1.51	50.51	74	-23.49	peak	H
4882	53.62	-4.11	49.51	74	-24.49	peak	V
7323	49.36	1.51	50.87	74	-23.13	peak	V

Worse case mode:		8DPSK(3DH5)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2483.5	56.99	-9.29	47.70	74	-26.30	Peak	H
4960	50.38	-4.04	46.34	74	-27.66	Peak	H
7440	49.14	1.57	50.71	74	-23.29	Peak	H
2483.5	55.17	-9.29	45.88	74	-28.12	Peak	V
4960	49.52	-4.04	45.48	74	-28.52	Peak	V
7440	50.94	1.57	52.51	74	-21.49	Peak	V

Right ear:

Worse case mode:		GFSK(DH5)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2390	53.38	-9.2	44.18	74	-29.82	Peak	H
2400	55.42	-9.39	46.03	74	-27.97	Peak	H
4804	51.34	-4.33	47.01	74	-26.99	Peak	H
7206	48.46	1.01	49.47	74	-24.53	Peak	H
2390	53.88	-9.2	44.68	74	-29.32	Peak	V
2400	54.61	-9.39	45.22	74	-28.78	Peak	V
4804	53.41	-4.33	49.08	74	-24.92	Peak	V
7206	49.91	1.01	50.92	74	-23.08	Peak	V

Worse case mode:		GFSK(DH5)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
4882	52.08	-4.11	47.97	74	-26.03	peak	H
7323	48.81	1.51	50.32	74	-23.68	peak	H
4882	53.44	-4.11	49.33	74	-24.67	peak	V
7323	48.59	1.51	50.10	74	-23.90	peak	V

Worse case mode:		GFSK(DH5)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2483.5	56.80	-9.29	47.51	74	-26.49	Peak	H
4960	52.39	-4.04	48.35	74	-25.65	Peak	H
7440	48.29	1.57	49.86	74	-24.14	Peak	H
2483.5	53.95	-9.29	44.66	74	-29.34	Peak	V
4960	50.73	-4.04	46.69	74	-27.31	Peak	V
7440	48.58	1.57	50.15	74	-23.85	Peak	V

Worse case mode:		4DQPSK(2DH5)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2390	56.80	-9.29	47.51	74	-26.49	Peak	H
2400	52.39	-4.04	48.35	74	-25.65	Peak	H
4804	48.29	1.57	49.86	74	-24.14	Peak	H
7206	53.95	-9.29	44.66	74	-29.34	Peak	H
2390	50.73	-4.04	46.69	74	-27.31	Peak	V
2400	48.58	1.57	50.15	74	-23.85	Peak	V
4804	56.80	-9.29	47.51	74	-26.49	Peak	V
7206	52.39	-4.04	48.35	74	-25.65	Peak	V

Worse case mode:		4DQPSK(2DH5)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
4882	51.64	-4.11	47.53	74	-26.47	peak	H
7323	51.09	1.51	52.60	74	-21.40	peak	H
4882	51.93	-4.11	47.82	74	-26.18	peak	V
7323	50.26	1.51	51.77	74	-22.23	peak	V

Worse case mode:		4DQPSK(2DH5)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2483.5	55.60	-9.29	46.31	74	-27.69	Peak	H
4960	50.81	-4.04	46.77	74	-27.23	Peak	H
7440	48.45	1.57	50.02	74	-23.98	Peak	H
2483.5	54.67	-9.29	45.38	74	-28.62	Peak	V
4960	51.08	-4.04	47.04	74	-26.96	Peak	V
7440	49.27	1.57	50.84	74	-23.16	Peak	V

Worse case mode:		8DPSK(3DH5)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2390	53.68	-9.2	44.48	74	-29.52	Peak	H
2400	55.35	-9.39	45.96	74	-28.04	Peak	H
4804	53.83	-4.33	49.50	74	-24.50	Peak	H
7206	49.86	1.01	50.87	74	-23.13	Peak	H
2390	56.09	-9.2	46.89	74	-27.11	Peak	V
2400	56.87	-9.39	47.48	74	-26.52	Peak	V
4804	54.78	-4.33	50.45	74	-23.55	Peak	V
7206	49.94	1.01	50.95	74	-23.05	Peak	V

Worse case mode:		8DPSK(3DH5)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
4882	51.10	-4.11	46.99	74	-27.01	peak	H
7323	49.79	1.51	51.30	74	-22.70	peak	H
4882	52.46	-4.11	48.35	74	-25.65	peak	V
7323	49.26	1.51	50.77	74	-23.23	peak	V

Worse case mode:		8DPSK(3DH5)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2483.5	56.64	-9.29	47.35	74	-26.65	Peak	H
4960	51.02	-4.04	46.98	74	-27.02	Peak	H
7440	51.09	1.57	52.66	74	-21.34	Peak	H
2483.5	54.76	-9.29	45.47	74	-28.53	Peak	V
4960	50.31	-4.04	46.27	74	-27.73	Peak	V
7440	48.66	1.57	50.23	74	-23.77	Peak	V

Remark:

- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.