

# RF EXPOSURE REPORT

## FOR

<b>Applicant</b>	:	Edifier International Limited
<b>Address</b>	:	P.O. Box 6264 General Post Office Hong Kong
<b>Equipment under Test</b>	:	Active Speaker
<b>Model No.</b>	:	EDF100001
<b>Trade Mark</b>	:	EDIFIER
<b>FCC ID</b>	:	Z9G-EDF109
<b>Manufacturer</b>	:	Beijing Edifier Technology Co., Ltd.
<b>Address</b>	:	8th floor, ZuoAn Building, NO.68 BeiSiHuanXiLu, Haidian District, Beijing 100080, CHINA

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add.:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,  
Dongguan City, Guangdong Province, China, 523808

**Tel.:** +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

## Table of Contents

- Test report declares.....3
- 1. General Information..... 5
  - 1.1. Description of equipment..... 5
  - 1.2. Assess laboratory ..... 5
- 2. RF Exposure evaluation ..... 6
  - 2.1. Requirement..... 6
  - 2.2. Calculation Method..... 6
  - 2.3. Estimation Result..... 7

## Test Report Declare

<b>Applicant</b>	:	Edifier International Limited
<b>Address</b>	:	P.O. Box 6264 General Post Office Hong Kong
<b>Equipment under Test</b>	:	Active Speaker
<b>Model No.</b>	:	EDF100001
<b>Trade mark</b>	:	EDIFIER
<b>Manufacturer</b>	:	Beijing Edifier Technology Co., Ltd.
<b>Address</b>	:	8th floor, ZuoAn Building, NO.68 BeiSiHuanXiLu, Haidian District, Beijing 100080, CHINA
<b>Factory</b>	:	Dongguan Edifier Technology Co., Ltd.
<b>Address</b>	:	No.2 Gongyedong Road, Songshan Lake Sci&Tech Industry Park, Dongguan, Guangdong 523808, PR. China

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No:</b>	DDT-R20071308-1E3		
<b>Date of Receipt:</b>	Jul. 20, 2020	<b>Date of Test:</b>	Jul. 20, 2020 ~ Jul. 31, 2020

**Prepared By:**

*Talent Zhang*

**Talent Zhang/Engineer**

**Approved By:**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

### Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Jul. 31, 2020	

## 1. General Information

### 1.1. Description of equipment

Eut* Name	: Active Speaker
Model Number	: EDF100001
EUT Function Description	: Please reference user manual of this device
Power Supply	: AC 120V/ 60Hz, 125mA
Radio Specification	: Bluetooth V5.0
Operation Frequency	: 2402MHz-2480MHz
Modulation	: GFSK, $\pi/4$ -DQPSK
Data Rate	: 1 Mbps, 2 Mbps
Antenna Type	: PCB antenna, maximum PK gain: 2.59 dBi
Sample Type	: Series production

### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,  
Guangdong Province, China, 523808

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com)

CNAS Registration No. CNAS L6451; A2LA Certificate Number: 3870.01;

FCC Designation Number: CN1182; FCC Test Firm Registration Number: 540522

Industry Canada Site Registration Number: 10288A-1

## 2. RF Exposure evaluation

### 2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

#### Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2. Calculation Method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = Peak RF output power (mW)

**G** = EUT Antenna numeric gain (numeric)=

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

### 2.3. Estimation Result

#### Manufacturing Tolerance

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-2	-2	-2
Tolerance $\pm$ (dB)	1	1	1
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-2	-2	-2
Tolerance $\pm$ (dB)	1	1	1

#### Estimation Result

Mode	F (GHz)	Distance (mm)	RF output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm <sup>2</sup> )	MPE Test Exclusion Threshold (mW/cm <sup>2</sup> )	MPE Test Exclusion
			dBm	mW					
BDR	2.441	20	-2	0.63	2.59	1.82	0.0002	1	Yes
EDR	2.441	20	-2	0.63	2.59	1.82	0.0002	1	Yes

Note: The estimation distance is 20cm

Conclusion: The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

**END OF REPORT**