

Prüfbericht-Nr.: <i>Test report no.:</i>	60429320 001	Auftrags-Nr.: <i>Order no.:</i>	168284162	Seite 1 von 28 <i>Page 1 of 28</i>
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2020-09-27	
Auftraggeber: <i>Client:</i>	Edifier International Limited P.O. Box 6264 General Post Office Hong Kong			
Prüfgegenstand: <i>Test item:</i>	Stereo Bluetooth Speaker			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	EDF100002 (Trademark: EDIFIER)			
Auftrags-Inhalt: <i>Order content:</i>	FCC and IC approval			
Prüfgrundlage: <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.207 CFR47 FCC Part 15: Subpart C Section 15.209 CFR47 FCC Part 2.1091 RSS-247 Issue 2 February 2017 RSS-Gen Issue 5 March 2019 RSS-102 Issue 5 March 2015			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2020-09-27	Please refer to photo documents		
Prüfmuster-Nr.: <i>Test sample no.:</i>	A002919243-001, 002, 003			
Prüfzeitraum: <i>Testing period:</i>	2020-10-14 – 2020-11-03			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland (Shenzhen) Co., Ltd. Testing Center			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von: <i>tested by:</i>	<u>X Alex Lan</u> <small>Signed by: Alex Lan</small>	genehmigt von: <i>authorized by:</i>	<u>X Winnie Hou</u> <small>Signed by: Winnie Hou</small>	
Datum: <i>Date:</i>	2020-12-11	Ausstellungsdatum: <i>Issue date:</i>	2020-12-11	
Stellung / Position	Senior Project Engineer	Stellung / Position	Department Manager	
Sonstiges / Other: FCC ID: Z9G-EDF113 IC: 10004A-EDF113 HVIN: EDF100002				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged:</i>		
<p>* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet</p> <p>Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specifications(s) F(ail) = failed a.m. test specifications(s) N/A = not applicable N/T = not tested</p>				
<p>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</p> <p><i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i></p>				

V05

Test Summary

5.1.1 ANTENNA REQUIREMENT*RESULT: Pass***5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER***RESULT: Pass***5.1.3 99% BANDWIDTH***RESULT: Pass***5.1.4 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHZ BANDWIDTH***RESULT: Pass***5.1.5 RADIATED SPURIOUS EMISSION***RESULT: Pass***5.1.6 20dB BANDWIDTH***RESULT: Pass***5.1.7 CARRIER FREQUENCY SEPARATION***RESULT: Pass***5.1.8 NUMBER OF HOPPING FREQUENCY***RESULT: Pass***5.1.9 TIME OF OCCUPANCY***RESULT: Pass***5.1.10 CONDUCTED EMISSION ON AC MAINS***RESULT: Pass***6.1.1 ELECTROMAGNETIC FIELDS***RESULT: Pass*

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES	5
2.1	TEST FACILITIES	5
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	8
2.4	CALIBRATION	8
2.5	MEASUREMENT UNCERTAINTY.....	8
2.6	LOCATION OF ORIGINAL DATA.....	8
2.7	STATUS OF FACILITY USED FOR TESTING.....	8
3	GENERAL PRODUCT INFORMATION	9
3.1	PRODUCT FUNCTION AND INTENDED USE.....	9
3.2	RATINGS AND SYSTEM DETAILS	9
3.3	INDEPENDENT OPERATION MODES	12
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	12
3.5	SUBMITTED DOCUMENTS.....	12
4	TEST SET-UP AND OPERATION MODES	13
4.1	PRINCIPLE OF CONFIGURATION SELECTION	13
4.2	TEST OPERATION AND TEST SOFTWARE.....	13
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT.....	13
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	13
4.5	TEST SETUP DIAGRAM.....	14
5	TEST RESULTS	16
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	16
<i>5.1.1</i>	<i>Antenna Requirement</i>	<i>16</i>
<i>5.1.2</i>	<i>Maximum Peak Conducted Output Power.....</i>	<i>17</i>
<i>5.1.3</i>	<i>99% Bandwidth</i>	<i>18</i>
<i>5.1.4</i>	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth.....</i>	<i>19</i>
<i>5.1.5</i>	<i>Radiated Spurious Emission</i>	<i>20</i>
<i>5.1.6</i>	<i>20dB Bandwidth.....</i>	<i>21</i>
<i>5.1.7</i>	<i>Carrier Frequency Separation.....</i>	<i>22</i>
<i>5.1.8</i>	<i>Number of Hopping Frequency.....</i>	<i>23</i>
<i>5.1.9</i>	<i>Time of Occupancy</i>	<i>24</i>
<i>5.1.10</i>	<i>Conducted Emission on AC Mains</i>	<i>25</i>
6	SAFETY HUMAN EXPOSURE	26
6.1	RADIO FREQUENCY EXPOSURE COMPLIANCE	26
<i>6.1.1</i>	<i>Electromagnetic Fields.....</i>	<i>26</i>
7	PHOTOGRAPHS OF THE TEST SET-UP	28

8	LIST OF TABLES.....	28
----------	----------------------------	-----------

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

Appendix B: Test Results of Conducted Testing

Appendix C: Test Results of Radiated Testing & AC Mains Conducted Emission

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

No. 362 Huanguan Road Middle, Longhua District, Shenzhen 518110, People's Republic of China

FCC Registration No.: 694916

IC Registration No.: 25069

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

TÜV Rheinland (Shenzhen) Co., Ltd.

Radio Spectrum Testing				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
Wireless Connectivity Tester	Rohde & Schwarz	CMW270	101375	2021-08-30
Signal Analyzer	Rohde & Schwarz	FSV 40	101441	2021-08-30
Vector Signal Generator	Rohde & Schwarz	SMBV100A	263301	2021-08-30
Signal Generator	Rohde & Schwarz	SMB100A	115186	2021-08-30
OSP	Rohde & Schwarz	OSP 150	101017	2021-12-20
Control PC	DELL	OptiPlex 7050	FTJZ9P2	N/A
Test Software	Rohde & Schwarz	WMS32 (V10.40.10)	N/A	N/A
Power Meter	Rohde & Schwarz	NRP2	107105	2021-12-20
Wideband Power Sensor	Rohde & Schwarz	NRP-Z81	105350	2021-12-20
Unwanted Emission Testing				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
Signal Generator	Rohde & Schwarz	SMB100A	180840	2021-08-30
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	165339	2021-08-30
Signal Analyzer	Rohde & Schwarz	FSV 40	101440	2021-08-30
System Controller Interface	Rohde & Schwarz	SCI-100	S10010036	N/A
Filterbank	Rohde & Schwarz	CDMA	100751	2021-08-30
Filterbank	Rohde & Schwarz	GSM	100811	2021-08-30
OSP	Rohde & Schwarz	OSP 120	102041	N/A
OSP	Rohde & Schwarz	OSP 150	101385	N/A
Pre-amplifier	Rohde & Schwarz	SCU08F1	08320030	2021-08-30
Amplifier	Rohde & Schwarz	SCU-18F	180079	2021-08-30
Amplifier	Rohde & Schwarz	SCU40A	100450	2021-09-03
Trilog Broadband Antenna (30 MHz - 1 GHz)	Schwarzbeck	VULB9162	192	2021-09-02
Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218719	2021-09-02
Wideband Ridged Horn Antenna (12-18 GHz)	Steatite	QMS-00208	18312	2021-09-02
Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19066	2021-09-02
Biconical Broadband	Schwarzbeck	VUBA 9117	357	2021-09-02

Antenna (30 MHz - 1 GHz)				
Double Ridged Broadband Horn Antenna (1 – 18 GHz)	Schwarzbeck	BBHA 9120 D	01760	2021-09-02
Broadband Horn Antenna (15 – 40 GHz)	Schwarzbeck	BBHA 9170	00862	2021-09-02
Test software	Rohde & Schwarz	EMC32 (V10.40.00)	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NW9P2	N/A
Conducted Emissions				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
EMI Test Receiver	R&S	ESR3	102428	2021-08-19
Artificial Mains Network	R&S	ENV216	102333	2021-08-19

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table

Item		Extended Uncertainty
Conducted Emission		± 2.74 dB
Radiated Emission (30-1000MHz)	Field strength (dBµV/m)	4.27dB
Radiated Emission (above 1000MHz)	Field strength (dBµV/m)	4.46dB
Radio Spectrum		± 1.5 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B & C of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at No. 362 Huanguan Road Middle, Longhua District, Shenzhen 518110, People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a Stereo Bluetooth Speaker which supports Bluetooth 5.0 (BDR&EDR) technology.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment	Stereo Bluetooth Speaker
Type Designation	EDF100002
Trade Mark	EDIFIER
FCC ID	Z9G-EDF113
IC	10004A-EDF113
HVIN	EDF100002
Operating Voltage	AC 100-240V, 50/60Hz, 300mA
Testing Voltage	AC 120V, 60Hz
Technical Specification of Bluetooth	
Technical Specification	Value
Operating Frequency	2402 - 2480 MHz
Type of Modulation	GFSK, $\pi/4$ DQPSK, 8DPSK
Channel Number	BDR & EDR mode:79 channels
Channel Separation	BDR & EDR mode:1MHz
Wireless Technology	Bluetooth 5.0
Antenna Type	Integral Antenna
Max. Antenna Gain	2.59 dBi

Table 3: RF Channel and Frequency of Bluetooth

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
00	2402.00	20	2422.00	40	2442.00	60	2462.00
01	2403.00	21	2423.00	41	2443.00	61	2463.00
02	2404.00	22	2424.00	42	2444.00	62	2464.00
03	2405.00	23	2425.00	43	2445.00	63	2465.00
04	2406.00	24	2426.00	44	2446.00	64	2466.00
05	2407.00	25	2427.00	45	2447.00	65	2467.00
06	2408.00	26	2428.00	46	2448.00	66	2468.00
07	2409.00	27	2429.00	47	2449.00	67	2469.00
08	2410.00	28	2430.00	48	2450.00	68	2470.00
09	2411.00	29	2431.00	49	2451.00	69	2471.00
10	2412.00	30	2432.00	50	2452.00	70	2472.00
11	2413.00	31	2433.00	51	2453.00	71	2473.00
12	2414.00	32	2434.00	52	2454.00	72	2474.00
13	2415.00	33	2435.00	53	2455.00	73	2475.00
14	2416.00	34	2436.00	54	2456.00	74	2476.00
15	2417.00	35	2437.00	55	2457.00	75	2477.00
16	2418.00	36	2438.00	56	2458.00	76	2478.00
17	2419.00	37	2439.00	57	2459.00	77	2479.00
18	2420.00	38	2440.00	58	2460.00	78	2480.00
19	2421.00	39	2441.00	59	2461.00	--	--

Table 4: Frequency Hopping Information

Technical Specification	Description
Hopping Range	<p>Hereby we declare that the frequency range of this device is 2402-2480MHz. This is according the Bluetooth Core Specification V5.0 for devices which will be operated in the USA. This was checked during the Bluetooth Qualification tests.</p>
Hopping Sequence	<p>Example of a 79 hopping sequence in data mode:</p> <p>33,04,21,44,23,42,53,46,55,48,40,59,72,29,76,31,08,73,07,75,09,45,60,39,58,13,47,11,77,52,35,50,65,54,67,56,69,62,71,64, 7,25,27,66,57,70,74,61,78,63,10,41,05,43,15,44,64,68,02,70,06,01,51,03,55,05,03,66,53,49,36,47..</p>
Receiver input bandwidth	<p>The input bandwidth of the receiver is 1MHz. In every connection one Bluetooth device is the master and the other one is the slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master.</p> <p>Additionally the type of connection is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.</p> <p>Repeating of a packer has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case.</p> <p>That means a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.</p>

3.3 Independent Operation Modes

The basic operation modes are:

- A. On
 - 1. Bluetooth transmitting mode (BDR & EDR mode)
 - a) Low Channel
 - b) Middle Channel
 - c) High Channel
- B. On, Transmitting on Hopping channel
- C. On, Bluetooth connecting mode
- D. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- Application Form
- Block Diagram
- Schematics
- Technical Description
- FCC/IC Label and Location Info
- Photo Document
- User Manual

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10: 2013.

4.3 Special Accessories and Auxiliary Equipment

Table 5: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N
Notebook	Lenovo	ThinkPad 260	PC0GP71G
Mobile Phone	HTC	D626w	N/A

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Mains Conduction Measurement





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass**Test Specification**

Test standard : FCC Part 15.247(b)(4) and Part 15.203
RSS-Gen Clause 8.3

According to the manufacturer declared, the EUT has an integral antenna, the directional gain of antenna is 2.59 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

5.1.2 Maximum Peak Conducted Output Power

RESULT:
Pass
Test Specification

Test standard	: FCC Part 15.247(b)(1) RSS-247 Clause 5.4(b)
Basic standard	: ANSI C63.10: 2013 FHSS<0.125W(Maximum peak conducted output
Limits	: power) < 4 W (e.i.r.p.)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 14.11.2020
Input voltage	: AC 120V, 60Hz
Operation mode	: A.1
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

Table 6: Test Result of Maximum Peak Conducted Output Power

Test Mode	Channel Frequency (MHz)	Measured Peak Output Power		Limit (W)
		(dBm)	(W)	
BDR	2402	4.26	0.00267	< 0.125
	2441	4.13	0.00259	
	2480	4.13	0.00259	
EDR	2402	4.27	0.00267	< 0.125
	2441	4.08	0.00256	
	2480	4.34	0.00272	

Note: The cable loss is taken into account in results and the maximum e.i.r.p. is 6.93 dBm less than 4W(36dBm).

5.1.3 99% Bandwidth

RESULT:
Pass
Test Specification

Test standard : RSS-Gen Clause 6.7
 Basic standard : ANSI C63.10: 2013
 Kind of test site : Shielded Room

Test Setup

Date of testing : 14.10.2020
 Input voltage : AC 120V, 60Hz
 Operation mode : A.1
 Test channel : Low / Middle / High
 Ambient temperature : 25 °C
 Relative humidity : 56 %
 Atmospheric pressure : 101 kPa

Table 7: Test Result of 99% Bandwidth

Test Mode	Channel Frequency (MHz)	99% Bandwidth (kHz)	Limit (kHz)
BDR	2402	910	/
	2441	910	
	2480	895	
EDR	2402	1165	/
	2441	1165	
	2480	1165	

For the measurement records, refer to the appendix B

5.1.4 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT:**Pass****Test Specification**

Test standard	:	FCC Part 15.247(d) RSS-247 Clause 5.5
Basic standard	:	ANSI C63.10: 2013
Limits	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power);
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	14.10.2020
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A.1, B
Test channel	:	Low / Middle / High
Ambient temperature	:	25 °C
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to following test plot, and compliance is achieved as well.

For the measurement records, refer to the appendix B.

5.1.5 Radiated Spurious Emission

RESULT:**Pass****Test Specification**

Test standard	:	FCC Part 15.247(d) & FCC Part 15.205 RSS-247 Clause 3.3
Basic standard	:	ANSI C63.10: 2013
Limits	:	Refer to 15.209(a) of FCC part 15.247(d) RSS-Gen Table 6 & Table 7
Kind of test site	:	3m Semi-anechoic Chamber

Test Setup

Date of testing	:	23.10.2020 -
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A.1
Test channel	:	Low / Middle / High
Ambient temperature	:	23 °C
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

Remark:

During the pretest the EUT was rotated through three orthogonal axes to determine the attitude that maximizes the emissions. After that the EUT was manually handled to find the orientation that has the maximum emission, which is the orientation shown in the test set-up photos.

Testing was carried out within frequency range 9kHz to the tenth harmonics.

For the measurement records, refer to the appendix C.

5.1.6 20dB Bandwidth

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(a)(1)
 : RSS-247 Clause 5.1(a)
 Basic standard : ANSI C63.10: 2013
 Kind of test site : Shielded Room

Test Setup

Date of testing : 14.10.2020
 Input voltage : AC 120V, 60Hz
 Operation mode : A.1
 Test channel : Low / Middle / High
 Ambient temperature : 25 °C
 Relative humidity : 56 %
 Atmospheric pressure : 101 kPa

Table 8: Test Result of 20dB Bandwidth

Test Mode	Channel Frequency (MHz)	20dB Bandwidth (kHz)	2/3 of 20dB Bandwidth (kHz)	Limit (MHz)
BDR	2402	935	623.333	/
	2441	935	623.333	
	2480	935	623.333	
EDR	2402	1235	823.333	/
	2441	1235	823.333	
	2480	1235	823.333	

For the measurement records, refer to the appendix B.

5.1.7 Carrier Frequency Separation

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(a)(1)
 : RSS-247 Clause 5.1(b)
 Basic standard : ANSI C63.10: 2013
 Limits : $\geq 25\text{kHz}$ or 2/3 of 20dB bandwidth, whichever is greater
 Kind of test site : Shielded Room

Test Setup

Date of testing : 10.09.2020
 Input voltage : AC 120V, 60Hz
 Operation mode : B
 Test channel : Low / Middle / High
 Ambient temperature : 25 °C
 Relative humidity : 56 %
 Atmospheric pressure : 101 kPa

Table 9: Test Result of Carrier Frequency Separation

Test Mode	Channel	Channel Frequency (MHz)	Measured Channel Separation (MHz)	Limit (kHz)	Result
BDR	Low Channel	2401.995050	1.009900	$\geq 25\text{kHz}$ or 2/3 of 20dB bandwidth	Pass
	Adjacency Channel	2403.004950			
	Middle Channel	2440.995050	1.009900		Pass
	Adjacency Channel	2442.004950			
	High Channel	2478.995050	1.009900		Pass
	Adjacency Channel	2480.004950			
EDR	Low Channel	2401.995050	1.009900	$\geq 25\text{kHz}$ or 2/3 of 20dB bandwidth	Pass
	Adjacency Channel	2403.004950			
	Middle Channel	2440.995050	1.009900		Pass
	Adjacency Channel	2442.004950			
	High Channel	2478.995050	1.009900		Pass
	Adjacency Channel	2480.004950			

Note:

The limit is maximum 2/3 of the 20 dB bandwidth: 823.333 KHz.

For the measurement records, refer to the appendix B.

5.1.8 Number of Hopping Frequency

RESULT:**Pass****Test Specification**

Test standard	:	FCC part 15.247(a)(1)(iii) RSS-247 Clause 5.1(d)
Basic standard	:	ANSI C63.10: 2013
Limits	:	≥ 15 non-overlapping channels
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	14.10.2020
Input voltage	:	AC 120V, 60Hz
Operation mode	:	B
Ambient temperature	:	25 °C
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

Table 10: Test Result of Number of Hopping Frequency

Frequency Range	Measured Quantity of Hopping Channel	Limit	Result
2402 to 2480 MHz	79	≥15	Pass

For the measurement records, refer to the appendix B.

5.1.9 Time of Occupancy

RESULT:
Pass
Test Specification

Test standard : FCC part 15.247(a)(1)(iii)
 : RSS-247 Clause 5.1(d)
 Basic standard : ANSI C63.10: 2013
 Limits : < 0.4s
 Kind of test site : Shielded Room

Test Setup

Date of testing : 14.10.2020
 Input voltage : AC 120V, 60Hz
 Operation mode : B
 Test channel : Low / Middle / High
 Ambient temperature : 25 °C
 Relative humidity : 56 %
 Atmospheric pressure : 101 kPa

Table 11: Test Result of Time of Occupancy

Test Mode	Channel	Data Packet	Pulse width (ms)	Measured Dwell time(s)	Limit (s)
BDR	2441	DH1	0.384	0.123	< 0.4s
		DH3	1.632	0.261	
		DH5	2.879	0.307	
EDR	2441	2DH1	0.389	0.124	< 0.4s
		2DH3	1.622	0.260	
		2DH5	2.861	0.305	

Note:

$$\text{Dwell time} = \text{Pulse width} \times (\text{Hopping rate} / \text{Number of channels}) \times \text{Period}$$

$$\text{Period} = 0.4 \times 79 \text{ (channel)} = 31.6 \text{ seconds}$$

5.1.10 Conducted Emission on AC Mains**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.207(a) RSS-Gen Clause 8.8
Basic standard	:	ANSI C63.10: 2013
Frequency range	:	0.15 – 30MHz
Limits	:	FCC Part 15.207(a) RSS-Gen Table 4
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	03.11.2020
Input voltage	:	AC 120V/60Hz
Operation mode	:	C
Earthing	:	Not connected
Ambient temperature	:	22 °C
Relative humidity	:	55 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix C.

6 Safety Human Exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT:**Pass****Test Specification**

Test standard : CFR47 FCC Part 2.1091
RSS-102 Issue 5 March 2015
FCC KDB Publication 447498 v06

Limit : CFR47 FCC Part 1.1310

FCC requirement: Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20cm normally can be maintained between the user and the device.

MPE Calculation Method according to OET Bulletin 65

Power Density: $S_{(mW/cm^2)} = PG/4\pi R^2$ or $EIRP/4\pi R^2$

Where:

S = power density (mW/cm²)

P = power input to the antenna (mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm)

The nominal maximum conducted output power specified:

BLuetooth: 4.34 dBm

From the peak RF output power, the minimum mobile separation distance, d=20 cm, as well as the antenna gain (2.59 dBi), the RF power density can be calculated as below:

For BLuetooth: $S_{(mW/cm^2)} = PG/4\pi R^2 = 0.001$ mW/cm²

Limits for Maximum Permissible Exposure (MPE) according to FCC Part 1.1310: 1.0 mW/cm²

- **IC requirements:** The EUT shall comply with the requirement of RSS-102 section 2.5.2.

Exemption from Routine Evaluation Limits – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;

- RF exposure evaluation exempted power for 2.4G DTS: 2.676 W

The nominal maximum conducted output power specified:

BLuetooth: 4.34 dBm

Antenna Gain: 2.59 dBi

The Max. e.i.r.p. for BLuetooth: 6.93dBm = 0.005 W

The e.i.r.p. of BLuetooth is less than the RF exposure evaluation exempted power. So RF exposure evaluation is not required.

“RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”

7 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.

8 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Technical Specification of EUT	9
Table 3: RF Channel and Frequency of Bluetooth	10
Table 4: Frequency Hopping Information.....	11
Table 5: List of Accessories and Auxiliary Equipment.....	13
Table 6: Test Result of Maximum Peak Conducted Output Power.....	17
Table 7: Test Result of 99% Bandwidth	18
Table 8: Test Result of 20dB Bandwidth.....	21
Table 9: Test Result of Carrier Frequency Separation	22
Table 10: Test Result of Number of Hopping Frequency	23
Table 11: Test Result of Time of Occupancy	24

Appendix B

Test Results of Conducted Testing


APPENDIX B	1
APPENDIX B.1: TEST PLOTS OF 99% BANDWIDTH	2
<i>BDR Mode, DH1</i>	2
<i>EDR Mode, 3DH1</i>	3
APPENDIX B.2: TEST PLOTS OF 20dB BANDWIDTH	5
<i>BDR Mode, DH1</i>	5
<i>EDR Mode, 3DH1</i>	6
APPENDIX B.3: TEST PLOTS OF CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH	8
<i>BDR Mode, Low Channel</i>	8
<i>BDR Mode, Middle Channel</i>	9
<i>BDR Mode, High Channel</i>	10
<i>BDR, Hopping</i>	11
<i>EDR Mode, Low Channel</i>	12
<i>EDR Mode, Middle Channel</i>	13
<i>EDR Mode, High Channel</i>	14
<i>EDR, Hopping</i>	15
<i>BDR Mode, Band Edge, Low Channel</i>	16
<i>BDR Mode, Band Edge, High Channel</i>	16
<i>BDR Mode, Hopping Band Edge</i>	17
<i>EDR Mode, Band Edge, Low Channel</i>	18
<i>EDR Mode, Band Edge, High Channel</i>	18
<i>EDR Mode, Hopping Band Edge</i>	19
APPENDIX B.4: TEST PLOTS OF CARRIER FREQUENCY SEPARATION	20
<i>BDR, Low Channel</i>	20
<i>BDR, Middle Channel</i>	20
<i>BDR, High Channel</i>	21
<i>EDR, Low Channel</i>	21
<i>EDR, Middle Channel</i>	22
<i>EDR, High Channel</i>	22
APPENDIX B.5: TEST PLOTS OF NUMBER OF HOPPING FREQUENCY	23
<i>BDR, Hopping</i>	23
<i>EDR, Hopping</i>	23
APPENDIX B.6: TEST PLOTS OF TIME OF OCCUPANCY	24
<i>BDR Mode, DH1, Middle Channel</i>	24
<i>BDR Mode, DH3, Middle Channel</i>	24
<i>BDR Mode, DH5, Middle Channel</i>	25
<i>EDR Mode, 3DH1, Middle Channel</i>	25
<i>EDR Mode, 3DH3, Middle Channel</i>	26
<i>EDR Mode, 3DH5, Middle Channel</i>	26

Appendix B.1: Test Plots of 99% Bandwidth


BDR Mode, DH1

RBW=10KHz, VBW=30KHz


99 % Bandwidth



99 % Bandwidth




99 % Bandwidth




EDR Mode, 3DH1

RBW=30KHz VBW=100KHz


99 % Bandwidth



99 % Bandwidth



99 % Bandwidth




Appendix B.2: Test Plots of 20dB Bandwidth


BDR Mode, DH1

RBW=10KHz VBW=30KHz


20 dB Bandwidth



20 dB Bandwidth




20 dB Bandwidth




EDR Mode, 3DH1

RBW=30KHz VBW=100KHz


20 dB Bandwidth



20 dB Bandwidth





20 dB Bandwidth




Appendix B.3: Test Plots of Conducted Spurious Emissions Measured in 100 kHz Bandwidth


BDR Mode, Low Channel



BDR Mode, Middle Channel





Date: 14.OCT.2020 08:19:40





Date: 14.OCT.2020 08:28:45


BDR Mode, High Channel




BDR, Hopping



EDR Mode, Low Channel



Date: 14.OCT.2020 08:37:06




Date: 14.OCT.2020 08:41:17

EDR Mode, Middle Channel




Date: 14.OCT.2020 08:37:48




Date: 14.OCT.2020 08:42:55

EDR Mode, High Channel





Date: 14.OCT.2020 08:38:38




Date: 14.OCT.2020 08:44:11

EDR, Hopping




BDR Mode, Band Edge, Low Channel





Date: 14.OCT.2020 08:24:48

BDR Mode, Band Edge, High Channel




Date: 14.OCT.2020 08:23:35

BDR Mode, Hopping Band Edge




EDR Mode, Band Edge, Low Channel




Date: 14.OCT.2020 08:40:26

EDR Mode, Band Edge, High Channel




Date: 14.OCT.2020 08:39:27

EDR Mode, Hopping Band Edge



Date: 14.OCT.2020 08:33:50




Date: 14.OCT.2020 08:34:28

Appendix B.4: Test Plots of Carrier Frequency Separation

BDR, Low Channel

RBW=300KHz, VBW=300KHz


CFS



BDR, Middle Channel

RBW=300KHz, VBW=300KHz


CFS



BDR, High Channel

RBW=300KHz, VBW=300KHz


CFS



EDR, Low Channel


RBW=300KHz, VBW=300KHz

CFS




EDR, Middle Channel
RBW=300KHz, VBW=300KHz

CFS



EDR, High Channel
RBW=300KHz, VBW=300KHz

CFS




Appendix B.5: Test Plots of Number of Hopping Frequency

BDR, Hopping

RBW=200KHzM, VBW=200KHz


Sequence



EDR, Hopping

RBW=200KHzM, VBW=200KHz


Sequence



Appendix B.6: Test Plots of Time of Occupancy

BDR Mode, DH1, Middle Channel
RBW=500KHzM, VBW=1MHz


Time of Channel Occupancy



— Trace — Threshold

BDR Mode, DH3, Middle Channel
RBW=500KHzM, VBW=1MHz

Time of Channel Occupancy(2)




— Trace — Threshold

BDR Mode, DH5, Middle Channel

RBW=500KHzM, VBW=1MHz

Time of Channel Occupancy(3)




— Trace — Threshold

EDR Mode, 3DH1, Middle Channel

RBW=500KHzM, VBW=1MHz


Time of Channel Occupancy



— Trace — Threshold


EDR Mode, 3DH3, Middle Channel
RBW=500KHzM, VBW=1MHz

Time of Channel Occupancy(2)



EDR Mode, 3DH5, Middle Channel
RBW=500KHzM, VBW=1MHz

Time of Channel Occupancy(3)



Appendix C

Test Results of Radiated Emission & AC Mains Conducted Emission

APPENDIX C	1
APPENDIX C.1: TEST PLOTS OF RADIATED SPURIOUS EMISSION	2
<i>BDR mode, 30MHz - 1GHz</i>	2
<i>BDR mode, 1GHz - 6.2GHz</i>	6
<i>BDR mode, 6.2GHz - 18GHz</i>	12
<i>EDR mode, 1GHz - 6.2GHz</i>	18
<i>EDR mode, 6.2GHz - 18GHz</i>	24
APPENDIX C.2: TEST PLOTS OF BAND EDGE (RADIATED)	30
<i>BDR mode, Low Channel</i>	30
<i>BDR mode, High Channel</i>	32
<i>EDR mode, Low Channel</i>	34
<i>EDR mode, High Channel</i>	36
APPENDIX C.3: TEST PLOTS OF AC MAINS CONDUCTED EMISSION	38


Note: The radiated spurious emission were measured from 9KHz to 26.5GHz, the measurement results below 30MHz and above 18GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported.

Appendix C.1: Test Plots of Radiated Spurious Emission

BDR mode, 30MHz - 1GHz

EUT Information

EUT Name:	Stereo Bluetooth Speaker
Model:	EDF100002
Test Mode:	TX_DH5_Low channel
Test Voltage::	120V/60Hz
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
31.843000	35.29	---	40.00	4.71	100.0	V	164.0	-22.7
50.030500	22.91	---	40.00	17.09	100.0	V	328.0	-18.3
225.503500	19.14	---	46.00	26.86	100.0	V	184.0	-18.3
327.111000	21.85	---	46.00	24.15	100.0	V	0.0	-15.6

rodunkte
Products

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_DH5_Low channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
58.518000	18.88	---	40.00	21.12	100.0	H	354.0	-18.8
216.919000	30.28	---	46.00	15.72	100.0	H	328.0	-18.7

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_DH5_High channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
31.988500	35.79	---	40.00	4.21	100.0	V	243.0	-22.7
57.111500	28.32	---	40.00	11.68	100.0	V	140.0	-18.7
214.930500	19.60	---	43.50	23.90	100.0	V	263.0	-18.7
389.433500	18.01	---	46.00	27.99	100.0	V	149.0	-13.9

rodunkte
 Products

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_DH5_High channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
58.615000	22.23	---	40.00	17.77	100.0	H	345.0	-18.8
214.688000	28.97	---	43.50	14.53	100.0	H	312.0	-18.8

BDR mode, 1GHz - 6.2GHz

EUT Information

EUT Name:	Stereo Bluetooth Speaker
Model:	EDF100002
Test Mode:	TX_DH5_Low channel
Test Voltage::	120V/60Hz
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2338.112500	---	42.02	54.00	11.98	100.0	V	263.0	6.8
2342.362500	49.30	---	74.00	24.70	100.0	V	81.0	6.8
4802.500000	51.57	---	74.00	22.43	100.0	V	152.0	13.6
4804.000000	---	42.37	54.00	11.63	100.0	V	110.0	13.6

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_DH5_Low channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2337.262500	49.57	---	74.00	24.43	100.0	H	48.0	6.8
2338.112500	---	42.04	54.00	11.96	100.0	H	58.0	6.8
4804.000000	52.38	---	74.00	21.62	100.0	H	53.0	13.6
4804.000000	---	44.18	54.00	9.82	100.0	H	53.0	13.6

rodunkte
Products

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_DH5_Mid channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4880.500000	50.29	---	74.00	23.71	100.0	V	320.0	13.4
4882.000000	---	40.07	54.00	13.93	100.0	V	320.0	13.4

rodunkte
 Products

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_DH5_Mid channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4881.500000	---	41.62	54.00	12.38	100.0	H	327.0	13.4
4897.000000	51.59	---	74.00	22.41	100.0	H	348.0	13.3

EUT Information

EUT Name:	Stereo Bluetooth Speaker
Model:	EDF100002
Test Mode:	TX_DH5_High channel
Test Voltage::	120V/60Hz
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2415.887500	---	41.37	54.00	12.63	100.0	V	280.0	7.1
2437.562500	50.35	---	74.00	23.65	100.0	V	188.0	7.4
4960.000000	---	41.13	54.00	12.87	100.0	V	1.0	13.2
4962.500000	51.05	---	74.00	22.95	100.0	V	60.0	13.2

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_DH5_High channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2416.100000	---	41.26	54.00	12.74	100.0	H	61.0	7.1
2416.525000	49.41	---	74.00	24.59	100.0	H	61.0	7.2
4959.500000	51.04	---	74.00	22.96	100.0	H	235.0	13.2
4960.000000	---	41.37	54.00	12.63	100.0	H	50.0	13.2

BDR mode, 6.2GHz - 18GHz

EUT Information

EUT Name:	Stereo Bluetooth Speaker
Model:	EDF100002
Test Mode:	TX_DH5_Low channel
Test Voltage::	120V/60Hz
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9607.741667	44.43	---	74.00	29.57	100.0	V	112.0	10.4
9607.741667	---	36.52	54.00	17.48	100.0	V	112.0	10.4

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_DH5_Low channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9607.741667	44.87	---	74.00	29.13	100.0	H	46.0	10.4
9607.741667	---	39.55	54.00	14.45	100.0	H	46.0	10.4

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_DH5_Mid channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9763.600000	44.45	---	74.00	29.55	100.0	V	120.0	10.4
9764.091667	---	38.60	54.00	15.40	100.0	V	120.0	10.4
17699.100000	---	49.69	54.00	4.31	100.0	V	106.0	22.9

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_DH5_Mid channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9764.091667	44.96	---	74.00	29.04	100.0	H	51.0	10.4
9764.091667	---	40.91	54.00	13.09	100.0	H	51.0	10.4

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_DH5_High channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9919.950000	44.49	---	74.00	29.51	100.0	V	109.0	10.8
9919.950000	---	40.03	54.00	13.97	100.0	V	109.0	10.8

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_DH5_High channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9919.458333	46.55	---	74.00	27.45	100.0	H	78.0	10.8
9919.950000	---	42.76	54.00	11.24	100.0	H	93.0	10.8

EDR mode, 1GHz - 6.2GHz

EUT Information

EUT Name:	Stereo Bluetooth Speaker
Model:	EDF100002
Test Mode:	TX_3DH5_Low channel
Test Voltage::	120V/60Hz
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4801.500000	---	40.88	54.00	13.12	100.0	V	300.0	13.6
4807.000000	51.83	---	74.00	22.17	100.0	V	203.0	13.6

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_3DH5_Low channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4804.000000	---	40.96	54.00	13.04	100.0	H	50.0	13.6
4807.500000	52.35	---	74.00	21.65	100.0	H	15.0	13.6

EUT Information

EUT Name:	Stereo Bluetooth Speaker
Model:	EDF100002
Test Mode:	TX_3DH5_Mid channel
Test Voltage::	120V/60Hz
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4882.000000	50.07	---	74.00	23.93	100.0	V	319.0	13.4
4882.000000	---	39.83	54.00	14.17	100.0	V	319.0	13.4

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_3DH5_Mid channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4881.500000	---	41.50	54.00	12.50	100.0	H	48.0	13.4
4887.500000	51.07	---	74.00	22.93	100.0	H	161.0	13.3

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_3DH5_High channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4966.500000	---	40.22	54.00	13.78	100.0	V	241.0	13.2
4969.000000	52.96	---	74.00	21.04	100.0	V	228.0	13.2

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_3DH5_High channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4958.500000	51.95	---	74.00	22.05	100.0	H	270.0	13.2
4960.000000	---	39.98	54.00	14.02	100.0	H	276.0	13.2

EDR mode, 6.2GHz - 18GHz

EUT Information

EUT Name:	Stereo Bluetooth Speaker
Model:	EDF100002
Test Mode:	TX_3DH5_Low channel
Test Voltage::	120V/60Hz
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9608.233333	46.06	---	74.00	27.94	100.0	H	130.0	10.4
9608.233333	---	41.92	54.00	12.08	100.0	H	130.0	10.4

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_3DH5_Low channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9607.741667	42.96	---	74.00	31.04	100.0	V	100.0	10.4
9607.741667	---	35.80	54.00	18.20	100.0	V	100.0	10.4

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_3DH5_Mid channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9764.091667	45.15	---	74.00	28.85	100.0	V	106.0	10.4
9764.091667	---	39.74	54.00	14.26	100.0	V	106.0	10.4

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_3DH5_Mid channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9763.600000	45.06	---	74.00	28.94	100.0	H	56.0	10.4
9764.091667	---	40.77	54.00	13.23	100.0	H	56.0	10.4

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_3DH5_High channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9919.950000	45.07	---	74.00	28.93	100.0	V	98.0	10.8
9919.950000	---	41.44	54.00	12.56	100.0	V	98.0	10.8

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_3DH5_High channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9919.950000	47.02	---	74.00	26.98	100.0	H	106.0	10.8
9919.950000	---	43.93	54.00	10.07	100.0	H	106.0	10.8

Appendix C.2: Test Plots of Band Edge (Radiated)

BDR mode, Low Channel

EUT Information

EUT Name:	Stereo Bluetooth Speaker
Model:	EDF100002
Test Mode:	TX_DH5_Low channel
Test Voltage::	120V/60Hz
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2337.959688	---	43.64	54.00	10.36	100.0	V	274.0	6.8
2338.209063	50.72	---	74.00	23.28	100.0	V	262.0	6.8

EUT Information

EUT Name:	Stereo Bluetooth Speaker
Model:	EDF100002
Test Mode:	TX_DH5_Low channel
Test Voltage::	120V/60Hz
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2337.977500	---	42.82	54.00	11.18	100.0	H	55.0	6.8
2338.494063	50.49	---	74.00	23.51	100.0	H	55.0	6.8

BDR mode, High Channel

EUT Information

EUT Name:	Stereo Bluetooth Speaker
Model:	EDF100002
Test Mode:	TX_DH5_High channel
Test Voltage::	120V/60Hz
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2484.095375	49.89	---	74.00	24.11	100.0	V	294.0	7.4
2484.125625	---	40.03	54.00	13.97	100.0	V	203.0	7.4

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_DH5_High channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2484.936875	50.16	---	74.00	23.84	100.0	H	254.0	7.4
2485.321875	---	40.03	54.00	13.97	100.0	H	47.0	7.4

EDR mode, Low Channel

EUT Information

EUT Name:	Stereo Bluetooth Speaker
Model:	EDF100002
Test Mode:	TX_3DH5_Low channel
Test Voltage::	120V/60Hz
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2337.775625	---	41.84	54.00	12.16	100.0	V	281.0	6.8
2337.846875	49.73	---	74.00	24.27	100.0	V	270.0	6.8

EUT Information

EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_3DH5_Low channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2337.757813	---	42.01	54.00	11.99	100.0	H	34.0	6.8
2338.226875	49.05	---	74.00	24.95	100.0	H	46.0	6.8

EDR mode, High Channel

EUT Information

EUT Name:	Stereo Bluetooth Speaker
Model:	EDF100002
Test Mode:	TX_3DH5_High channel
Test Voltage::	120V/60Hz
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2485.716500	49.98	---	74.00	24.02	100.0	V	319.0	7.4
2487.388500	---	39.49	54.00	14.51	100.0	V	187.0	7.4

EUT Information


EUT Name: Stereo Bluetooth Speaker
 Model: EDF100002
 Test Mode: TX_3DH5_High channel
 Test Voltage:: 120V/60Hz
 Remark: Temp 23 Humi:56%
 Test Standard: FCC 15.247
 Tested By: Kei Zhang
 Reviewed By: Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2484.193000	50.76	---	74.00	23.24	100.0	H	295.0	7.4
2485.997000	---	39.54	54.00	14.46	100.0	H	34.0	7.4

Appendix C.3: Test Plots of AC Mains Conducted Emission



Final Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.154500	48.33	---	65.75	17.42	1000.	9.000	N	9.6
0.199500	41.65	---	63.63	21.98	1000.	9.000	L1	9.6
0.253500	40.30	---	61.64	21.34	1000.	9.000	N	9.6
0.384000	---	38.63	48.19	9.56	1000.	9.000	N	9.6
0.388500	34.09	---	58.10	24.01	1000.	9.000	L1	9.6
0.730500	---	24.02	46.00	21.98	1000.	9.000	L1	9.7
0.834000	---	30.40	46.00	15.60	1000.	9.000	L1	9.7
0.834000	35.89	---	56.00	20.11	1000.	9.000	N	9.7
1.482000	---	21.89	46.00	24.11	1000.	9.000	L1	9.7
2.580000	---	19.07	46.00	26.93	1000.	9.000	L1	9.8
24.643500	---	31.03	50.00	18.97	1000.	9.000	L1	10.4
24.778500	36.05	---	60.00	23.95	1000.	9.000	L1	10.4