



EDIFIER

Active Speaker System
S360DB Active Subwoofer

Status  
Pair



100-240V~
50/60Hz 400mA



The active satellite speaker has been paired with the subwoofer before leaving factory. The wireless connection is supposed to resume automatically when both active satellite speaker and subwoofer are powered on, and the red indicator will be constantly lit. If the wireless connection fails to resume, please follow the steps below to complete the pairing again.

1. Power on the subwoofer, the red indicator should blink in a breathing pattern, which means no active wireless connection.
2. Press and hold the Pair button on back panel of subwoofer for 2 seconds to put it into pairing mode. The red indicator will blink rapidly.
3. Press and hold the "Pair" button on back panel of active satellite speaker to put it into pairing mode.
4. Wait until the red indicator on subwoofer is lit constantly. Then the pairing is done and wireless connection is made.

FCC statement:
"This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation."
IC statement:
CAN ICES-003(B)/NMB-003(B).
FCC ID: Z9G-EDF172 IC: 10004A-EDF172 HVIN: EDF172

Model: EDF100043
Edifier International Limited
Address: P.O. Box 6264 General Post Office,
Hong Kong Made in China

丝印PAN 425C
底面喷黑色沙纹漆

物料名称	物料编码	版本
S360DB 21版低音箱后面板AP	MP-001-S0360D-07	V1.0

文件编号	EDF/JS-TSY-	版次 A0
文件名称	(音箱) S360DB 21版低音箱后面板AP	
绘制		东莞市漫步者 科技有限公司
审核		
批准		