


Site: NS-AC1	Test Date: 2024-04-11
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Horizontal
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by DH5 at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2369.470	56.785	26.066	-17.215	74.000	30.719	PK
2		2390.000	54.626	23.975	-19.374	74.000	30.651	PK
3		2401.817	91.715	61.062	N/A	N/A	30.653	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-11
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Horizontal
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by DH5 at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2376.785	43.518	12.763	-10.482	54.000	30.755	AV
2		2390.000	43.416	12.765	-10.584	54.000	30.651	AV
3		2402.008	91.384	60.730	N/A	N/A	30.654	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-11
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Vertical
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by DH5 at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2371.133	56.977	26.250	-17.023	74.000	30.728	PK
2		2390.000	53.940	23.289	-20.060	74.000	30.651	PK
3		2401.817	82.350	51.697	N/A	N/A	30.653	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-11
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Vertical
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by DH5 at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2372.748	43.456	12.721	-10.544	54.000	30.735	AV
2		2390.000	43.319	12.668	-10.681	54.000	30.651	AV
3		2402.008	81.601	50.947	N/A	N/A	30.654	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-09
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Horizontal
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by DH5 at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1		2480.134	87.742	57.166	N/A	N/A	30.575	PK
2		2483.500	57.295	26.715	-16.705	74.000	30.580	PK
3	*	2486.118	58.675	28.091	-15.325	74.000	30.584	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-09
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Horizontal
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by DH5 at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2480.002	87.433	56.858	N/A	N/A	30.575	AV
2		2483.500	45.140	14.560	-8.860	54.000	30.580	AV
3	*	2483.753	45.160	14.579	-8.840	54.000	30.581	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-09
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Vertical
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by DH5 at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2480.134	85.620	55.044	N/A	N/A	30.575	PK
2		2483.500	56.604	26.024	-17.396	74.000	30.580	PK
3	*	2484.831	58.442	27.860	-15.558	74.000	30.582	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-09
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Vertical
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by DH5 at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2480.002	85.240	54.665	N/A	N/A	30.575	AV
2		2483.500	45.102	14.522	-8.898	54.000	30.580	AV
3	*	2483.830	45.141	14.560	-8.859	54.000	30.581	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-11
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Horizontal
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 2DH5 at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2375.835	56.502	25.752	-17.498	74.000	30.751	PK
2		2390.000	55.677	25.026	-18.323	74.000	30.651	PK
3		2402.103	86.475	55.820	N/A	N/A	30.654	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-11
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Horizontal
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 2DH5 at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1	*	2362.677	43.468	12.782	-10.532	54.000	30.686	AV
2		2390.000	43.360	12.709	-10.640	54.000	30.651	AV
3		2402.008	82.980	52.326	N/A	N/A	30.654	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-11
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Vertical
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 2DH5 at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2340.685	56.878	26.059	-17.122	74.000	30.819	PK
2		2390.000	54.588	23.937	-19.412	74.000	30.651	PK
3		2402.150	83.985	53.330	N/A	N/A	30.655	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-11
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Vertical
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 2DH5 at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2375.978	43.457	12.706	-10.543	54.000	30.751	AV
2		2390.000	43.338	12.687	-10.662	54.000	30.651	AV
3		2402.008	80.405	49.751	N/A	N/A	30.654	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-09
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Horizontal
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 2DH5 at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2480.112	89.810	59.234	N/A	N/A	30.575	PK
2		2483.500	56.775	26.195	-17.225	74.000	30.580	PK
3	*	2484.204	58.699	28.118	-15.301	74.000	30.581	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-09
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Horizontal
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 2DH5 at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2479.958	86.603	56.028	N/A	N/A	30.575	AV
2		2483.500	45.171	14.591	-8.829	54.000	30.580	AV
3	*	2484.446	45.198	14.616	-8.802	54.000	30.581	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-09
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Vertical
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 2DH5 at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2479.892	87.557	56.982	N/A	N/A	30.575	PK
2		2483.500	56.646	26.066	-17.354	74.000	30.580	PK
3	*	2487.174	59.286	28.700	-14.714	74.000	30.585	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-09
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Vertical
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 2DH5 at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2480.013	84.279	53.704	N/A	N/A	30.575	AV
2		2483.500	45.156	14.576	-8.844	54.000	30.580	AV
3	*	2486.305	45.189	14.605	-8.811	54.000	30.584	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-11
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Horizontal
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 3DH5 at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2362.583	56.979	26.293	-17.021	74.000	30.686	PK
2		2390.000	54.741	24.090	-19.259	74.000	30.651	PK
3		2402.008	86.738	56.084	N/A	N/A	30.654	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-11
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Horizontal
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 3DH5 at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2362.535	43.540	12.855	-10.460	54.000	30.686	AV
2		2390.000	43.251	12.600	-10.749	54.000	30.651	AV
3		2402.008	83.216	52.562	N/A	N/A	30.654	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-11
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Vertical
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 3DH5 at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2348.190	57.876	27.106	-16.124	74.000	30.769	PK
2		2390.000	54.740	24.089	-19.260	74.000	30.651	PK
3		2402.008	84.005	53.351	N/A	N/A	30.654	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-11
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Vertical
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 3DH5 at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2344.532	43.458	12.659	-10.542	54.000	30.800	AV
2		2390.000	43.244	12.593	-10.756	54.000	30.651	AV
3		2402.008	80.273	49.619	N/A	N/A	30.654	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-09
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Horizontal
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 3DH5 at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2479.980	90.294	59.719	N/A	N/A	30.575	PK
2		2483.500	56.680	26.100	-17.320	74.000	30.580	PK
3	*	2485.238	58.406	27.823	-15.594	74.000	30.583	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-09
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Horizontal
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 3DH5 at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2480.013	86.677	56.102	N/A	N/A	30.575	AV
2		2483.500	45.335	14.755	-8.665	54.000	30.580	AV
3	*	2483.643	45.344	14.763	-8.656	54.000	30.581	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-09
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Vertical
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 3DH5 at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1		2479.980	87.899	57.324	N/A	N/A	30.575	PK
2		2483.500	57.258	26.678	-16.742	74.000	30.580	PK
3	*	2487.878	59.039	28.452	-14.961	74.000	30.587	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: NS-AC1	Test Date: 2024-04-09
Limit: FCC_2.4G_RE(3m)	Engineer: Ted Chen
Probe: NS-AC1_BBHA9120D_2111_1-18GHz	Polarity: Vertical
EUT: True Wireless Planar Magnetic Earbuds with Active Noise Cancellation - Right Earbud	Power: By Battery
Test Mode: Transmit by 3DH5 at 2480MHz	



No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2480.013	84.270	53.695	N/A	N/A	30.575	AV
2		2483.500	45.220	14.640	-8.780	54.000	30.580	AV
3	*	2483.764	45.228	14.647	-8.772	54.000	30.581	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Appendix B - Test Setup Photograph

Refer to "2401RSZ049-UT" file.

Appendix C - EUT Photograph

Refer to "2401RSZ049-UE" file.

————— The End —————