

IB-200-W0200T-00 说明书W200T/英法西德意葡日等26国语言/出口V1.0

页面数及装订方式:44面22页, 风琴折再从中间对折

成型尺寸:90x90mm

工艺:四色印刷

材质:80g书纸



封面

对折线

封底

EDIFIER
W200T
Model: EDF280A1
True Wireless Earbuds

Manual

For more information, please visit our website:
www.edifier.com

Scan and download EDIFIER Connex App

WHAT'S IN THE BOX

1. Earbuds x1

2. Charging case x1

3. User manual x1

4. USB-C charging cable x1

5. EDIFIER Connex App

POWER ON/OFF

Take out or place in both earbuds to power on/off.

2. More information, please visit our website:
www.edifier.com

FIRST PAIRING

1. Once powered on, the earbuds will auto-enter Bluetooth pairing mode.

2. Select "EDIFIER W200T" from your device list to connect.

PAIRING FOR NEW DEVICE

1. In ON state, press and hold the button on both earbuds for 3s.

2. Select "EDIFIER W200T" from your device list to connect.

Note: For subsequent use, the earbuds will automatically connect to the device used last time.

MULTIPOINT CONNECTION

1. Pair device A with the earbuds manually and keep the earbuds in the case;

2. Re-enter Bluetooth pairing mode and select "EDIFIER W200T" in device B settings to connect.

3. Select "EDIFIER W200T" again in device A settings to reconnect.

Note: For subsequent use, the earbuds will automatically reconnect to the two devices used last time.

RESET

1. Place the earbuds in the case and keep it open.

2. Press the button on the case 3 times, white LED blinks until the reset is complete, then the earbuds will auto-enter Bluetooth pairing mode.

CONTROLS

Note:
1. Default sound control: High noise cancellation / Ambient sound / Noise cancellation off.

2. Download EDIFIER Connex App for more customizable control settings.

CHARGING

Input: 5V~200mA(Earbuds) 5V~1A(Charging case)
Note: Make sure the USB port is completely dry before charging.

RESET

1. Place the earbuds in the case and keep it open.

2. Press the button on the case 3 times, white LED blinks until the reset is complete, then the earbuds will auto-enter Bluetooth pairing mode.

เครื่องโทรคมนาคมไทยยูนิคอดี มีจำกัด
มัลติมีเดียเทคโนโลยีซอสไทย จำกัด

บริษัทยูนิคอดี เทคโนโลยี จำกัด
มัลติมีเดียเทคโนโลยีซอสไทย จำกัด
พริตตี้เทคโนโลยีซอสไทย จำกัด
มัลติมีเดียเทคโนโลยีซอสไทย จำกัด
เทคโนโลยีซอสไทย จำกัด

2498

กานทอง, โทคมนาคม

Call Center : 090 100 1000

EDIFIER 200T

รุ่น	สี	น้ำหนัก	ความถี่	แบตเตอรี่	ระยะส่ง
EDIFIER 200T	ขาว	~10g	~20kHz	~15h	~10m
EDIFIER 200T	ดำ	~10g	~20kHz	~15h	~10m

Note: 1. "Transmission 10m" and "Transmission 15h" indicate that the percentage coverage of the received signal is approximately 100% and 15h respectively. 2. "Transmission 10m" and "Transmission 15h" indicate that the percentage coverage of the received signal is approximately 100% and 15h respectively.