

EDIFIER

Date: 2017-8-21


FCC ID: Z9G-EDF54

IC: 10004A-EDF54

| Type of Module: Limited Single Modular Transmitter | | | |
|--|---|--|--------------|
| No. | Requirements | Device Conditions | Comply (Y/N) |
| 1 | The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements. | The module does not have RF shielding. Refer to the external photos. | N |
| 2 | The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation. | The EUT has buffered modulation/data inputs. It's integrated on the chipset. | Y |
| 3 | The modular transmitter must have its own power supply regulation. | The chip is internally controlled | Y |
| 4 | The modular transmitter must comply with the antenna and transmission system requirements of § § 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler. | PCB Antenna | Y |
| 5 | The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing for compliance with part 15 requirements. | The modular transmitter was tested in stand-alone configuration via a laptop PC USB interface. | Y |
| 6 | The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number. | FCC ID is permanently on the PCB. Refer to the label location and label. | Y |
| 7 | The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. | User manual explains how to use OEM. | Y |
| 8 | The modular transmitter must comply with any applicable RF exposure requirements in its final configuration. | refer to the test report | Y |

If you have any questions regarding this, please don't hesitate to contact us.

Sincerely,



(DingkunShen /roject Manager)

Company Name: Edifier International Limited