

Report No.: HKEM190100003001 Page: 1 of 54 FCC ID: Z9O-92053067

TEST REPORT

Application No.:	HKEM1901000030AT
Applicant:	Ecolab, Inc
Address:	Ecolab, Inc 650 Ione Oak Drive Eagan, MN 55121
FCC ID:	Z9O-92053067
Product Description:	HHCM915 CompassNet Network Hub
Model No.:	92053067
Country of Origin:	China
Country of Destination:	United States of America
Standards:	47 CFR Part 15, Subpart C 15.247
Date of Receipt:	2019-02-14
Date of Test:	2019-03-06 to 2019-03-07
Date of Issue:	2019-03-07
Test Result:	Pass*

* In the configuration tested, the EUT detailed in this report complied with the standards specified above. Please refer to section 3 of this report for further detail.

Ivan Toa EMC Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx, Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents is unlawifu and offenders may be prosecuted to the fullest extent of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawifu and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



2 Test Summary

Test	Test Requirement	Test method	Result
Antenna Requirement	FCC PART 15 C section 15.247 (c) and Section 15.203	FCC PART 15 C section 15.247 (c) and Section 15.203	PASS
Occupied Bandwidth	FCC PART 15 C section 15.247 (a)(1)	ANSI C63.10: Clause 6.9.1	PASS
Carrier Frequencies Separated	FCC PART 15 C section 15.247(a)(1)	ANSI C63.10: Clause 7.8.2	PASS
Hopping Channel Number	FCC PART 15 C section 15.247(a)(1)(iii)	ANSI C63.10: Clause 7.8.3	PASS
Dwell Time	FCC PART 15 C section 15.247(a)(1)(iii)	ANSI C63.10: Clause 7.8.4	PASS
Pseudorandom Frequency Hopping Sequence	FCC PART 15 C section 15.247(a)(1)	ANSI C63.10: Clause 7.7.5	PASS
Maximum Peak Output Power	FCC PART 15 C section 15.247(b)(1)	ANSI C63.10: Clause 7.8.5	PASS
Conducted Spurious Emission	FCC PART 15 C section 15.247(d)	ANSI C63.10: Clause 7.8.8	PASS
Radiated Spurious Emission	FCC PART 15 C section 15.247(d)	ANSI C63.10: Clause 6.10.4	PASS
Band Edges Measurement	FCC PART 15 C section 15.247 (d) &15.205	ANSI C63.10: clause 7.8.6	PASS

SGS

3 Contents

1	COVE	R PAGE	1
2	TEST	SUMMARY	2
3	CONT	ENTS	3
4	GENE	RAL INFORMATION	4
	4.1	Client Information	4
	4.2	General Description of E.U.T.	4
	4.3	Details of E.U.T.	4
	4.4	Modulation configures	5
	4.5	Description of Support Units	5
	4.6	Deviation from Standards	5
	4.7	Abnormalities from Standard Conditions	5
	4.8	Other Information Requested by the Customer	5
	4.9	Test Location	5
	4.10	Test Facility	6
	4.11	Measurement Uncertainty (95% confidence levels, k=2)	6
5	EQUIF	PMENT USED DURING TEST	7
6	TEST	RESULTS	9
	6.1	E.U.T. test conditions	9
	6.2	Antenna Requirement	
	6.3	Conducted Disturbance at AC Power Line(150kHz-30MHz)	13
	6.4	Occupied Bandwidth	
	6.5	Carrier Frequencies Separated	
	6.6	Hopping Channel Number	
	6.7	Dwell Time	
	6.8	Pseudorandom Frequency Hopping Sequence	
	6.9	Maximum Peak Output Power	
	6.10	Conducted Spurious Emissions	
	6.11	Radiated Spurious Emissions	
	6.12	Band Edges Requirement	
7	РНОТ	OGRAPHS	
	71	Radiated Spurious Emission Test Setup	
	/.1	Radiated Spurious Emission rest Setup	



4 General Information

4.1 Client Information

Applicant:	Ecolab, Inc
Address of Applicant:	Ecolab, Inc 650 Ione Oak Drive Eagan, MN 55121

4.2 General Description of E.U.T.

Product Name:	HHCM915 CompassNet Network Hub
Model No.:	92053067

4.3 Details of E.U.T.

Operating Frequency	913.75 MHz to 916.30 MHz
Type of Modulation:	FHSS
Number of Channels	50 Channels
Channel Separation:	50 kHz
Dwell time	Per channel is less than 0.4s.
Antenna Type	Integral
Antenna gain:	2.15dBi
Specialty:	
Function:	Network Hub
Power Supply:	AC100-240V ~ 50-60Hz to DC 24V
Adapter no.:	ATS024T-W240U
Power cord:	DC cable: 150cm unshielded cable with ferrite cord

Remark: The device meets the requirements stated within Parts 15.247(g) & (h) in that they were developed under the protocol and operate as a true frequency hopping system. The device does not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cavonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



4.4 Modulation configures

None.

4.5 Description of Support Units

The EUT has been tested as an independent unit for fixed frequency by client.

4.6 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.

4.7 Abnormalities from Standard Conditions

None.

4.8 Other Information Requested by the Customer None.

4.9 Test Location

All tests were performed at: SGS IECC Limited (Member of the SGS Group (SGS SA)) No. 16-B, Yip Wo Street, On Lok Tsuen, Fanling, N.T., Hong Kong Tel: +852 2305 2570 Fax: +852 2756 4480. No tests were sub-contracted.



Report No.: HKEM190100003001 Page: 6 of 54 FCC ID: Z9O-92053067

4.10 Test Facility

The test facility is recognized or accredited by the following organizations:

• HOKLAS (Lab Code: 125)

SGS IECC Limited has been accepted by HKAS Executive, on the recommendation of the Accreditation Advisory Board, as a HOKLAS Accredited Laboratory, this laboratory meets the requirements of ISO/IEC 17025:2005 an it has been accredited for performing specific test as listed in the scope of accreditation within the test category of Electrical and Electronic Products.

• FCC Recognized Accredited Test Firm (CAB Registration No.: 446297)

SGS IECC Limited has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: HK0010, Test Firm Registration Number: 446297.

• Industry Canada (Site Registration No.: 5193A; CAB Identifier No.: HK0001)

SGS IECC Limited has been recognized by Department of Innovation, Science and Economic Development (ISED) Canada as a wireless testing laboratory. The acceptance letter from the ISED is maintained in our files. CAB Identifier No: HK0001, Site Registration Number: 5193A.

4.11 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio frequency	±7.25 x 10 ⁻⁸
2	RF power (conducted)	±0.75dB
2	Dedicted Sourious emission	±5.26dB (30MHz-1GHz)
3 Radia	Radiated Spundus emission	±5.11dB (1GHz-25GHz)
4	Temperature test	±1°C
5	Humidity test	±3%
6	DC and low frequency voltages test	±0.5%

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Radiated Emission Equipment Manufacturer Model / Serial No. Cal. Due Date EMI Test Receiver 9kHz to Rohde & Schwarz ESR3 / 102326 2019/08/12 3.6GHz Schaffner CBL6111C / 2791 Antenna 2019/10/26 Loop Antenna Rohde & Schwarz HFH2-Z2 / 871336/48 2019/01/22 Antenna Schwarzbeck BBA9106 / TE039A 2020/01/29 Antenna Schwarzbeck UHALP9107 / TE039B 2020/01/29 Millivoltmeter Rohde & Schwarz URV5 / 846254/013 2019/09/24 100V insertion Unit Rohde & Schwarz URV5-Z4 / 100138 2019/09/24 Amplifier TESEQ CBAIG-070 / T43859 ---Antenna Mast System Schwarzbeck AM9104 / ----Turntable with Controller Drehtisch DT312/----Spectrum Analyzer Rohde & Schwarz FSP30 / 101474 2019/05/22 Horn Antenna Schwarzbeck BBHA9120D / 9120D-1070 2020/01/29 Horn Antenna Schwarzbeck BBHA9170 / 9170-492 2019/10/16 Schwarzbeck BBV9718 / 9718-223 Preamplifier 2019/01/28 Preamplifier Schwarzbeck BBV9719 / 9719-019 2019/12/20 **Highpass Filter** Wainwright WHNX3.5/26.5G-6SS / nil 2019/12/18 WRCJV **Band Reject Filter** Wainwright 2400/2500-2100/2800-40/3S 2019/12/18 S / nil HUBER+SUHNER RF cable SF104-26.5/2 2019/12/26

5 Equipment Used during Test



Conducted Emission			
Equipment	Manufacturer	Model / Serial No.	Calibration Due
Test Receiver	Rohde & Schwarz	ESHS 30 / 839667/002	2019/09/17
Signal Generator	Rohde & Schwarz	SMT03 / 832939/017	2019/05/22
Artificial Mains Network (LISN)	Schwarzbeck	NSLK 8127 / 8127312	2019/05/22
Impulse Limiter	Rohde & Schwarz	ESH-3-Z2 / 357881052	2019/10/07

RF Conducted			
Equipment	Manufacturer	Model / Serial No.	Cal. Due Date
Wireless Conn. Tester (CMW)	Rohde & Schwarz	CMW270	2019/10/03
OSP	Rohde & Schwarz	OSP-B157W8	2019/10/03
FSV40 SIGNAL ANALYZER 40GHz	Rohde & Schwarz	FSV40	2019/08/12
SMBV100A VECTOR SIGNAL GENERATOR	Rohde & Schwarz	SMBV100A	2019/08/12
Cable	Rohde & Schwarz	J12J103539-00-2	2019/08/27



Report No.: HKEM190100003001 Page: 9 of 54 FCC ID: Z9O-92053067

6 Test Results

6.1 E.U.T. test conditions

Test Voltage:	AC120V
Temperature:	20.0 -25.0 °C
Humidity:	38-50 % RH
Atmospheric Pressure:	1000 -1010 mbar
Requirements:	 15.31(e): For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery. 15.32: Power supplies and CPU boards used with personal computers and for which separate authorizations are required to be obtained shall be tested as follows: Testing shall be in accordance with the procedures specified in Section 15.31 of this part.
Test frequencies and frequency range:	According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:
	According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:



Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which	Number of	Location in frequency range
device operates	frequencies	of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More then 40 Mile	2	1 near top, 1 near middle and 1
More than 10 MHZ	3	near bottom

Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz,
9 KHZ 10 BEIOW 10 GHZ	whichever is lower
At or above 10 GHz to below	5th harmonic of highest fundamental frequency or to 100 GHz,
30 GHz	whichever is lower
At or above 20 CHz	5th harmonic of highest fundamental frequency or to 200 GHz,
At of above 30 GHz	whichever is lower, unless otherwise specified



Report No.: HKEM190100003001 Page: 11 of 54 FCC ID: Z9O-92053067

Channel Number	Frequency (MHz)	Channel Index
1	913.75	20
2	913.80	7
3	913.85	1
4	913.90	48
5	913.95	11
6	914.00	44
7	914.05	14
8	914.10	38
9	914.15	50
10	914.20	2
11	914.25	12
12	914.30	36
13	914.35	31
14	914.40	39
15	914.45	9
16	914.50	6
17	914.55	33
18	914.60	13
19	914.65	16
20	914.70	5
21	914.75	Reserved
22	914.80	49
23	914.85	10
24	914.90	23
25	914.95	8
26	915.00	25

EUT channels and frequencies list:

Channel Number	Frequency (MHz)	Channel Index
27	915.05	34
28	915.10	3
29	915.15	35
30	915.20	32
31	915.25	Reserved
32	915.30	17
33	915.35	42
34	915.40	15
35	915.45	47
36	915.50	29
37	915.55	37
38	915.60	40
39	915.65	26
40	915.70	22
41	915.75	28
42	915.80	46
43	915.85	18
44	915.90	41
45	915.95	27
46	916.00	30
47	916.05	24
48	916.10	43
49	916.15	21
50	916.20	4
51	916.25	19
52	916.30	45

Test frequencies are the lowest channel: 1 channel (913.75MHz), middle channel: 52 channel(916.30MHz)

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



6.2 Antenna Requirement

Standard requirement

15.203 requirement:

For intentional device. According to 15.203. an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz bands that are used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna

The antenna is integrated on the main PCB and no consideration of replacement. The maximum gain of the antenna is **2.15** dBi.

Test result: The unit does meet the FCC requirements.



6.3 Conducted Disturbance at AC Power Line(150kHz-30MHz)

Test Requirement	47 CFR Part 15, Subpart C 15.207
Test Method:	ANSI C63.10 (2013) Section 6.2
Limit:	

Frequency of emission(MHz)

Conducted limit(dBµV)

	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the	he frequency.	

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



6.3.1 E.U.T. Operation

Operating Environment:

Temperature:	23.0 °C	Humidity:	58 % RH	Atmospheric Pressure:	1010	mbar
Test mode	Pre-test the E (916.30 MHz)	UT in contin channel.	uous transmit	ing mode at the lowest (913.	.75MHz)) and
The worst case	Final test the	EUT in contir	nuous transmit	ting mode at lowest (913.75 M	1Hz) cha	annel
for final test:	as worst case	mode.				

6.3.2 Test Setup Diagram





6.3.3 Measurement Data

1) The mains terminal disturbance voltage test was conducted in a shielded room.

2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50 μ H + 50hm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,

4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: HKEM190100003001 Page: 16 of 54 FCC ID: Z9O-92053067



Level = Read Level + LISN Factor + Cable Loss



Report No.: HKEM190100003001 Page: 17 of 54 FCC ID: Z9O-92053067



Level = Read Level + LISN Factor + Cable Loss

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-end-Terms-end-Conditions/Terms-end-Conditions/Terms-end-Condition



6.4 Occupied Bandwidth

(a)(1) (i) For frequency hopping systems operating in the 902-928 MHz band: If the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period;

If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

Test Method: ANSI C63.10 : Clause 6.9.1

Test Status:Pre-test the EUT in continuous transmitting mode at the lowest (913.75 MHz)
and the highest (916.30 MHz) channel.

Test Configuration:



Test Procedure:

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
- 2. Set the spectrum analyser: Span = approximately 2 to 3 times the 20dB bandwidth, centring on a hopping channel;
- Set the spectrum analyser: RBW >= 1% of the 20dB bandwidth VBW >= RBW. Sweep = auto; Detector Function = Peak. Trace = Max Hold.
- 4. Mark the peak frequency and -20 dB points bandwidth.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Test result:

Test Channel	Bandwidth(kHz)	Limit(kHz)
913.75	27.4	Less than 250
916.30	26.8	Less than 250



Result plot as follows:

Channel (913.75 MHz):



Date: 6.MAR.2019 15:36:12

Channel (916.30 MHz):



Date: 6.MAR.2019 15:37:32

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



6.5 Carrier Frequencies Separated

Test Requirement:	FCC Part 15 C section 15.247
	(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
Test Method:	ANSI C63.10: Clause 7.7.2
Test Status:	Pre-test the EUT in hopping mode.
Test Configuration:	



Ground Reference Plane

Test Procedure:

- 1. Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.
- 2. Set the spectrum analyser: RBW >= 1% of the span, VBW >= RBW. Sweep = auto; Detector Function = Peak. Trace = Max, hold.
- Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cavonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Test result:

Test Channel	Carrier Frequencies Separated (kHz)	Limit①(kHz)	Pass/Fail
(channel 1 and channel 2)	49.6	27.4	Pass
(channel 51 and channel 52)	49.6	26.8	Pass

Remark:

 $(1)\,$ The limit is the 20 dB bandwidth of hopping channel.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Result plot as follows:

Lowest Channels: Carrier Frequencies Separated



Date: 7.MAR.2019 16:11:18



Highest Channels: Carrier Frequencies Separated

Date: 7.MAR.2019 16:15:50

Test result: The unit does meet the FCC requirements.



6.6 Hopping Channel Number

Test Requirement:	FCC Part15 C section 15.247
	(a)(1)(i) Frequency hopping systems in the 913.75 - 916.30 MHz band shall
	use at least 50 channels.
Test Method:	ANSI C63.10: Clause 7.7.3
Test Status:	Pre-test the EUT in hopping mode.

Test Configuration:



Test Procedure:

- 1. Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.
- 2. Set the spectrum analyzer: RBW = 10 kHz. VBW = 30 kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
- 3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
- 4. Set the spectrum analyzer: start frequency = 913.5 MHz. stop frequency = 916.5 MHz. Submit the test result graph.





Test result: Total channels are 50 channels.

Date: 7.MAR.2019 16:24:32

Test result: The unit does meet the FCC requirements.



6.7 Dwell Time

Test Requirement:	FCC Part 15 C section 15.247
	(a)(1) (i) For frequency hopping systems operating in the 902-928 MHz band:
	If the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period;
	If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
Test Method:	ANSI C63.10: Clause 7.7.4
Test Status:	Test the EUT in hopping mode at the lowest (913.75 MHz and highest (916.3 MHz) channel.

Test Configuration:



Ground Reference Plane



Report No.: HKEM190100003001 Page: 27 of 54 FCC ID: Z9O-92053067

Test Procedure:

1. Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.

2. Set spectrum analyzer span = 0. centered on a hopping channel;

3.Set RBW = 100 kHz and VBW = 100 kHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Detector Function = Peak. Trace = Max hold;

4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g. data rate. modulation format. etc.). Repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s). An oscilloscope may be used instead of a spectrum analyzer.

Test Result:

The test period: T= 20 s

```
1. Channel 1: 913.75 MHz
   time slot
                =
                    388
                                                             388
                           (ms)
                                    1
                                                                    ms
2. Channel 52: 916.30 MHz
   time slot
                =
                    388
                           (ms)
                                    1
                                                             388
                                                                    ms
```

The results are not greater than 0.4 seconds.

The unit does meet the FCC requirements.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Result plot as follows:

1. Lowest channel (913.75 MHz):

Pulse Width:



Date: 7.MAR.2019 17:32:58

Number of Pulses in 20s observation period:



Date: 7.MAR.2019 17:47:18

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



2. Highest Channel (916.30 MHz):

Pulse Width:



Date: 7.MAR.2019 17:30:09

Number of Pulses in 20s observation period:



Date: 7.MAR.2019 17:48:00

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



6.8 Pseudorandom Frequency Hopping Sequence

6.8.1 Standard requirement

15.247(a)(1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.



6.8.2 EUT Pseudorandom Frequency Hopping Sequence

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 29 -1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

0 64 75	6	6	52	2	4	78	5	73	1	77
		1				1			r	Г
		1			8	8.1			L	1
	6	1			8	1			L	L .
										1

Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



6.9 Maximum Peak Output Power

Test Requirement:	FCC Part 15 C section 15.247
	(b)(1)For frequency hopping systems operating in the 902-928 MHz band: 1
	watt for systems employing at least 50 hopping channels; and, 0.25 watts for
	systems employing less than 50 hopping channels.
	Refer to the result "Hopping channel number" of this document. The 1 watt
	(30.0 dBm) limit applies.
Test Method:	ANSI C63.10: Clause 6.10.1
Test Limit:	
Test mode:	Test the EUT in continuous transmitting mode at the lowest (913.75 MHz)
	and highest (916.30 MHz) channel.

Test Configuration:



Test Procedure:

- 1. Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.
- Set the spectrum analyzer: RBW = 300 kHz. VBW = 300 kHz. Sweep = auto; Detector Function = Peak.
- 3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.



Test Result:	Test Result:						
Fundamental Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Result				
913.75	24.92	30.0	Pass				
916.30	<u>25.51</u>	30.0	Pass				
Remark: cable lose=1.5 dB							
Test result: The unit does meet the FCC requirements.							



Result plot as follows:

Channel (913.75 MHz):



Date: 6.MAR.2019 10:58:58

Channel (916.30 MHz):



Date: 6.MAR.2019 10:59:45



6.10 Conducted Spurious Emissions

Test Requirement:	FCC Part15 C section 15.247
	(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at
	least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.
Test Method:	ANSI C63.10: Clause 6.7
Test Status:	Test the EUT in continuous transmitting mode at the lowest (913.75 MHz) and highest (916.30 MHz) channel.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attenuation RF cable from the antenna port to the spectrum.

2. Set the spectrum analyser: RBW = 100 kHz. VBW >= RBW. Sweep = auto; Detector Function = Peak (Max. hold).

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cancer exonerate parties to a transaction form exercising all their rights and obligations under the transaction document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: HKEM190100003001 Page: 36 of 54 FCC ID: Z9O-92053067

Result plot as follows:





Date: 6.MAR.2019 11:06:17

Channel (913.75 MHz): 1 GHz to 5 GHz



Date: 6.MAR.2019 11:07:08





Channel (913.75 MHz): 5 GHz to 25 GHz

Date: 6.MAR.2019 11:07:48



Channel (916.30 MHz): 30 MHz to 1 GHz

Date: 6.MAR.2019 11:08:49





Channel (916.30 MHz): 1 GHz to 5 GHz

Date: 6.MAR.2019 11:09:10



Channel (916.30 MHz): 5 GHz to 25 GHz

Date: 6.MAR.2019 11:09:33



6.11 Radiated Spurious Emissions

Test Requirement:	FCC Part15 C section 15.247
Test Method:	 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that Contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, and provided the transmitter demonstrates compliance with the peak conducted power limits. ANSI C63.10: Clause 6.4, 6.5 and 6.6
Test Status:	Test the EUT in continuous transmitting mode at the lowest (913.75 MHz)
	and highest (916.30 MHz) channel.
Detector:	For PK value: RBW = 1 MHz for f > 1 GHz, 100 kHz for f < 1 GHz
	VBW > RBW
	Sweep = auto
	Detector function = peak
	Trace = max hold
	For AV value:
	RBW = 1 MHz for $f \ge 1$ GHz,
	VBW =10 Hz
	Sweep = auto
	Detector function = peak
	Trace = max hold
15.209 Limit:	40.0 dB μ V/m between 30MHz & 88MHz
	43.5 dB μ V/m between 88MHz & 216MHz
	46.0 dB μ V/m between 216MHz & 960MHz
	54.0 dB μ V/m above 960MHz



Report No.: HKEM190100003001 Page: 40 of 54 FCC ID: Z9O-92053067

Test Configuration:

1) 9 kHz to 30 MHz emissions:



2) 30 MHz to 1 GHz emissions:



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: HKEM190100003001 Page: 41 of 54 FCC ID: Z9O-92053067

3) 1 GHz to 40 GHz emissions:



Test Procedure:

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2007 was used to perform radiated emission test above 1 GHz.

The receiver scanned from the lowest frequency generated within the EUT to 25GHz.When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst-case emissions were reported.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from 20log (dwell time/100 ms), in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



6.11.1 Harmonic and other spurious emissions

6.11.1.1 Test the lowest Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Spurious Emissions. Quasi-Peak Measurement

Quasi-peak measurement:



Frequency (MHz)	Antenna Polarization	Correction Factor (dB/m)	Receiver QP Reading (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Over Limit (dB)
35.860	V	13.7	7.5	21.2	40	-18.8
54.360	Н	13.4	5.1	18.5	40	-21.5
160.240	V	14.7	5.8	20.5	43.5	-23.0
244.090	Н	12.7	13.7	26.4	46	-19.6
346.860	Н	15.9	4.7	20.6	46	-25.4
722.650	V	23.5	6.6	30.1	46	-15.9

1. All readings are Quasi-Peak values.

2. Correction Factor = Antenna Factor + Cable Loss.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cancer exonerate parties to a transaction form exercising all their rights and obligations under the transaction document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement:

Frequency	Antenna	Emission Le	vel (dBµV/m)	Limit (c	IBμV/m)	Bomork
(MHz)	Polarization	Peak	Average	Peak	Average	Remark
2741	V	50.94	47.66	74	54	Pass
3655	V	53.61	50.37	74	54	Pass
4569	Н	47.98	41.79	74	54	Pass
5483	V	47.96	44.80	74	54	Pass
6396	V	47.78	44.74	74	54	Pass



6.11.1.2 Test the highest Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Spurious Emissions. Quasi-Peak Measurement

Quasi-peak measurement:



Frequency (MHz)	Antenna Polarization	Correction Factor (dB/m)	Receiver QP Reading (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/ m)	Over Limit (dB)
32.870	Н	13.7	7.3	21.0	40	-19.0
62.310	V	12.5	5.9	18.4	40	-21.6
189.290	V	11.2	19.8	31.0	43.5	-12.5
230.030	Н	11.6	13.6	25.2	46	-20.8
463.580	Н	18.7	5.0	23.7	46	-22.3
726.010	V	23.6	8.5	32.1	46	-13.9

1. All readings are Quasi-Peak values.

2. Correction Factor = Antenna Factor + Cable Loss.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement:

Frequency	Antenna	Emission Level (dBµV/m)		Limit (d	lBμV/m)	Domork
(MHz)	Polarization	Peak	Average	Peak	Average	Remark
2749	V	53.14	50.30	74	54	Pass
3665	V	53.27	49.76	74	54	Pass
4581	Н	46.99	42.83	74	54	Pass
5498	V	47.60	39.91	74	54	Pass
6414	V	42.82	36.56	74	54	Pass

Remark:

1). The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Loss –Preamplifier Factor.

- 2). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

Test result: The unit does meet the FCC requirements.



6.11.2 Radiated Emissions which fall in the restricted bands

Test Requirement:	FCC Part15 C Section 15.247
	(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method:	ANSI C63.10: Clause 6.4, 6.5 and 6.6
Test Status:	Pre-test the EUT in continuous transmitting mode at the lowest (913.75 MHz) and highest (916.30 MHz) channel.
Measurement	3m (Semi-Anechoic Chamber)
Distance:	
Limit:	Section 15.209(a)
	40.0 dBµV/m between 30MHz & 88MHz;
	43.5 dBμV/m between 88MHz & 216MHz;
	46.0 dBμV/m between 216MHz & 960MHz;
	54.0 dBμV/m above 960MHz.
Detector:	For PK value:
	RBW = 1 MHz for $f \ge 1$ GHz, 100 kHz for $f < 1$ GHz
	VBW ≥ RBW
	Sweep = auto
	Detector function = peak
	For AV value:
	RBW = 1 MHz for $f \ge 1$ GHz.
	VBW =10 Hz
	Sweep = auto
	Detector function = peak
	Trace = max hold



Test Result:

Test at lowest Channel (913.75 MHz) in transmitting status

Frequency	Antenna	Emission Level (dBµV/m)	Limit (dBµV/m)	Bomork
(MHz)	Polarization	QP	QP	Remark
<1000		No emission is detected	46	PASS

Frequency	Antenna	Emission Le	vel (dBµV/m)	Limit (dBµV/m)		Domorila	
(MHz)	Polarization	Peak	Average	Peak	Average	Remark	
2741	V	50.94	47.66	74	54	Pass	
3655	V	53.61	50.37	74	54	Pass	
4569	Н	47.98	41.79	74	54	Pass	
5483	V	47.96	44.80	74	54	Pass	
6396	V	47.78	44.74	74	54	Pass	

Test at highest Channel (916.30 MHz) in transmitting status

Frequency	Antenna	Emission Level (dBµV/m)	Limit (dBµV/m)	Bomork
(MHz)	Polarization	QP QP		Reindik
<1000		No emission is detected	46	PASS

Frequency	Antenna	Emission Level (dBµV/m)		Limit (dBµV/m)		Demerile
(MHz)	Polarization	Peak	Average	Peak	Average	Remark
2749	V	53.14	50.30	74	54	Pass
3665	V	53.27	49.76	74	54	Pass
4581	Н	46.99	42.83	74	54	Pass
5498	V	47.60	39.91	74	54	Pass
6414	V	42.82	36.56	74	54	Pass

Remark: above table only record the worse data of emissions in restricted frequency bands.

Test result: The unit does meet the FCC requirements.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-end-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: HKEM190100003001 Page: 48 of 54 FCC ID: Z9O-92053067

Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section. only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	
13.36 - 13.41			



6.12 Band Edges Requirement

Test Requirement:	FCC Part15 C section 15.247
	(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Frequency Band:	913.75 MHz to 916.30 MHz
Test Method:	ANSI C63.10 (2013) Section 7.8.6
Test Status:	Pre-test the EUT in continuous transmitting mode at the lowest (913.75 MHz) and highest (916.30 MHz) channel.

Test Configuration:



Ground Reference Plane

Test Procedure:Use the following spectrum analyzer settings:
Span = 10MHz (wide enough to capture the peak level of the emission
operating on the channel closest to the bandedge, as well as any
modulation products which fall outside of the authorized band of operation.)
RBW = 100 kHz (1% of the span) and VBW = 300 kHz
Sweep = auto
Detector function = peak
Trace = max hold

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cancer exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: HKEM190100003001 Page: 50 of 54 FCC ID: Z9O-92053067

Test Result:

Compare with the output power of the lowest frequency, the Lower Edges attenuated more than 20dB Compare with the output power of the highest frequency, the Upper Edges attenuated more than 20dB.

Channel (913.75 MHz):



Date: 6.MAR.2019 11:20:18



Channel (916.30 MHz):



Date: 6.MAR.2019 11:21:29

Test result: The unit does meet the FCC requirements.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: HKEM190100003001 Page: 52 of 54 FCC ID: Z9O-92053067

7 Photographs

7.1 Radiated Spurious Emission Test Setup





This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



8 EUT Constructional Details





This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction for exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.







--End of Report--