

TEST REPORT

Application No.: HKEM2111001161AT
Applicant: ECOLAB Inc.
Address of Applicant: FCC: 1 Ecolab Place, St Paul, Minnesota, United States, 55102
 IC: Ecolab Schuman Center-F6, 655 Lone Oak Drive, Eagan, MN United States, 55121

Equipment Under Test (EUT):
EUT Name: HHCM NEXA POC Holder
Model No.: 92053075
Trade Mark: EcoLab
Standard(s) : 47 CFR Part 1.1307; 47 CFR Part 2.1093
 KDB447498D01 General RF Exposure Guidance v06
 RSS102 Issue 5 March 2015

FCC ID: Z9O-92053075
IC: 10060A-92053075
HVIN: 92053075
Date of Receipt: 2021-12-05
Date of Test: 2021-12-06 to 2021-12-20
Date of Issue: 2021-12-28

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Law Man Kit
EMC Manager

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request and accessible at <http://www.sgs.com/en/Terms-and-conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. The document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2021-12-28		Original

Authorized for issue by:			
			
		<hr/> Panny Leung /Project Engineer	Date: 2021-12-28
			
		<hr/> Law Man Kit /Reviewer	Date: 2021-12-28



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
RF Exposure	47 CFR Part 1.1307, 47 CFR Part 2.1093, KDB 447498 D01	KDB447498D01	KDB447498D01	PASS
RF Exposure	RSS102 Issue 5	RSS-102 Section 2.5.1	RSS102 Issue 5	PASS

Declaration of EUT Family Grouping:

N/A

Abbreviation:

- Tx: In this whole report Tx (or tx) means Transmitter.
 - Rx: In this whole report Rx (or rx) means Receiver.
 - RF: In this whole report RF means Radiated Frequency.
 - CH: In this whole report CH means channel.
 - Volt: In this whole report Volt means Voltage.
 - Temp: In this whole report Temp means Temperature.
 - Humid: In this whole report Humid means humidity.
 - Press: In this whole report Press means Pressure.
 - N/A: In this whole report not application.
-



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 DETAILS OF E.U.T.....	5
4.2 DESCRIPTION OF SUPPORT UNITS.....	6
4.3 MEASUREMENT UNCERTAINTY	7
4.4 TEST LOCATION	8
4.5 TEST FACILITY	8
4.6 DEVIATION FROM STANDARDS	8
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	8
5 RADIO SPECTRUM TECHNICAL REQUIREMENT	9
5.1 RF EXPOSURE	9
5.1.1 <i>Test Requirement:</i>	9
5.1.1 <i>IC Radiofrequency radiation</i>	10
5.1.2 <i>EUT RF Exposure Evaluation</i>	11
6 PHOTOGRAPHS	12

4 General Information

4.1 Details of E.U.T.

Power supply:	DC 3.0V ('AA' size battery x2)
Test voltage:	DC 3.0V
Antenna Gain:	-1dBi
Antenna Type:	Ceramic Chip Antenna
Modulation Type:	GFSK
Number of Channels:	50
Operation Frequency:	913.75MHz to 916.30MHz OR 917MHz
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)
Series number:	A1
Hardware Version:	Rev.A
Software Version:	V1.01
	Remark: Power level setting was not adjustable and fixed default through SW Version.

Frequency List

Channel Number	Frequency (MHz)	Channel Index
1	913.75	20
2	913.80	7
3	913.85	1
4	913.90	48
5	913.95	11
6	914.00	44
7	914.05	14
8	914.10	38
9	914.15	50
10	914.20	2
11	914.25	12
12	914.30	36
13	914.35	31
14	914.40	39
15	914.45	9
16	914.50	6
17	914.55	33
18	914.60	13
19	914.65	16
20	914.70	5
21	914.75	Reserved
22	914.80	49
23	914.85	10
24	914.90	23
25	914.95	8
26	915.00	25

Channel Number	Frequency (MHz)	Channel Index
27	915.05	34
28	915.10	3
29	915.15	35
30	915.20	32
31	915.25	Reserved
32	915.30	17
33	915.35	42
34	915.40	15
35	915.45	47
36	915.50	29
37	915.55	37
38	915.60	40
39	915.65	26
40	915.70	22
41	915.75	28
42	915.80	46
43	915.85	18
44	915.90	41
45	915.95	27
46	916.00	30
47	916.05	24
48	916.10	43
49	916.15	21
50	916.20	4
51	916.25	19
52	916.30	45

Test frequencies are the lowest channel: 913.75 MHz, and highest channel:916.30 MHz

OR

Channel	Frequency (MHz)
1	917

Test frequencies is 917MHz.

4.2 Description of Support Units

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

RF

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power (30MHz-40GHz)	1.5dB
5	RF power density	1.5dB
6	Conducted Spurious emissions	1.5dB
7	RF Radiated power	4.4dB (30MHz-1GHz)
		4.7dB (1GHz-6GHz)
8	Radiated Spurious emission test	4.7dB (6GHz-18GHz)
		5.7dB (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Supply voltages	$\pm 1.5\%$
12	Time	$\pm 3\%$

Remark:

The U_{lab} (lab Uncertainty) is less than U_{cispr} (CISPR Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

According to decision rule based on Clause 4.2 of CISPR 16-4-2, the EUT complied with the standards specified above.

4.4 Test Location

All tests were performed at:

SGS Hong Kong Limited
Unit 2 and 3, G/F, Block A, Po Lung Centre,
11 Wang Chiu Road, Kowloon Bay, Kowloon, Hong Kong
Tel: +852 2305 2570 Fax: +852 2756 4480

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **HOKLAS (Lab Code: 009)**

SGS Hong Kong Limited has been accepted by HKAS Executive, on the recommendation of the Accreditation Advisory Board, as a HOKLAS Accredited Laboratory, this laboratory meets the requirements of ISO/IEC 17025:2017 and it has been accredited for performing specific test as listed in the scope of accreditation within the test category of Electrical and Electronic Products.

• **IAS Accreditation (Lab Code: TL-817)**

SGS Hong Kong Limited has met the requirements of AC89, IAS Accreditation Criteria for Testing Laboratories, and has demonstrated compliance with ISO/IEC Standard 17025:2017, General requirements for the competence of testing and calibration laboratories. This organization is accredited to provide the services specified in the scope of accreditation maintained on the IAS website (www.iasonline.org).

The report must not be used by the client to claim product certification, approval, or endorsement by IAS, NIST, or any agency of the Federal Government.

• **FCC Recognized Accredited Test Firm (CAB Registration No.: 514599)**

SGS Hong Kong Limited has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: HK0015, Test Firm Registration Number: 514599.

• **Industry Canada (Site Registration No.: 26103; CAB Identifier No.: HK0015)**

SGS Hong Kong Limited has been recognized by Department of Innovation, Science and Economic Development (ISED) Canada as a wireless testing laboratory. The acceptance letter from the ISED is maintained in our files. CAB Identifier No: HK0015, Site Registration Number: 26103.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

5 Radio Spectrum Technical Requirement

5.1 RF Exposure

5.1.1 Test Requirement:

CFR 47 Part 1.1310

Limit:

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in Part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

According to IEEE C95.3:2002 section 5.5.1.1, The power density S at a point on the axis at a distance d from a transmitting antenna is given by the Friis free-space transmission formula

$$S = \frac{PG}{4\pi d^2}$$

S = power density (mW/cm²)

P = the net power delivered to the antenna (mW)

G = gain of the antenna in linear scale

d = distance between observation point and center of the radiator (cm)

5.1.1 IC Radiofrequency radiation

According to RSS-102 Issue 5, section 2.5.2 Exemption.

RF exposure evaluation is required if the separation distance between the user and the device's radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $22.48/f^{0.5}W$ (adjusted for tune-up tolerance), where f is in MHz;

at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);

at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834} W$ (adjusted for tune-up tolerance), where f is in MHz;

at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

5.1.2 EUT RF Exposure Evaluation

Antenna Gain: -1 dBi

The maximum Gain measured in fully anechoic chamber is 0.79 in linear term.

Output Power Into Antenna & RF Exposure Evaluation Distance:

For FCC;

FHSS:

Channel	Frequency (MHz)	Conduct power (including Tune-up tolerance) (dBm)	Conduct power (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Low	913.75	7.9	6.166	0.00097	0.61	PASS
High	916.70	7.7	5.888	0.00093	0.61	PASS

917MHz:

Frequency (MHz)	Conduct power (including Tune-up tolerance) (dBm)	Conduct power (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
917.00	-11.73	0.05	0.00001	0.61	PASS

For IC:

FHSS:

Channel	Frequency (MHz)	Conduct power (dBm)	E.I.R.P (dBm)	E.I.R.P (W)	Limit (W)	Result
Low	913.75	7.9	6.9	0.00490	1.38	PASS
High	916.70	7.7	6.7	0.00468	1.39	PASS

917MHz:

Frequency (MHz)	Conduct power (dBm)	E.I.R.P (dBm)	E.I.R.P (W)	Limit (W)	Result
917.00	-11.73	-12.73	0.00005	1.39	PASS

Note: 1. Refer to report No. HKEM21100116102& HKEM21100116103 for EUT test conducted power value;
2. Two working bands couldn't transmit simultaneously.



6 Photographs

Remark: Photos refer to Appendix: External Photo, Internal Photo and setup Photo.

- End of the Report -
