



Excellence in Compliance Testing

## Certification Test Report

**FCC ID: Z9O-FAS1527  
IC: 10060A-FAS1527**

**FCC Rule Part: 15.249  
IC Radio Standards Specification: RSS-210**

**ACS Report Number: 13-2002.W06.2A**

Manufacturer: UltraClenz, LLC  
Model(s): FAS1527-00, FAS1527-01, FAS1527-02

Test Begin Date: **January 9, 2013**  
Test End Date: **June 3, 2014**

Report Issue Date: June 3, 2014



FOR THE SCOPE OF ACCREDITATION UNDER CERTIFICATE NUMBER AT-1533

This report must not be used by the client to claim product certification, approval, or endorsement by ACLASS, ANSI, or any agency of the Federal Government.

**Project Manager:**

**Thierry Jean-Charles  
EMC Engineer  
Advanced Compliance Solutions, Inc.**

**Reviewed by:**

**Kirby Munroe  
Director, Wireless Certifications  
Advanced Compliance Solutions, Inc.**

This test report shall not be reproduced except in full. This report may be reproduced in part with prior written consent of ACS, Inc. The results contained in this report are representative of the sample(s) submitted for evaluation.

**This report contains 14 pages**

## **TABLE OF CONTENTS**

<b>1</b>	<b>GENERAL .....</b>	<b>3</b>
1.1	Purpose.....	3
1.2	Product description .....	3
1.3	Test Methodology and Considerations .....	3
<b>2</b>	<b>TEST FACILITIES .....</b>	<b>4</b>
2.1	Location.....	4
2.2	Laboratory Accreditations/Recognitions/Certifications .....	4
2.3	Radiated & Conducted Emissions Test Site Description .....	5
<b>3</b>	<b>APPLICABLE STANDARD REFERENCES.....</b>	<b>6</b>
<b>4</b>	<b>LIST OF TEST EQUIPMENT.....</b>	<b>7</b>
<b>5</b>	<b>SUPPORT EQUIPMENT .....</b>	<b>8</b>
<b>6</b>	<b>EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM .....</b>	<b>8</b>
<b>7</b>	<b>SUMMARY OF TESTS.....</b>	<b>9</b>
7.1	Antenna Requirement – FCC: Section 15.203 .....	9
7.2	20dB / 99% Bandwidth: IC RSS-Gen 4.6.1 .....	9
7.3	Radiated Spurious Emissions - FCC Section 15.249 (a); IC: RSS-210 A2.9.....	11
<b>8</b>	<b>CONCLUSION.....</b>	<b>13</b>

## 1 GENERAL

### 1.1 Purpose

The purpose of this report is to demonstrate compliance with Part 15 Subpart C of the FCC's Code of Federal Regulations and Industry Canada's Radio Standards Specification RSS-210.

### 1.2 Product description

The Ultraclenz, LLC models FAS1527-00, FAS1527-01, FAS1527-02 are part of the UltraClenz' patient safeguard system which monitors health workers' sanitation in hospitals. The equipment is a badge that incorporates a 2.4 GHz wireless transceiver and a 125 kHz receiver. The models FAS1527-00, FAS1527-01, FAS1527-02 are identical except for the enclosure color.

#### Technical Details

Frequency of Operation: 2405 MHz

Number of Channels: 1

Modulation: GFSK

Data Rate: 2 Mbps

Antenna / Gain: Inverted-F PCB antenna / 6.3 dBi

Input Voltage: 3 VDC

Manufacturer Information:

UltraClenz, LLC

1201 Jupiter Park Drive

Jupiter, FL 33458

Test Sample Serial Number(s): N/A

Test Sample Condition: Good

### 1.3 Test Methodology and Considerations

The model FAS1527-00 was tested in full and was deemed representative of all the models listed. The unit was powered via battery. The EUT was evaluated for radiated emissions in three orthogonal orientations corresponding to the XY, XZ and YZ planes. The 2.4 GHz radio was continuously pulsing during the evaluation. The average levels were calculated using a duty cycle correction factor of 0.864 % as defined in the equipment theory of operation.

The unintentional emissions evaluations is documented separately in a verification report.

## 2 TEST FACILITIES

### 2.1 Location

The radiated and conducted emissions test sites are located at the following address:

Advanced Compliance Solutions, Inc.  
3998 FAU Blvd, Suite 310  
Boca Raton, Florida 33431  
Phone: (561) 961-5585  
Fax: (561) 961-5587  
[www.acstestlab.com](http://www.acstestlab.com)

FCC Test Firm Registration #: 475089

Industry Canada Lab Code: 4175C

### 2.2 Laboratory Accreditations/Recognitions/Certifications

ACS is accredited to ISO/IEC 17025 by ANSI-ASQ National Accreditation Board under their ACCLASS program and has been issued certificate number AT-1533 in recognition of this accreditation. Unless otherwise specified, all test methods described within this report are covered under the ISO/IEC 17025 scope of accreditation.

## 2.3 Radiated & Conducted Emissions Test Site Description

### 2.3.1 Semi-Anechoic Chamber Test Site

The EMC radiated test facility consists of an RF-shielded enclosure. The interior dimensions of the indoor semi-anechoic chamber are approximately 48 feet (14.6 m) long by 36 feet (10.8 m) wide by 24 feet (7.3 m) high and consist of rigid, 1/8 inch (0.32 cm) steel-clad, wood core modular panels with steel framing. In the shielded enclosure, the faces of the panels are galvanized and the chamber is self-supporting. 8-foot RF absorbing cones are installed on 4 walls and the ceiling. The steel-clad ground plane is covered with vinyl floor.

The turntable is driven by pneumatic motor, which is capable of supporting a 2000 lb. load. The turntable is flushed with the chamber floor which it is connected to, around its circumference, with a continuous metallic loaded spring. An EMCO Model 1050 Multi-device Controller controls the turntable position.

A pneumatic motor is used to control antenna polarizations and height relative to the ground. The height information is displayed on the control unit EMCO Model 1050.

The control room is an RF shielded enclosure attached to the semi-anechoic chamber with two bulkhead panels for connecting RF, and control cables. The dimension of the room is 7.3 m x 4.9 m x 3 m high and the entrance doors of both control and conducted rooms are 3 feet (0.91 m) by 7 feet (2.13 m).

A diagram of the Semi-Anechoic Chamber Test Site is shown in Figure 2.3.1-1 below:




Figure 2.3.1-1: Semi-Anechoic Chamber Test Site

### 2.3.2 Conducted Emissions Test Site Description

The dimensions of the shielded conducted room are  $7.3 \times 4.9 \times 3 \text{ m}^3$ . As per ANSI C63.4 2003 requirements, the data were taken using two LISNs; a Solar Model 8028-50 50  $\Omega$ /50  $\mu\text{H}$  and an EMCO Model 3825, which are installed as shown in Photograph 3. For 220 V, 50 Hz, a Polarad LISN (S/N 879341/048) is used in conjunction with a 1 kVA, 50 Hz/220 V EDGAR variable frequency generator, Model 1001B, to filter conducted noise from the generator.

A diagram of the room is shown below in figure 2.3.2-1:




Figure 2.3.2-1: AC Mains Conducted EMI Site

## 3 APPLICABLE STANDARD REFERENCES

The following standards were used:

- ❖ ANSI C63.4-2003: Method of Measurements of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the 9KHz to 40GHz
- ❖ ANSI C63.10-2009: American National Standard for Testing Unlicensed Wireless Devices
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 2, Subpart J: Equipment Authorization Procedures, 2014
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 15, Subpart C: Radio Frequency Devices, Intentional Radiators, 2014
- ❖ Industry Canada Radio Standards Specification: RSS-210 - Low-power License-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Issue 8 December 2010.
- ❖ Industry Canada Radio Standards Specification: RSS-GEN – General Requirements and Information for the Certification of Radiocommunication Equipment, Issue 3, Dec 2010.

#### 4 LIST OF TEST EQUIPMENT

The calibration interval of test equipment is annually or the manufacturer's recommendations. Where the calibration interval deviates from the annual cycle based on the instrument manufacturer's recommendations, it shall be stated below.

**Table 4-1: Test Equipment**

AssetID	Manufacturer	Model #	Equipment Type	Serial #	Last Calibration Date	Calibration Due Date
523	Agilent	E7405	Spectrum Analyzers	MY45103293	1/8/2013	1/8/2015
524	Chase	CBL6111	Antennas	1138	1/7/2013	1/7/2015
2006	EMCO	3115	Antennas	2573	3/2/2011	3/2/2013
2006	EMCO	3115	Antennas	2573	4/24/2013	4/24/2015
2008	COM-Power	AH-826	Antennas	81009	NCR	NCR
2011	Hewlett-Packard	HP 8447D	Amplifiers	2443A03952	12/31/2012	12/31/2013
2011	Hewlett-Packard	HP 8447D	Amplifiers	2443A03952	12/31/2013	12/31/2014
2037	ACS Boca	Chamber EMI Cable Set	Cable Set	2037	1/1/2013	1/1/2014
2037	ACS Boca	Chamber EMI Cable Set	Cable Set	2037	1/1/2014	1/1/2015
2037	ACS Boca	Chamber EMI Cable Set	Cable Set	2037	2/27/2014	2/27/2015
2044	QMI	N/A	Cables	2044	12/31/2012	12/31/2013
2044	QMI	N/A	Cables	2044	12/31/2013	12/31/2014
2070	Mini Circuits	VHF-8400+	Filter	2070	12/31/2012	12/31/2013
2070	Mini Circuits	VHF-8400+	Filter	2070	1/1/2014	1/1/2015
2072	Mini Circuits	VHF-3100+	Filter	30737	12/31/2012	12/31/2013
2072	Mini Circuits	VHF-3100+	Filter	30737	1/1/2014	1/1/2015
2076	Hewlett Packard	HP5061-5458	Cables	2076	12/29/2012	12/29/2013
2076	Hewlett Packard	HP5061-5458	Cables	2076	12/31/2013	12/31/2014
2086	Merrimac	FAN-6-10K	Attenuators	23148-83-1	12/29/2012	12/29/2013
2086	Merrimac	FAN-6-10K	Attenuators	23148-83-1	12/31/2013	12/31/2014
2089	Agilent Technologies, Inc.	83017A	Amplifiers	3123A00214	12/20/2012	12/20/2013
2089	Agilent Technologies, Inc.	83017A	Amplifiers	3123A00214	12/16/2013	12/16/2014
2095	ETS Lindgren	TILE4! - Version 4.2.A	Software	85242	NCR	NCR

**Notes:**


- **NCR=No Calibration Required**
- **The calibration information for the assets is provided to cover the entire test period.**
- **The assets listed above were only used during the active period of the calibration cycle.**
- **Maintenance was performed on asset 2037 requiring calibration before the end of the previous calibration cycle.**

## 5 SUPPORT EQUIPMENT

Table 5-1: Support Equipment

Item	Equipment Type	Manufacturer	Model Number	Serial Number
There is no support equipment associated with this product				

## 6 EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM



## 7 SUMMARY OF TESTS

Along with the tabular data shown below, plots were taken of all signals deemed important enough to document.

### 7.1 Antenna Requirement – FCC: Section 15.203

The FAS1527-00 uses an internal 6.3 dBi PCB inverted-F antenna, thus meeting the requirements of 15.203.

### 7.2 20dB / 99% Bandwidth: FCC Section 15.215, IC RSS-Gen 4.6.1

#### 7.2.1 Measurement Procedure

The EUT was rotated through 360° and the receive antenna height was varied from 1m to 4m so that the maximum radiated emissions level would be detected.

The spectrum analyzer span was set to 2 to 5 times the estimated bandwidth of the emission. The RBW was to  $\geq 1\%$  to 5% of the estimated emission bandwidth. The trace was set to max hold with a peak detector active. The Delta function of the analyzer was utilized to determine the 20 dB bandwidth of the emission.

The 99% occupied bandwidth was measured with the spectrum analyzer span set to fully display the emission, including the emissions skirts. The RBW was greater or equal to 1% of the span. The occupied 99% bandwidth was measured by using a delta marker at the lower and upper frequencies leading to 0.5% of the total power.

#### 7.2.2 Measurement Results

Results are shown below in Table 7.2.2-1 and Figures 7.2.2-1 through 7.2.2-2

Table 7.2.2-1: 20dB / 99% Bandwidth

Frequency [MHz]	20dB Bandwidth [kHz]	99% Bandwidth [kHz]
2405	2631	3081




Figure 7.2.2-1: 20dB BW




Figure 7.2.2-2: 99% OBW

### 7.3 Radiated Spurious Emissions - FCC Section 15.249 (a); IC: RSS-210 A2.9

#### 7.3.1 Measurement Procedure

Radiated emissions tests were made over the frequency range of 30MHz to 26GHz, 10 times the highest fundamental frequency.

The EUT was rotated through 360° and the receive antenna height was varied from 1m to 4m so that the maximum radiated emissions level would be detected. For frequencies below 1000MHz, quasi-peak measurements were made using a resolution bandwidth RBW of 120 kHz and a video bandwidth VBW of 300 kHz. For frequencies above 1000MHz, peak and average measurements made with RBW and VBW of 1 MHz and 3MHz respectively.

The unit was continuously pulsing during the evaluation. A Duty Cycle Correction of 0.864% corresponding to -41.27 dB was applied to the peak measurements for the average results. The justification of the duty cycle is provided in the customer's theory of operation.

### 7.3.2 Measurement Results

Radiated spurious emissions found in the band of 30MHz to 26GHz are reported in the Table 7.3.2-1 below.

**Table 7.3.2-1: Radiated Spurious Emissions Tabulated Data**

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)			
	pk	avg			pk	avg	pk	avg	pk	avg		
<b>XZ plane (Standing)</b>												
<b>Fundamental Frequency</b>												
2405	85.31	85.31	H	-7.94	77.37	36.10	114	94	36.6	57.9		
2405	86.14	86.14	V	-7.94	78.20	36.93	114	94	35.8	57.1		
<b>Spurious Emissions</b>												
4810	47.61	47.61	H	-1.45	46.16	4.89	74.0	54.0	27.8	49.1		
4810	47.73	47.73	V	-1.45	46.28	5.01	74.0	54.0	27.7	49.0		
<b>XY plane (Side)</b>												
<b>Fundamental Frequency</b>												
2405	86.07	86.07	H	-7.94	78.13	36.86	114	94	35.9	57.1		
2405	84.35	84.35	V	-7.94	76.41	35.14	114	94	37.6	58.9		
<b>Spurious Emissions</b>												
4810	47.27	47.27	H	-1.45	45.82	4.55	74.0	54.0	28.2	49.5		
4810	47.60	47.60	V	-1.45	46.15	4.88	74.0	54.0	27.9	49.1		
<b>YZ plane (Flat)</b>												
<b>Fundamental Frequency</b>												
2405	85.14	85.14	H	-7.94	77.20	35.93	114	94	36.8	58.1		
2405	88.05	88.05	V	-7.94	80.11	38.84	114	94	33.9	55.2		
<b>Spurious Emissions</b>												
4810	45.57	45.57	H	-1.45	44.12	2.85	74.0	54.0	29.9	51.2		
4810	45.96	45.96	V	-1.45	44.51	3.24	74.0	54.0	29.5	50.8		

**Note:**

- The fundamental emissions measurements were measured using a resolution bandwidth of 1 MHz with the field strength integrated over the 99% occupied bandwidth.
- All emissions above 4810 MHz were attenuated below the permissible limits and the noise floor of the measurement equipment.

### 7.3.3 Sample Calculation:

$$R_C = R_U + CF_T$$

Where:

$CF_T$  = Total Correction Factor (AF+CA+AG)-DC (Average Measurements Only)

$R_U$  = Uncorrected Reading

$R_C$  = Corrected Level

AF = Antenna Factor

CA = Cable Attenuation

AG = Amplifier Gain

DC = Duty Cycle Correction Factor

#### Example Calculation: Peak

Corrected Level:  $47.61 + (-1.45) = 46.16 \text{ dBuV/m}$

Margin:  $74 \text{ dBuV/m} - 46.16 \text{ dBuV/m} = 27.8 \text{ dB}$

#### Example Calculation: Average

Corrected Level:  $47.61 + (-1.45) - 41.27 = 4.89 \text{ dBuV/m}$

Margin:  $54 \text{ dBuV/m} - 4.89 \text{ dBuV/m} = 49.1 \text{ dB}$

## 8 CONCLUSION

In the opinion of ACS, Inc. the models FAS1527-00, FAS1527-01, FAS1527-02 manufactured by UltraClenz, LLC meet the requirements of FCC Part 15 subpart C and Industry Canada's Radio Standards Specification RSS-210.

**END REPORT**