

FCC REPORT (WIFI)

Applicant: 8Devices

Address of Applicant: Gedimino 47, Kaunas, LT-44242, Lithuania

Equipment Under Test (EUT)

Product Name: Komikan

Model No.: Komikan

FCC ID: Z9W-KOM

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: 24 Mar., 2020

Date of Test: 24 Mar., to 06 May, 2020

Date of report issued: 06 May, 2020

Test Result: PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	06 May, 2020	Original

Tested by: Mike.ou **Date:** 06 May, 2020
Test Engineer

Reviewed by: Winner Zhang **Date:** 06 May, 2020
Project Engineer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST ENVIRONMENT AND TEST MODE.....	6
5.4 DESCRIPTION OF SUPPORT UNITS.....	6
5.5 MEASUREMENT UNCERTAINTY.....	6
5.6 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD.....	6
5.7 LABORATORY FACILITY.....	7
5.8 LABORATORY LOCATION.....	7
5.9 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA	8
6.1 ANTENNA REQUIREMENT.....	8
6.2 CONDUCTED EMISSION.....	10
6.3 CONDUCTED OUTPUT POWER.....	13
6.4 OCCUPY BANDWIDTH.....	19
6.5 POWER SPECTRAL DENSITY.....	28
6.6 BAND EDGE.....	34
6.6.1 Conducted Emission Method.....	34
6.6.2 Radiated Emission Method.....	39
6.7 SPURIOUS EMISSION.....	112
6.7.1 Conducted Emission Method.....	112
6.7.2 Radiated Emission Method.....	117
7 TEST SETUP PHOTO	139
8 EUT CONSTRUCTIONAL DETAILS	142

4 Test Summary

Test Items	Section in CFR 47	Result
Antenna requirement	15.203 & 15.247 (b)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247 (d)	Pass
Spurious Emission	15.205 & 15.209	Pass
<p>Remark:</p> <ol style="list-style-type: none"> 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: Not Applicable. 3. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 1.0dB (provided by the customer). 		
Test Method:	ANSI C63.4-2014 ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02	

5 General Information

5.1 Client Information

Applicant:	8Devices
Address:	Gedimino 47, Kaunas, LT-44242, Lithuania
Manufacturer/ Factory:	8Devices
Address:	Gedimino 47, Kaunas, LT-44242, Lithuania

5.2 General Description of E.U.T.

Product Name:	Komikan
Model No.:	Komikan
Operation Frequency:	2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)) 2422MHz~2452MHz (802.11n(HT40))
Channel numbers:	11 for 802.11b/802.11g/802.11(HT20) 7 for 802.11n(HT40)
Channel separation:	5MHz
Modulation technology: (IEEE 802.11b)	Direct Sequence Spread Spectrum (DSSS)
Modulation technology: (IEEE 802.11g/802.11n)	Orthogonal Frequency Division Multiplexing(OFDM)
Data speed (IEEE 802.11b):	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
Data speed (IEEE 802.11g):	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
Data speed (IEEE 802.11n):	Up to 150Mbps
Antenna Type:	Ceramic Antenna, Whip Antenna, Flex Antenna
Antenna gain:	Ceramic Antenna: 2.09 dBi Flex Antenna: 3.20 dBi Whip Antenna: 4.00 dBi
Power supply:	DC 3.3V
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

Operation Frequency each of channel for 802.11b/g/n(HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

- For 802.11n-HT40 mode, the channel number is from 3 to 9;
- Channel 1, 6 & 11 selected for 802.11b/g/n-HT20 as Lowest, Middle and Highest channel. Channel 3, 6 & 9 selected for 802.11n-HT40 as Lowest, Middle and Highest Channel.

5.3 Test environment and test mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Transmitting mode	Keep the EUT in continuous transmitting with modulation
Remark:	<i>Conducted Emission and Radiated Emission below 1GHz pre-scan Ceramic Antenna and Flex Antenna and Whip Antenna, found Whip Antenna was worse case mode, the report only reflects the worst mode</i>
<p>Radiated Emission: The sample was placed 0.8m (below 1GHz)/1.5m (above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:</p>	
Per-scan all kind of data rate, the follow list were the worst case.	
Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	6.5Mbps
802.11n(HT40)	13.5Mbps

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX7070	2J8XSZ2	DoC
DELL	MONITOR	SE2018HR	3M7QPY2	DoC
DELL	KEYBOARD	KB216d	N/A	DoC
DELL	MOUSE	MS116t1	N/A	DoC

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.38 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.36 dB (k=2)

5.6 Additions to, deviations, or exclusions from the method

No

5.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.8 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
 Address: No.110~116, Building B, Jinyuan Business Building, Xixiang Road,
 Bao'an District, Shenzhen, Guangdong, China
 Tel: +86-755-23118282, Fax: +86-755-23116366
 Email: info@ccis-cb.com, Website: <http://www.ccis-cb.com>

5.9 Test Instruments list

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
Loop Antenna	SCHWARZBECK	FMZB1519B	044	03-07-2020	03-06-2021
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-18-2019	11-17-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2020	03-06-2021
Pre-amplifier	CD	PAP-1G18	11804	03-07-2020	03-06-2021
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-05-2020	03-04-2021
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-18-2019	11-17-2020
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-05-2020	03-04-2021
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2020	03-06-2021
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2020	03-06-2021
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2020	03-06-2021
RF Switch Unit	MWRFTTEST	MW200	N/A	N/A	N/A
Test Software	MWRFTTEST	MTS8200	Version: 2.0.0.0		


Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-05-2020	03-04-2021
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-05-2020	03-04-2021
LISN	CHASE	MN2050D	1447	03-05-2020	03-04-2021
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2017	07-20-2020
Cable	HP	10503A	N/A	03-05-2020	03-04-2021
EMI Test Software	AUDIX	E3	Version: 6.110919b		

6 Test results and Measurement Data

6.1 Antenna requirement

Standard requirement:	FCC Part 15 C Section 15.203 /247(b)									
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>										
E.U.T Antenna:										
<p><i>The product is a professionally installed device which has two types of antennas for the application. The antennas information as below table:</i></p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Antenna Type</th> <th>Antenna Gain (dBi)</th> </tr> </thead> <tbody> <tr> <td>Ceramic Antenna</td> <td>2.09</td> </tr> <tr> <td>Flex Antenna</td> <td>3.20</td> </tr> <tr> <td>Whip Antenna</td> <td>4.00</td> </tr> </tbody> </table> <p><i>According to above information, the antennas meet the requirements of this section</i></p>			Antenna Type	Antenna Gain (dBi)	Ceramic Antenna	2.09	Flex Antenna	3.20	Whip Antenna	4.00
Antenna Type	Antenna Gain (dBi)									
Ceramic Antenna	2.09									
Flex Antenna	3.20									
Whip Antenna	4.00									

Ceramic Antenna



Flex Antenna



Whip Antenna




6.2 Conducted Emission

Test Requirement:	FCC Part 15 C Section 15.207		
Test Frequency Range:	150 kHz to 30 MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9 kHz, VBW=30 kHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test procedure	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.), which provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10(latest version) on conducted measurement. 		
Test setup:	<p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>		
Test Instruments:	Refer to section 5.9 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Passed		

Measurement Data:

Product name:	Komikan	Product model:	Komikan
Test by:	Mike	Test mode:	Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%




	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.489	26.63	-0.39	-0.26	10.76	36.74	56.19	-19.45	QP
2	0.535	19.54	-0.39	-0.36	10.76	29.55	46.00	-16.45	Average
3	0.567	19.25	-0.39	-0.37	10.76	29.25	46.00	-16.75	Average
4	1.032	32.51	-0.38	0.42	10.87	43.42	56.00	-12.58	QP
5	2.664	18.11	-0.43	-0.24	10.93	28.37	46.00	-17.63	Average
6	3.661	21.00	-0.46	-0.09	10.90	31.35	46.00	-14.65	Average
7	3.681	29.14	-0.46	-0.09	10.90	39.49	56.00	-16.51	QP
8	3.985	28.86	-0.46	-0.05	10.89	39.24	56.00	-16.76	QP
9	4.454	28.41	-0.47	0.02	10.87	38.83	56.00	-17.17	QP
10	18.135	18.79	-0.87	1.82	10.92	30.66	50.00	-19.34	Average
11	19.428	30.35	-0.94	1.20	10.93	41.54	60.00	-18.46	QP
12	19.950	19.69	-0.97	0.89	10.93	30.54	50.00	-19.46	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

Product name:	Komikan	Product model:	Komikan
Test by:	Mike	Test mode:	Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%




Trace: 9

	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.274	32.60	-0.64	0.01	10.74	42.71	60.98	-18.27	QP
2	0.461	22.11	-0.65	0.00	10.74	32.20	46.67	-14.47	Average
3	0.513	23.97	-0.65	0.03	10.76	34.11	46.00	-11.89	Average
4	0.555	23.70	-0.65	0.03	10.76	33.84	46.00	-12.16	Average
5	0.567	31.82	-0.65	0.03	10.76	41.96	56.00	-14.04	QP
6	1.016	19.86	-0.63	0.08	10.87	30.18	46.00	-15.82	Average
7	1.032	32.72	-0.63	0.08	10.87	43.04	56.00	-12.96	QP
8	2.527	29.78	-0.67	0.25	10.94	40.30	56.00	-15.70	QP
9	2.678	21.42	-0.67	0.27	10.93	31.95	46.00	-14.05	Average
10	17.383	28.06	-1.12	1.63	10.92	39.49	60.00	-20.51	QP
11	18.920	20.64	-1.29	0.81	10.92	31.08	50.00	-18.92	Average
12	19.122	29.39	-1.32	0.73	10.92	39.72	60.00	-20.28	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

6.3 Conducted Output Power

Test Requirement:	FCC Part 15 C Section 15.247 (b)(3)
Limit:	30dBm
Test setup:	 <p>The diagram illustrates the test setup for conducted output power measurement. It shows a Spectrum Analyzer connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table, which is supported by two legs. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:


Mode	Test CH	Ant. Port	Conducted Output power(dBm)	Total power (dBm)	Limit (dBm)	Result
802.11b (SISO)	Lowest	TX0	22.25	/	30.00	Pass
		TX1	22.56			
	Middle	TX0	22.18			
		TX1	22.15			
	Highest	TX0	22.09			
		TX1	20.51			
802.11g (SISO)	Lowest	TX0	19.47	/	30.00	Pass
		TX1	20.01			
	Middle	TX0	21.17			
		TX1	21.35			
	Highest	TX0	19.37			
		TX1	19.74			
802.11n(HT20) (MIMO)	Lowest	TX0	19.60	22.48	Ceramic Antenna:30 Flex Antenna:29.8 Whip Antenna:29.0	Pass
		TX1	19.34	22.55		
	Middle	TX0	19.56	22.29		
		TX1	19.52			
	Highest	TX0	19.10			
		TX1	19.46			
802.11n(HT40) (MIMO)	Lowest	TX0	18.76	21.68	Ceramic Antenna:30 Flex Antenna:29.8 Whip Antenna:29.0	Pass
		TX1	18.58	22.70		
	Middle	TX0	19.77	22.18		
		TX1	19.60			
	Highest	TX0	19.23			
		TX1	19.10			

Remark:


- Because transmit signals are correlated, Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi.
- So Ceramic Antenna: The Directional gain= $2.09 + 10 \log(2)=5.09$ dBi, The directional Gain of antenna is not exceed 6 dBi, so the limit of power is 30 dBm(for 802.11n).
Flex Antenna: The Directional gain= $3.2 + 10 \log(2)=6.2$ dBi, The directional Gain of antenna is greater than 6 dBi, so the limit of power is 29.8 dBm(for 802.11n).
Whip Antenna: The Directional gain= $4 + 10 \log(2)=7.0$ dBi, The directional Gain of antenna is greater than 6 dBi, so the limit of power is 29.0 dBm(for 802.11n).

Test plot as follows:

TX 0:




802.11n(HT20)




Date: 1.APR.2020 11:00:50

802.11n(HT40)




Date: 1.APR.2020 11:06:17

Lowest channel




Date: 1.APR.2020 11:02:47

Lowest channel




Date: 1.APR.2020 11:08:21

Middle channel



Date: 1.APR.2020 11:03:26


Middle channel




Date: 1.APR.2020 11:07:54

Highest channel

TX 1:




802.11n(HT20)




Date: 1.APR.2020 11:17:44

802.11n(HT40)




Date: 1.APR.2020 11:09:26

Lowest channel




Date: 1.APR.2020 11:18:13

Lowest channel




Date: 1.APR.2020 11:10:02

Middle channel



Date: 1.APR.2020 11:18:57

Middle channel



Date: 1.APR.2020 11:10:28

Highest channel

6.4 Occupy Bandwidth

Test Requirement:	FCC Part 15 C Section 15.247 (a)(2)
Limit:	>500kHz
Test setup:	<p>The diagram shows a Spectrum Analyzer on the left and an E.U.T (Equipment Under Test) on the right. They are connected by a red cable. Both are placed on a table labeled 'Non-Conducted Table'. Below the table is a 'Ground Reference Plane'.</p>
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

TX 0:


Test CH	6dB Emission Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	10.24	16.64	17.76	36.80	>500	Pass
Middle	10.24	16.64	17.76	36.80		
Highest	10.24	16.64	17.76	36.80		
Test CH	99% Occupy Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	15.04	16.80	17.60	36.32	N/A	N/A
Middle	15.12	17.04	17.68	36.48		
Highest	15.20	16.80	17.68	36.48		

TX 1:

Test CH	6dB Emission Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	10.24	16.64	17.76	36.80	>500	Pass
Middle	10.24	16.64	17.76	36.80		
Highest	10.24	16.64	17.76	36.80		
Test CH	99% Occupy Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	15.04	16.72	17.60	36.32	N/A	N/A
Middle	15.04	16.88	17.60	36.48		
Highest	15.04	16.80	17.60	36.48		


Test plot as follows:

TX 0:




802.11g

6dB EBW




Date: 1.APR.2020 15:18:31

99% OBW




Date: 1.APR.2020 15:29:30

Lowest channel




Date: 1.APR.2020 15:19:18

Lowest channel




Date: 1.APR.2020 15:29:51

Middle channel



Date: 1.APR.2020 15:20:07

Middle channel



Date: 1.APR.2020 15:30:12

Highest channel


Date: 1.APR.2020 15:20:07

Highest channel

Date: 1.APR.2020 15:30:12


802.11n(HT20)

6dB EBW




Date: 1.APR.2020 15:20:59

99% OBW




Date: 1.APR.2020 15:31:27

Lowest channel




Date: 1.APR.2020 15:21:44

Lowest channel




Date: 1.APR.2020 15:31:10

Middle channel



Date: 1.APR.2020 15:22:21

Middle channel




Date: 1.APR.2020 15:30:46

Highest channel

Highest channel


802.11n(HT40)

6dB EBW




Date: 1.APR.2020 15:23:14

99% OBW




Date: 1.APR.2020 15:26:08

Lowest channel




Date: 1.APR.2020 15:24:00

Lowest channel




Date: 1.APR.2020 15:25:49

Middle channel



Date: 1.APR.2020 15:25:00

Middle channel




Date: 1.APR.2020 15:25:29

Highest channel


Highest channel

TX 1:




802.11g

6dB EBW




Date: 1.APR.2020 16:14:31

99% OBW




Date: 1.APR.2020 16:24:18

Lowest channel




Date: 1.APR.2020 16:13:39

Lowest channel




Date: 1.APR.2020 16:23:58

Middle channel



Date: 1.APR.2020 16:12:52

Middle channel




Date: 1.APR.2020 16:23:38

Highest channel

Highest channel


802.11n(HT20)

6dB EBW




Date: 1.APR.2020 16:15:24

99% OBW




Date: 1.APR.2020 16:22:23

Lowest channel




Date: 1.APR.2020 16:16:17

Lowest channel




Date: 1.APR.2020 16:22:45

Middle channel



Date: 1.APR.2020 16:17:04

Middle channel




Date: 1.APR.2020 16:23:11

Highest channel

Highest channel


802.11n(HT40)

6dB EBW




Date: 1.APR.2020 16:18:28

99% OBW




Date: 1.APR.2020 16:21:41

Lowest channel




Date: 1.APR.2020 16:19:20

Lowest channel




Date: 1.APR.2020 16:21:21

Middle channel



Date: 1.APR.2020 16:20:20

Middle channel



Date: 1.APR.2020 16:20:58


Highest channel

Date: 1.APR.2020 16:20:20

Highest channel

Date: 1.APR.2020 16:20:58

6.5 Power Spectral Density

Test Requirement:	FCC Part 15 C Section 15.247 (e)
Limit:	8dBm/3kHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:


Mode	Test CH	Ant. Port	Conducted P.S.D(dBm/3KHz)	Total P.S.D (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b (SISO)	Lowest	TX0	-10.27	/	8.0	Pass
		TX1	-9.18			
	Middle	TX0	-9.43			
		TX1	-9.45			
	Highest	TX0	-9.43			
		TX1	-9.50			
802.11g (SISO)	Lowest	TX0	-10.73	/	8.0	Pass
		TX1	-9.93			
	Middle	TX0	-8.68			
		TX1	-8.66			
	Highest	TX0	-10.61			
		TX1	-10.18			
802.11n(HT20) (MIMO)	Lowest	TX0	-10.16	-6.84	Ceramic Antenna:8.0 Flex Antenna:7.8 Whip Antenna:7.0	Pass
		TX1	-9.57			
	Middle	TX0	-11.30	-7.83		
		TX1	-10.42			
	Highest	TX0	-10.63	-7.50		
		TX1	-10.40			
802.11n(HT40) (MIMO)	Lowest	TX0	-14.46	-10.59	Ceramic Antenna:8.0 Flex Antenna:7.8 Whip Antenna:7.0	Pass
		TX1	-12.88			
	Middle	TX0	-13.70	-11.29		
		TX1	-14.99			
	Highest	TX0	-13.99	-10.86		Pass
		TX1	-13.76			

Remark:


- Because transmit signals are correlated, Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi.
- So Ceramic Antenna: The Directional gain= $2.09 + 10 \log(2)=5.09$ dBi, The directional Gain of antenna is not exceed 6 dBi, so the limit of P.S.D is 8 dBm/3KHz (for 802.11n).
Flex Antenna: The Directional gain= $3.2 + 10 \log(2)=6.2$ dBi, The directional Gain of antenna is greater than 6 dBi, so the limit of P.S.D is 7.8 dBm/3KHz (for 802.11n).
Whip Antenna: The Directional gain= $4 + 10 \log(2)=7.0$ dBi, The directional Gain of antenna is greater than 6 dBi, so the limit of P.S.D is 7dBm/3KHz (for 802.11n).

Test plot as follows:

TX 0:




Test mode: 802.11n(HT20)




Date: 1.APR.2020 15:36:34

Test mode: 802.11n(HT40)




Date: 1.APR.2020 15:41:40

Lowest channel




Date: 1.APR.2020 15:37:04

Lowest channel




Date: 1.APR.2020 15:41:05

Middle channel



Date: 1.APR.2020 15:37:25

Middle channel




Date: 1.APR.2020 15:40:10

Highest channel

Highest channel


TX 1:

Test mode: 802.11b




Date: 1.APR.2020 16:26:46

Test mode: 802.11g




Date: 1.APR.2020 15:50:59

Lowest channel




Date: 1.APR.2020 16:27:06

Lowest channel




Date: 1.APR.2020 15:51:30

Middle channel



Date: 1.APR.2020 16:26:21

Middle channel




Date: 1.APR.2020 15:51:57

Highest channel


Highest channel

Test mode: 802.11n(HT20)




Date: 1.APR.2020 15:45:22

Lowest channel



Date: 1.APR.2020 15:46:58


Middle channel



Date: 1.APR.2020 15:47:37


Highest channel

Test mode: 802.11n(HT40)




Date: 1.APR.2020 15:42:37

Lowest channel



Date: 1.APR.2020 15:43:13

Middle channel




Date: 1.APR.2020 15:44:07

Highest channel


6.6 Band Edge

6.6.1 Conducted Emission Method


Test Requirement:	FCC Part 15 C Section 15.247 (d)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs and sits on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Test plot as follows:

TX 0:




802.11n(HT20)



Date: 1.APR.2020 13:54:41


Lowest channel



Date: 1.APR.2020 13:56:03


Highest channel

802.11n(HT40)



Date: 1.APR.2020 10:36:03

Lowest channel




Date: 1.APR.2020 10:38:54

Highest channel


TX 1:

802.11b



Date: 1.APR.2020 11:23:32


Lowest channel



Date: 1.APR.2020 11:35:59


Highest channel

802.11g



Date: 1.APR.2020 10:30:50


Lowest channel



Date: 1.APR.2020 10:44:08


Highest channel

802.11n(HT20)



Date: 1.APR.2020 10:23:45


Lowest channel



Date: 1.APR.2020 10:42:51


Highest channel

802.11n(HT40)



Date: 1.APR.2020 10:35:16

Lowest channel



Date: 1.APR.2020 10:40:03

Highest channel


6.6.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205				
Test Frequency Range:	2310 MHz to 2390 MHz and 2483.5 MHz to 2500 MHz				
Test Distance:	3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
RMS		1MHz	3MHz	Average Value	
Limit:	Frequency	Limit (dBuV/m @3m)		Remark	
	Above 1GHz	54.00		Average Value	
		74.00		Peak Value	
Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 				
Test setup:					
Test Instruments:	Refer to section 5.9 for details				
Test mode:	Refer to section 5.3 for details				
Test results:	Passed				

Ceramic Antenna:

802.11b mode TX0:

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Freq	ReadAntenna	Cable Preamp	Level	Limit	Over	Remark	
	MHz	Level	Factor	Loss	Factor	Line	Limit	
		dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	
1	2390.000	21.03	27.07	4.69	0.00	52.79	74.00	-21.21 Peak
2	2390.000	11.40	27.07	4.69	0.00	43.16	54.00	-10.84 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Line	Limit	Remark	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	21.69	27.08	4.69	0.00	53.46	74.00	-20.54 Peak
2	2390.000	12.25	27.08	4.69	0.00	44.02	54.00	-9.98 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Read	Antenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	23.85	27.36	4.81	0.00	56.02	74.00 -17.98 Peak
2	2483.500	12.07	27.36	4.81	0.00	44.24	54.00 -9.76 Average
3	2484.153	26.40	27.36	4.81	0.00	58.57	74.00 -15.43 Peak
4	2484.153	12.82	27.36	4.81	0.00	44.99	54.00 -9.01 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	23.19	27.35	4.81	0.00	55.35	74.00	-18.65	Peak
2	2483.500	15.19	27.35	4.81	0.00	47.35	54.00	-6.65	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11b mode TX1:

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Read Freq	Antenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	21.93	27.07	4.69	0.00	53.69	74.00	-20.31	Peak
2	2390.000	11.05	27.07	4.69	0.00	42.81	54.00	-11.19	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Read	Antenna	Cable	Preamp	Level	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	18.48	27.08	4.69	0.00	50.25	74.00	-23.75 Peak
2	2390.000	10.76	27.08	4.69	0.00	42.53	54.00	-11.47 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	ReadAntenna	Cable	Preamp	Limit	Over				
Freq	Level	Loss	Factor	Line	Limit	Remark			
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2483.500	22.65	27.36	4.81	0.00	54.82	74.00	-19.18	Peak
2	2483.500	14.29	27.36	4.81	0.00	46.46	54.00	-7.54	Average
3	2487.623	25.48	27.36	4.81	0.00	57.65	74.00	-16.35	Peak
4	2487.623	14.61	27.36	4.81	0.00	46.78	54.00	-7.22	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	26.07	27.35	4.81	0.00	58.23	74.00	-15.77	Peak
2	2483.500	16.45	27.35	4.81	0.00	48.61	54.00	-5.39	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11g mode TX0:

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Read	Antenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	20.23	27.07	4.69	0.00	51.99	74.00 -22.01 Peak
2	2390.000	11.29	27.07	4.69	0.00	43.05	54.00 -10.95 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamp Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	28.09	27.08	4.69	0.00	59.86	74.00	-14.14	Peak
2	2390.000	12.72	27.08	4.69	0.00	44.49	54.00	-9.51	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	23.41	27.36	4.81	0.00	55.58	74.00	-18.42	Peak
2	2483.500	15.17	27.36	4.81	0.00	47.34	54.00	-6.66	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preampifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Read Freq	Antenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	29.63	27.35	4.81	0.00	61.79	74.00	-12.21	Peak
2	2483.500	18.07	27.35	4.81	0.00	50.23	54.00	-3.77	Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11g mode TX1:

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Read	Antenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Factor	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	21.85	27.07	4.69	0.00	53.61	74.00 -20.39 Peak
2	2390.000	12.73	27.07	4.69	0.00	44.49	54.00 -9.51 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamp Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	Read	Antenna	Cable	Preamp	Level	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
-----	-----	-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	24.43	27.08	4.69	0.00	56.20	74.00	-17.80 Peak
2	2390.000	13.31	27.08	4.69	0.00	45.08	54.00	-8.92 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	31.95	27.36	4.81	0.00	64.12	74.00	-9.88	Peak
2	2483.500	18.13	27.36	4.81	0.00	50.30	54.00	-3.70	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamp Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	ReadAntenna	Cable Preamp	Limit	Over					
Freq	Level	Factor	Loss	Factor	Level				
MHz	dBuV	dB/m	dB	dB	dBuV/m				
1	2483.500	36.07	27.35	4.81	0.00	68.23	74.00	-5.77	Peak
2	2483.500	20.63	27.35	4.81	0.00	52.79	54.00	-1.21	Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11n-HT20 (MIMO):

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Read	Antenna	Cable	Preamp	Limit	Over			
Freq	Level	Factor	Loss	Factor	Level	Line	Limit		
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2390.000	23.33	27.07	4.69	0.00	55.09	74.00	-18.91	Peak
2	2390.000	12.20	27.07	4.69	0.00	43.96	54.00	-10.04	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Read	Antenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	27.54	27.08	4.69	0.00	59.31	74.00 -14.69 Peak
2	2390.000	13.07	27.08	4.69	0.00	44.84	54.00 -9.16 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamp Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	Read Freq	Antenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	26.28	27.36	4.81	0.00	58.45	74.00	-15.55	Peak
2	2483.500	16.60	27.36	4.81	0.00	48.77	54.00	-5.23	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	Read Freq	Antenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	38.22	27.35	4.81	0.00	70.38	74.00	-3.62	Peak
2	2483.500	20.14	27.35	4.81	0.00	52.30	54.00	-1.70	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11n-HT40 (MIMO):

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Freq	ReadLevel	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	22.54	27.07	4.69	0.00	54.30	74.00	-19.70	Peak
2	2390.000	12.48	27.07	4.69	0.00	44.24	54.00	-9.76	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamp Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Read	Antenna	Cable	Preamp	Level	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	27.25	27.08	4.69	0.00	59.02	74.00	-14.98 Peak
2	2390.000	15.48	27.08	4.69	0.00	47.25	54.00	-6.75 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Read	Antenna	Cable	Preamp	Level	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	23.80	27.36	4.81	0.00	55.97	74.00	-18.03 Peak
2	2483.500	14.61	27.36	4.81	0.00	46.78	54.00	-7.22 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%



	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit Remark	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	32.92	27.35	4.81	0.00	65.08	74.00	-8.92 Peak
2	2483.500	19.97	27.35	4.81	0.00	52.13	54.00	-1.87 Average


Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Flex Antenna:

802.11b mode TX0:

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Read	Antenna	Cable	Preamp	Level	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	22.60	27.07	4.69	0.00	54.36	74.00	-19.64 Peak
2	2390.000	11.50	27.07	4.69	0.00	43.26	54.00	-10.74 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	20.80	27.08	4.69	0.00	52.57	74.00	-21.43	Peak
2	2390.000	11.70	27.08	4.69	0.00	43.47	54.00	-10.53	Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Komikan	Product Model:	Komikan
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%



	Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	22.87	27.36	4.81	0.00	55.04	74.00	-18.96	Peak
2	2483.500	11.82	27.36	4.81	0.00	43.99	54.00	-10.01	Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamp Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.