

Test report no. : 215162-3

Item tested : CC2520EM

Type of equipment : 2.4 GHz Transceiver

FCC ID : ZAT2520EM

Client : Texas Instruments Norway AS

www.nemko.com

FCC Part 15.247

Digital Transmission System

RSS-210, Issue 8

Low Power Licence-Exempt
Radiocommunication Devices

27 June 2013

Authorized by : 

Frode Sveinsen
Technical Verificator

CONTENTS

1	GENERAL INFORMATION	3
1.1	Testhouse Info	3
1.2	Client Information	3
1.3	Responsible Manufacturer (If other than client)	3
2	TEST INFORMATION	4
2.1	Test Item	4
2.2	Test Environment	5
2.3	Test Period	5
3	TEST REPORT SUMMARY	6
3.1	General	6
3.2	Test Summary	7
3.3	Description of modification for Modification Filing	7
3.4	Comments	7
3.5	Family List Rational	7
4	TEST RESULTS	8
4.1	Power Line Conducted Emissions	8
4.2	Minimum 6 dB Bandwidth	9
4.3	20 dB Bandwidth	13
4.4	Peak Power Output	15
4.5	Spurious Emissions (Radiated)	25
4.6	Power Spectral Density (PSD)	63
5	LIST OF TEST EQUIPMENT	67
6	BLOCK DIAGRAM	68
6.1	Power Line Conducted Emission	68
6.2	Test Site Radiated Emission	68

1 GENERAL INFORMATION

1.1 Testhouse Info

Name : Nemko AS
Address : Nemko Kjeller
Instituttveien 6, Box 96
NO-2027 Kjeller, NORWAY
Telephone : +47 64 84 57 00
Fax : +47 64 84 57 05
E-mail: comlab@nemko.com
FCC test firm : 994405
IC OATS : 2040D-1
Total Number of Pages: 68

1.2 Client Information

Name : Texas Instruments Norway AS
Address : Gaustadalléen 21,
NO-0349 Oslo, Norway
Telephone : +47 22 95 85 44
Fax : +47 22 95 85 46

Contact:

Name : Dag Grini
Telephone : +47 22 95 83 01
E-mail : d.grini@ti.com

1.3 Responsible Manufacturer (If other than client)

Same as the client.

2 TEST INFORMATION

2.1 Test Item

Name :	Texas Instruments
FCC ID :	ZAT2520EM
IC :	451H-2520EM
Model/version :	CC2520EM
Serial number :	-
Hardware identity and/or version:	-
Software identity and/or version :	-
Frequency Range :	2405 – 2480 MHz
Number of Channels :	16
Type of Modulation :	250 kbps, OQPSK (Digital)
Conducted Output Power:	1.2 mW (Peak)
User Frequency Adjustment :	None
Type of Power Supply :	3.0V _{DC} (Two AA 1.5 V _{DC} batteries)
Antenna Connector :	SMA , Antenna type: PULSE W1010
Antenna Diversity Supported :	No
Desktop Charger :	None

Description of Test Item

The CC2520EM RF-transceiver module is an evaluation module developed for the 2.4 GHz ISM band. It is based on the CC2520 system on-chip device. The physical layer of the radio complies with the IEEE 802.15.4 standard with Direct Sequence Spread Spectrum (DSSS) and offset-QPSK modulation.

Exposure Evaluation

The EUT is exempted from RF Exposure Evaluation.

2.2 Test Environment

2.2.1 Normal test condition

Temperature:	21 – 23 °C
Relative humidity:	41 – 46 %
Normal test voltage:	Nominal 3.0 V DC (2 x AA battery)

New batteries were used for all tests.

The values are the limit registered during the test period.

2.3 Test Period

Item received date:	2013-05-22
Test period :	from 2013-05-29 to 2013-06-08

3 TEST REPORT SUMMARY

3.1 General

Manufacturer: Texas Instruments

Model No.: CC2520EM

All measurements are traceable to national standards.

The tests were conducted for the purpose of demonstrating compliance with FCC CFR 47 Part 15, paragraph 15.247 and Industry Canada RSS-210 Issue 8.


Radiated tests were conducted in accordance with ANSI C63.4-2003. The radiated tests were made in a semi-anechoic chamber at measuring distances of 3m and 10m.

- | | |
|---|---|
| <input checked="" type="checkbox"/> New Submission | <input type="checkbox"/> Production Unit |
| <input type="checkbox"/> Class II Permissive Change | <input checked="" type="checkbox"/> Pre-production Unit |
| DTS Equipment Code | <input type="checkbox"/> Family Listing |

THIS TEST REPORT APPLIES ONLY TO THE ITEM(S) AND CONFIGURATIONS TESTED.
Deviations from, additions to, or exclusions from the test specifications are described in "Summary of Test Data".



TEST REPORT #: 215162-3

TESTED BY: 
G.Suhanthakumar, Test engineer

DATE: 2013-06-25

Nemko Group authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any reproduction of parts of this report requires approval in writing from Nemko Group.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damages suffered by any third party as a result of decisions made or actions based on this report.

3.2 Test Summary

Name of test	FCC Part 15 reference	RSS-210 Issue 8 reference	Result
Antenna Requirement	15.203	7.1.4 (RSS-GEN)	Pass ¹
Power Line Conducted Emission	15.107(a) 15.207(a)	7.2.2 (RSS-GEN)	N/A ²
Minimum 6 dB Bandwidth	15.247(a)(2)	A8.2	Pass
Peak Power Output	15.247(b)	A8.4	Pass
Power Spectral Density	15.247(d)	A8.2	Pass
Spurious Emissions (Antenna Conducted)	15.247(c)	A8.5	Pass
Spurious Emissions (Radiated)	15.247(c) 15.109(a) 15.209(a)	A8.5	Pass
Receiver Emissions (Radiated)	N/A	2.3	N/A

¹ SMA connector

² EUT is battery operated only

3.3 Description of modification for Modification Filing

Not applicable.

3.4 Comments

All ports were populated during spurious emission measurements.

3.5 Family List Rational

Not Applicable.

4 TEST RESULTS

4.1 Power Line Conducted Emissions

Para. No.: 15.207 (a)

The test is not applicable since the device is battery powered.

Test Performed By: -	Date of Test: -
----------------------	-----------------

Measurement procedure: ANSI C63.4-2003 using 50 μ H/50 ohms LISN.

Test Results: -

Measurement Data: -

4.2 Minimum 6 dB Bandwidth

Para. No.: 15.247 (a)(2)

Test Performed By: G.Suwanthakumar	Date of Test: 29 May 2013
------------------------------------	---------------------------

Test Results: Complies


Measurement Data:

Measured 6 dB Bandwidth (MHz)		
2405MHz	2440 MHz	2480MHz
1.84	1.81	1.84

Tested according to KDB 558074 D01 DTS Meas Guidance v02, Section 7.1.


Requirements:

For Digital Transmission Systems in the 2400-2483.5 MHz band the minimum 6 dB bandwidth shall be at least 500 KHz.




Date: 30.MAY.2013 08:35:42

6 dB Bandwidth at 2405 MHz



Date: 30.MAY.2013 08:39:15

6 dB Bandwidth at 2440 MHz



Date: 30.MAY.2013 08:31:08

6 dB Bandwidth at 2480 MHz

4.3 20 dB Bandwidth

Test Performed By: G.Suwanthakumar	Date of Test: 30 May 2013
------------------------------------	---------------------------

Measurement Data:


Measured 20 dB Bandwidth (MHz)
2440 MHz
2.92

Requirements:

No requirements. Reported for information only.



Ref 20.5 dBm *Att 10 dB *RBW 30 kHz Delta 1 [T1] 0.39 dB
 *VBW 100 kHz 2.916666667 MHz
 SWT 25 ms



Date: 30.MAY.2013 08:40:17

20 dB Bandwidth at 2440 MHz

4.4 Peak Power Output

Para. No.: 15.247 (b)

Test Performed By: G.Suwanthakumar	Date of Test: 29 & 30 May 2013
------------------------------------	--------------------------------

Test Results: Complies

Measurement Data:

RF channel	2405 MHz	2440 MHz	2480 MHz
Measured Maximum Field strength (dBµV/m) –VP	97.7	98.0	98.6
Calc. Radiated Power (dBm)	2.5	2.8	3.4
Calc. Radiated Power (mW)	1.8	1.9	2.2
Measured Conducted Power (dBm)	0.85	0.52	0.27
Measured Conducted Power (mW)	1.2	1.1	1.1
Calculated Antenna Gain (dBi)	1.3	1.7	2.3

Tested according to KDB 558074 D01 DTS Meas Guidance v02, Section 8.1.1.

EIRP is calculated according to KDB 558074 D01 DTS Meas Guidance v02, Section 10.2.2.1

The maximum field strength is obtained in XY plane and Vertical polarization.

See attached graph.

Detachable antenna?

Yes No

If detachable, is the antenna connector non-standard?

Yes No

EUT has a SMA connector. This is a development board intended for professional use only.

Requirements:


The maximum peak output power shall not exceed the following limits:

For Digital Transmission Systems in the 2400 - 2483.5 MHz band: 1 Watt

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power from the intentional radiator shall be reduced below the stated value above by the amount in dB that the directional gain of the antenna exceeds 6 dBi.



Ref 110 dB μ V/m *Att 10 dB *RBW 5 MHz Marker 1 [T1]
 VBW 10 MHz 97.71 dB μ V/m
 SWT 2.5 ms 2.404375000 GHz




Date: 29.MAY.2013 13:42:53

Radiated Field strength, VP , 2405 MHz



Ref 110 dB μ V/m *Att 10 dB *RBW 5 MHz Marker 1 [T1]
VBW 10 MHz 86.03 dB μ V/m
SWT 2.5 ms 2.404471154 GHz

1 PK
MAXH




Date: 29.MAY.2013 13:44:38

Radiated field strength, HP, 2405 MHz




Ref 110 dB μ V/m *Att 10 dB *RBW 5 MHz Marker 1 [T1]
 VBW 10 MHz 97.98 dB μ V/m
 SWT 2.5 ms 2.439807692 GHz




Date: 29.MAY.2013 14:06:40

Radiated field strength, VP, 2440 MHz




Date: 29.MAY.2013 14:05:18

Radiated field strength, HP, 2440 MHz




Date: 29.MAY.2013 14:13:46

Radiated field strength, VP, 2480 MHz



Date: 29.MAY.2013 14:15:21

Radiated field strength, HP, 2480 MHz




Date: 30.MAY.2013 08:28:51

Conducted power – 2405MHz




Ref 20.5 dBm *Att 10 dB *RBW 5 MHz Marker 1 [T1]
Offset 10.5 dB VBW 10 MHz 0.52 dBm
SWT 2.5 ms 2.439278846 GHz



Date: 30.MAY.2013 08:29:26

Conducted power – 2440MHz



Date: 30.MAY.2013 08:29:50

Conducted power – 2480MHz

4.5 Spurious Emissions (Radiated)

Para. No.: 15.247 (c)

Test Performed By: G.Suhanthakumar	Date of Test: 29 May & 8 June 2013
------------------------------------	------------------------------------

Test Results: Complies

Measurement Data:

Band-edge, @3m

Frequency	Measured Field Strength @3m, dB μ V/m	Detector	Limit dB μ V/m	Margin dB
2.39 GHz	44.2	PK	74	29.8
	36.2	AV	54	17.8
2.4835 GHz	70.8	PK	74	3.2
	52.67	AV	54	1.33

Tested according to KDB 913591.

Band-edge field strength 2.4835 GHz:

Marker Delta 100kHz RBW: 44.06 dB

Average Field Strength: 96.73– 44.06 = 52.67 dB μ V/m

100% duty cycle


See attached plots.

RF conducted power

Scan performed with 100 kHz Bandwidth from 0.01 to 25 GHz.


All emissions are more than 20dB below carrier.

See plots.



Date: 29.MAY.2013 14:27:21

Band Edge, 2390 MHz, Peak Detector




Date: 29.MAY.2013 14:27:52

Band Edge, 2390 MHz, Average Detector




Ref 110 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 10 MHz 96.73 dB μ V/m
 SWT 2.5 ms 2.479495192 GHz



Date: 8.JUN.2013 16:39:41

Field strength at 2480MHz for delta marker




Date: 29.MAY.2013 14:22:31

Delta marker, 2483.5MHz, AV detector




Ref 110 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 70.81 dB μ V/m
 SWT 2.5 ms 2.483533654 GHz




Date: 29.MAY.2013 14:20:44

Band Edge, 2483.5 MHz, Peak Detector




Date: 30.MAY.2013 08:34:23

Conducted spurious emissions 10MHz – 25GHz - 2405MHz



Date: 30.MAY.2013 08:41:24

Conducted spurious emissions 10MHz – 25GHz - 2440MHz




Date: 30.MAY.2013 08:33:28

Conducted spurious emissions 10MHz – 25GHz - 2480MHz

Radiated emissions 9kHz - 30 MHz.

Detector: Quasi-Peak

Measuring distance 10 m.



Date: 30.MAY.2013 09:12:15

Radiated Emissions, 9 kHz – 30 MHz @10m


Radiated emission 30 – 1000 MHz.

Detector: Peak

Measuring distance at 3m.

All values are below the limit even when measured with Peak Detector.

See attached plot.



Radiated Emissions, 30 – 1000 MHz, VP and HP, @3m

Radiated Emissions, 1-25 GHz

1-8.5 GHz measured at a distance of 3 m

8.5 - 25 GHz measured at 1m

Peak detector


Frequency MHz	Channel MHz	Field Strength @3m dB μ V/m	Detector	Limit dB μ V/m	Margin dB
4810	2405	49.1	Pk	74	24.9
4880	2440	49.0	Pk	74	25
4960	2480	48.7	Pk	74	25.3

Average detector

Frequency MHz	Channel MHz	Field Strength @3m dB μ V/m	Detector	Limit dB μ V/m	Margin dB
4810	2405	38.0	AV	54	16
4880	2440	41.4	AV	54	12.6
4960	2480	41.6	AV	54	12.4

Antenna factor, amplifier gain and cable loss are included in Spectrum Analyzer "Transducer factor".

See attached graphs.




Date: 29.MAY.2013 14:29:56

Radiated Emissions, 2405 MHz, 1 – 3 GHz, VP, @3m – Pre-scan with Peak detector




Ref 110 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 87.40 dB μ V/m
 SWT 5 ms 2.407051282 GHz




Date: 29.MAY.2013 14:31:48

Radiated Emissions, 2405 MHz, 1 – 3 GHz, HP, @3m – Pre-scan with Peak detector




Date: 29.MAY.2013 14:34:13

Radiated Emissions, 2440 MHz, 1 – 3 GHz, VP, @3m – Pre-scan with Peak detector



Date: 29.MAY.2013 14:33:06

Radiated Emissions, 2440 MHz, 1 – 3 GHz, HP, @3m – Pre-scan with Peak detector



Date: 29.MAY.2013 14:35:19

Radiated Emissions, 2480 MHz, 1 – 3 GHz, VP, @3m – Pre-scan with Peak detector




*RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 86.69 dBµV/m
 SWI 5 ms 2.480769231 GHz

Ref 110 dBµV/m

*Att 10 dB

1 PK
 MAXH



Date: 29.MAY.2013 14:36:31

Radiated Emissions, 2480 MHz, 1 – 3 GHz, HP, @3m – Pre-scan with Peak detector




*RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 49.09 dBμV/m
 SWI 20 ms 4.810024038 GHz

Ref 87 dBμV/m

*Att 10 dB

1 PK
MAXH




Date: 29.MAY.2013 16:17:07

2nd harmonic, 2405 MHz, VP, @3m –Peak detector



Ref 87 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 10 MHz 38.02 dB μ V/m
 SWT 20 ms 4.809903846 GHz



Date: 29.MAY.2013 16:17:47

2nd harmonic, 2405 MHz, VP, @3m –AV detector




*RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 48.99 dBμV/m
 SWT 20 ms 4.880456731 GHz

Ref 87 dBμV/m

*Att 10 dB

1 PK
MAXH



Center 4.88 GHz

1.5 MHz/


Span 15 MHz

Date: 29.MAY.2013 16:21:46

2nd harmonic, 2440 MHz, VP, @3m –Peak detector



Ref 87 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 10 MHz 41.43 dB μ V/m
 SWT 20 ms 4.880024038 GHz



Date: 29.MAY.2013 16:22:41

2nd harmonic, 2440 MHz, VP, @3m –AV detector




*RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 48.72 dBµV/m
 SWT 20 ms 4.959975962 GHz

Ref 87 dBµV/m

*Att 10 dB

1 PK
MAXH




Center 4.96 GHz 1.5 MHz/ Span 15 MHz

Date: 29.MAY.2013 16:02:48

2nd harmonic, 2480 MHz, VP, @3m –Peak detector



Ref 87 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 10 MHz 41.59 dB μ V/m
 SWT 20 ms 4.960096154 GHz



Date: 29.MAY.2013 16:04:09

2nd harmonic, 2405 MHz, VP, @3m –AV detector




*RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 50.16 dBμV/m
 SWT 35 ms 8.491185897 GHz

Ref 87 dBμV/m

*Att 10 dB

1 PK
MAXH



Date: 29.MAY.2013 16:19:16

**Radiated Emissions, 2405 MHz, 3 – 8.5 GHz, HP,
 @3m – Pre-scan with Peak detector and HP filter**




*RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 50.60 dBµV/m
 SWT 35 ms 8.217948718 GHz

Ref 87 dBµV/m

*Att 10 dB

1 PK
MAXH




Date: 29.MAY.2013 16:18:37

**Radiated Emissions ch. 2405 MHz, 3 – 8.5 GHz, VP,
 @3m – Pre-scan with Peak detector and HP filter**



Ref 77.5 dBµV *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 44.46 dBµV
 SWT 25 ms 11.433493590 GHz




Date: 29.MAY.2013 16:37:31

**Radiated Emissions ch. 2405 MHz, 8.5 – 12 GHz, VP,
 @1m – Pre-scan with Peak detector, Distance Correction factor of -9.5 dB is included in the plot**



Ref 77.5 dB μ V *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 43.94 dB μ V
 SWI 25 ms 11.764423077 GHz




Date: 29.MAY.2013 16:38:59

**Radiated Emissions ch. 2405 MHz, 8.5 – 12 GHz, HP,
 @1m – Pre-scan with Peak detector, Distance Correction factor of -9.5 dB is included in the plot**



*RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 46.28 dBμV
 SWI 35 ms 17.817307692 GHz




Date: 29.MAY.2013 16:42:09

Radiated Emissions ch. 2405 MHz, 12 – 18 GHz, VP,
@1m – Pre-scan with Peak detector, Distance Correction factor of -9.5 dB is included in the plot



*RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 45.71 dBµV
 SWI 35 ms 17.759615385 GHz




Date: 29.MAY.2013 16:41:43

**Radiated Emissions ch. 2405 MHz, 12 – 18 GHz, HP,
 @1m – Pre-scan with Peak detector, Distance Correction factor of -9.5dB is included in the plot**



Ref 77.5 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 28.72 dB μ V/m
 SWI 45 ms 23.709935897 GHz



Date: 29.MAY.2013 16:47:33

Radiated Emissions ch. 2405 MHz, 18 – 25 GHz, VP/HP, Pre-scan with Peak detector, Distance Correction factor -9.5dB is included in the plot

In receive mode detected LO leakage emissions:

Peak detector

Frequency MHz	Channel MHz	Field Strength @3m dB μ V/m	Detector	Limit dB μ V/m	Margin dB
4810	2405	40.3	Pk	74	33.7
4880	2440	41.3	Pk	74	32.7
4960	2480	40.8	Pk	74	33.2

Average detector

Frequency MHz	Channel MHz	Field Strength @3m dB μ V/m	Detector	Limit dB μ V/m	Margin dB
4810	2405	35.6	Av	54	18.4
4880	2440	36.8	Av	54	17.2
4960	2480	36.2	Av	54	17.8


The detected spurious emissions are within the restricted band (4.5 - 5.15 GHz).

The maximum is detected in vertical polarization.

See attached graphs.



Ref 77.5 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 40.25 dB μ V/m
 SWT 20 ms 4.809951923 GHz




Date: 29.MAY.2013 16:57:11

LO leakage at ch 2405MHz – VP : PK detector



Ref 77.5 dBµV/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 10 MHz 35.60 dBµV/m
 SWT 20 ms 4.810000000 GHz




Date: 29.MAY.2013 16:57:38

LO leakage at ch 2405MHz – VP : AV detector



Ref 77.5 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 41.34 dB μ V/m
 SWT 20 ms 4.879903846 GHz




Date: 29.MAY.2013 17:00:16

LO leakage at ch 2440MHz – VP : PK detector



Ref 77.5 dBµV/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 10 MHz 36.79 dBµV/m
 SWT 20 ms 4.879975962 GHz




Date: 29.MAY.2013 16:59:54

LO leakage at ch 2440MHz – VP : AV detector



Ref 77.5 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 40.78 dB μ V/m
 SWT 20 ms 4.960120192 GHz




Date: 29.MAY.2013 17:01:29

LO leakage at ch 2480MHz – VP : PK detector



Ref 77.5 dBµV/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 10 MHz 36.17 dBµV/m
 SWT 20 ms 4.959927885 GHz



Date: 29.MAY.2013 17:01:46

LO leakage at ch 2480MHz – VP : AV detector

4.6 Power Spectral Density (PSD)

Para. No.: 15.247 (e)

Test Performed By: G.Suwanthakumar	Date of Test: 30 May 2013
------------------------------------	---------------------------

Test Results: Complies

Measured and Calculated Data:

	Calculated Peak PSD dBm
Power Spectral Density @2405 MHz	-14.4
Power Spectral Density @2440 MHz	-14.8
Power Spectral Density @2480 MHz	-15.5


Tested according to KDB 558074 D01 DTS Meas Guidance v02, Section 9.1.

Requirements:

The Power Spectral Density of a Digital Transmission System shall be no greater than +8 dBm in any 3 kHz band.




Ref 20.5 dBm *Att 10 dB *RBW 3 kHz Marker 1 [T1]
 *VBW 100 kHz -14.37 dBm
 SWT 320 ms 2.405584615 GHz




Date: 30.MAY.2013 08:36:45

PSD Measurement - 2405MHz



Date: 30.MAY.2013 08:37:28

PSD Measurement – 2440MHz



Date: 30.MAY.2013 08:37:57

PSD Measurement - 2480MHz


5 LIST OF TEST EQUIPMENT

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the test laboratory.

No.	Instrument/ ancillary	Type of instrument/ ancillary	Manufacturer	Ref. no.	Cal. Date	Cal. Due
1	ESU40	EMI Receiver	Rohde & Schwarz	LR1639	2010.06	2013.06
2	3115	Antenna horn	EMCO	LR 1330	2010.08.05	2013.08.05
3	643	Antenna horn	Narda	LR 093	2009.01.26	2014.01.26
4	642	Antenna horn	Narda	LR 220	2009.01.26	2014.01.26
5	PM7320X	Antenna horn	Siverts lab	LR 103	2009.01.26	2014.01.26
6	DBF-520-20	Antenna horn	Systron Donner	LR 101	2009.01.26	2014.01.26
7	638	Antenna horn	Narda	LR 098	2010.06.17	2015.06.17
8	VULB 9163	Antenna TriLog	Schwarzbeck	LR1616	2012-08	2013-08
9	8449B	Pre-amplifier	Hewlett Packard	LR 1322	2012-09-27	2013-09-27
10	LNA6900	Pre-amplifier	Teseq	LR 1593	2012-11	2013-11
11	80S	Signal Generator	Powertron	LT 502	Cal b4 use	
12	Model 87 V	Multimeter	Fluke	LR 1598	2012-12-14	2014-12-14
13	6810.17A	10 attenuator	Suhner	LR 1143	2012.09.15	2014.09.15
14	FA210A1010003 030	Microwave cable	Rosenberger	LR1566	Cal b4 use	
15	6HC 3000-18000	HP Filter	Trithlic	LR1614	Cal b4 use	
16	6HC 2500-18000	HP Filter	Trithlic	LR1615	Cal b4 use	
17	FSW	Spectrum Analyzer	Rohde & Schwarz	LR1640	2012.06	2014.06

6 BLOCK DIAGRAM

6.1 Power Line Conducted Emission



6.2 Test Site Radiated Emission

