



Test report no. : 215160-3

Item tested : CC2530EM

Type of equipment : 2.4 GHz Transceiver

FCC ID : ZAT2530EM

Client : Texas Instruments Norway AS

FCC Part 15.247

Digital Transmission System

RSS-210, Issue 8

Low Power Licence-Exempt
Radiocommunication Devices

25 July 2013

Authorized by :


Frode Sveinsen
Technical Vericator

CONTENTS

1	GENERAL INFORMATION	3
1.1	Testhouse Info	3
1.2	Client Information.....	3
1.3	Responsible Manufacturer (If other than client)	3
2	TEST INFORMATION.....	4
2.1	Test Item	4
2.2	Test Environment.....	5
2.3	Test Period.....	5
3	TEST REPORT SUMMARY	6
3.1	General	6
3.2	Test Summary.....	7
3.3	Description of modification for Modification Filing.....	7
3.4	Comments	7
3.5	Family List Rational	7
4	TEST RESULTS	8
4.1	Power Line Conducted Emissions	8
4.2	Minimum 6 dB Bandwidth	9
4.3	20 dB Bandwidth.....	13
4.4	Peak Power Output.....	15
4.5	Spurious Emissions (Radiated)	25
4.6	Power Spectral Density (PSD).....	64
5	LIST OF TEST EQUIPMENT.....	68
6	BLOCK DIAGRAM	69
6.1	Power Line Conducted Emission	69
6.2	Test Site Radiated Emission.....	69

1 GENERAL INFORMATION

1.1 Testhouse Info

Name : Nemko AS
Address : Nemko Kjeller
Instituttveien 6, Box 96
NO-2027 Kjeller, NORWAY
Telephone : +47 64 84 57 00
Fax : +47 64 84 57 05
E-mail: comlab@nemko.com
FCC test firm : 994405
IC OATS : 2040D-1
Total Number of Pages: 69

1.2 Client Information

Name : Texas Instruments Norway AS
Address : Gaustadalléen 21,
NO-0349 Oslo, Norway
Telephone : +47 22 95 85 44
Fax : +47 22 95 85 46

Contact:

Name : Dag Grini
Telephone : +47 22 95 83 01
E-mail : d.grini@ti.com

1.3 Responsible Manufacturer (If other than client)

Same as the client.

2 TEST INFORMATION

2.1 Test Item

Name :	Texas Instruments
FCC ID :	ZAT2530EM
IC :	451H-2530EM
Model/version :	CC2530EM
Serial number :	-
Hardware identity and/or version:	-
Software identity and/or version :	-
Frequency Range :	2405 – 2480 MHz
Number of Channels :	16
Type of Modulation :	250 kbps, OQPSK (Digital)
Conducted Output Power:	2.3 mW (Peak)
User Frequency Adjustment :	None
Type of Power Supply :	3.0V _{DC} (Two AA 1.5 V _{DC} batteries)
Antenna Connector :	SMA , Antenna type: PULSE W1010
Antenna Diversity Supported :	No
Desktop Charger :	None

Description of Test Item

The CC2530EM RF-transceiver module is an evaluation module developed for the 2.4 GHz ISM band. It is based on the CC2530 system on-chip device. The physical layer of the radio complies with the IEEE 802.15.4 standard with Direct Sequence Spread Spectrum (DSSS) and offset-QPSK modulation.

Exposure Evaluation

The EUT is exempted from RF Exposure Evaluation.

2.2 Test Environment

2.2.1 Normal test condition

Temperature:	21 – 23 °C
Relative humidity:	41 – 46 %
Normal test voltage:	Nominal 3.0 V DC (2 x AA battery)

New batteries were used for all tests.

The values are the limit registered during the test period.

2.3 Test Period

Item received date:	2013-04-05
Test period :	from 2013-04-18 to 2013-04-24

3 TEST REPORT SUMMARY

3.1 General

Manufacturer: Texas Instruments

Model No.: CC2530EM

All measurements are traceable to national standards.

The tests were conducted for the purpose of demonstrating compliance with FCC CFR 47 Part 15, paragraph 15.247 and Industry Canada RSS-210 Issue 8.


Radiated tests were conducted in accordance with ANSI C63.4-2003. The radiated tests were made in a semi-anechoic chamber at measuring distances of 3m and 10m.

- | | |
|---|---|
| <input checked="" type="checkbox"/> New Submission | <input type="checkbox"/> Production Unit |
| <input type="checkbox"/> Class II Permissive Change | <input checked="" type="checkbox"/> Pre-production Unit |
| DTS Equipment Code | <input type="checkbox"/> Family Listing |

THIS TEST REPORT APPLIES ONLY TO THE ITEM(S) AND CONFIGURATIONS TESTED.
Deviations from, additions to, or exclusions from the test specifications are described in "Summary of Test Data".



TEST REPORT #: 215160-3

TESTED BY:  DATE: 2013-05-30
G.Suhanthakumar, Test engineer

Nemko Group authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any reproduction of parts of this report requires approval in writing from Nemko Group.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damages suffered by any third party as a result of decisions made or actions based on this report.

3.2 Test Summary

Name of test	FCC Part 15 reference	RSS-210 Issue 8 reference	Result
Antenna Requirement	15.203	7.1.4 (RSS-GEN)	Pass ¹
Power Line Conducted Emission	15.107(a) 15.207(a)	7.2.2 (RSS-GEN)	N/A ²
Minimum 6 dB Bandwidth	15.247(a)(2)	A8.2	Pass
Peak Power Output	15.247(b)	A8.4	Pass
Power Spectral Density	15.247(d)	A8.2	Pass
Spurious Emissions (Antenna Conducted)	15.247(c)	A8.5	Pass
Spurious Emissions (Radiated)	15.247(c) 15.109(a) 15.209(a)	A8.5	Pass
Receiver Emissions (Radiated)	N/A	2.3	N/A

¹ SMA connector

² EUT is battery operated only

3.3 Description of modification for Modification Filing

Not applicable.

3.4 Comments

All ports were populated during spurious emission measurements.

3.5 Family List Rational

Not Applicable.

4 TEST RESULTS

4.1 Power Line Conducted Emissions

Para. No.: 15.207 (a)

The test is not applicable since the device is battery powered.

Test Performed By: -	Date of Test: -
----------------------	-----------------

Measurement procedure: ANSI C63.4-2003 using 50 μ H/50 ohms LISN.

Test Results: -

Measurement Data: -

4.2 Minimum 6 dB Bandwidth

Para. No.: 15.247 (a)(2)

Test Performed By: G.Suwanthakumar	Date of Test: 18 April 2013
------------------------------------	-----------------------------

Test Results: **Complies**


Measurement Data:

Measured 6 dB Bandwidth (MHz)		
2405MHz	2440 MHz	2480MHz
1.8	1.8	1.8

Tested according to KDB 558074 D01 DTS Meas Guidance v02, Section 7.1.


Requirements:

For Digital Transmission Systems in the 2400-2483.5 MHz band the minimum 6 dB bandwidth shall be at least 500 KHz.




Date: 18.APR.2013 12:58:50

6 dB Bandwidth at 2405 MHz



Date: 18.APR.2013 12:59:23

6 dB Bandwidth at 2440 MHz



Date: 18.APR.2013 12:57:52

6 dB Bandwidth at 2480 MHz

4.3 20 dB Bandwidth


Test Performed By: G.Suwanthakumar	Date of Test: 18 April 2013
------------------------------------	-----------------------------

Measurement Data:

Measured 20 dB Bandwidth (MHz)
2440 MHz
2.70

Requirements:

No requirements. Reported for information only.



Date: 18.APR.2013 13:00:11

20 dB Bandwidth at 2440 MHz

4.4 Peak Power Output

Para. No.: 15.247 (b)

Test Performed By: G.Suhanthakumar	Date of Test: 18 April 2013
------------------------------------	-----------------------------

Test Results: Complies

Measurement Data:

RF channel	2405 MHz	2440 MHz	2480 MHz
Measured Maxium Field strength (dB μ V/m) –VP	101.3	100.9	93.9
Calc. Radiated Power (dBm)	6.1	5.7	-1.3
Calc. Radiated Power (mW)	4.1	3.7	0.7
Measured Conducted Power (dBm)	3.7	3.5	-3.5
Measured Conducted Power (mW)	2.3	2.2	0.4
Calculated Antenna Gain (dBi)	2.4	2.2	2.2

Tested according to KDB 558074 D01 DTS Meas Guidance v02, Section 8.1.1.

EIRP is calculated according to KDB 558074 D01 DTS Meas Guidance v02, Section 10.2.2.1

The maximum field strength is obtained in XY plane and Vertical polarization.

See attached graph.

Detachable antenna?

Yes No

If detachable, is the antenna connector non-standard?

Yes No


EUT has a SMA connector. This is a development board intended for professional use only.

Requirements:

The maximum peak output power shall not exceed the following limits:


For Digital Transmission Systems in the 2400 - 2483.5 MHz band: 1 Watt

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power from the intentional radiator shall be reduced below the stated value above by the amount in dB that the directional gain of the antenna exceeds 6 dBi.




Date: 18.APR.2013 11:25:57

Radiated Field strength, VP , 2405 MHz



Date: 18.APR.2013 11:24:54

Radiated field strength, HP, 2405 MHz




Date: 18.APR.2013 11:08:46

Radiated field strength, VP, 2440 MHz



Ref 110 dB μ V/m *Att 20 dB *RBW 3 MHz Marker 1 [T1]
 VBW 10 MHz 90.03 dB μ V/m
 SWT 2.5 ms 2.439663462 GHz




Date: 18.APR.2013 11:07:53

Radiated field strength, HP, 2440 MHz




Ref 110 dB μ V/m *Att 20 dB *RBW 3 MHz Marker 1 [T1]
 VBW 10 MHz 93.87 dB μ V/m
 SWT 2.5 ms 2.479615385 GHz




Date: 18.APR.2013 11:16:35

Radiated field strength, VP, 2480 MHz




Date: 18.APR.2013 12:55:34

Conducted power – 2405MHz



Date: 18.APR.2013 12:56:20

Conducted power – 2440MHz



Date: 18.APR.2013 12:56:40

Conducted power – 2480MHz

4.5 Spurious Emissions (Radiated)

Para. No.: 15.247 (c)

Test Performed By: G.Suhanthakumar	Date of Test: 1 & 18 Jan 2013
------------------------------------	-------------------------------

Test Results: Complies

Measurement Data:

Band-edge, @3m

Frequency	Measured Field Strength @3m, dB μ V/m	Detector	Limit dB μ V/m	Margin dB
2.39 GHz	45.4	PK	74	28.6
	38.4	AV	54	15.6
2.4835 GHz	64.3	PK	74	9.7
	46.6	AV	54	7.4

Tested according to KDB 913591.

Band-edge field strength 2.4835 GHz:

Marker Delta 100kHz RBW: 48.00 dB

Average Field Strength: $94.62 - 48.00 = 46.6$ dB μ V/m

100% duty cycle

See attached plots.

RF conducted power


Scan performed radiated with 100 kHz Bandwidth from 0.01 to 25 GHz.

All emissions are more than 20dB below carrier.

See plots.



Ref 117 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 45.40 dB μ V/m
 SWT 2.5 ms 2.390064103 GHz




Date: 18.APR.2013 08:29:02

Band Edge, 2390 MHz, Peak Detector



Ref 117 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 10 MHz 38.37 dB μ V/m
 SWT 2.5 ms 2.390064103 GHz




Date: 18.APR.2013 08:29:34

Band Edge, 2390 MHz, Average Detector



Ref 117 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 94.62 dB μ V/m
 SWT 2.5 ms 2.479519231 GHz




Date: 18.APR.2013 08:19:40

Field strength at 2480MHz for delta marker



Ref 117 dBµV/m *Att 10 dB *RBW 100 kHz Delta 1 [T1]
 VBW 1 MHz 48.00 dB
 SWT 10 ms -3.759615385 MHz



Date: 18.APR.2013 08:23:33


Delta marker, 2483.5MHz, AV detector



* RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 64.25 dBμV/m
 SWT 2.5 ms 2.483533654 GHz


Ref 117 dBμV/m * Att 10 dB

1 PK
 MAXH



Date: 18.APR.2013 08:21:09


Band Edge, 2483.5 MHz, Peak Detector



Date: 19.APR.2013 13:18:10

Conducted spurious emission 10MHz – 25GHz - ch2440MHz

DELTA MARKER 1		*RBW 100 kHz	Delta 1 [T1]
-2.282740385 GHz		VBW 300 kHz	-47.02 dB
Ref 10 dBm	* Att 10 dB	SWT 2.5 s	-2.282740385 GHz




Date: 19.APR.2013 13:18:39

Conducted spurious emission 10MHz – 25GHz - ch2480MHz

Radiated emissions 9kHz - 30 MHz.

Detector: Quasi-Peak

Measuring distance 10 m.



Date: 18.APR.2013 12:52:06

Radiated Emissions, 9 kHz – 30 MHz @10m


Radiated emission 30 – 1000 MHz.

Detector: Peak

Measuring distance at 3m.

All values are below the limit even when measured with Peak Detector.

See attached plot.



Radiated Emissions, 30 – 1000 MHz, VP and HP, @3m

Radiated Emissions, 1-25 GHz

1-8.5 GHz measured at a distance of 3 m

8.5 - 25 GHz measured at 1m

Peak detector


Frequency MHz	Channel MHz	Field Strength @3m dBµV/m	Detector	Limit dBµV/m	Margin dB
4810	2405	47.2	Pk	74	26.8
4880	2440	50.4	Pk	74	23.6
4960	2480	48.9	Pk	74	25.1

Average detector

Frequency MHz	Channel MHz	Field Strength @3m dBµV/m	Detector	Limit dBµV/m	Margin dB
4810	2405	38.8	AV	54	15.2
4880	2440	44.2	AV	54	9.8
4960	2480	41.5	AV	54	12.5

Antenna factor, amplifier gain and cable loss are included in Spectrum Analyzer "Transducer factor".

See attached graphs.



Date: 18.APR.2013 08:44:40

Radiated Emissions ch. 2405 MHz, 1 – 3 GHz, VP, @3m – Pre-scan with Peak detector




* RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 100.92 dBμV/m
 SWT 5 ms 2.407051282 GHz

Ref 117 dBμV/m

* Att 10 dB

1 PK
 MAXH




Date: 18.APR.2013 08:45:25

Radiated Emissions ch. 2405 MHz, 1 – 3 GHz, HP, @3m – Pre-scan with Peak detector



Ref 117 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 100.00 dB μ V/m
 SWT 5 ms 2.439102564 GHz



Date: 18.APR.2013 08:48:22

Radiated Emissions ch. 2440 MHz, 1 – 3 GHz, VP, @3m – Pre-scan with Peak detector




* RBW 1 MHz Marker 1 [T1]
VBW 3 MHz 100.04 dBμV/m
SWT 5 ms 2.439102564 GHz

Ref 117 dBμV/m

* Att 10 dB

1 PK
MAXH




Date: 18.APR.2013 08:48:01

Radiated Emissions ch. 2440 MHz, 1 – 3 GHz, HP, @3m – Pre-scan with Peak detector



Ref 117 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 94.66 dB μ V/m
 SWT 5 ms 2.480769231 GHz




Date: 18.APR.2013 08:49:45

Radiated Emissions ch. 2480 MHz, 1 – 3 GHz, VP, @3m – Pre-scan with Peak detector



Ref 117 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 94.65 dB μ V/m
 SWT 5 ms 2.480769231 GHz




Date: 18.APR.2013 08:50:03

Radiated Emissions ch. 2480 MHz, 1 – 3 GHz, HP, @3m – Pre-scan with Peak detector



Ref 72 dB μ V/m * Att 10 dB * RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 46.56 dB μ V/m
 SWT 35 ms 4.260416667 GHz




Date: 1.FEB.2013 16:04:51

Radiated Emissions ch. 2405 MHz, 3 – 8.5 GHz, VP, @3m – Pre-scan with Peak detector



* RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 47.21 dBµV/m
 Ref 82 dBµV/m * Att 10 dB SWT 20 ms 4.810160256 GHz




Date: 18.APR.2013 09:25:26

2nd harmonic , ch. 2405 MHz, VP, @3m –Peak detector



* RBW 1 MHz Marker 1 [T1]
 VBW 10 MHz 38.76 dBμV/m
 SWT 20 ms 4.810000000 GHz
 Ref 82 dBμV/m * Att 10 dB




Date: 18.APR.2013 09:25:56

2nd harmonic , ch. 2405 MHz, VP, @3m –AV detector



Ref 82 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 50.41 dB μ V/m
 SWT 20 ms 4.880096154 GHz




Date: 18.APR.2013 10:25:42

2nd harmonic , ch. 2440 MHz, VP, @3m –Peak detector



Ref 82 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 10 MHz 44.19 dB μ V/m
 SWT 20 ms 4.880120192 GHz




Date: 18.APR.2013 10:26:14

2nd harmonic , ch. 2440 MHz, VP, @3m –AV detector



Ref 82 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 48.94 dB μ V/m
 SWT 20 ms 4.879855769 GHz




Date: 18.APR.2013 09:59:56

2nd harmonic , ch. 2480 MHz, VP, @3m –Peak detector



Ref 82 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 10 MHz 41.48 dB μ V/m
 SWT 20 ms 4.879879808 GHz




Date: 18.APR.2013 10:00:28

2nd harmonic , ch. 2405 MHz, VP, @3m –AV detector



* RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 50.77 dB μ V/m
 Ref 82 dB μ V/m * Att 10 dB SWT 35 ms 8.376602564 GHz




Date: 18.APR.2013 09:26:30

Radiated Emissions ch. 2405 MHz, 3 – 8.5 GHz, HP, @3m – Pre-scan with Peak detector and HP filter



Ref 82 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 50.47 dB μ V/m
 SWT 35 ms 8.394230769 GHz




Date: 18.APR.2013 09:28:51

Radiated Emissions ch. 2405 MHz, 3 – 8.5 GHz, VP, @3m – Pre-scan with Peak detector and HP filter




Ref 72.5 dBµV *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 45.47 dBµV
 SWT 35 ms 17.932692308 GHz



Date: 18.APR.2013 10:51:37

Radiated Emissions ch. 2405 MHz, 8.5 – 12 GHz, VP, @1m – Pre-scan with Peak detector , Distance Correction factor of -9.5 dB is included in the graph




Date: 18.APR.2013 10:51:56

Radiated Emissions ch. 2405 MHz, 8.5 – 12 GHz, HP, @1m – Pre-scan with Peak detector , Distance Correction factor of -9.5 dB is included in the graph.



Ref 72.5 dBµV *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 46.19 dBµV
 SWT 35 ms 17.932692308 GHz




Date: 24.APR.2013 07:51:21

Radiated Emissions ch. 2405 MHz, 12 – 18 GHz, VP, @1m – Pre-scan with Peak detector, Distance Correction factor of -9.5 dB is included in the graph.



Ref 72.5 dBµV *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 46.60 dBµV
 SWT 35 ms 17.759615385 GHz




Date: 24.APR.2013 07:52:18

Radiated Emissions ch. 2405 MHz, 12 – 18 GHz, HP, @1m – Pre-scan with Peak detector, Distance Correction factor of -9.5dB is included in the graph.



Ref 72.5 dBµV/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 29.62 dBµV/m
 SWT 45 ms 24.315705128 GHz



Date: 18.APR.2013 10:57:30

Radiated Emissions ch. 2405 MHz, 18 – 25 GHz, VP/HP, Pre-scan with Peak detector, Distance Correction factor -9.5dB is not included in the graph.

In receive mode detected LO leakage emissions:

Peak detector

Frequency MHz	Channel MHz	Field Strength @3m dB μ V/m	Detector	Limit dB μ V/m	Margin dB
4810	2405	47.9	Pk	74	26.1
4880	2440	48.7	Pk	74	25.3
4960	2480	48.2	Pk	74	25.8


Average detector

Frequency MHz	Channel MHz	Field Strength @3m dB μ V/m	Detector	Limit dB μ V/m	Margin dB
4810	2405	41.4	Av	54	12.6
4880	2440	41.8	Av	54	12.2
4960	2480	40.3	Av	54	13.7

The detected spurious emissions are within the restricted band (4.5 - 5.15 GHz).

The maximum is detected in vertical polarization.

See attached graphs.




Date: 18.APR.2013 12:22:39

LO leakage at ch 2405MHz – VP : PK detector



Ref 82 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 10 MHz 41.35 dB μ V/m
 SWT 20 ms 4.810040064 GHz




Date: 18.APR.2013 12:23:09

LO leakage at ch 2405MHz – VP : AV detector



Ref 82 dB μ V/m * Att 10 dB * RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 48.68 dB μ V/m
 SWT 20 ms 4.880088141 GHz




Date: 18.APR.2013 12:29:00

LO leakage at ch 2440MHz – VP : PK detector



Ref 82 dB μ V/m *Att 10 dB *RBW 1 MHz Marker 1 [T1]
 VBW 10 MHz 41.77 dB μ V/m
 SWT 20 ms 4.880016026 GHz




Date: 18.APR.2013 12:29:22

LO leakage at ch 2440MHz – VP : AV detector




Ref 82 dB μ V/m * Att 10 dB * RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz 48.20 dB μ V/m
 SWT 20 ms 4.960048578 GHz



Date: 18.APR.2013 12:30:41

LO leakage at ch 2480MHz – VP : PK detector



Date: 18.APR.2013 12:31:08

LO leakage at ch 2480MHz – VP : AV detector

4.6 Power Spectral Density (PSD)

Para. No.: 15.247 (e)

Test Performed By: G.Suwanthakumar	Date of Test: 18 April 2013
------------------------------------	-----------------------------

Test Results: Complies


Measured and Calculated Data:

	calculated peak PSD dBm
Power Spectral Density @2405 MHz	-11.6
Power Spectral Density @2440 MHz	-12.5
Power Spectral Density @2480 MHz	-19.4

Tested according to KDB 558074 D01 DTS Meas Guidance v02, Section 9.1.


Requirements:

The Power Spectral Density of a Digital Transmission System shall be no greater than +8 dBm in any 3 kHz band.




Date: 18.APR.2013 13:02:36

PSD Measurement - 2405MHz



Date: 18.APR.2013 13:01:21

PSD Measurement – 2440MHz



Date: 18.APR.2013 13:01:58

PSD Measurement - 2480MHz


5 LIST OF TEST EQUIPMENT

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the test laboratory.

No.	Instrument/ ancillary	Type of instrument/ ancillary	Manufacturer	Ref. no.	Cal. Date	Cal. Due
1	ESU40	EMI Receiver	Rohde & Schwarz	LR1639	2010.06	2013.06
2	3115	Antenna horn	EMCO	LR 1330	2010.08.05	2013.08.05
3	643	Antenna horn	Narda	LR 093	2009.01.26	2014.01.26
4	642	Antenna horn	Narda	LR 220	2009.01.26	2014.01.26
5	PM7320X	Antenna horn	Siverts lab	LR 103	2009.01.26	2014.01.26
6	DBF-520-20	Antenna horn	Systron Donner	LR 101	2009.01.26	2014.01.26
7	638	Antenna horn	Narda	LR 098	2010.06.17	2015.06.17
8	VULB 9163	Antenna TriLog	Schwarzbeck	LR1616	2012-08	2013-08
9	8449B	Pre-amplifier	Hewlett Packard	LR 1322	2012-09-27	2013-09-27
10	LNA6900	Pre-amplifier	Teseq	LR 1593	2012-11	2013-11
11	80S	Signal Generator	Powertron	LT 502	Cal b4 use	
12	Model 87 V	Multimeter	Fluke	LR 1598	2012-12-14	2014-12-14
13	6810.17A	10 attenuator	Suhner	LR 1143	2012.09.15	2014.09.15
14	FA210A1010003 030	Microwave cable	Rosenberger	LR1566	Cal b4 use	
15	6HC 3000-18000	HP Filter	Trithlic	LR1614	Cal b4 use	
16	6HC 2500-18000	HP Filter	Trithlic	LR1615	Cal b4 use	
17	FSW	Spectrum Analyzer	Rohde & Schwarz	LR1640	2012.06	2014.06

6 BLOCK DIAGRAM

6.1 Power Line Conducted Emission



6.2 Test Site Radiated Emission

