

MPE Evaluation

FCC ID : ZB9-STICK
Brand : Plugwise
Model : Stick
Description : A Digital Transmission System operating in the frequencyband
2405MHz up to 2480MHz

Smidshornerweg 18
P.O. Box 15
9822 ZG Niekerk
The Netherlands

www.tuv-eps.com

T +31 594 505005
F +31 594 504804
E info@tuv-eps.com

Subject
RF Exposure statement

Date
July 18,2011.

Our reference
11030302

Your reference
--

Page
1 of 1

Our General Terms and Conditions, as filed at the Chamber of Commerce in Groningen, are applicable to all orders given to TÜV Rheinland EPS B.V.

TÜV Rheinland EPS B.V. is registered at the Chamber of Commerce in Groningen with no. 27247331.

This device has an e.i.r.p. less than -1.59 dBm (0.69 mW, including a maximum antenna gain of +1.8 dBi), which means that the worst case prediction of power density (100% reflection) at 20 cm distance (worst case) can be calculated as follows :

$$S = \frac{EIRP}{4 * \pi * R^2} \quad (\text{power density without reflection})$$

$$S = \frac{2^2 * EIRP}{4 * \pi * R^2} \quad (\text{power density with 100% reflection})$$

$$S = \frac{2^2 * EIRP}{4 * \pi * R^2} = \frac{0.69mW}{\pi * (20cm)^2} = 0.00055 \text{ mW/cm}^2 \quad (\text{limit} = 1.0 \text{ mW/cm}^2)$$

This means that according to OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), the equipment fulfills the requirements on power density for general population/uncontrolled exposure.

Best regards,
TÜV Rheinland EPS B.V.



R .van der Meer
Test Engineer