



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle Section, Science & Technology Park,
Shenzhen, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM180600487602
Page: 1 of 10

Human Exposure Report

Application No.: SZEM1806004876CR
Applicant: SHENZHEN DNS INDUSTRIES CO., LTD.
Address of Applicant: 23/F Building A, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian, Shenzhen, China
Manufacturer: SHENZHEN DNS INDUSTRIES CO., LTD.
Address of Manufacturer: 23/F Building A, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian, Shenzhen, China
Factory: HUIZHOU D&S CABLE CO., LTD.
Address of Factory: Longjin Dongjiang Industry Zone Shuikou, Huicheng, Huizhou, Guangdong, China
Equipment Under Test (EUT):
EUT Name: Wireless Charger
Model No.: AC62LZ41, AC62LZ42, AC62LZ43, AC62LZ44, AC62LZ45, AC62LZ46, AC63LZ41, AC63LZ42, AC63LZ43, AC63LZ44, AC63LZ45, AC63LZ46 ♣
 ♣ Please refer to section 3.1 of this report which indicates which model was actually tested and which were electrically identical.
Trade mark: DNS, NOVOO, omars
FCC ID: ZBCAC62LZ4
Standards: 47 CFR PART 1, Subpart I, Section 1.1310
Date of Receipt: 2018-06-08
Date of Test: 2018-06-23 to 2018-07-05
Date of Issue: 2018-07-05

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above



Keny Xu
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



2 Contents

1	COVER PAGE	1
2	CONTENTS	2
3	GENERAL INFORMATION	3
3.1	DETAILS OF E.U.T.	3
3.2	DESCRIPTION OF SUPPORT UNITS	4
3.3	TEST LOCATION.....	5
3.4	TEST FACILITY	5
3.5	DEVIATION FROM STANDARDS	5
3.6	ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4	EQUIPMENTS USED DURING TEST	6
5	TEST RESULTS	7
5.1	RF EXPOSURE TEST	7
5.1.1	<i>E.U.T. Operation</i>	7
5.1.2	<i>Measurement Data</i>	8
6	PHOTOGRAPHS.....	10



3 General Information

3.1 Details of E.U.T.

Power supply: Input: DC 5V/2A, DC 9V/2A, DC 12V/2A
Output: DC 5V/1A, DC 9V/1.67A, DC 12V/1.25A (15W Max.)

Operation frequency: 119.7-151kHz

Modulation type: Load modulation

Antenna type: Inductive Loop Coil Antenna

Remark: Tests were conducted in all three load modes and the worst case (DC 12V/1.25A) is reported only.

Remark:

Model No.: AC62LZ41, AC62LZ42, AC62LZ43, AC62LZ44, AC62LZ45, AC62LZ46, AC63LZ41, AC63LZ42, AC63LZ43, AC63LZ44, AC63LZ45, AC63LZ46

Only the model AC62LZ44 was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for the above models, only different on model name, enclosure, capacitance type and connector, details see below:

Model No.	capacitance		Connector			Enclosure shape
	CBB	NPO	micro USB	type C	DC2.5	
AC62LZ41	Yes	No	Yes	No	No	AC62****
AC62LZ42	Yes	No	No	Yes	No	
AC62LZ43	Yes	No	No	No	Yes	
AC62LZ44	No	Yes	Yes	No	No	
AC62LZ45	No	Yes	No	Yes	No	
AC62LZ46	No	Yes	No	No	Yes	
AC63LZ41	Yes	No	Yes	No	No	AC63****
AC63LZ42	Yes	No	No	Yes	No	
AC63LZ43	Yes	No	No	No	Yes	
AC63LZ44	No	Yes	Yes	No	No	
AC63LZ45	No	Yes	No	Yes	No	
AC63LZ46	No	Yes	No	No	Yes	



3.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	Apple	A1357 W010A051	REF. No.SEA0500
Load Resistor	SGS	N/A	REF. No.SEA0600
Mobile Phone	SAMSUNG	SM-G9500	R28J9140LPB



3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,
No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.



4 Equipments Used during Test

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Due date
1	Electric Field Meter	Schaffner	EMC20	EMC068	2019-03-21



5 Test Results

5.1 RF Exposure test

Test Requirement: 47 CFR PART 1, Subpart I, Section 1.1310

Measurement Distance: 15cm

Limit:

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30
F=frequency in MHz *=Plane-wave equivalent power density RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).				

5.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C Humidity: 52% RH Atmospheric Pressure: 1015 mbar

EUT Operation:

This device has been tested the worst status of full load and the device has been tested with mobile phone at zero charge, intermediate charge, and full charge.



5.1.2 Measurement Data

Output Voltage=DC 12V; The max output power =15W

Electric Field Emissions

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result (V/m)	50% Limit (V/m)
143.4 kHz	15	Side 1	4.76	307
		Side 2	4.83	307
		Side 3	4.70	307
		Side 4	4.72	307
		Top	3.87	307

Magnetic Field Emissions

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result (A/m)	50% Limit (A/m)
143.4 kHz	15	Side 1	0.0548	0.815
		Side 2	0.0534	0.815
		Side 3	0.0558	0.815
		Side 4	0.0542	0.815
		Top	0.1246	0.815



Mobile phone has been charge at zero charge, intermediate charge, and full charge.

Electric Field Emissions

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result(V/m)			50%Limit (V/m)
			zero charge	intermediate charge	full charge	
143.4 kHz	15	Side 1	4.37	4.75	4.63	307
		Side 2	4.71	5.47	4.93	307
		Side 3	4.85	5.29	5.42	307
		Side 4	4.57	4.92	4.75	307
		Top	3.79	4.16	3.97	307

Magnetic Field Emissions

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result(A/m)			50%Limit (A/m)
			zero charge	intermediate charge	full charge	
143.4 kHz	15	Side 1	0.0846	0.0936	0.0888	0.815
		Side 2	0.0842	0.0935	0.0847	0.815
		Side 3	0.0868	0.0938	0.0937	0.815
		Side 4	0.0853	0.0952	0.0824	0.815
		Top	0.1915	0.2098	0.2047	0.815



6 Photographs

Please refer to RF Exposure setup photo.

- End of the Report -