

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a WIRELESS SPEAKER with Bluetooth function. The EUT was powered by DC 3.7V lithium battery and charged by DC 5V USB port. For more detail information pls. refer to the user manual.

Modulation Type: GFSK

Bluetooth Version: 2.1.

Antenna Type: Integral antenna.

Antenna Gain: 1.2dBi.

The nominal conducted output power specified: 3.8dBm +/-3dB.

The nominal radiated output power (e.i.r.p) specified: 5dBm (+/- 3dB)

According to the KDB 447498:

The maximum peak radiated emission for the EUT is 103.0dB μ V/m at 3m in the frequency 2480MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = 7.77dBm
which is within the production variation.

The minimum peak radiated emission for the EUT is 101.9dB μ V/m at 3m in the frequency 2441MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = 6.67dBm
which is within the production variation.

The maximum conducted output power specified is 6.8dBm = 4.8mW

The source-based time-averaging conducted output power
= 4.8 * Duty Cycle mW (where Duty Cycle \leq 1)
= 4.8 mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)
= 3.0 * 5 / sqrt(2.480) mW
= 9.5 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.