



BUREAU
VERITAS

Test Report No.: RF190418W001-2



FCC TEST REPORT

(Part 15, Subpart C)


Applicant:	Corporativo Lanix S.A. de C.V.
Address:	Carretera Internacional Hermosillo-Nogales Km 8.5, Hermosillo Sonora, Mexico

Manufacturer or Supplier:	Corporativo Lanix S.A. de C.V.
Address:	Carretera Internacional Hermosillo-Nogales Km 8.5, Hermosillo Sonora, Mexico
Product:	smartphone
Brand Name:	LANIX
Model Name:	Ilium M9s
FCC ID:	ZC4M9S
Date of tests:	Apr. 19, 2019 ~ May. 27, 2019

The tests have been carried out according to the requirements of the following standard:

- ☒ FCC Part 15, Subpart C, Section 15.247
- ☒ ANSI C63.10-2013

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Alex Chen Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
	
Date: May. 29, 2019	Date: May. 29, 2019

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS.....	5
1.1 MEASUREMENT UNCERTAINTY	5
2 GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	8
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST	9
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	9
2.3 DUTY CYCLE OF TEST SIGNAL	12
2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS	13
2.5 DESCRIPTION OF SUPPORT UNITS	13
3 TEST TYPES AND RESULTS.....	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	14
3.1.2 TEST INSTRUMENTS.....	14
3.1.3 TEST PROCEDURES	15
3.1.4 DEVIATION FROM TEST STANDARD	15
3.1.5 TEST SETUP	16
3.1.6 EUT OPERATING CONDITIONS	16
3.1.7 TEST RESULTS	17
3.2 RADIATED EMISSION MEASUREMENT	21
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	21
3.2.2 TEST INSTRUMENTS.....	22
3.2.3 TEST PROCEDURES	23
3.2.4 DEVIATION FROM TEST STANDARD	23
3.2.5 TEST SETUP	24
3.2.6 EUT OPERATING CONDITIONS	25
3.2.7 TEST RESULTS	26
3.3 6 DB BANDWIDTH MEASUREMENT	42
3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT	42
3.3.2 TEST INSTRUMENTS.....	42
3.3.3 TEST PROCEDURE.....	42
3.3.4 DEVIATION FROM TEST STANDARD	42
3.3.5 TEST SETUP	43



3.3.6	EUT OPERATING CONDITIONS	43
3.3.7	TEST RESULTS	44
3.4	CONDUCTED OUTPUT POWER.....	48
3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	48
3.4.2	TEST SETUP	48
3.4.3	TEST INSTRUMENTS.....	48
3.4.4	TEST PROCEDURES	48
3.4.5	DEVIATION FROM TEST STANDARD	48
3.4.6	EUT OPERATING CONDITIONS	48
3.4.7	TEST RESULTS	49
3.4.7.1	MAXIMUM PEAK OUTPUT POWER.....	49
3.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	50
3.5	POWER SPECTRAL DENSITY MEASUREMENT	51
3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	51
3.5.2	TEST SETUP	51
3.5.3	TEST INSTRUMENTS.....	51
3.5.4	TEST PROCEDURE.....	51
3.5.5	DEVIATION FROM TEST STANDARD	51
3.5.6	EUT OPERATING CONDITION	51
3.5.7	TEST RESULTS	52
3.6	OUT OF BAND EMISSION MEASUREMENT	56
3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	56
3.6.2	TEST SETUP	56
3.6.3	TEST INSTRUMENTS.....	56
3.6.4	TEST PROCEDURE.....	56
3.6.5	DEVIATION FROM TEST STANDARD	57
3.6.6	EUT OPERATING CONDITION	57
3.6.7	TEST RESULTS	57
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	66
5	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	67



Test Report No.: RF190418W001-2

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF190418W001-2	Original release	May. 29, 2019



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -4.28dB at 0.612000MHz.
15.205 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -7.23dB at 2483.5MHz.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	$\pm 2.70\text{dB}$
All Radiated emissions	$\pm 4.48\text{dB}$
Conducted emissions	$\pm 2\text{ dB}$
Occupied Channel Bandwidth	$\pm 21.7\text{KHz}$
Conducted Output power	$\pm 1.03\text{ dB}$
Power Spectral Density	$\pm 0.95\text{ dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	smartphone
BRAND NAME	LANIX
MODEL NAME	Ilium M9s
NOMINAL VOLTAGE	5.0Vdc (adapter or host equipment) 3.85Vdc (Li-ion, battery)
MODULATION TECHNOLOGY	DSSS, OFDM, DTS
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM BT-LE(GFSK) for DTS
TRANSMISSION RATE	802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n: up to 65 Mbps BT_LE: 1 Mbps
OPERATING FREQUENCY	2412-2462MHz for 11b/g/n(HT20) 2402-2480MHz for BT-LE(GFSK)
MAX. OUTPUT POWER	WLAN: 138.676mW (Maximum) BT-LE: 5.070mW (Maximum)
ANTENNA TYPE	PIFA Antenna with 1dBi gain
HW VERSION	V0.10
SW VERSION	Ilium M9s_SW_01_V01
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB cable: non-shielded, detachable, 1.0m Earphone cable: non-shielded, detachable, 1.2m

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
802.11b	1TX /1RX
802.11g	1TX /1RX
802.11n (20MHz)	1TX /1RX
BT_LE	1TX /1RX



3. The EUT was powered by the following adapter:

ADAPTER	
BRAND:	Ianix
MODEL:	Ilium M9s-C
INPUT:	AC 100-240V, 250mA
OUTPUT:	DC 5V, 1550mA

4. The EUT matched the following USB cable and Earphone:

USB CABLE	
BRAND:	Ianix
MODEL:	M9s
SIGNAL LINE:	1.0 meter

EARPHONE	
BRAND:	Ianix
MODEL:	M9s
SIGNAL LINE:	1.2 meter

5. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



2.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.
The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz **RE≥1G**: Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
BT-LE	0 to 39	0	DTS	GFSK	1
802.11g	1 to 11	11	OFDM	BPSK	6.0



RADIATED EMISSION TEST (ABOVE 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
BT-LE	0 to 39	0,19, 39	DTS	GFSK	1

POWER LINE CONDUCTED EMISSION TEST:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	11	OFDM	BPSK	6.0

BANDEDGE MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 11	OFDM	BPSK	6.5
BT-LE	0 to 39	0, 39	DTS	GFSK	1



ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
BT-LE	0 to 39	0, 19, 39	DTS	GFSK	1

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	22deg. C, 54%RH	DC 5V from adaptor	Star Le
RE≥1G	22deg. C, 54%RH	DC 5V from adaptor	Star Le
PLC	24deg. C, 55%RH	DC 5V from adaptor	John Wen
APCM	25deg. C, 60%RH	3.85Vdc from battery	Rain Wang




2.3 Duty Cycle of Test Signal

WIFI 2.4GHz

802.11b: Duty cycle = $1.272/1.336 = 0.952 < 98\%$, Duty factor = $10 * \log(1/0.952) = 0.213$

802.11g: Duty cycle = $1.356/1.422 = 0.954 < 98\%$, Duty factor = $10 * \log(1/0.954) = 0.206$

802.11n (HT20): Duty cycle = $1.266/1.313 = 0.964 < 98\%$, Duty factor = $10 * \log(1/0.964) = 0.158$



2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

558074 D01 15.247 Meas Guidance v05r02

ANSI C63.10-2013

Note:

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m



3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:** 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Feb. 26,19	Feb. 25,20
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Feb. 26,19	Feb. 25,20

NOTE:

1. The test was performed in CE shielded room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GREGT/CHINA and NIM/CHINA.



3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



3.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80
from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- Turned on the power and connected of all equipment.
- EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



3.1.7 TEST RESULTS


CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25deg. C, 52RH
Tested By	John Wen	TEST DATE	2019/04/25
Test Voltage	DC 5V From Adapter		

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.632000	---	39.29	46.00	-6.71	L	ON	10.0
0.632000	50.32	---	56.00	-5.68	L	ON	10.0
3.480000	---	34.67	46.00	-11.33	L	ON	10.2
3.480000	43.38	---	56.00	-12.62	L	ON	10.2
3.584000	---	32.20	46.00	-13.80	L	ON	10.2
3.584000	41.21	---	56.00	-14.79	L	ON	10.2
8.700000	---	37.27	50.00	-12.73	L	ON	10.4
8.700000	45.66	---	60.00	-14.34	L	ON	10.4
12.664000	---	37.99	50.00	-12.01	L	ON	10.5
12.664000	47.02	---	60.00	-12.98	L	ON	10.5
18.428000	---	36.10	50.00	-13.90	L	ON	10.5
18.428000	46.16	---	60.00	-13.84	L	ON	10.5

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.

Full Spectrum






Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25deg. C, 52RH
Tested By	John Wen	TEST DATE	2019/04/25
Test Voltage	DC 5V From Adapter		

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.612000	---	41.72	46.00	-4.28	N	ON	9.9
0.612000	49.57	---	56.00	-6.43	N	ON	9.9
3.368000	---	31.24	46.00	-14.76	N	ON	10.1
3.368000	40.67	---	56.00	-15.33	N	ON	10.1
4.716000	---	31.20	46.00	-14.80	N	ON	10.1
4.716000	39.50	---	56.00	-16.50	N	ON	10.1
9.912000	---	33.95	50.00	-16.05	N	ON	10.3
9.912000	41.70	---	60.00	-18.30	N	ON	10.3
11.576000	---	35.15	50.00	14.85	N	ON	10.3
11.576000	43.76	---	60.00	-16.24	N	ON	10.3
18.372000	---	30.22	50.00	-19.78	N	ON	10.4
18.372000	39.08	---	60.00	-20.92	N	ON	10.4

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum






Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25deg. C, 52RH
Tested By	John Wen	TEST DATE	2019/04/25
Test Voltage	Data Transmission		

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.182000	---	29.80	54.39	-24.60	L	ON	9.9
0.182000	49.27	---	64.39	-15.13	L	ON	9.9
0.200000	---	32.99	53.61	-20.62	L	ON	9.9
0.200000	48.64	---	63.61	-14.97	L	ON	9.9
0.444000	---	18.04	46.99	-28.94	L	ON	10.0
0.444000	33.15	---	56.99	-23.84	L	ON	10.0
2.008000	---	20.92	46.00	-25.08	L	ON	10.1
2.008000	33.51	---	56.00	-22.49	L	ON	10.1
3.686000	---	25.15	46.00	-20.85	L	ON	10.2
3.686000	37.47	---	56.00	-18.53	L	ON	10.2
4.368000	---	34.12	46.00	-11.88	L	ON	10.2
4.368000	45.04	---	56.00	-10.96	L	ON	10.2

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum






Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25deg. C, 52RH
Tested By	John Wen	TEST DATE	2019/04/25
Test Voltage	Data Transmission		

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.182000	---	29.66	54.39	-24.73	N	ON	9.9
0.182000	48.14	---	64.39	-16.25	N	ON	9.9
0.208000	---	21.42	53.28	31.86	N	ON	9.9
0.208000	42.58	---	63.28	-20.70	N	ON	9.9
0.500000	---	23.29	46.00	-22.71	N	ON	9.9
0.500000	38.81	---	56.00	-17.19	N	ON	9.9
1.616000	---	23.80	46.00	-22.20	N	ON	10.0
1.616000	37.42	---	56.00	-18.58	N	ON	10.0
3.652000	---	22.14	46.00	-23.86	N	ON	10.1
3.652000	34.80	---	56.00	-21.20	N	ON	10.1
4.408000	---	31.82	46.00	-14.18	N	ON	10.1
4.408000	42.08	---	56.00	-13.92	N	ON	10.1

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	Feb. 26,19	Feb. 25,20
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Feb. 26,19	Feb. 25,20
Horn Antenna	ETS-LINDGREN	3117	00168728	Feb. 26,19	Feb. 25,20
Loop antenna	Daze	ZN30900A	0708	Oct. 23,18	Oct. 22, 19
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Nov. 21, 18	Nov. 20, 19
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jul. 09,18	Jul. 08,19
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Feb. 26,19	Feb. 25,20
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jul. 09,18	Jul. 08,19
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jul. 09,18	Jul. 08,19
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jul. 09,18	Jul. 08,19

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed in 3m Chamber.
 3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be performed using fresh batteries. The turntable was rotated to maximize the emission level.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.


3.2.4 DEVIATION FROM TEST STANDARD

No deviation




3.2.5 TEST SETUP

< Frequency Range below 30MHz >




< Frequency Range 30MHz~1GHz >





<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



3.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

9 KHz – 30 MHz data: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

30 MHz – 1GHz data:


802.11g

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
40.67	26.36	50.23	40	-13.64	12.7	0.93	37.5	100	360	QP
99.84	18.44	44.61	43.5	-25.06	9.68	1.31	37.16	100	360	QP
191.99	21.45	45.69	43.5	-22.05	10.6	1.75	36.59	100	360	QP
236.61	20.51	42.75	46	-25.49	12.41	1.97	36.62	100	360	QP
422.85	25.93	42.6	46	-20.07	17.5	2.7	36.87	100	360	QP
692.51	25.38	36.62	46	-20.62	22.78	3.5	37.52	100	360	QP

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.






CHANNEL	TX Channel 11	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
40.67	30.2	53.89	40	-9.8	12.88	0.93	37.5	0	0	QP
84.32	18.82	46.46	40	-21.18	8.43	1.23	37.3	0	0	QP
199.75	16.27	40.23	43.5	-27.23	10.8	1.79	36.55	0	0	QP
296.75	14.02	34.42	46	-31.98	14.14	2.2	36.74	0	0	QP
422.85	23.64	40.19	46	-22.36	17.62	2.7	36.87	0	0	QP
655.65	20.67	33.05	46	-25.33	21.71	3.37	37.46	0	0	QP

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.





Test Report No.: RF190418W001-2

ABOVE 1GHz WORST-CASE DATA:

Note: For higher frequency, the emission is too low to be detected.

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.15	54.61	74	-22.85	33.1	4.88	41.44	124	335	Peak
2390	39.75	43.21	54	-14.25	33.1	4.88	41.44	124	335	Average
2412	99.84	103.25			33.14	4.9	41.45	124	335	Peak
2412	97.09	100.5			33.14	4.9	41.45	124	335	Average
2483.5	50.47	53.68	74	-23.53	33.27	4.98	41.46	124	335	Peak
2483.5	40.05	43.26	54	-13.95	33.27	4.98	41.46	124	335	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	49.91	54.26	74	-24.09	32.21	4.88	41.44	100	115	Peak
2390	40.21	44.56	54	-13.79	32.21	4.88	41.44	100	115	Average
2412	110.02	114.3			32.27	4.9	41.45	100	115	Peak
2412	97.94	102.22			32.27	4.9	41.45	100	115	Average
2483.5	49.46	53.48	74	-24.54	32.46	4.98	41.46	100	115	Peak
2483.5	41.14	45.16	54	-12.86	32.46	4.98	41.46	100	115	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	49.72	53.18	74	-24.28	33.1	4.88	41.44	125	326	Peak
2390	39.1	42.56	54	-14.9	33.1	4.88	41.44	125	326	Average
2437	99.01	102.34			33.19	4.93	41.45	125	326	Peak
2437	96.72	100.05			33.19	4.93	41.45	125	326	Average
2483.5	51.17	54.38	74	-22.83	33.27	4.98	41.46	125	326	Peak
2483.5	40.04	43.25	54	-13.96	33.27	4.98	41.46	125	326	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.07	54.42	74	-23.93	32.21	4.88	41.44	100	124	Peak
2390	39.5	43.85	54	-14.5	32.21	4.88	41.44	100	124	Average
2437	101.05	105.23			32.34	4.93	41.45	100	124	Peak
2437	98.94	103.12			32.34	4.93	41.45	100	124	Average
2483.5	51.09	55.11	74	-22.91	32.46	4.98	41.46	100	124	Peak
2483.5	39.26	43.28	54	-14.74	32.46	4.98	41.46	100	124	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	49.81	53.27	74	-24.19	33.1	4.88	41.44	123	312	Peak
2390	38.89	42.35	54	-15.11	33.1	4.88	41.44	123	312	Average
2462	99.95	103.21			33.23	4.96	41.45	123	312	Peak
2462	97.05	100.31			33.23	4.96	41.45	123	312	Average
2483.5	51.43	54.64	74	-22.57	33.27	4.98	41.46	123	312	Peak
2483.5	41.06	44.27	54	-12.94	33.27	4.98	41.46	123	312	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.02	54.37	74	-23.98	32.21	4.88	41.44	100	118	Peak
2390	39.3	43.65	54	-14.7	32.21	4.88	41.44	100	118	Average
2462	101.19	105.28			32.4	4.96	41.45	100	118	Peak
2462	98.33	102.42			32.4	4.96	41.45	100	118	Average
2483.5	50.6	54.62	74	-23.4	32.46	4.98	41.46	100	118	Peak
2483.5	40.55	44.57	54	-13.45	32.46	4.98	41.46	100	118	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	59.75	63.21	74	-14.25	33.1	4.88	41.44	128	335	Peak
2390	45.16	48.62	54	-8.84	33.1	4.88	41.44	128	335	Average
2412	100.17	103.58			33.14	4.9	41.45	128	335	Peak
2412	89.81	93.22			33.14	4.9	41.45	128	335	Average
2483.5	50.28	53.49	74	-23.72	33.27	4.98	41.46	128	335	Peak
2483.5	40.09	43.3	54	-13.91	33.27	4.98	41.46	128	335	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	61.01	65.36	74	-12.99	32.21	4.88	41.44	100	112	Peak
2390	44.76	49.11	54	-9.24	32.21	4.88	41.44	100	112	Average
2412	101.08	105.36			32.27	4.9	41.45	100	112	Peak
2412	89.05	93.33			32.27	4.9	41.45	100	112	Average
2483.5	49.79	53.81	74	-24.21	32.46	4.98	41.46	100	112	Peak
2483.5	39.25	43.27	54	-14.75	32.46	4.98	41.46	100	112	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.26	53.72	74	-23.74	32.21	4.88	41.44	100	121	Peak
2390	39.22	42.68	54	-14.78	32.21	4.88	41.44	100	121	Average
2437	100.23	103.56			32.34	4.93	41.45	100	121	Peak
2437	89.53	92.86			32.34	4.93	41.45	100	121	Average
2483.5	51.03	54.24	74	-22.97	32.46	4.98	41.46	100	121	Peak
2483.5	41.49	44.7	54	-12.51	32.46	4.98	41.46	100	121	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	49.88	54.23	74	-24.12	32.21	4.88	41.44	100	121	Peak
2390	39.8	44.15	54	-14.2	32.21	4.88	41.44	100	121	Average
2437	102.23	106.41			32.34	4.93	41.45	100	121	Peak
2437	91.48	95.66			32.34	4.93	41.45	100	121	Average
2483.5	50.29	54.31	74	-23.71	32.46	4.98	41.46	100	121	Peak
2483.5	39.26	43.28	54	-14.74	32.46	4.98	41.46	100	121	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.32	53.78	74	-23.68	33.1	4.88	41.44	132	341	Peak
2390	40.69	44.15	54	-13.31	33.1	4.88	41.44	132	341	Average
2462	101.06	104.32			33.23	4.96	41.45	132	341	Peak
2462	100.6	103.86			33.23	4.96	41.45	132	341	Average
2483.5	60.25	63.46	74	-13.75	33.27	4.98	41.46	132	341	Peak
2483.5	46.42	49.63	54	-7.58	33.27	4.98	41.46	132	341	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.03	54.38	74	-23.97	32.21	4.88	41.44	122	69	Peak
2390	39.31	43.66	54	-14.69	32.21	4.88	41.44	122	69	Average
2462	102.49	106.58			32.4	4.96	41.45	122	69	Peak
2462	102.16	106.25			32.4	4.96	41.45	122	69	Average
2483.5	60.39	64.41	74	-13.61	32.46	4.98	41.46	122	69	Peak
2483.5	46.77	50.79	54	-7.23	32.46	4.98	41.46	122	69	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



Test Report No.: RF190418W001-2

802.11n (20MHz)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	59.78	63.24	74	-14.22	33.1	4.88	41.44	115	317	Peak
2390	44.12	47.58	54	-9.88	33.1	4.88	41.44	115	317	Average
2412	100.11	103.52			33.14	4.9	41.45	115	317	Peak
2412	89.06	92.47			33.14	4.9	41.45	115	317	Average
2483.5	50.47	53.68	74	-23.53	33.27	4.98	41.46	115	317	Peak
2483.5	40.25	43.46	54	-13.75	33.27	4.98	41.46	115	317	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	60.24	64.59	74	-13.76	32.21	4.88	41.44	100	112	Peak
2390	44.61	48.96	54	-9.39	32.21	4.88	41.44	100	112	Average
2412	100.19	104.47			32.27	4.9	41.45	100	112	Peak
2412	100.08	104.36			32.27	4.9	41.45	100	112	Average
2483.5	50.36	54.38	74	-23.64	32.46	4.98	41.46	100	112	Peak
2483.5	41.1	45.12	54	-12.9	32.46	4.98	41.46	100	112	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2412MHz: Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.75	54.21	74	-23.25	33.1	4.88	41.44	132	289	Peak
2390	40.19	43.65	54	-13.81	33.1	4.88	41.44	132	289	Average
2437	100.28	103.61			33.19	4.93	41.45	132	289	Peak
2437	99.45	102.78			33.19	4.93	41.45	132	289	Average
2483.5	51.12	54.33	74	-22.88	33.27	4.98	41.46	132	289	Peak
2483.5	39.18	42.39	54	-14.82	33.27	4.98	41.46	132	289	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	49.78	54.13	74	-24.22	32.21	4.88	41.44	100	125	Peak
2390	38.87	43.22	54	-15.13	32.21	4.88	41.44	100	125	Average
2437	101.02	105.2			32.34	4.93	41.45	100	125	Peak
2437	91.18	95.36			32.34	4.93	41.45	100	125	Average
2483.5	49.93	53.95	74	-24.07	32.46	4.98	41.46	100	125	Peak
2483.5	40.36	44.38	54	-13.64	32.46	4.98	41.46	100	125	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.66	54.12	74	-23.34	33.1	4.88	41.44	125	306	Peak
2390	40.86	44.32	54	-13.14	33.1	4.88	41.44	125	306	Average
2462	100.28	103.54			33.23	4.96	41.45	125	306	Peak
2462	99.61	102.87			33.23	4.96	41.45	125	306	Average
2483.5	60.38	63.59	74	-13.62	33.27	4.98	41.46	125	306	Peak
2483.5	44.21	47.42	54	-9.79	33.27	4.98	41.46	125	306	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.54	54.89	74	-23.46	32.21	4.88	41.44	140	54	Peak
2390	39.32	43.67	54	-14.68	32.21	4.88	41.44	140	54	Average
2462	101.04	105.13			32.4	4.96	41.45	140	54	Peak
2462	100.56	104.65			32.4	4.96	41.45	140	54	Average
2483.5	60.13	64.15	74	-13.87	32.46	4.98	41.46	140	54	Peak
2483.5	44.73	48.75	54	-9.27	32.46	4.98	41.46	140	54	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.

**BELOW 1GHz WORST-CASE DATA:**

9 KHz – 30 MHz data: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

30 MHz – 1GHz data:


BT-LE (GFSK)

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
40.67	22.45	46.32	40	-17.55	12.7	0.93	37.5	100	0	QP
95.96	20.47	47.15	43.5	-23.03	9.22	1.3	37.2	100	0	QP
191.99	22.34	46.58	43.5	-21.16	10.6	1.75	36.59	100	0	QP
238.55	21.2	43.35	46	-24.8	12.5	1.98	36.63	100	0	QP
327.79	20.43	39.92	46	-25.57	14.96	2.32	36.77	100	0	QP
422.85	25.63	42.3	46	-20.37	17.5	2.7	36.87	100	0	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value






CHANNEL	TX Channel 0	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
40.67	34.76	58.45	40	-5.24	12.88	0.93	37.5	100	360	QP
50.37	26	54.94	40	-14	7.38	1	37.32	100	360	QP
85.29	27.3	54.89	40	-12.7	8.46	1.24	37.29	100	360	QP
251.16	21.64	43.03	46	-24.36	13.22	2.04	36.65	100	360	QP
416.06	21.82	38.48	46	-24.18	17.52	2.68	36.86	100	360	QP
486.87	21.42	36.94	46	-24.58	18.52	2.94	36.98	100	360	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value





ABOVE 1GHz TEST DATA:

Note: For higher frequency, the emission is too low to be detected.

BT-LE (GFSK)

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	52.26	55.72	74	-21.74	33.1	4.88	41.44	100	89	Peak
2390	40.22	43.68	54	-13.78	33.1	4.88	41.44	100	89	Average
2402	95.88	99.31			33.12	4.89	41.44	100	89	Peak
2402	85.99	89.42			33.12	4.89	41.44	100	89	Average
2483.5	51.15	54.36	74	-22.85	33.27	4.98	41.46	100	89	Peak
2483.5	41.42	44.63	54	-12.58	33.27	4.98	41.46	100	89	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	49.86	54.21	74	-24.14	32.21	4.88	41.44	100	105	Peak
2390	39.43	43.78	54	-14.57	32.21	4.88	41.44	100	105	Average
2402	95.56	99.86			32.25	4.89	41.44	100	105	Peak
2402	83.15	87.45			32.25	4.89	41.44	100	105	Average
2483.5	50.5	54.52	74	-23.5	32.46	4.98	41.46	100	105	Peak
2483.5	39.63	43.65	54	-14.37	32.46	4.98	41.46	100	105	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2402MHz: Fundamental frequency.



CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.3	54.76	74	-22.7	33.1	4.88	41.44	115	216	Peak
2390	39.8	43.26	54	-14.2	33.1	4.88	41.44	115	216	Average
2440	95.64	98.96			33.19	4.94	41.45	115	216	Peak
2440	84.19	87.51			33.19	4.94	41.45	115	216	Average
2483.5	51.92	55.13	74	-22.08	33.27	4.98	41.46	115	216	Peak
2483.5	40.39	43.6	54	-13.61	33.27	4.98	41.46	115	216	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	49.81	54.16	74	-24.19	32.21	4.88	41.44	100	115	Peak
2390	39.27	43.62	54	-14.73	32.21	4.88	41.44	100	115	Average
2440	97.18	101.35			32.34	4.94	41.45	100	115	Peak
2440	86.07	90.24			32.34	4.94	41.45	100	115	Average
2483.5	49.72	53.74	74	-24.28	32.46	4.98	41.46	100	115	Peak
2483.5	39.83	43.85	54	-14.17	32.46	4.98	41.46	100	115	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2440MHz: Fundamental frequency.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.78	54.24	74	-23.22	33.1	4.88	41.44	14	251	Peak
2390	39.4	42.86	54	-14.6	33.1	4.88	41.44	14	251	Average
2480	94.24	97.46			33.26	4.98	41.46	14	251	Peak
2480	83.32	86.54			33.26	4.98	41.46	14	251	Average
2483.5	50.16	53.37	74	-23.84	33.27	4.98	41.46	14	251	Peak
2483.5	39.48	42.69	54	-14.52	33.27	4.98	41.46	14	251	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50	54.35	74	-24	32.21	4.88	41.44	100	123	Peak
2390	38.77	43.12	54	-15.23	32.21	4.88	41.44	100	123	Average
2480	98.31	102.34			32.45	4.98	41.46	100	123	Peak
2480	87.25	91.28			32.45	4.98	41.46	100	123	Average
2483.5	49.65	53.67	74	-24.35	32.46	4.98	41.46	100	123	Peak
2483.5	38.57	42.59	54	-15.43	32.46	4.98	41.46	100	123	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.



3.3 6 dB BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

3.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Meter	ANRITSU	ML2495A	1506002	Feb. 26,19	Feb. 25,20
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510322	Feb. 26,19	Feb. 25,20
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	Feb. 26,19	Feb. 25,20
Power Sensor	ANRITSU	MA2411B	1339352	Feb. 26,19	Feb. 25,20

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

3.3.3 TEST PROCEDURE


1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.3.4 DEVIATION FROM TEST STANDARD

No deviation.



3.3.5 TEST SETUP



3.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



3.3.7 TEST RESULTS

802.11b


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	9.12	0.5	PASS
6	2437	8.82	0.5	PASS
11	2462	8.61	0.5	PASS






802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.38	0.5	PASS
6	2437	15.75	0.5	PASS
11	2462	15.73	0.5	PASS



802.11n (20MHz)


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.60	0.5	PASS
6	2437	16.37	0.5	PASS
11	2462	16.09	0.5	PASS





BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	0.51	0.5	PASS
19	2440	0.51	0.5	PASS
39	2480	0.51	0.5	PASS




3.4 CONDUCTED OUTPUT POWER

3.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

3.4.2 TEST SETUP



3.4.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

3.4.5 DEVIATION FROM TEST STANDARD

No deviation.

3.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



3.4.7 TEST RESULTS

3.4.7.1 MAXIMUM PEAK OUTPUT POWER

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	19.65	92.257	1	PASS
6	2437	20.60	114.815	1	PASS
11	2462	20.13	103.039	1	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	21.20	131.826	1	PASS
6	2437	21.42	138.676	1	PASS
11	2462	21.25	133.352	1	PASS

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	20.50	112.202	1	PASS
6	2437	20.63	115.611	1	PASS
11	2462	20.56	113.763	1	PASS

BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
0	2402	5.28	3.373	1	PASS
19	2440	7.05	5.070	1	PASS
39	2480	5.42	3.483	1	PASS

**3.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)**

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	16.42	N/A
6	2437	17.85	N/A
11	2462	17.35	N/A

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	13.09	N/A
6	2437	14.22	N/A
11	2462	13.50	N/A

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	12.37	N/A
6	2437	12.70	N/A
11	2462	12.68	N/A

BT-LE (GFSK)


CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	2.26	N/A
19	2440	3.68	N/A
39	2480	2.43	N/A

3.5 POWER SPECTRAL DENSITY MEASUREMENT

3.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

3.5.2 TEST SETUP



3.5.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.5.4 TEST PROCEDURE

1. Set the span to 1.5 times the DTS bandwidth
2. Set the RBW = 3 kHz, VBW $\geq 3 \times$ RBW, Detector = peak.
3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

3.5.5 DEVIATION FROM TEST STANDARD

No deviation.

3.5.6 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



3.5.7 TEST RESULTS

802.11b


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-9.78	8	PASS
6	2437	-7.29	8	PASS
11	2462	-6.44	8	PASS





802.11g


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-14.57	8	PASS
6	2437	-11.89	8	PASS
11	2462	-11.57	8	PASS





802.11n (20MHz)


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-14.67	8	PASS
6	2437	-11.99	8	PASS
11	2462	-12.95	8	PASS





BT-LE (GFSK)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	-11.10	8	PASS
19	2440	-9.10	8	PASS
39	2480	-10.17	8	PASS




3.6 OUT OF BAND EMISSION MEASUREMENT

3.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

3.6.2 TEST SETUP



3.6.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

3.6.5 DEVIATION FROM TEST STANDARD

No deviation.

3.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.




BUREAU
VERITAS


Test Report No.: RF190418W001-2

802.11b


CH 1



CH 6



CH 11



BV 7Layers Communications Technology
(Shenzhen) Co. Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan
Avenue, North Area, Hi-Tech Industrial Park, Nanshan
District, Shenzhen, Guangdong, China


Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email: customerservice.dg@cn.bureauveritas.com




BUREAU
VERITAS

Test Report No.: RF190418W001-2

CH 1 Band Edge



CH 11 Band Edge



BV 7Layers Communications Technology
(Shenzhen) Co. Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan
Avenue, North Area, Hi-Tech Industrial Park, Nanshan
District, Shenzhen, Guangdong, China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email: customerservice.dg@cn.bureauveritas.com




BUREAU
VERITAS


Test Report No.: RF190418W001-2

802.11g


CH 1



CH 6




CH 11





BUREAU
VERITAS

Test Report No.: RF190418W001-2



BV 7Layers Communications Technology
(Shenzhen) Co. Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan
Avenue, North Area, Hi-Tech Industrial Park, Nanshan
District, Shenzhen, Guangdong, China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email: customerservice.dg@cn.bureauveritas.com




BUREAU
VERITAS


Test Report No.: RF190418W001-2

802.11n (20MHz)


CH 1



CH 6



CH 11







BUREAU
VERITAS

Test Report No.: RF190418W001-2

CH 1 Band Edge



CH 11 Band Edge



BV 7Layers Communications Technology
(Shenzhen) Co. Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan
Avenue, North Area, Hi-Tech Industrial Park, Nanshan
District, Shenzhen, Guangdong, China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email: customerservice.dg@cn.bureauveritas.com




BUREAU
VERITAS


Test Report No.: RF190418W001-2

BT-LE (GFSK)


CH 0



CH 19




CH 39





BUREAU
VERITAS

Test Report No.: RF190418W001-2



BV 7Layers Communications Technology
(Shenzhen) Co. Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan
Avenue, North Area, Hi-Tech Industrial Park, Nanshan
District, Shenzhen, Guangdong, China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email: customerservice.dg@cn.bureauveritas.com



Test Report No.: RF190418W001-2

4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF190418W001-2

5 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---