

FCC REPORT (Mobile phone)

Applicant: Corporativo Lanix S.A. de C.V.

Address of Applicant: Carrtera internacional Hermosillo-Nogale Km 8.5 Hermosillo,
83000 Mexico

Equipment Under Test (EUT)

Product Name: MOBILE PHONE

Model No.: Z20

Trade mark: LANIX

FCC ID: ZC4Z20

Applicable standards: FCC CFR Title 47 Part 2: 2010
FCC CFR Title 47 Part22 Subpart H: 2010
FCC CFR Title 47 Part24 Subpart E: 2010

Date of sample receipt: 02 Jun., 2011

Date of Test: 03-28 Jun., 2011

Date of report issued: 02 Jul., 2011

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS International Electrical Approvals or testing done by GTS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by GTS International Electrical Approvals in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Version

Version No.	Date	Description
00	2011-07-02	Original

Prepared By: Collin He **Date:** 2011-07-02
Project Engineer

Check By: Hans Hu **Date:** 2011-07-02
Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	5
5 GENERAL INFORMATION	6
5.1 CLIENT INFORMATION	6
5.2 GENERAL DESCRIPTION OF E.U.T.....	6
5.3 RELATED SUBMITTAL(S) / GRANT (S)	6
5.4 TEST METHODOLOGY	6
5.5 TEST FACILITY.....	7
5.6 TEST LOCATION.....	7
5.7 TEST INSTRUMENTS LIST.....	8
6 SYSTEM TEST CONFIGURATION	9
6.1 EUT CONFIGURATION	9
6.2 EUT EXERCISE	9
6.3 TEST PROCEDURE	9
6.3.1 Conducted Emissions.....	9
6.3.2 Radiated Emissions.....	9
6.4 CONFIGURATION OF TESTED SYSTEM.....	9
6.5 DESCRIPTION OF TEST MODES.....	10
7 RF POWER OUTPUT MEASUREMENT	11
7.1 STANDARD APPLICABLE	11
7.2 TEST SETUP.....	11
7.3 MEASUREMENT PROCEDURE	11
7.4 TEST RESULT	11
8 ERP, EIRP MEASUREMENT	13
8.1 STANDARD APPLICABLE	13
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	13
8.3 MEASUREMENT PROCEDURE	14
8.4 MEASUREMENT RESULT	15
9 MODULATION CHARACTERISTIC	17
10 OCCUPIED BANDWIDTH	18
10.1 STANDARD APPLICABLE	18
10.2 TEST SETUP.....	18
10.3 TEST PROCEDURE	18
10.4 TEST RESULT	18
11 OUT OF BAND EMISSION AT ANTENNA TERMINALS	25
11.1 STANDARD APPLICABLE	25

11.2	TEST SETUP.....	25
11.3	MEASUREMENT PROCEDURE	25
11.4	MEASUREMENT RESULT	25
11.4.1	Spurious emission.....	26
11.4.2	Band edge emission	32
12	FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	34
12.1	STANDARD APPLICABLE	34
12.2	EUT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	34
12.3	MEASUREMENT PROCEDURE	35
12.4	TEST RESULT	36
13	FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT	42
13.1	STANDARD APPLICABLE	42
13.2	TEST SETUP.....	42
13.3	TEST PROCEDURE	42
13.4	TEST RESULT	43
14	FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT	44
14.1	STANDARD APPLICABLE	44
14.2	TEST SETUP.....	44
14.3	TEST PROCEDURE	44
14.4	TEST RESULT	45
15	AC POWER LINE CONDUCTED EMISSION TEST	46
15.1	STANDARD APPLICABLE	46
15.2	TEST SETUP.....	46
15.3	TEST PROCEDURE	46
15.4	MEASUREMENT RESULT	46

4 Test Summary

Test Item	Section in CFR 47	Result
RF Exposure (SAR)	Part 1.1307 Part 2.1093	Passed* (Please refer to SAR Report)
RF Output Power	Part 2.1046 Part 22.913 (a)(2) Part 24.232 (c)	Pass
Modulation Characteristics	Part 2.1047	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 22.917 Part 24.238	Pass
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 22.917 (a) Part 24.238 (a)	Pass
Field Strength of Spurious Radiation	Part 2.1053 Part 22.917 (a) Part 24.238 (a)	Pass
Out of band emission, Band Edge	Part 22.917 (a) Part 24.238 (a)	Pass
Frequency stability vs. temperature	Part 2.1055(a)(1)(b)	Pass
Frequency stability vs. voltage	Part 2.1055(d)(1)(2)	Pass

5 General Information

5.1 Client Information

Applicant:	Corporativo Lanix S.A. de C.V.
Address of Applicant:	Carrera internacional Hermosillo-Nogale Km 8.5 Hermosillo, 83000 Mexico
Manufacturer:	Shenzhen Xiangyue Perfect Digital Science & Technology Co.,Ltd.
Address of Manufacturer:	Building A1, Jiujiutongxin Industrial zone II, Xinbu, Tongle, Longgang, shenzhen

5.2 General Description of E.U.T.

Product Name:	MOBILE PHONE
Model No.:	Z20
Data cable(USB):	Length 1m
Earphone line:	Length 1.5m
Power supply:	DC 3.7V Li-ion rechargeable Battery
AC adapter:	Input: AC 100-240V 50/60Hz 0.15A Max Output: DC 5V 500mA
Operation Frequency range:	GSM/GPRS 850: 824MHz-849MHz PCS1900: 1850MHz-1910MHz
Type of Emission:	248KGXW
IMEI:	357295001000020 861582010000001
Software Version:	KAAT518_MXB_En_1.00.C28
Hardware Version:	V1.2

5.3 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is filing to comply with Section Part 22 subpart H and Part 24 subpart E of the FCC CFR 47 Rules.

5.4 Test Methodology

Both conducted and radiated testing were performed according to the procedures document on chapter 13 of ANSI C63.4 (2003) and FCC CFR 47.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055 and 2.1057

5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- FCC —Registration No.: 600491

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, July 20, 2010.

- Industry Canada (IC)

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-1.

5.6 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China

Tel: 0755-27798480

Fax: 0755-27798960

5.7 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi-Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS201	Mar. 30 2011	Mar. 30 2012
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS202	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Sept. 10 2010	Sept. 10 2011
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS204	Feb. 26 2011	Feb. 26 2012
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS205	June 30 2010	June 30 2011
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Coaxial Cable	GTS	N/A	GTS400	Apr. 01 2011	Apr. 01 2012
8	Coaxial Cable	GTS	N/A	GTS401	Apr. 01 2011	Apr. 01 2012
9	Coaxial cable	GTS	N/A	GTS402	Apr. 01 2011	Apr. 01 2012
10	Coaxial Cable	GTS	N/A	GTS407	Apr. 01 2011	Apr. 01 2012
11	Coaxial Cable	GTS	N/A	GTS408	Apr. 01 2011	Apr. 01 2012
12	Amplifier(10KHz-5GHz)	Sonnoma Instrument	305-1052	GTS210	Apr. 01 2011	Apr. 01 2012
13	Amplifier(2GHz-20GHz)	HP	8349B	GTS231	Apr. 01 2011	Apr. 01 2012
14	Universal radio communication tester	Rohde & Schwarz	CMU200	GTS235	May 11 2010	May 11 2011
15	Signal Generator	Rohde & Schwarz	SML03	GTS236	May 11 2010	May 11 2011
16	Temp. Humidity/Barometer	Oregon Scientific	BA-888	GTS248	May 11 2010	May 11 2011
17	D.C. Power Supply	Instek	PS-3030	GTS232	NA	NA
18	Splitter	Agilent	11636B	GTS237	May 11 2010	May 11 2011

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.0(L)x3.0(W)x3.0(H)	GTS206	Apr. 10 2011	Apr. 10 2012
2	EMI Test Receiver	Rohde & Schwarz	ESCS30	GTS208	Sept. 14 2010	Sept. 14 2011
3	10dB Pulse Limita	Rohde & Schwarz	N/A	GTS209	Sept. 14 2010	Sept. 14 2011
4	LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	GTS207	Apr. 14 2011	Apr. 14 2012
5	Coaxial Cable	GTS	N/A	GTS406	Apr. 01 2011	Apr. 01 2012
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

6 SYSTEM TEST CONFIGURATION

6.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

6.2 EUT Exercise

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency which was for the purpose of the measurements.

6.3 Test Procedure


6.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8m above ground plane. According to the requirements in Section 7 and 13 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the frequency range between 0.15MHz and 30MHz using CISPR Quasi-Peak and Average detector mode.

6.3.2 Radiated Emissions

The EUT is placed on a turn table which is 1.0m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 8 and 13 of ANSI C63.4-2003.

6.3.3 Configuration of Tested System



6.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

EUT staying in continuous transmitting mode. Channel Low, Mid and High for each type band with rated data rate were chosen for full testing.

The field strength of spurious radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for both GSM/PCS with power adaptors, earphone and Data cable. The worst-case H mode for GSM 850 band, PCS1900 band.

7 RF POWER OUTPUT MEASUREMENT


7.1 Standard Applicable

According to FCC §2.1046.

FCC 22.913(a) Mobile station are limited to 7W

FCC 24.232(b) Mobile station are limited to 2W.

7.2 Test setup



Note: Measurement setup for testing on Antenna connector

7.3 Measurement Procedure

The transmitter output was connected to a calibrated attenuator, the other end of which was connected to a spectrum analysis. Transmitter output was read off the spectrum analysis in dBm. The power output at the transmitter antenna port was determined by adding the value of the attenuator to spectrum analysis reading.

7.4 Test Result


EUT Mode	Frequency (MHz)	Channel	PK power (dBm)
GSM 850	824.20	128	31.05
	836.60	190	31.32
	848.80	251	32.07

EUT Mode	Frequency (MHz)	Channel	PK power (dBm)
PCS 1900	1850.20	512	29.21
	1880.00	661	28.93
	1909.80	810	29.15


Please refer to the following plots.

Please refer to the following plots.

Test mode:	GSM850	Test channel:	128/190/251
------------	--------	---------------	-------------



Test mode:	PCS1900	Test channel:	512/661/810
------------	---------	---------------	-------------



8 ERP, EIRP MEASUREMENT

8.1 Standard Applicable


According to FCC §2.1046

FCC 22.913(a) Mobile station are limited to 7W ERP.


FCC 24.232(b) Mobile station are limited to 2W EIRP.

8.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



(C) Substituted Method Test Set-UP



8.3 Measurement Procedure

The EUT was placed on a non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer.

During the measurement, the EUT was in communication with the station. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna from 4m to 1m. The reading was recorded and the field strength (E in dBuV/m) was calculated.

ERP in frequency band 824.2 –848.80.8MHz were measured using a substitution method. The EUT was replaced by a dipole antenna connected, the S.G. output was recorded and ERP was calculated as follows:

EIRP in frequency band 1850.2 –1909.8MHz were measured using a substitution method. The EUT was replaced by a horn antenna connected, the S.G. output was recorded and EIRP was calculated as follows:

$$\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable Loss (dB)}$$

$$\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable Loss (dB)}$$

8.4 Measurement Result

EUT mode	Frequency (MHz)	CH	EUT Pol.	Antenna Pol.	SPA Reading (dBuV)	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	ERP (dBm)	Limit (dBm)
GSM 850	824.20	128	H	V	122.78	36.39	-7.87	3.62	24.90	38.45
				H	129.56	46.29	-7.87	3.62	34.80	38.45
			E1	V	125.51	39.12	-7.87	3.62	27.63	38.45
				H	118.98	33.71	-7.87	3.62	22.22	38.45
			E2	V	120.05	33.66	-7.87	3.62	22.17	38.45
				H	127.97	41.70	-7.87	3.62	30.21	38.45
	836.60	190	H	V	123.75	37.50	-7.88	3.65	25.97	38.45
				H	131.26	46.15	-7.88	3.65	34.62	38.45
			E1	V	126.87	40.62	-7.88	3.65	29.09	38.45
				H	120.03	33.80	-7.88	3.65	22.27	38.45
			E2	V	120.94	34.69	-7.88	3.65	23.16	38.45
				H	129.84	43.61	-7.88	3.65	32.08	38.45
	848.80	251	H	V	125.53	39.41	-7.88	3.68	27.85	38.45
				H	133.10	45.87	-7.88	3.68	34.31	38.45
			E1	V	129.10	42.98	-7.88	3.68	31.42	38.45
				H	121.13	34.94	-7.88	3.68	23.38	38.45
			E2	V	122.34	36.22	-7.88	3.68	24.66	38.45
				H	129.98	43.74	-7.88	3.68	32.18	38.45

Remark :

- (1) The RBW,VBW of SPA for frequency
 Below 1GHz was RBW=100 KHz, VBW=300KHz,
 Above 1GHz was RBW= 1MHz , VBW= 3MHz

EUT mode	Frequency (MHz)	CH	EUT Pol.	Antenna Pol.	SPA Reading (dBuV)	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)
PCS 1900	1850.20	512	H	V	123.39	19.00	9.90	5.56	23.34	33.00
				H	130.56	26.14	9.90	5.56	30.48	33.00
			E1	V	124.87	20.48	9.90	5.56	24.82	33.00
				H	127.99	23.81	9.90	5.56	28.15	33.00
			E2	V	126.53	22.14	9.90	5.56	26.48	33.00
				H	129.40	24.22	9.90	5.84	28.28	33.00
	1880.00	661	H	V	121.60	17.24	9.99	5.61	21.62	33.00
				H	130.30	26.16	9.99	5.61	30.54	33.00
			E1	V	127.38	23.02	9.99	5.61	27.40	33.00
				H	127.03	23.19	9.99	5.61	27.57	33.00
			E2	V	125.09	21.73	9.99	5.61	26.11	33.00
				H	130.67	24.53	9.99	5.61	28.91	33.00
	1909.80	810	H	V	121.82	17.49	10.08	5.66	21.91	33.00
				H	129.30	26.19	10.08	5.66	30.61	33.00
			E1	V	126.32	20.99	10.08	5.66	25.41	33.00
				H	126.51	22.40	10.08	5.66	26.82	33.00
			E2	V	125.59	21.26	10.08	5.66	25.68	33.00
				H	128.73	24.62	10.08	5.66	29.04	33.00

Remark :

- (1) The RBW,VBW of SPA for frequency
 Below 1GHz was RBW=100 KHz, VBW=300KHz,
 Above 1GHz was RBW= 1MHz , VBW= 3MHz

9 MODULATION CHARACTERISTIC


According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

10 OCCUPIED BANDWIDTH

10.1 Standard Applicable

CFR 47 §2.1049

10.2 Test setup



Note: Measurement setup for testing on Antenna connector

10.3 Test Procedure

The EUT's output RF connector was connected with a short cable to the spectrum analyzer, RBW (10/47KHz) was set to about 1% of emission BW, VBW= 3 times RBW(30/150KHz), -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

10.4 Test Result


EUT Mode	Frequency(MHz)	CH	26dB bandwidth	99% Bandwidth(MHz)
GSM 850	824.20	128	318.00	245.00
	836.60	190	300.00	244.00
	848.80	251	309.00	246.00

EUT Mode	Frequency(MHz)	CH	26dB bandwidth	99% Bandwidth(MHz)
PCS 1900	1850.20	512	313.00	245.00
	1880.00	661	310.00	246.00
	1909.80	810	317.00	243.00

Please refer to the following plots.


99% bandwidth:

Test mode:	GSM850	Test channel:	128
------------	--------	---------------	-----




Date: 23.JUN.2011 17:24:17

Test mode:	GSM850	Test channel:	190
------------	--------	---------------	-----




Date: 23.JUN.2011 17:22:57

Test mode:	GSM850	Test channel:	251
------------	--------	---------------	-----




Date: 23.JUN.2011 17:15:59

Test mode:	PCS1900	Test channel:	512
------------	---------	---------------	-----




Date: 23.JUN.2011 17:08:12

Test mode:	PCS1900	Test channel:	661
------------	---------	---------------	-----




Date: 23.JUN.2011 17:06:54

Test mode:	PCS1900	Test channel:	810
------------	---------	---------------	-----




Date: 23.JUN.2011 17:01:21

Test mode:	GSM850	Test channel:	251
------------	--------	---------------	-----




Date: 23.JUN.2011 17:16:15

Test mode:	PCS1900	Test channel:	512
------------	---------	---------------	-----




Date: 23.JUN.2011 17:07:53

Test mode:	PCS1900	Test channel:	661
------------	---------	---------------	-----



Date: 23.JUN.2011 17:07:17

Test mode:	PCS1900	Test channel:	810
------------	---------	---------------	-----



Date: 23.JUN.2011 17:01:44


11 OUT OF BAND EMISSION AT ANTENNA TERMINALS

11.1 Standard Applicable

According to FCC §2.1051.

FCC §22.917(a), §24.238(a), the magnitude of each spurious and harmonic emission that can be detected when the equipment is operated under the conditions specified in the instruction manual and/ or alignment procedure, shall not be less than $43 + 10 \log$ (mean output power in watts) dBc below the mean power output outside a license's frequency block (-13dBm)

11.2 Test setup



Note: Measurement setup for testing on Antenna connector

11.3 Measurement Procedure

The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic.

For the out of band: Set the RBW, VBW = 1MHz, Start=30MHz, Stop= 10th harmonic.

Limit = -13dBm


Band Edge Requirements: In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.

Limit = -13dBm.


11.4 Measurement Result

11.4.1 Spurious emission

Test mode:	GSM850	Test channel:	128
------------	--------	---------------	-----




Date: 23.JUN.2011 17:26:07




Date: 23.JUN.2011 17:25:24

Test mode:	GSM850	Test channel:	190
------------	--------	---------------	-----




Date: 23.JUN.2011 17:21:05




Date: 23.JUN.2011 17:21:32

Test mode:	GSM850	Test channel:	251
------------	--------	---------------	-----




Date: 23.JUN.2011 17:16:58




Date: 23.JUN.2011 17:17:19

Test mode:	PCS1900	Test channel:	512
------------	---------	---------------	-----




Date: 23.JUN.2011 17:08:47




Date: 23.JUN.2011 17:09:11

Test mode:	PCS1900	Test channel:	661
------------	---------	---------------	-----




Date: 23.JUN.2011 17:05:41




Date: 23.JUN.2011 17:05:19

Test mode:	PCS1900	Test channel:	810
------------	---------	---------------	-----




Date: 23.JUN.2011 17:03:55



Date: 23.JUN.2011 17:04:44


11.4.2 Band edge emission

Test mode:	GSM850	Test channel:	128
------------	--------	---------------	-----




Date: 23.JUN.2011 17:27:30

Test mode:	GSM850	Test channel:	251
------------	--------	---------------	-----




Date: 23.JUN.2011 17:19:48

Test mode:	PCS1900	Test channel:	512
------------	---------	---------------	-----



Date: 23.JUN.2011 17:10:36

Test mode:	PCS1900	Test channel:	810
------------	---------	---------------	-----



Date: 23.JUN.2011 17:03:30

12 FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT


12.1 Standard Applicable

According to FCC §2.1053,


FCC §22.917(a), §24.238(a), the magnitude of each spurious and harmonic emission that can be detected when the equipment is operated under the conditions specified in the instruction manual and/ or alignment procedure, shall not be less than $43 + 10 \log$ (mean output power in watts) dBc below the mean power output outside a license's frequency block (-13dBm)

12.2 EUT Setup (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency below 1000MHz



(B) Radiated Emission Test Set-UP Frequency over 1 GHz



(C) Substituted Method Test Set-UP



12.3 Measurement Procedure

The EUT was placed on a non-conductive, The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission were identified, the power of the emission was determined using the substitution method.

The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency.

$$\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain(dBi)} - \text{Cable Loss (dB)}$$

12.4 Test Result

Test mode:	GSM850	Test channel:	128	EUT position	H
------------	--------	---------------	-----	--------------	---

Freq(MHz)	SPA reading	Ant. Pol.	S.G output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/EIRP (dBm)	Limit (dBm)	Margin (dBm)
125.58	54.67	V	-50.03	-7.34	0.95	-58.32	-13.00	-45.32
561.84	50.71	V	-51.05	-7.76	1.37	-60.18	-13.00	-47.18
824.00	78.69	V	-7.31	-7.87	3.62	-18.80	-13.00	-5.80
1648.40	67.31	V	-37.27	9.29	5.23	-33.21	-13.00	-20.21
2472.60	63.76	V	-35.25	10.08	6.53	-31.70	-13.00	-18.70
3296.80	---	V					-13.00	13.00
4121.00	---	V					-13.00	13.00
4945.20	---	V					-13.00	13.00
5769.40	---	V					-13.00	13.00

Freq(MHz)	SPA reading	Ant. Pol.	S.G output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/EIRP (dBm)	Limit (dBm)	Margin (dBm)
125.58	53.29	H	-53.50	-7.34	0.95	-61.79	-13.00	-48.79
561.84	52.91	H	-49.51	-7.76	1.37	-58.64	-13.00	-45.64
824.00	76.66	H	-9.73	-7.87	3.62	-21.22	-13.00	-8.22
1648.40	68.03	H	-37.79	9.29	5.23	-33.73	-13.00	-20.73
2472.60	67.08	H	-37.99	10.08	6.53	-34.44	-13.00	-21.44
3296.80	---	H					-13.00	
4121.00	---	H					-13.00	
4945.20	---	H					-13.00	
5769.40	---	H					-13.00	

Remark :

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark”---“ means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:

$$\text{ERP/EIRP (dBm)} = \text{SG Setting(dBm)} + \text{Antenna Gain (dB/dBi)} - \text{Cable loss (dB)}$$

Test mode:	GSM850	Test channel:	190	EUT position	H
------------	--------	---------------	-----	--------------	---

Freq(MHz)	SPA reading	Ant. Pol.	S.G output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/EIRP (dBm)	Limit (dBm)	Margin (dBm)
295.68	50.86	V	-45.98	-7.67	1.10	-54.75	-13.00	-41.75
651.27	47.78	V	-44.48	-7.83	1.58	-53.89	-13.00	-40.89
1673.20	67.44	V	-30.99	9.36	5.27	-26.90	-13.00	-13.90
2509.80	66.78	V	-35.76	10.09	6.58	-32.25	-13.00	-19.25
3346.40	69.23	V	-36.44	12.28	7.79	-31.95	-13.00	-18.95
4183.00	---	V					-13.00	
5019.60	---	V					-13.00	
5856.20	---	V					-13.00	
6692.80	---	V					-13.00	

Freq(MHz)	SPA reading	Ant. Pol.	S.G output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/EIRP (dBm)	Limit (dBm)	Margin (dBm)
295.68	52.10	H	-46.17	-7.67	1.10	-54.94	-13.00	-41.94
651.27	52.01	H	-43.40	-7.83	1.58	-52.81	-13.00	-39.81
1673.20	69.29	H	-29.51	9.36	5.27	-25.42	-13.00	-12.42
2509.80	67.24	H	-36.51	10.09	6.58	-33.00	-13.00	-20.00
3346.40	66.82	H	-37.25	12.28	7.79	-32.76	-13.00	-19.76
4183.00	---	H					-13.00	
5019.60	---	H					-13.00	
5856.20	---	H					-13.00	
6692.80	---	H					-13.00	

Remark :

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:

$$\text{ERP/EIRP (dBm)} = \text{SG Setting(dBm)} + \text{Antenna Gain (dB/dBi)} - \text{Cable loss (dB)}$$

Test mode:	GSM850	Test channel:	251	EUT position	H
------------	--------	---------------	-----	--------------	---

Freq(MHz)	SPA reading	Ant. Pol.	S.G output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/EIRP (dBm)	Limit (dBm)	Margin (dBm)
325.48	51.58	V	-49.09	-7.77	1.38	-58.24	-13.00	-45.24
748.51	49.75	V	-47.33	-7.88	2.88	-58.09	-13.00	-45.09
849.00	74.34	V	-8.20	-7.88	3.68	-19.76	-13.00	-6.76
1697.60	67.38	V	-36.47	9.44	5.31	-32.34	-13.00	-19.34
2546.40	68.52	V	-30.56	10.20	6.63	-26.99	-13.00	-13.99
3395.20	---	V					-13.00	
4244.00	---	V					-13.00	
5092.80	---	V					-13.00	
5941.60	---	V					-13.00	

Freq(MHz)	SPA reading	Ant. Pol.	S.G output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/EIRP (dBm)	Limit (dBm)	Margin (dBm)
212.57	52.43	H	-44.94	-7.77	1.38	-54.09	-13.00	-41.09
598.68	52.46	H	-41.94	-7.88	2.88	-52.70	-13.00	-39.70
824.00	72.67	H	-9.80	-7.88	3.68	-21.36	-13.00	-8.36
1648.40	68.94	H	-35.78	9.44	5.31	-31.65	-13.00	-18.65
2472.60	69.63	H	-31.73	10.20	6.63	-28.16	-13.00	-15.16
3296.80	---	H					-13.00	
4121.00	---	H					-13.00	
4945.20	---	H					-13.00	
5769.40	---	H					-13.00	

Remark :

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:

$$\text{ERP/EIRP (dBm)} = \text{SG Setting(dBm)} + \text{Antenna Gain (dB/dBi)} - \text{Cable loss (dB)}$$

Test mode:	PCS1900	Test channel:	512	EUT position	H
------------	---------	---------------	-----	--------------	---

Freq(MHz)	SPA reading	Ant. Pol.	S.G output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/EIRP (dBm)	Limit (dBm)	Margin (dBm)
527.54	54.67	V	-46.85	-7.83	1.41	-56.09	-13.00	-43.09
1387.27	50.71	V	-46.77	8.44	4.31	-42.64	-13.00	-29.64
1850.00	75.00	V	-23.79	9.90	5.56	-19.45	-13.00	-6.45
3700.40	70.07	V	-26.96	12.61	8.31	-22.66	-13.00	-9.66
5550.60	68.41	V	-30.34	13.23	10.33	-27.44	-13.00	-14.44
7400.80	---	V					-13.00	
9251.00	---	V					-13.00	
11101.20	---	V					-13.00	
12951.40	---	V					-13.00	

Freq(MHz)	SPA reading	Ant. Pol.	S.G output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/EIRP (dBm)	Limit (dBm)	Margin (dBm)
527.54	53.96	H	-47.95	-7.83	1.41	-57.19	-13.00	-44.19
1578.41	49.37	H	-44.62	8.17	4.76	-41.21	-13.00	-28.21
1850.00	73.84	H	-25.18	9.90	5.56	-20.84	-13.00	-7.84
3700.40	68.06	H	-29.11	12.61	8.31	-24.81	-13.00	-11.81
5550.60	67.81	H	-31.10	13.23	10.33	-28.20	-13.00	-15.20
7400.80	---	H					-13.00	
9251.00	---	H					-13.00	
11101.20	---	H					-13.00	
12951.40	---	H					-13.00	

Remark :

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:

$$\text{ERP/EIRP (dBm)} = \text{SG Setting(dBm)} + \text{Antenna Gain (dB/dBi)} - \text{Cable loss (dB)}$$

Test mode:	PCS1900	Test channel:	661	EUT position	H
------------	---------	---------------	-----	--------------	---

Freq(MHz)	SPA reading	Ant. Pol.	S.G output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/EIRP (dBm)	Limit (dBm)	Margin (dBm)
527.54	55.55	V	-45.90	-7.83	1.41	-55.14	-13.00	-42.14
1607.43	49.98	V	-43.91	8.19	4.82	-40.54	-13.00	-27.54
3760.00	71.87	V	-26.64	12.60	8.39	-22.43	-13.00	-9.43
5640.00	65.99	V	-33.33	13.36	10.41	-30.38	-13.00	-17.38
7520.00	66.54	V	-32.38	11.45	12.19	-33.12	-13.00	-20.12
9400.00	---	V					-13.00	
11280.00	---	V					-13.00	
13160.00	---	V					-13.00	
15040.00	---	V					-13.00	

Freq(MHz)	SPA reading	Ant. Pol.	S.G output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/EIRP (dBm)	Limit (dBm)	Margin (dBm)
527.54	56.83	H	-45.05	-7.83	1.41	-54.29	-13.00	-41.29
1201.45	50.23	H	-45.43	7.89	4.58	-42.12	-13.00	-29.12
3760.00	72.73	H	-26.36	12.60	8.39	-22.15	-13.00	-9.15
5640.00	66.53	H	-32.03	13.36	10.41	-29.08	-13.00	-16.08
7520.00	68.43	H	-30.80	11.45	12.19	-31.54	-13.00	-18.54
9400.00	---	H					-13.00	
11280.00	---	H					-13.00	
13160.00	---	H					-13.00	
15040.00	---	H					-13.00	

Remark :

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:

$$\text{ERP/EIRP (dBm)} = \text{SG Setting(dBm)} + \text{Antenna Gain (dB/dBi)} - \text{Cable loss (dB)}$$

Test mode:	PCS1900	Test channel:	810	EUT position	H
------------	---------	---------------	-----	--------------	---

Freq(MHz)	SPA reading	Ant. Pol.	S.G output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/EIRP (dBm)	Limit (dBm)	Margin (dBm)
527.54	55.55	V	-45.97	-7.83	1.41	-55.21	-13.00	-42.21
1388.22	50.98	V	-44.11	7.56	4.56	-41.11	-13.00	-28.11
1910.00	74.35	V	-22.88	10.08	5.66	-18.46	-13.00	-5.46
3819.60	63.89	V	-32.56	12.60	8.69	-28.65	-13.00	-15.65
5729.40	65.32	V	-32.12	13.86	10.73	-28.99	-13.00	-15.99
7639.20	---	V					-13.00	13.00
9549.00	---	V					-13.00	13.00
11458.80	---	V					-13.00	13.00
13368.60	---	V					-13.00	13.00

Freq(MHz)	SPA reading	Ant. Pol.	S.G output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/EIRP (dBm)	Limit (dBm)	Margin (dBm)
527.54	54.84	H	-46.81	-7.83	1.41	-56.05	-13.00	-43.05
895.39	52.18	H	-43.85	-7.84	3.68	-55.37	-13.00	-42.37
1910.00	72.59	H	-24.56	10.08	5.66	-20.14	-13.00	-7.14
3819.60	62.09	H	-34.93	12.60	8.69	-31.02	-13.00	-18.02
5729.40	64.45	H	-35.31	13.86	10.73	-32.18	-13.00	-19.18
7639.20	---	H					-13.00	
9549.00	---	H					-13.00	
11458.80	---	H					-13.00	
13368.60	---	H					-13.00	

Remark :

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:

$$\text{ERP/EIRP (dBm)} = \text{SG Setting(dBm)} + \text{Antenna Gain (dB/dBi)} - \text{Cable loss (dB)}$$


13 FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT

13.1 Standard Applicable

According to FCC §2.1055(a)(1)(b).

Frequency Tolerance: 2.5 ppm

13.2 Test setup



Note : Measurement setup for testing on Antenna connector

13.3 Test Procedure

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

13.4 Test Result

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz				
Temperature (°C)	Power Supplied (Vdc)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-20	3.7	32	0.0383	2.5
-10	3.7	33	0.0394	2.5
0	3.7	31	0.0371	2.5
10	3.7	34	0.0406	2.5
20	3.7	36	0.0430	2.5
30	3.7	34	0.0406	2.5
40	3.7	36	0.0430	2.5
50	3.7	32	0.0383	2.5

Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz				
Temperature (°C)	Power Supplied (Vdc)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-20	3.7	37	0.0197	2.5
-10	3.7	41	0.0218	2.5
0	3.7	33	0.0176	2.5
10	3.7	35	0.0186	2.5
20	3.7	31	0.0165	2.5
30	3.7	34	0.0181	2.5
40	3.7	39	0.0207	2.5
50	3.7	43	0.0229	2.5


14 FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT

14.1 Standard Applicable

According to FCC §2.1055(d)(1)(2).

Frequency Tolerance: 2.5 ppm

14.2 Test setup



Note : Measurement setup for testing on Antenna connector

14.3 Test Procedure

Set chamber temperature to 25°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specified extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.

14.4 Test Result

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz				
Temperature (°C)	Power Supplied (Vdc)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
25	4.25	32	0.0383	2.5
25	3.7	34	0.0406	2.5
25	3.4	31	0.0371	2.5

Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz				
Temperature (°C)	Power Supplied (Vdc)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
25	4.25	39	0.0207	2.5
25	3.7	31	0.0165	2.5
25	3.4	44	0.0234	2.5

15 AC POWER LINE CONDUCTED EMISSION TEST

15.1 Standard Applicable

According to FCC §15.207. The emission value for frequency within 150KHz to 30MHz shall not Exceed criteria of below chart.

Frequency range (MHz)	Limits dB(uV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
Note 1.The lower limit shall apply at the transition frequencies 2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.		

15.2 Test setup

1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.4-2001.
2. The EUT was plug-in DC power adaptor and was placed on the center of the back edge on the test table. The peripherals like earphone was placed on the side of the EUT. The rear of the EUT and peripherals were placed flushed with the rear of the tabletop.
3. The Power adaptor was connected with 110Vac/60Hz power source.


15.3 Test Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

15.4 Measurement Result

Test mode: GSM850


Line:



Condition : FCC PART15 CLASSB QP LISN(2011) LINE
 Job No. : 426RF
 Test Mode : Communicate mode
 Test Engineer: Dick
 Remark : GSM850

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.203	32.64	0.65	0.10	33.39	53.49	-20.10	Average
2	0.203	48.46	0.65	0.10	49.21	63.49	-14.28	QP
3	0.307	25.98	0.61	0.10	26.69	50.06	-23.37	Average
4	0.307	43.68	0.61	0.10	44.39	60.06	-15.67	QP
5	0.611	20.64	0.53	0.10	21.27	46.00	-24.73	Average
6	0.611	37.80	0.53	0.10	38.43	56.00	-17.57	QP
7	0.914	22.43	0.49	0.10	23.02	46.00	-22.98	Average
8	0.914	39.46	0.49	0.10	40.05	56.00	-15.95	QP
9	1.949	23.31	0.40	0.10	23.81	46.00	-22.19	Average
10	1.949	40.13	0.40	0.10	40.63	56.00	-15.37	QP
11	4.136	16.75	0.32	0.10	17.17	46.00	-28.83	Average
12	4.136	34.57	0.32	0.10	34.99	56.00	-21.01	QP

Neutral:




Condition : FCC PART15 CLASSB QP LISN(2011) NEUTRAL
 Job No. : 426RF
 Test Mode : Communicate mode
 Test Engineer: Dick
 Remark : GSM850

	Read	LISN	Cable	Limit	Over	
Freq	Level	Factor	Loss	Line	Limit	Remark
MHz	dBuV	dB	dB	dBuV	dB	
1	0.151	35.74	0.69	0.10	36.53	55.96 -19.43 Average
2	0.151	47.69	0.69	0.10	48.48	65.96 -17.48 QP
3	0.205	30.55	0.65	0.10	31.30	53.40 -22.10 Average
4	0.205	42.50	0.65	0.10	43.25	63.40 -20.15 QP
5	0.307	32.38	0.61	0.10	33.09	50.06 -16.97 Average
6	0.307	40.29	0.61	0.10	41.00	60.06 -19.06 QP
7	0.611	31.34	0.53	0.10	31.97	46.00 -14.03 Average
8	0.611	41.56	0.53	0.10	42.19	56.00 -13.81 QP
9	2.001	27.06	0.40	0.10	27.56	46.00 -18.44 Average
10	2.001	40.13	0.40	0.10	40.63	56.00 -15.37 QP
11	4.158	24.75	0.32	0.10	25.17	46.00 -20.83 Average
12	4.158	34.83	0.32	0.10	35.25	56.00 -20.75 QP

Test mode: PCS1900


Line:



Condition : FCC PART15 CLASSB QP LISN(2011) LINE
 Job No. : 426RF
 Test Mode : Communicate mode
 Test Engineer: Dick
 Remark : PCS1900

	Read	LISN	Cable	Limit	Over		
Freq	Level	Factor	Loss	Line	Limit	Remark	
MHz	dBuV	dB	dB	dBuV	dB		
1	0.203	33.54	0.65	0.10	34.29	53.49	-19.20 Average
2	0.203	45.46	0.65	0.10	46.21	63.49	-17.28 QP
3	0.307	33.51	0.61	0.10	34.22	50.06	-15.84 Average
4	0.307	44.68	0.61	0.10	45.39	60.06	-14.67 QP
5	0.611	29.78	0.53	0.10	30.41	46.00	-15.59 Average
6	0.611	40.80	0.53	0.10	41.43	56.00	-14.57 QP
7	0.914	29.62	0.49	0.10	30.21	46.00	-15.79 Average
8	0.914	38.46	0.49	0.10	39.05	56.00	-16.95 QP
9	2.012	19.26	0.40	0.10	19.76	46.00	-26.24 Average
10	2.012	35.17	0.40	0.10	35.67	56.00	-20.33 QP
11	4.136	16.54	0.32	0.10	16.96	46.00	-29.04 Average
12	4.136	33.57	0.32	0.10	33.99	56.00	-22.01 QP

Neutral:



Condition : FCC PART15 CLASSB QP LISN(2011) NEUTRAL
 Job No. : 426RF
 Test Mode : Communicate mode
 Test Engineer: Dick
 Remark : PCS1900

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.307	32.38	0.61	0.10	33.09	50.06	-16.97	Average
2	0.307	42.56	0.61	0.10	43.27	60.06	-16.79	QP
3	0.611	30.34	0.53	0.10	30.97	46.00	-15.03	Average
4	0.611	38.26	0.53	0.10	38.89	56.00	-17.11	QP
5	1.135	26.07	0.46	0.10	26.63	46.00	-19.37	Average
6	1.135	38.13	0.46	0.10	38.69	56.00	-17.31	QP
7	2.001	27.06	0.40	0.10	27.56	46.00	-18.44	Average
8	2.001	38.16	0.40	0.10	38.66	56.00	-17.34	QP
9	3.509	23.68	0.34	0.10	24.12	46.00	-21.88	Average
10	3.509	34.77	0.34	0.10	35.21	56.00	-20.79	QP
11	5.867	18.31	0.28	0.11	18.70	50.00	-31.30	Average
12	5.867	33.29	0.28	0.11	33.68	60.00	-26.32	QP