

Channel 142

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5613.050	54.70	-24.86	34.61	44.95	68.30	13.60	V
5804.250	54.78	-24.83	34.96	44.65	68.30	13.52	H
11419.800	45.13	-32.38	38.17	39.35	68.30	23.17	H
16451.750	50.66	-27.62	41.42	36.85	68.30	17.64	V
16891.500	50.67	-27.19	42.05	35.81	68.30	17.63	V
17432.500	50.58	-26.77	41.68	35.67	68.30	17.72	H

802.11ac-HT80

Channel 42

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5145.625	59.31	-25.69	34.32	50.68	74.00	14.69	H
5146.562	59.59	-25.69	34.32	50.96	74.00	14.41	H
10419.900	44.26	-33.18	37.54	39.90	68.30	24.04	H
15630.050	47.90	-28.64	40.36	36.19	68.30	20.40	H
16845.550	51.82	-27.25	41.61	37.46	68.30	16.48	H
17229.450	51.75	-26.91	41.47	37.19	68.30	16.55	H

Channel 58

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5350.839	62.28	-25.76	34.48	53.56	74.00	11.72	H
5352.014	60.47	-25.76	34.49	51.74	74.00	13.53	H
10578.850	45.61	-33.25	37.65	41.21	68.30	22.69	V
15869.850	49.62	-28.05	40.65	37.03	68.30	18.68	V
17026.500	52.68	-27.05	41.67	38.05	68.30	15.62	H
17166.200	52.19	-26.93	41.53	37.59	68.30	16.11	V

Channel 106

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5465.245	61.35	-25.30	34.57	52.07	68.30	6.95	V
5469.220	61.33	-25.28	34.58	52.03	68.30	6.97	H
11059.550	46.47	-32.49	37.97	40.99	68.30	21.83	V
16589.250	49.58	-27.60	41.45	35.72	68.30	18.72	V
16638.750	51.47	-27.55	41.48	37.53	68.30	16.83	H
17040.800	52.29	-27.03	41.66	37.66	68.30	16.01	H

Channel 122

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5733.200	56.19	-24.80	34.89	46.10	68.30	12.11	H
5735.462	56.14	-24.79	34.89	46.04	68.30	12.16	H
11220.250	44.35	-32.06	38.17	38.24	68.30	23.95	H
16830.550	51.23	-27.26	41.60	36.89	68.30	17.07	V
17756.500	51.23	-26.51	41.25	36.49	68.30	17.06	V
17325.540	50.86	-26.86	41.37	36.34	68.30	17.44	H

Channel 138

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5600.250	56.39	-24.93	34.59	46.73	68.30	11.91	H
5845.460	54.81	-25.05	35.03	44.82	68.30	13.49	H
11380.250	45.98	-32.29	38.15	40.13	68.30	22.32	V
17070.500	49.44	-27.00	42.11	34.32	68.30	18.86	H
17868.580	49.73	-26.30	41.53	34.51	68.30	18.56	H
17916.230	50.62	-26.19	41.52	35.30	68.30	17.68	H

802.11ac-HT160

Channel 50

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5149.118	58.94	-25.70	34.32	50.31	74.00	15.06	H
5149.852	60.24	-25.70	34.32	51.61	74.00	13.76	V
10500.200	45.11	-33.09	37.60	40.60	68.30	23.19	H
15749.950	47.33	-28.43	40.50	35.26	68.30	20.97	V
5354.376	63.11	-25.76	34.49	54.38	68.30	5.19	H
5355.510	63.22	-25.76	34.49	54.49	68.30	5.08	H

Channel 114

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5465.110	64.30	-25.30	34.57	55.03	68.30	4.00	H
5469.100	64.28	-25.28	34.58	54.98	68.30	4.02	V
11140.550	44.34	-32.19	38.07	38.46	68.30	23.96	H
16710.000	50.95	-27.43	41.53	36.86	68.30	17.35	H
5725.512	63.52	-24.80	34.88	53.44	68.30	4.78	H
5733.700	63.39	-24.80	34.89	53.30	68.30	4.91	H

802.11ax-HT20

Channel 36

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5141.417	55.43	-25.68	34.08	47.03	74.00	18.57	H
5147.962	55.75	-25.69	34.10	47.35	74.00	18.25	H
10359.950	45.31	-33.07	37.62	40.76	68.30	22.99	H
15539.850	48.27	-28.84	39.90	37.21	68.30	20.03	V
16948.950	51.81	-27.13	41.25	37.69	68.30	16.49	H
17087.000	52.76	-26.98	40.93	38.81	68.30	15.54	H

Channel 40

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5179.600	57.55	-25.78	34.16	49.18	68.30	10.75	V
5220.800	56.44	-25.76	34.20	48.00	68.30	11.86	V
10400.100	44.17	-33.17	37.70	39.64	68.30	24.13	H
15599.800	47.83	-28.71	39.90	36.64	68.30	20.47	H
17439.000	51.45	-26.77	40.80	37.42	68.30	16.84	H
17463.750	51.94	-26.75	40.80	37.89	68.30	16.36	V

Channel 48

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5220.600	58.78	-25.76	34.20	50.34	68.30	9.52	H
5260.600	57.14	-25.77	34.24	48.67	68.30	11.16	V
10479.850	44.13	-33.11	37.78	39.46	68.30	24.17	H
15720.250	47.02	-28.48	40.06	35.44	68.30	21.28	V
16765.800	51.79	-27.34	41.27	37.87	68.30	16.51	H
17025.950	51.44	-27.05	41.05	37.44	68.30	16.86	V

Channel 52

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5235.600	58.40	-25.75	34.30	49.85	68.30	9.90	V
5280.600	59.93	-25.79	34.31	51.41	68.30	8.37	V
10995.200	33.15	-32.69	38.00	27.84	68.30	35.15	V
15690.400	35.19	-28.53	40.33	23.39	68.30	33.11	V
16044.800	36.64	-27.92	40.77	23.79	68.30	31.66	H
17855.200	37.15	-26.33	41.53	21.95	68.30	31.15	V

Channel 56

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5259.000	56.75	-25.77	34.31	48.22	68.30	11.55	V
5302.000	56.93	-25.79	34.32	48.40	68.30	11.37	H
10931.200	32.91	-32.88	37.97	27.82	68.30	35.39	H
15840.000	36.38	-28.18	40.51	24.05	68.30	31.92	H
16041.600	36.75	-27.91	40.77	23.89	68.30	31.55	V
17852.800	37.05	-26.34	41.53	21.86	68.30	31.25	V

Channel 64

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5351.055	58.73	-25.76	34.34	50.15	74.00	15.27	V
5352.581	58.74	-25.76	34.34	50.15	74.00	15.26	H
10640.000	32.20	-33.30	37.86	27.65	68.30	36.10	V
15960.000	36.53	-27.65	40.65	23.53	68.30	31.77	V
16162.400	36.41	-28.01	40.96	23.46	68.30	31.89	V
17883.200	36.89	-26.27	41.52	21.63	68.30	31.41	H

Channel 100

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5468.163	55.39	-25.29	34.39	46.29	68.30	12.91	V
5468.688	55.95	-25.28	34.39	46.85	68.30	12.34	V
10994.100	33.80	-32.70	38.00	28.50	68.30	34.49	V
15941.900	36.81	-27.73	40.63	23.91	68.30	31.48	V
17742.600	37.69	-26.53	41.55	22.67	68.30	30.61	H
17964.800	38.14	-26.08	41.51	22.72	68.30	30.16	V

Channel 120

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5579.000	56.66	-25.05	34.55	47.16	68.30	11.63	V
5621.800	57.66	-24.83	34.63	47.86	68.30	10.64	V
11119.500	32.76	-32.27	38.05	26.98	68.30	35.54	H
15940.800	36.90	-27.74	40.63	24.01	68.30	31.40	H
17846.000	37.95	-26.36	41.53	22.77	68.30	30.35	H
17959.300	38.07	-26.09	41.51	22.65	68.30	30.23	V

Channel 140

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5728.962	56.03	-24.80	34.82	46.01	68.30	12.27	V
5729.250	55.77	-24.80	34.82	45.75	68.30	12.53	H
11400.000	33.52	-32.34	38.16	27.70	68.30	34.77	H
15946.300	36.85	-27.71	40.64	23.92	68.30	31.45	V
17847.100	37.84	-26.35	41.53	22.66	68.30	30.46	V
17968.100	38.07	-26.07	41.51	22.63	68.30	30.23	H

Channel 144

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5667.250	53.62	-24.74	34.71	43.65	68.30	14.68	H
5816.250	53.65	-24.89	34.98	43.57	68.30	14.65	H
11440.350	43.51	-32.43	38.18	37.76	68.30	35.42	H
16610.700	50.97	-27.60	41.66	36.91	68.30	31.71	V
17183.550	50.33	-26.93	41.98	35.28	68.30	30.67	H
17438.750	50.85	-26.77	41.67	35.95	68.30	31.42	H

802.11ax-HT40

Channel 38

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5149.467	56.28	-25.70	34.10	47.88	74.00	17.72	H
5149.852	56.77	-25.70	34.10	48.37	74.00	17.23	V
10379.750	44.09	-33.12	37.66	39.55	68.30	24.21	H
15570.100	46.66	-28.78	39.90	35.54	68.30	21.64	V
16650.850	51.19	-27.53	41.15	37.57	68.30	17.11	H
17835.450	51.33	-26.89	40.84	37.39	68.30	16.97	V

Channel 46

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5195.200	58.44	-25.79	34.19	50.03	68.30	9.86	V
5267.000	59.34	-25.78	34.27	50.85	68.30	8.96	V
10460.050	44.50	-33.13	37.76	39.87	68.30	23.80	H
15690.000	47.50	-28.53	39.99	36.05	68.30	20.80	V
16870.850	51.29	-27.22	41.37	37.14	68.30	17.01	H
17221.750	51.64	-26.91	40.96	37.59	68.30	16.66	H

Channel 54

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5223.600	56.05	-25.76	34.29	47.52	68.30	12.25	H
5310.800	57.09	-25.79	34.33	48.54	68.30	11.21	H
11801.600	34.43	-31.97	38.50	27.90	68.30	33.87	H
15810.400	36.09	-28.31	40.47	23.93	68.30	32.21	V
17868.750	37.11	-26.30	41.53	21.88	68.30	31.19	V
17960.500	37.22	-26.09	41.51	21.80	68.30	31.08	V

Channel 62

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5350.137	61.37	-25.76	34.34	52.79	74.00	12.63	H
5351.528	59.63	-25.76	34.34	51.05	74.00	14.37	V
10620.000	31.89	-33.33	37.85	27.36	68.30	36.41	H
15930.550	36.32	-27.78	40.62	23.49	68.30	31.98	V
17783.250	36.77	-26.47	41.54	21.70	68.30	31.53	V
17861.450	37.11	-26.32	41.53	21.90	68.30	31.19	H

Channel 102

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5467.360	60.52	-25.29	34.39	51.42	68.30	7.78	H
5469.123	60.41	-25.28	34.39	51.31	68.30	7.89	H
11019.750	46.55	-32.62	38.01	41.16	68.30	21.75	V
16529.750	48.73	-27.61	41.54	34.80	68.30	19.57	V
17046.500	51.50	-27.02	42.14	36.38	68.30	16.80	H
17663.750	51.04	-26.63	41.57	36.10	68.30	17.26	V

Channel 118

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5554.200	57.33	-25.15	34.50	47.98	68.30	10.97	H
5628.600	58.97	-24.82	34.64	49.15	68.30	9.33	V
11180.000	45.32	-32.10	38.07	39.35	68.30	34.98	V
16770.200	49.38	-27.34	41.88	34.83	68.30	31.37	H
17235.500	51.12	-26.91	41.92	36.11	68.30	30.72	V
17623.750	51.49	-26.67	41.57	36.59	68.30	30.09	V

Channel 134

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5728.125	56.13	-24.80	34.82	46.12	68.30	12.17	V
5730.913	56.33	-24.80	34.83	46.30	68.30	11.97	H
11340.050	45.38	-32.19	38.14	39.43	68.30	35.10	V
17010.000	50.23	-27.06	42.19	35.11	68.30	31.56	H
17624.500	51.56	-26.67	41.57	36.66	68.30	30.74	V
17567.400	51.74	-26.70	41.59	36.86	68.30	30.18	V

Channel 142

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5593.850	54.48	-24.96	34.58	44.87	68.30	13.82	H
5787.850	54.63	-24.74	34.93	44.44	68.30	13.67	V
11419.800	45.13	-32.38	38.17	39.35	68.30	23.17	H
16451.750	50.66	-27.62	41.42	36.85	68.30	17.64	H
16885.500	50.75	-27.20	42.04	35.91	68.30	17.55	H
17478.500	50.95	-26.74	41.63	36.07	68.30	17.35	H

802.11ax-HT80

Channel 42

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5146.562	59.59	-25.69	34.32	50.96	74.00	14.41	H
5147.455	58.91	-25.69	34.32	50.28	74.00	15.09	H
10419.900	44.77	-33.18	37.54	40.41	68.30	23.53	V
15630.050	47.82	-28.64	40.36	36.11	68.30	20.48	V
16543.500	51.99	-27.61	41.43	38.17	68.30	16.31	V
16975.250	51.23	-27.10	41.69	36.65	68.30	17.07	V

Channel 58

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5354.984	60.28	-25.76	34.49	51.55	74.00	13.72	H
5356.333	60.48	-25.76	34.49	51.74	74.00	13.52	V
10579.950	44.16	-33.25	37.65	39.76	68.30	24.13	H
15869.850	46.88	-28.05	40.65	34.28	68.30	21.42	H
16914.500	51.26	-27.17	41.65	36.78	68.30	17.04	V
17165.450	51.55	-26.93	41.53	36.95	68.30	16.75	H

Channel 106

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5469.002	60.10	-25.28	34.58	50.80	68.30	8.20	V
5469.408	60.33	-25.28	34.58	51.04	68.30	7.97	H
11060.350	44.34	-32.49	37.97	38.86	68.30	23.96	V
16590.250	50.54	-27.60	41.45	36.68	68.30	17.76	V
17733.250	51.32	-26.54	41.25	36.61	68.30	16.98	H
17795.750	51.43	-26.46	41.26	36.63	68.30	16.87	V

Channel 122

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5725.150	56.43	-24.80	34.88	46.36	68.30	11.87	H
5737.738	57.04	-24.79	34.89	46.94	68.30	11.26	V
11220.250	44.35	-32.06	38.17	38.24	68.30	23.95	H
16830.050	51.23	-27.26	41.60	36.90	68.30	17.07	V
17764.750	51.23	-26.50	41.25	36.48	68.30	17.06	V
17335.500	50.92	-26.85	41.36	36.41	68.30	17.38	V

Channel 138

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5563.250	54.60	-25.14	34.52	45.21	68.30	13.70	V
5770.260	56.22	-24.74	34.90	46.07	68.30	12.08	H
11380.000	45.87	-32.29	38.15	40.01	68.30	22.43	H
17070.250	49.53	-27.00	42.11	34.41	68.30	18.77	H
17870.450	49.69	-26.30	41.53	34.46	68.30	18.61	H
17945.150	50.72	-26.13	41.51	35.34	68.30	17.58	V

802.11ax-HT160

Channel 50

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5145.985	59.80	-25.69	34.32	51.17	74.00	14.20	H
5149.802	59.91	-25.70	34.32	51.29	74.00	14.09	V
10500.200	45.11	-33.09	37.60	40.60	68.30	23.19	H
15749.750	47.13	-28.43	40.50	35.06	68.30	21.17	H
5351.876	62.53	-25.76	34.49	53.81	68.30	5.77	H
5355.942	61.91	-25.76	34.49	53.18	68.30	6.39	H

Channel 114

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5464.375	64.01	-25.31	34.57	54.74	74.00	9.99	V
5463.745	64.49	-25.31	34.57	55.23	74.00	9.51	H
11140.550	44.13	-32.19	38.07	38.25	68.30	24.17	H
16710.000	50.99	-27.43	41.53	36.90	68.30	17.31	V
5728.337	64.09	-24.80	34.88	54.01	68.30	4.21	H
5726.938	64.28	-24.80	34.88	54.21	68.30	4.02	V

Note: the spurious emission above 18G is noise only

Conclusion: PASS

SPEED

The measurements were performed separately in Chain A, Chain B, and MIMO (Chain A+B), and only the worst cases are shown in this section.

AVERAGE Results:

802.11a

Channel 36

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5149.650	40.25	-25.70	34.10	31.85	54.00	13.75	V
5149.950	40.18	-25.70	34.10	31.78	54.00	13.82	H
11940.000	34.22	-31.69	38.80	27.11	54.00	19.78	H
15540.000	35.69	-28.84	39.90	24.63	54.00	18.31	V
17858.400	36.90	-26.33	40.24	22.98	54.00	17.10	H
17956.800	36.85	-26.10	40.20	22.75	54.00	17.15	H

Channel 40

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5147.750	40.78	-25.69	34.10	32.37	54.00	13.22	V
5438.850	41.06	-25.45	34.40	32.12	54.00	12.94	V
11918.400	34.22	-31.75	38.80	27.17	54.00	19.78	V
15600.000	35.11	-28.71	39.90	23.92	54.00	18.89	H
17776.800	36.64	-26.48	40.32	22.80	54.00	17.36	H
17861.600	36.90	-26.32	40.24	22.98	54.00	17.10	H

Channel 48

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5149.050	40.25	-25.70	34.10	31.85	54.00	13.75	V
5149.800	40.28	-25.70	34.10	31.88	54.00	13.72	V
11889.600	34.26	-31.83	38.78	27.31	54.00	19.74	V
15720.000	35.22	-28.48	40.06	23.65	54.00	18.78	V
17776.000	36.68	-26.48	40.32	22.84	54.00	17.32	H
17861.600	36.85	-26.32	40.24	22.93	54.00	17.15	H

Channel 52

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5140.900	39.96	-25.67	34.08	31.55	54.00	14.04	V
5357.050	40.48	-25.76	34.31	31.92	54.00	13.52	V
11944.000	34.32	-31.68	38.80	27.20	54.00	19.68	V
15780.000	35.45	-28.38	40.24	23.59	54.00	18.55	V
17856.000	36.90	-26.33	40.24	22.99	54.00	17.10	H
17952.800	36.80	-26.11	40.20	22.71	54.00	17.20	H

Channel 56

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5140.050	40.23	-25.67	34.08	31.82	54.00	13.77	V
5350.900	40.75	-25.76	34.30	32.20	54.00	13.25	V
11939.200	34.26	-31.69	38.80	27.16	54.00	19.74	V
15840.000	36.10	-28.18	40.30	23.98	54.00	17.90	H
17865.600	36.89	-26.31	40.23	22.97	54.00	17.11	V
17954.400	36.79	-26.10	40.20	22.70	54.00	17.21	H

Channel 64

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5350.200	41.67	-25.76	34.30	33.13	54.00	12.33	V
5351.950	41.72	-25.76	34.30	33.18	54.00	12.28	V
11916.000	34.27	-31.76	38.80	27.22	54.00	19.73	H
15960.000	36.29	-27.65	40.30	23.64	54.00	17.71	H
17771.200	36.75	-26.49	40.33	22.91	54.00	17.25	H
17860.000	36.86	-26.32	40.24	22.94	54.00	17.14	H

Channel 100

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5454.700	41.38	-25.36	34.41	32.33	54.00	12.62	V
5456.950	41.54	-25.35	34.41	32.47	54.00	12.46	V
11000.000	33.09	-32.68	37.90	27.86	54.00	20.91	H
16143.200	36.64	-28.10	40.60	24.14	54.00	17.36	V
17864.000	37.09	-26.31	40.24	23.17	54.00	16.91	H
17960.000	36.98	-26.09	40.20	22.88	54.00	17.02	V

Channel 120

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5450.250	40.13	-25.38	34.40	31.11	54.00	13.87	V
5454.950	40.24	-25.36	34.41	31.19	54.00	13.76	V
11200.000	33.39	-32.08	38.00	27.47	54.00	20.61	V
15948.800	36.80	-27.70	40.30	24.20	54.00	17.20	H
17862.400	36.97	-26.32	40.24	23.05	54.00	17.03	H
17956.800	36.92	-26.10	40.20	22.82	54.00	17.08	H

Channel 140

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5453.550	40.05	-25.36	34.41	31.00	54.00	13.95	V
5456.600	40.13	-25.35	34.41	31.07	54.00	13.87	V
11400.000	33.40	-32.34	38.00	27.74	54.00	20.60	V
16028.000	36.68	-27.86	40.38	24.16	54.00	17.32	H
17769.600	36.74	-26.49	40.33	22.90	54.00	17.26	V
17862.400	36.79	-26.32	40.24	22.87	54.00	17.21	V

Channel 144

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5448.700	39.94	-25.39	34.40	30.93	54.00	14.06	V
5456.650	40.04	-25.35	34.41	30.97	54.00	13.96	V
11440.000	32.77	-32.43	38.00	27.20	54.00	21.23	V
16045.950	36.55	-27.92	40.44	24.03	54.00	17.45	H
17748.250	37.49	-26.52	40.35	23.66	54.00	16.51	H
17790.250	37.12	-26.47	40.31	23.28	54.00	16.88	V

802.11n-HT20

Channel 36

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5149.000	40.82	-25.70	34.10	32.42	54.00	13.18	V
5149.650	40.71	-25.70	34.10	32.31	54.00	13.29	V
11924.480	34.25	-31.73	38.80	27.18	54.00	19.75	V
15540.000	35.63	-28.84	39.90	24.57	54.00	18.37	V
17774.400	36.63	-26.49	40.33	22.79	54.00	17.37	H
17864.800	36.75	-26.31	40.24	22.83	54.00	17.25	V

Channel 40

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5148.100	41.20	-25.69	34.10	32.80	54.00	12.80	V
5148.750	41.07	-25.70	34.10	32.67	54.00	12.93	H
11940.000	34.20	-31.69	38.80	27.10	54.00	19.80	H
15600.000	35.17	-28.71	39.90	23.98	54.00	18.83	V
17771.200	36.59	-26.49	40.33	22.76	54.00	17.41	H
17861.600	36.72	-26.32	40.24	22.81	54.00	17.28	V

Channel 48

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5147.100	39.93	-25.69	34.09	31.53	54.00	14.07	V
5149.200	39.94	-25.70	34.10	31.54	54.00	14.06	V
11885.600	34.24	-31.84	38.77	27.32	54.00	19.76	H
15720.000	35.32	-28.48	40.06	23.74	54.00	18.68	V
17774.400	36.68	-26.49	40.33	22.84	54.00	17.32	V
17865.600	36.77	-26.31	40.23	22.84	54.00	17.23	V

Channel 52

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5142.400	40.60	-25.68	34.08	32.19	54.00	13.40	V
5356.600	41.21	-25.76	34.31	32.65	54.00	12.79	V
11921.600	34.42	-31.74	38.80	27.36	54.00	19.58	V
15780.000	35.46	-28.38	40.24	23.60	54.00	18.54	H
17857.600	36.89	-26.33	40.24	22.98	54.00	17.11	H
17953.600	36.78	-26.11	40.20	22.68	54.00	17.22	V

Channel 56

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5142.300	40.05	-25.68	34.08	31.65	54.00	13.95	V
5357.150	41.02	-25.76	34.31	32.46	54.00	12.98	V
11756.000	34.23	-31.99	38.47	27.76	54.00	19.77	V
15840.000	36.28	-28.18	40.30	24.16	54.00	17.72	H
17744.000	36.58	-26.53	40.36	22.75	54.00	17.42	V
17857.600	36.72	-26.33	40.24	22.81	54.00	17.28	V

Channel 64

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5351.750	41.57	-25.76	34.30	33.02	54.00	12.43	V
5356.050	41.58	-25.76	34.31	33.03	54.00	12.42	V
10640.000	32.08	-33.30	37.90	27.49	54.00	21.92	V
15960.000	36.27	-27.65	40.30	23.62	54.00	17.73	V
17744.000	36.61	-26.53	40.36	22.78	54.00	17.39	H
17854.400	36.81	-26.34	40.25	22.90	54.00	17.19	H

Channel 100

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5454.650	40.91	-25.36	34.41	31.86	54.00	13.09	V
5456.650	40.95	-25.35	34.41	31.88	54.00	13.05	V
11000.000	32.73	-32.68	37.90	27.51	54.00	21.27	H
16031.200	36.49	-27.87	40.39	23.97	54.00	17.51	H
17771.200	36.71	-26.49	40.33	22.87	54.00	17.29	H
17870.400	36.79	-26.30	40.23	22.86	54.00	17.21	V

Channel 120

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5452.150	40.24	-25.37	34.40	31.21	54.00	13.76	V
5457.200	40.28	-25.34	34.41	31.21	54.00	13.72	V
11200.000	33.23	-32.08	38.00	27.31	54.00	20.77	V
16032.000	36.64	-27.88	40.40	24.12	54.00	17.36	H
17860.000	36.75	-26.32	40.24	22.83	54.00	17.25	H
17959.200	36.77	-26.09	40.20	22.66	54.00	17.23	H

Channel 140

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5456.550	40.09	-25.35	34.41	31.03	54.00	13.91	V
5457.250	40.05	-25.34	34.41	30.98	54.00	13.95	V
11400.000	33.42	-32.34	38.00	27.76	54.00	20.58	H
16051.200	36.55	-27.94	40.45	24.03	54.00	17.45	H
17859.200	36.74	-26.32	40.24	22.82	54.00	17.26	V
17950.400	36.62	-26.11	40.20	22.54	54.00	17.38	H

Channel 144

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5457.950	39.99	-25.34	34.42	30.92	54.00	14.01	V
5458.750	40.02	-25.34	34.42	30.94	54.00	13.98	V
11440.250	32.88	-32.43	38.00	27.31	54.00	21.12	V
16016.450	36.57	-27.82	40.35	24.04	54.00	17.43	H
17742.750	37.45	-26.53	40.36	23.62	54.00	16.55	V
17765.250	36.69	-26.50	40.33	22.85	54.00	17.31	V

802.11n-HT40

Channel 38

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5144.100	41.07	-25.68	34.09	32.66	54.00	12.93	V
5146.900	41.23	-25.69	34.09	32.83	54.00	12.77	V
11937.600	34.25	-31.70	38.80	27.15	54.00	19.75	V
15570.400	35.25	-28.77	39.90	24.13	54.00	18.75	V
17769.600	36.82	-26.49	40.33	22.98	54.00	17.18	H
17852.800	37.01	-26.34	40.25	23.10	54.00	16.99	V

Channel 46

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5142.800	40.34	-25.68	34.09	31.94	54.00	13.66	V
5362.700	40.20	-25.75	34.33	31.63	54.00	13.80	V
11952.000	34.23	-31.66	38.80	27.09	54.00	19.77	H
15690.400	35.02	-28.53	39.99	23.56	54.00	18.98	V
17859.200	36.88	-26.32	40.24	22.97	54.00	17.12	H
17984.000	36.76	-26.04	40.20	22.59	54.00	17.24	V

Channel 54

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5141.550	40.10	-25.68	34.08	31.69	54.00	13.90	V
5356.950	41.10	-25.76	34.31	32.55	54.00	12.90	V
11956.000	34.37	-31.65	38.80	27.21	54.00	19.63	V
15810.400	35.93	-28.31	40.30	23.95	54.00	18.07	V
17775.200	36.76	-26.49	40.32	22.92	54.00	17.24	H
17865.500	36.87	-26.31	40.23	22.94	54.00	17.13	V

Channel 62

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5351.500	43.61	-25.76	34.30	35.06	54.00	10.39	V
5353.600	43.08	-25.76	34.31	34.52	54.00	10.92	V
10620.000	31.92	-33.33	37.90	27.35	54.00	22.08	V
15930.400	36.31	-27.78	40.30	23.79	54.00	17.69	V
17744.000	36.69	-26.53	40.36	22.86	54.00	17.31	H
17859.200	36.87	-26.32	40.24	22.96	54.00	17.13	V

Channel 102

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5456.950	40.99	-25.35	34.41	31.92	54.00	13.01	V
5458.000	41.12	-25.34	34.42	32.04	54.00	12.88	V
11020.000	32.65	-32.62	37.92	27.35	54.00	21.35	V
15944.000	36.64	-27.72	40.30	24.06	54.00	17.36	V
17860.000	36.95	-26.32	40.24	23.04	54.00	17.05	H
17955.200	36.81	-26.10	40.20	22.72	54.00	17.19	H

Channel 118

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5455.250	40.36	-25.35	34.41	31.30	54.00	13.64	V
5458.950	40.36	-25.34	34.42	31.27	54.00	13.64	V
11180.000	33.43	-32.10	38.00	27.54	54.00	20.57	H
15946.400	36.59	-27.71	40.30	24.00	54.00	17.41	V
17854.400	36.84	-26.34	40.25	22.93	54.00	17.16	V
17956.800	36.81	-26.10	40.20	22.71	54.00	17.19	V

Channel 134

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5456.250	40.05	-25.35	34.41	30.99	54.00	13.95	V
5458.400	40.17	-25.34	34.42	31.10	54.00	13.83	V
11340.000	33.54	-32.19	38.00	27.73	54.00	20.46	H
16036.000	36.55	-27.89	40.41	24.03	54.00	17.45	H
17865.600	36.88	-26.31	40.23	22.96	54.00	17.12	V
17956.800	36.90	-26.10	40.20	22.80	54.00	17.10	H

Channel 142

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5453.950	40.10	-25.36	34.41	31.05	54.00	13.90	V
5458.450	40.00	-25.34	34.42	30.92	54.00	14.00	V
11420.250	33.45	-32.38	38.00	27.83	54.00	20.55	H
16020.450	36.63	-27.84	40.36	24.11	54.00	17.37	H
17872.850	36.72	-26.29	40.23	22.79	54.00	17.28	H
17945.360	37.44	-26.13	40.20	23.36	54.00	16.56	V

802.11ac-HT20

Channel 36

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5141.800	41.07	-25.68	34.08	32.66	54.00	12.93	V
5142.750	40.98	-25.68	34.09	32.57	54.00	13.02	V
11888.800	34.20	-31.83	38.78	27.26	54.00	19.80	H
15540.000	35.63	-28.84	39.90	24.57	54.00	18.37	H
17777.600	36.67	-26.48	40.32	22.83	54.00	17.33	V
17861.600	36.78	-26.32	40.24	22.86	54.00	17.22	V

Channel 40

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5148.750	41.21	-25.70	34.10	32.81	54.00	12.79	V
5149.200	41.11	-25.70	34.10	32.71	54.00	12.89	V
11945.600	34.36	-31.68	38.80	27.24	54.00	19.64	H
15600.000	35.14	-28.71	39.90	23.95	54.00	18.86	H
17769.600	36.68	-26.49	40.33	22.84	54.00	17.32	V
17864.800	36.64	-26.31	40.24	22.72	54.00	17.36	V

Channel 48

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5141.850	40.99	-25.68	34.08	32.58	54.00	13.01	V
5143.550	40.99	-25.68	34.09	32.58	54.00	13.01	V
11883.200	34.23	-31.85	38.77	27.31	54.00	19.77	H
15720.000	35.30	-28.48	40.06	23.72	54.00	18.70	H
17774.400	36.66	-26.49	40.33	22.82	54.00	17.34	V
17856.000	36.84	-26.33	40.24	22.93	54.00	17.16	V

Channel 52

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5145.600	40.38	-25.69	34.09	31.98	54.00	13.62	V
5353.150	41.02	-25.76	34.31	32.47	54.00	12.98	V
11769.600	34.29	-31.99	38.51	27.77	54.00	19.71	H
15780.000	35.33	-28.38	40.24	23.47	54.00	18.67	H
17859.200	36.79	-26.32	40.24	22.87	54.00	17.21	H
17952.800	36.76	-26.11	40.20	22.67	54.00	17.24	H

Channel 56

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5144.700	40.25	-25.68	34.09	31.84	54.00	13.75	V
5352.350	41.52	-25.76	34.30	32.97	54.00	12.48	V
11763.200	34.16	-31.99	38.49	27.66	54.00	19.84	H
15840.000	36.14	-28.18	40.30	24.03	54.00	17.86	H
17772.000	36.71	-26.49	40.33	22.88	54.00	17.29	H
17865.600	36.83	-26.31	40.23	22.90	54.00	17.17	V

Channel 64

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5352.050	42.05	-32.29	34.34	40.00	54.00	11.95	V
5362.700	41.95	-32.29	34.35	39.90	54.00	12.05	V
10640.000	32.32	-29.30	37.86	23.77	54.00	21.68	H
15960.000	36.41	-23.82	40.65	19.57	54.00	17.59	H
17766.750	36.69	-22.33	41.55	17.47	54.00	17.31	V
17864.500	36.84	-22.55	41.53	17.86	54.00	17.16	H

Channel 100

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5457.200	40.86	-25.34	34.41	31.79	54.00	13.14	V
5459.000	40.89	-25.33	34.42	31.81	54.00	13.11	V
11000.000	32.86	-32.68	37.90	27.64	54.00	21.14	H
16024.800	36.66	-27.85	40.37	24.14	54.00	17.34	V
17788.000	36.70	-26.47	40.31	22.85	54.00	17.30	V
17866.400	36.88	-26.31	40.23	22.96	54.00	17.12	H

Channel 120

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5450.450	40.29	-25.38	34.40	31.27	54.00	13.71	V
5457.800	40.31	-25.34	34.42	31.24	54.00	13.69	V
11200.000	33.25	-32.08	38.00	27.33	54.00	20.75	H
16026.400	36.54	-27.86	40.38	24.02	54.00	17.46	H
17852.800	36.78	-26.34	40.25	22.87	54.00	17.22	H
17864.800	36.80	-26.31	40.24	22.88	54.00	17.20	V

Channel 140

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5450.550	40.02	-25.38	34.40	31.00	54.00	13.98	V
5452.800	40.06	-25.37	34.41	31.02	54.00	13.94	V
11400.000	33.37	-32.34	38.00	27.71	54.00	20.63	V
16031.200	36.61	-27.87	40.39	24.09	54.00	17.39	V
17767.200	36.70	-26.50	40.33	22.86	54.00	17.30	V
17863.200	36.74	-26.32	40.24	22.82	54.00	17.26	H

Channel 144

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
54546.000	40.08	0.00	0.00	40.08	54.00	13.92	V
5457.250	39.98	-25.34	34.41	30.91	54.00	14.02	V
11440.000	32.84	-32.43	38.00	27.27	54.00	21.16	V
16015.450	36.54	-27.82	40.35	24.01	54.00	17.46	V
17742.750	37.46	-26.53	40.36	23.63	54.00	16.54	H
17770.580	36.63	-26.49	40.33	22.79	54.00	17.37	H

802.11ac-HT40
Channel 38

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5146.000	41.86	-25.69	34.09	33.46	54.00	12.14	V
5148.250	42.40	-25.69	34.10	33.99	54.00	11.60	V
11944.800	34.35	-31.68	38.80	27.23	54.00	19.65	V
15570.400	35.15	-28.77	39.90	24.02	54.00	18.85	V
17769.000	36.76	-26.49	40.33	22.92	54.00	17.24	H
17861.600	36.85	-26.32	40.24	22.93	54.00	17.15	V

Channel 46

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5143.900	40.21	-25.68	34.09	31.80	54.00	13.79	V
5354.400	40.25	-25.76	34.31	31.70	54.00	13.75	V
11916.800	34.26	-31.76	38.80	27.21	54.00	19.74	H
15690.400	35.06	-28.53	39.99	23.61	54.00	18.94	H
17764.800	36.74	-26.50	40.34	22.91	54.00	17.26	V
17853.600	36.78	-26.34	40.25	22.88	54.00	17.22	V

Channel 54

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5143.800	39.97	-25.68	34.09	31.56	54.00	14.03	V
5359.000	40.97	-25.75	34.32	32.40	54.00	13.03	V
11795.200	33.96	-31.98	38.59	27.35	54.00	20.04	H
15810.400	35.91	-28.31	40.30	23.92	54.00	18.09	V
17856.800	36.84	-26.33	40.24	22.92	54.00	17.16	V
17956.000	36.81	-26.10	40.20	22.71	54.00	17.19	H

Channel 62

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5351.000	44.28	-25.76	34.30	35.74	54.00	9.72	V
5352.300	43.81	-25.76	34.30	35.27	54.00	10.19	V
10620.000	31.95	-33.33	37.90	27.38	54.00	22.05	V
15930.400	36.35	-27.78	40.30	23.83	54.00	17.65	H
17764.800	36.67	-26.50	40.34	22.84	54.00	17.33	H
17863.200	36.89	-26.32	40.24	22.96	54.00	17.11	V

Channel 102

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5458.200	41.29	-25.34	34.42	32.21	54.00	12.71	V
5459.150	41.09	-25.33	34.42	32.01	54.00	12.91	V
11020.000	32.70	-32.62	37.92	27.39	54.00	21.30	H
16024.000	36.60	-27.85	40.37	24.07	54.00	17.40	H
17864.000	36.94	-26.31	40.24	23.02	54.00	17.06	V
17955.200	36.89	-26.10	40.20	22.79	54.00	17.11	V

Channel 118

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5475.000	40.29	-25.25	34.45	31.09	54.00	13.71	V
5459.700	40.26	-25.33	34.42	31.17	54.00	13.74	V
11180.000	33.45	-32.10	38.00	27.55	54.00	20.55	H
16026.400	36.59	-27.86	40.38	24.07	54.00	17.41	V
17853.600	36.93	-26.34	40.25	23.02	54.00	17.07	V
17868.800	36.90	-26.30	40.23	22.97	54.00	17.10	V

Channel 134

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5456.100	40.11	-25.35	34.41	31.04	54.00	13.89	V
5457.900	40.12	-25.34	34.42	31.04	54.00	13.88	V
11340.000	33.56	-32.19	38.00	27.75	54.00	20.44	V
16033.600	36.56	-27.88	40.40	24.04	54.00	17.44	H
17770.400	36.88	-26.49	40.33	23.04	54.00	17.12	V
17860.800	36.84	-26.32	40.24	22.92	54.00	17.16	V

Channel 142

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5457.050	40.09	-25.35	34.41	31.02	54.00	13.91	V
5459.900	40.87	-25.33	34.42	31.78	54.00	13.13	V
11420.000	33.52	-32.38	38.00	27.91	54.00	20.48	H
16047.950	36.55	-27.93	40.44	24.03	54.00	17.45	H
17735.450	36.76	-26.54	40.36	22.93	54.00	17.24	V
17865.345	37.23	-26.31	40.23	23.31	54.00	16.77	V

802.11ac-HT80

Channel 42

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5149.050	43.62	-25.70	34.10	35.22	54.00	10.38	V
5149.950	43.64	-25.70	34.10	35.24	54.00	10.36	V
11751.200	34.09	-31.99	38.45	27.63	54.00	19.91	V
15630.400	35.37	-28.64	39.93	24.08	54.00	18.63	V
17860.800	36.86	-26.32	40.24	22.94	54.00	17.14	H
17959.200	36.89	-26.09	40.20	22.79	54.00	17.11	V

Channel 58

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5350.650	43.95	-25.76	34.30	35.41	54.00	10.05	V
5351.400	44.04	-25.76	34.30	35.50	54.00	9.96	V
11768.800	34.25	-31.99	38.51	27.73	54.00	19.75	V
15870.400	35.47	-28.05	40.30	23.22	54.00	18.53	H
17857.600	36.89	-26.33	40.24	22.97	54.00	17.11	V
17958.400	36.81	-26.09	40.20	22.71	54.00	17.19	V

Channel 106

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5458.500	41.92	-25.34	34.42	32.84	54.00	12.08	V
5459.900	41.92	-25.33	34.42	32.83	54.00	12.08	V
11060.000	32.91	-32.49	37.96	27.45	54.00	21.09	H
16028.000	36.55	-27.86	40.38	24.02	54.00	17.45	V
17863.200	36.89	-26.32	40.24	22.97	54.00	17.11	V
17956.000	36.83	-26.10	40.20	22.73	54.00	17.17	H

Channel 122

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5459.350	40.39	-25.33	34.42	31.30	54.00	13.61	V
5459.800	40.40	-25.33	34.42	31.31	54.00	13.60	V
11220.750	44.28	-32.06	38.00	38.34	54.00	9.72	V
17730.550	36.64	-26.54	40.37	22.82	54.00	17.36	V
17748.650	36.56	-26.52	40.35	22.73	54.00	17.44	H
17812.750	36.76	-26.43	40.29	22.90	54.00	17.24	V

Channel 138

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5450.150	40.20	-25.38	34.40	31.18	54.00	13.80	V
5457.200	40.17	-25.34	34.41	31.10	54.00	13.83	V
11340.550	34.62	-32.19	38.00	28.82	54.00	19.38	V
17736.150	36.55	-26.54	40.36	22.72	54.00	17.45	H
17723.750	36.66	-26.55	40.38	22.83	54.00	17.34	H
17879.150	36.56	-26.28	40.22	22.62	54.00	17.44	H

802.11ac-HT160

Channel 50

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5138.500	44.10	-25.67	34.08	35.69	54.00	9.90	V
5139.550	44.09	-25.67	34.08	35.68	54.00	9.91	V
11764.800	34.23	-31.99	38.49	27.72	54.00	19.77	H
15750.400	35.04	-28.43	40.15	23.32	54.00	18.96	V
5350.050	44.05	-25.76	34.30	35.51	54.00	9.95	V
5350.450	44.00	-25.76	34.30	35.46	54.00	10.00	V

Channel 114

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5456.600	43.54	-25.35	34.41	34.47	54.00	10.46	V
5459.700	43.55	-25.33	34.42	34.46	54.00	10.45	V
11140.000	34.06	-32.19	38.00	28.25	54.00	19.94	V
16033.600	36.48	-27.88	40.40	23.96	54.00	17.52	H
17774.400	36.70	-26.49	40.33	22.86	54.00	17.30	H
17864.000	36.79	-26.31	40.24	22.86	54.00	17.21	H

802.11ax-HT20

Channel 36

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5141.750	41.46	-25.68	34.08	33.05	54.00	12.54	V
5144.850	41.44	-25.68	34.09	33.03	54.00	12.56	V
11937.600	34.21	-31.70	38.80	27.11	54.00	19.79	V
15540.000	35.66	-28.84	39.90	24.60	54.00	18.34	V
17784.800	36.55	-26.47	40.32	22.71	54.00	17.45	H
17862.400	36.66	-26.32	40.24	22.74	54.00	17.34	V

Channel 40

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5147.750	41.20	-25.69	34.10	32.79	54.00	12.80	V
5147.900	41.22	-25.69	34.10	32.81	54.00	12.78	V
11943.200	34.23	-31.68	38.80	27.11	54.00	19.77	V
15600.000	35.04	-28.71	39.90	23.85	54.00	18.96	H
17768.800	36.72	-26.49	40.33	22.88	54.00	17.28	V
17858.400	36.75	-26.33	40.24	22.84	54.00	17.25	H

Channel 48

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5144.900	40.75	-25.69	34.09	32.35	54.00	13.25	V
5147.200	40.74	-25.69	34.09	32.34	54.00	13.26	V
11950.400	34.24	-31.66	38.80	27.10	54.00	19.76	H
15720.000	35.24	-28.48	40.06	23.66	54.00	18.76	V
17770.400	36.66	-26.49	40.33	22.82	54.00	17.34	V
17861.600	36.79	-26.32	40.24	22.87	54.00	17.21	V

Channel 52

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5144.600	40.53	-25.68	34.09	32.13	54.00	13.47	V
5359.000	40.97	-25.75	34.32	32.41	54.00	13.03	V
11770.400	34.28	-31.99	38.51	27.75	54.00	19.72	H
15780.000	35.37	-28.38	40.24	23.51	54.00	18.63	V
17747.200	36.71	-26.52	40.35	22.88	54.00	17.29	H
17852.800	36.82	-26.34	40.25	22.91	54.00	17.18	V

Channel 56

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5143.200	40.00	-25.68	34.09	31.59	54.00	14.00	V
5353.150	41.08	-25.76	34.31	32.53	54.00	12.92	V
11769.600	34.27	-31.99	38.51	27.74	54.00	19.73	H
15840.000	36.24	-28.18	40.30	24.12	54.00	17.76	H
17778.400	36.67	-26.48	40.32	22.83	54.00	17.33	V
17853.600	36.92	-26.34	40.25	23.01	54.00	17.08	V

Channel 64

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5352.200	41.92	-25.76	34.30	33.37	54.00	12.08	V
5355.150	41.69	-25.76	34.31	33.13	54.00	12.31	V
10640.000	32.22	-33.30	37.90	27.62	54.00	21.78	H
15960.000	36.27	-27.65	40.30	23.62	54.00	17.73	V
17764.800	36.77	-26.50	40.34	22.93	54.00	17.23	H
17860.000	36.76	-26.32	40.24	22.85	54.00	17.24	H

Channel 100

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5450.650	40.82	-25.38	34.40	31.80	54.00	13.18	V
5458.850	40.93	-25.34	34.42	31.85	54.00	13.07	V
11000.000	32.88	-32.68	37.90	27.66	54.00	21.12	H
15942.000	36.66	-27.73	40.30	24.09	54.00	17.34	V
17767.200	36.69	-26.50	40.33	22.85	54.00	17.31	H
17856.000	36.67	-26.33	40.24	22.76	54.00	17.33	V

Channel 120

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5451.400	40.27	-25.38	34.40	31.24	54.00	13.73	V
5457.300	40.31	-25.34	34.41	31.24	54.00	13.69	V
11200.000	33.28	-32.08	38.00	27.36	54.00	20.72	H
15926.400	36.40	-27.80	40.30	23.90	54.00	17.60	H
17866.400	36.81	-26.31	40.23	22.88	54.00	17.19	V
17953.600	36.80	-26.11	40.20	22.70	54.00	17.20	H

Channel 140

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5452.350	40.08	-25.37	34.40	31.05	54.00	13.92	V
5458.900	40.12	-25.34	34.42	31.03	54.00	13.88	V
11400.000	33.39	-32.34	38.00	27.73	54.00	20.61	H
15941.600	36.65	-27.73	40.30	24.08	54.00	17.35	V
17856.800	36.88	-26.33	40.24	22.97	54.00	17.12	V
17956.000	36.82	-26.10	40.20	22.72	54.00	17.18	V

Channel 144

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5453.050	40.09	-25.37	34.41	31.05	54.00	13.91	V
5454.850	40.07	-25.36	34.41	31.02	54.00	13.93	V
11440.000	32.73	-32.43	38.00	27.16	54.00	21.27	V
16045.125	36.55	-27.92	40.44	24.04	54.00	17.45	H
17748.450	37.55	-26.52	40.35	23.72	54.00	16.45	H
17790.250	37.62	-26.47	40.31	23.78	54.00	16.38	V

802.11ax-HT40

Channel 38

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5147.600	42.85	-25.69	34.10	34.45	54.00	11.15	V
5148.800	42.96	-25.70	34.10	34.56	54.00	11.04	V
11957.600	34.26	-31.64	38.80	27.10	54.00	19.74	H
15570.400	35.04	-28.77	39.90	23.91	54.00	18.96	V
17768.800	36.71	-26.49	40.33	22.87	54.00	17.29	H
17856.800	36.80	-26.33	40.24	22.88	54.00	17.20	V

Channel 46

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5351.550	40.58	-25.76	34.30	32.03	54.00	13.42	V
5359.700	40.49	-25.75	34.32	31.93	54.00	13.51	V
11944.800	34.35	-31.68	38.80	27.22	54.00	19.65	H
15690.400	34.99	-28.53	39.99	23.53	54.00	19.01	V
17765.600	36.80	-26.50	40.33	22.97	54.00	17.20	H
17856.000	36.91	-26.33	40.24	22.99	54.00	17.09	H

Channel 54

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5143.850	40.59	-25.68	34.09	32.19	54.00	13.41	V
5357.100	40.74	-25.76	34.31	32.18	54.00	13.26	V
11763.200	34.25	-31.99	38.49	27.74	54.00	19.75	H
15810.400	35.90	-28.31	40.30	23.91	54.00	18.10	H
17859.200	37.01	-26.32	40.24	23.09	54.00	16.99	V
17956.800	36.84	-26.10	40.20	22.74	54.00	17.16	H

Channel 62

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5351.000	43.64	-25.76	34.30	35.10	54.00	10.36	V
5350.350	43.88	-25.76	34.30	35.33	54.00	10.12	V
10620.000	31.95	-33.33	37.90	27.38	54.00	22.05	H
15930.400	36.24	-27.78	40.30	23.72	54.00	17.76	H
17770.400	36.63	-26.49	40.33	22.79	54.00	17.37	H
17854.400	36.90	-26.34	40.25	22.99	54.00	17.10	V

Channel 102

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5458.250	41.09	-25.34	34.42	32.01	54.00	12.91	V
5459.050	41.08	-25.33	34.42	32.00	54.00	12.92	V
11020.000	32.60	-32.62	37.92	27.30	54.00	21.40	V
16028.000	36.57	-27.86	40.38	24.05	54.00	17.43	H
17774.400	36.66	-26.49	40.33	22.82	54.00	17.34	H
17868.800	36.79	-26.30	40.23	22.86	54.00	17.21	V

Channel 118

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5459.150	40.37	-25.33	34.42	31.29	54.00	13.63	V
5459.500	40.27	-25.33	34.42	31.18	54.00	13.73	V
11180.000	33.46	-32.10	38.00	27.56	54.00	20.54	V
16040.000	36.53	-27.90	40.42	24.02	54.00	17.47	H
17771.200	36.87	-26.49	40.33	23.03	54.00	17.13	V
17863.200	37.00	-26.32	40.24	23.08	54.00	17.00	V

Channel 134

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5455.450	40.16	-25.35	34.41	31.10	54.00	13.84	V
5459.600	40.13	-25.33	34.42	31.04	54.00	13.87	V
11340.000	33.58	-32.19	38.00	27.77	54.00	20.42	H
15936.000	36.59	-27.76	40.30	24.04	54.00	17.41	H
17777.600	36.89	-26.48	40.32	23.05	54.00	17.11	V
17860.800	36.89	-26.32	40.24	22.98	54.00	17.11	V

Channel 142

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5450.700	40.78	-25.38	34.40	31.76	54.00	13.22	V
5457.300	40.86	-25.34	34.41	31.79	54.00	13.14	V
11420.000	33.51	-32.38	38.00	27.90	54.00	20.49	H
16047.950	36.58	-27.93	40.44	24.06	54.00	17.42	V
17740.550	36.75	-26.53	40.36	22.92	54.00	17.25	H
17880.450	37.63	-26.28	40.22	23.69	54.00	16.37	V

802.11ax-HT80

Channel 42

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5149.450	43.12	-25.70	34.10	34.72	54.00	10.88	V
5149.750	43.15	-25.70	34.10	34.75	54.00	10.85	V
11763.200	34.26	-31.99	38.49	27.75	54.00	19.74	H
15630.400	35.42	-28.64	39.93	24.13	54.00	18.58	V
17860.800	36.81	-26.32	40.24	22.89	54.00	17.19	H
17956.000	36.86	-26.10	40.20	22.76	54.00	17.14	V

Channel 58

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5350.650	43.60	-25.76	34.30	35.06	54.00	10.40	V
5351.700	43.68	-25.76	34.30	35.13	54.00	10.32	V
11757.600	34.25	-31.99	38.47	27.77	54.00	19.75	V
15870.400	35.48	-28.05	40.30	23.22	54.00	18.52	H
17856.000	36.77	-26.33	40.24	22.86	54.00	17.23	V
17958.400	36.71	-26.09	40.20	22.61	54.00	17.29	H

Channel 106

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5457.750	41.74	-25.34	34.42	32.67	54.00	12.26	V
5459.900	41.77	-25.33	34.42	32.69	54.00	12.23	V
11060.450	34.43	-32.49	37.96	28.96	54.00	19.57	V
17956.250	36.50	-26.10	40.20	22.40	54.00	17.50	H
17736.450	36.61	-26.54	40.36	22.78	54.00	17.39	H
17780.500	36.84	-26.48	40.32	23.00	54.00	17.16	H

Channel 122

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5450.100	40.39	-25.38	34.40	31.37	54.00	13.61	V
5457.250	40.40	-25.34	34.41	31.33	54.00	13.60	V
11220.250	44.52	-32.06	38.00	38.58	54.00	9.48	H
17730.750	36.62	-26.54	40.37	22.80	54.00	17.38	H
17750.350	36.52	-26.52	40.35	22.69	54.00	17.48	H
17825.150	36.69	-26.40	40.27	22.82	54.00	17.31	V

Channel 138

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5454.850	40.24	-25.36	34.41	31.19	54.00	13.76	V
5457.550	40.23	-25.34	34.42	31.15	54.00	13.77	V
11340.350	34.36	-32.19	38.00	28.55	54.00	19.64	H
17746.750	36.48	-26.52	40.35	22.65	54.00	17.52	H
17726.450	36.62	-26.55	40.37	22.80	54.00	17.38	H
17882.550	36.55	-26.27	40.22	22.60	54.00	17.45	V

802.11ax-HT160
Channel 50

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5141.500	43.48	-25.68	34.08	35.08	54.00	10.52	V
5143.250	43.39	-25.68	34.09	34.98	54.00	10.61	V
11756.800	34.15	-31.99	38.47	27.67	54.00	19.85	V
15750.400	35.16	-28.43	40.15	23.44	54.00	18.84	V
5350.050	43.27	-25.76	34.30	34.73	54.00	10.73	V
5350.400	43.24	-25.76	34.30	34.70	54.00	10.76	V

Channel 114

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5458.500	42.97	-25.34	34.42	33.89	54.00	11.03	V
5459.150	43.10	-25.33	34.42	34.02	54.00	10.90	V
11140.000	34.33	-32.19	38.00	28.51	54.00	19.67	H
17711.050	36.69	-26.57	40.39	22.86	54.00	17.31	H
17778.250	36.68	-26.48	40.32	22.84	54.00	17.32	V
17825.550	37.12	-26.40	40.27	23.25	54.00	16.88	V

PEAK Results:
802.11a

Channel 36

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5148.977	55.72	-25.70	34.10	47.32	74.00	18.28	V
5149.310	56.44	-25.70	34.10	48.04	74.00	17.56	H
10359.950	45.12	-33.07	37.62	40.58	68.30	23.18	V
15539.850	47.36	-28.84	39.90	36.30	74.00	26.64	V
16756.450	51.74	-27.36	41.26	37.84	68.30	16.56	V
17036.400	52.38	-27.03	41.03	38.38	68.30	15.92	H

Channel 40

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5157.600	52.90	-25.72	34.12	44.50	68.30	15.40	V
5259.210	54.68	-25.77	34.24	46.21	68.30	13.62	V
10100.100	44.83	-33.02	37.50	40.35	68.30	23.47	V
15599.800	47.70	-28.71	39.90	36.51	74.00	26.30	H
16682.200	51.32	-27.48	41.18	37.62	68.30	16.98	V
17044.100	51.35	-27.03	41.01	37.37	68.30	16.95	V

Channel 48

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5178.800	53.13	-25.78	34.16	44.75	68.30	15.17	V
5301.600	54.03	-25.79	34.40	45.42	68.30	14.27	H
10479.850	44.31	-33.11	37.78	39.64	68.30	23.99	H
15720.250	47.59	-28.48	40.06	36.01	74.00	26.41	V
16508.900	51.00	-27.61	41.01	37.60	68.30	17.30	V
17115.050	51.64	-26.95	40.92	37.67	68.30	16.66	H

Channel 52

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5214.400	53.16	-25.77	34.20	44.73	68.30	15.14	H
5318.800	53.37	-25.78	34.36	44.79	68.30	14.93	H
10520.000	43.35	-33.11	37.82	38.64	68.30	24.95	H
15780.200	47.57	-28.38	40.24	35.71	74.00	26.43	V
16868.100	50.91	-27.22	41.37	36.76	68.30	17.39	H
17009.450	50.97	-27.06	41.08	36.95	68.30	17.33	H

Channel 56

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5251.600	57.09	-25.76	34.21	48.64	68.30	11.21	H
5312.000	55.86	-25.79	34.38	47.27	68.30	12.44	V
10560.150	44.02	-33.20	37.86	39.36	68.30	24.28	H
15840.150	47.67	-28.18	40.30	35.55	74.00	26.33	V
16942.350	51.42	-27.14	41.27	37.29	68.30	16.88	H
17122.200	51.20	-26.95	40.92	37.22	68.30	17.10	H

Channel 64

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5350.016	57.78	-25.76	34.30	49.24	74.00	16.22	H
5350.394	57.61	-25.76	34.30	49.07	74.00	16.39	H
10639.900	44.42	-33.30	37.90	39.82	74.00	29.58	V
15960.050	47.71	-27.65	40.30	35.06	74.00	26.29	H
16825.200	51.14	-27.27	41.33	37.08	68.30	17.16	V
17140.900	50.66	-26.94	40.94	36.66	68.30	17.64	V

Channel 100

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5468.148	56.51	-25.29	34.44	47.36	68.30	11.79	V
5469.302	56.18	-25.28	34.44	47.02	68.30	12.12	H
11000.150	45.02	-32.68	37.90	39.79	74.00	28.98	V
16500.150	49.53	-27.61	41.00	36.15	68.30	18.77	H
17069.950	51.64	-27.00	40.96	37.68	68.30	16.66	V
17255.300	51.50	-26.90	40.89	37.51	68.30	16.80	H

Channel 120

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5573.000	54.92	-25.08	34.50	45.50	68.30	13.38	V
5633.400	55.48	-24.81	34.50	45.78	68.30	12.82	H
11200.350	44.75	-32.08	38.00	38.83	68.30	23.55	H
16799.350	49.17	-27.30	41.30	35.17	68.30	19.13	H
16937.950	50.85	-27.14	41.29	36.71	68.30	17.45	V
17428.000	50.64	-26.78	40.80	36.61	68.30	17.66	H

Channel 140

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5733.450	55.50	-24.80	34.67	45.63	68.30	12.80	V
5734.750	56.23	-24.80	34.67	46.35	68.30	12.07	V
11399.450	45.34	-32.34	38.00	39.68	68.30	22.96	H
16877.450	51.37	-27.21	41.38	37.20	68.30	16.93	H
17099.650	48.38	-26.97	40.90	34.45	68.30	19.92	H
17552.300	51.92	-26.71	40.70	37.94	68.30	16.38	H

Channel 144

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5699.800	55.28	-24.77	34.60	45.45	68.30	13.02	V
5738.200	56.55	-24.79	34.68	46.66	68.30	11.75	H
11445.250	44.24	-32.44	38.00	38.69	68.30	24.05	V
16820.750	50.75	-27.27	41.32	36.71	68.30	17.55	H
16978.150	51.34	-27.10	41.17	37.27	68.30	16.96	H
17162.150	50.42	-26.93	40.96	36.40	68.30	17.88	V

802.11n-HT20

Channel 36

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5148.995	56.89	-25.70	34.10	48.48	74.00	17.11	H
5149.922	55.82	-25.70	34.10	47.42	74.00	18.18	V
10359.950	44.15	-33.07	37.62	39.60	68.30	24.15	H
15539.850	46.62	-28.84	39.90	35.56	74.00	27.38	H
16757.550	50.98	-27.36	41.26	37.08	68.30	17.31	H
17040.800	51.23	-27.03	41.02	37.24	68.30	17.07	V

Channel 40

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5163.000	54.22	-25.74	34.13	45.83	68.30	14.08	H
5240.000	54.88	-25.75	34.20	46.43	68.30	13.42	V
10400.100	43.95	-33.17	37.70	39.42	68.30	24.35	H
15599.800	47.25	-28.71	39.90	36.06	74.00	26.75	H
16407.750	50.88	-27.59	40.72	37.75	68.30	17.42	H
16874.150	50.83	-27.21	41.37	36.67	68.30	17.47	H

Channel 48

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5203.800	53.99	-25.78	34.20	45.57	74.00	20.01	H
5277.200	54.92	-25.79	34.31	46.40	74.00	19.08	V
10478.850	44.88	-33.12	37.78	40.22	68.30	23.42	V
15720.250	46.47	-28.48	40.06	34.89	74.00	27.53	H
16863.700	51.04	-27.23	41.36	36.91	68.30	17.26	H
17542.950	51.40	-26.71	40.71	37.39	68.30	16.90	V

Channel 52

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5223.400	53.38	-25.76	34.20	44.94	68.30	14.91	V
5283.000	53.80	-25.79	34.33	45.26	68.30	14.50	V
10520.000	44.37	-33.11	37.82	39.66	68.30	23.93	V
15780.200	47.79	-28.38	40.24	35.93	74.00	26.21	H
16667.350	51.10	-27.50	41.17	37.44	68.30	17.20	V
17168.400	51.71	-26.93	40.97	37.68	68.30	16.59	H

Channel 56

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5250.600	52.68	-25.76	34.20	44.24	68.30	15.62	V
5314.600	53.21	-25.78	34.37	44.63	68.30	15.09	H
10560.150	44.82	-33.20	37.86	40.16	68.30	23.48	H
15840.150	46.84	-28.18	40.30	34.72	74.00	27.16	V
16776.800	50.84	-27.32	41.28	36.88	68.30	17.46	V
17274.000	50.43	-26.89	40.85	36.47	68.30	17.87	H

Channel 64

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5351.433	59.23	-25.76	34.30	50.68	74.00	14.77	V
5352.405	57.30	-25.76	34.30	48.76	74.00	16.70	V
10639.900	44.53	-33.30	37.90	39.94	74.00	29.47	H
15690.050	48.17	-28.53	39.99	36.71	74.00	25.83	H
16622.250	50.72	-27.58	41.12	37.18	68.30	17.58	V
17113.400	51.07	-26.95	40.91	37.11	68.30	17.23	V

Channel 100

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5468.672	57.19	-25.28	34.44	48.04	74.00	16.81	H
5469.880	55.40	-25.28	34.44	46.23	74.00	18.60	H
11000.150	44.37	-32.68	37.90	39.15	68.30	23.93	H
16500.150	48.28	-27.61	41.00	34.90	68.30	20.02	H
16752.600	51.06	-27.36	41.25	37.18	68.30	17.24	H
16826.300	51.05	-27.27	41.33	36.99	68.30	17.25	V

Channel 120

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5580.600	56.90	-25.04	34.50	47.44	68.30	11.40	V
5628.600	56.05	-24.82	34.50	46.36	68.30	12.25	H
11200.350	44.94	-32.08	38.00	39.02	68.30	23.36	H
16799.900	49.96	-27.30	41.30	35.95	68.30	18.34	V
16898.350	50.92	-27.19	41.40	36.71	68.30	17.38	V
16970.400	50.85	-27.11	41.19	36.77	68.30	17.45	V

Channel 140

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5729.863	55.44	-24.80	34.66	45.58	68.30	12.86	V
5730.775	55.88	-24.80	34.66	46.02	68.30	12.42	V
11400.000	45.72	-32.34	38.00	40.06	68.30	22.58	V
16984.150	51.28	-27.09	41.15	37.23	68.30	17.02	V
17027.600	50.95	-27.04	41.04	36.95	68.30	17.35	V
17101.300	48.13	-26.96	40.90	34.19	68.30	20.17	H

Channel 144

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5698.800	55.08	-24.77	34.60	45.25	68.30	13.22	V
5739.800	55.27	-24.79	34.68	45.37	68.30	13.03	H
11460.000	44.24	-32.47	38.00	38.72	68.30	24.05	H
16825.250	50.64	-27.27	41.33	36.59	68.30	17.66	H
16975.820	51.25	-27.10	41.17	37.18	68.30	17.05	V
17165.020	50.54	-26.93	40.97	36.51	68.30	17.76	H

802.11n-HT40

Channel 38

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5147.840	47.23	-25.69	34.10	38.83	74.00	26.77	H
5148.785	56.58	-25.70	34.10	48.18	74.00	17.42	V
10379.750	44.01	-33.12	37.66	39.47	68.30	24.29	V
15570.100	46.77	-28.78	39.90	35.64	74.00	27.23	V
16739.950	50.97	-27.38	41.24	37.11	68.30	17.33	V
16884.600	50.49	-27.20	41.38	36.30	68.30	17.81	H

Channel 46

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5173.800	53.82	-25.77	34.15	45.44	74.00	20.18	H
5292.800	54.74	-25.80	34.37	46.17	74.00	19.26	H
10460.050	43.89	-33.13	37.76	39.26	68.30	24.41	V
15690.000	46.51	-28.53	39.99	35.05	74.00	27.49	V
16472.650	51.00	-27.62	40.92	37.69	68.30	17.30	V
17150.250	50.73	-26.94	40.95	36.72	68.30	17.57	H

Channel 54

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5210.600	53.68	-25.77	34.20	45.25	68.30	14.62	H
5321.600	53.80	-25.78	34.36	45.23	68.30	14.49	V
10539.800	43.15	-33.15	37.84	38.46	68.30	25.15	V
15809.900	47.19	-28.32	40.30	35.21	74.00	26.81	H
16759.750	50.21	-27.35	41.26	36.30	68.30	18.09	H
17224.500	50.83	-26.91	40.95	36.79	68.30	17.47	H

Channel 62

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5350.920	59.62	-25.76	34.30	51.08	74.00	14.38	H
5351.770	58.48	-25.76	34.30	49.94	74.00	15.52	V
10620.100	43.64	-33.33	37.90	39.07	74.00	30.36	H
15929.800	47.46	-27.78	40.30	34.95	74.00	26.54	H
16639.300	50.65	-27.55	41.14	37.06	68.30	17.65	H
17250.900	51.03	-26.90	40.90	37.04	68.30	17.27	V

Channel 102

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5461.450	55.67	-25.32	34.42	46.57	68.30	12.63	H
5469.812	55.83	-25.28	34.44	46.66	68.30	12.47	H
11019.950	44.83	-32.62	37.92	39.53	68.30	23.47	H
16532.600	49.24	-27.61	41.03	35.82	68.30	19.06	H
16593.650	50.76	-27.60	41.09	37.26	68.30	17.54	V
17497.300	51.37	-26.74	40.80	37.30	68.30	16.93	V

Channel 118

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5549.600	55.35	-25.14	34.50	45.99	68.30	12.95	V
5634.000	55.61	-24.81	34.50	45.92	68.30	12.69	H
11180.550	46.31	-32.10	38.00	40.41	68.30	21.99	V
16770.200	49.18	-27.34	41.27	35.25	68.30	19.12	V
16792.200	51.39	-27.31	41.29	37.40	68.30	16.91	V
17448.900	50.80	-26.76	40.80	36.76	68.30	17.50	V

Channel 134

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5730.275	55.51	-24.80	34.66	45.65	68.30	12.79	H
5738.725	55.65	-24.79	34.68	45.76	68.30	12.65	V
11341.150	46.37	-32.19	38.00	40.56	68.30	17.77	H
16354.400	50.53	-27.55	40.56	37.52	68.30	18.54	H
17008.900	49.76	-27.06	41.08	35.74	68.30	18.54	V
17051.250	50.62	-27.02	41.00	36.64	68.30	17.68	V

Channel 142

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5677.600	56.60	-24.74	34.56	46.78	68.30	11.70	H
5740.200	55.59	-24.79	34.68	45.70	68.30	12.71	V
11419.750	46.32	-32.38	38.00	40.70	68.30	21.98	H
16538.750	50.45	-27.61	41.04	37.02	68.30	17.85	H
17130.850	48.23	-26.94	40.93	34.25	68.30	20.06	V
17450.350	50.89	-26.76	40.80	36.85	68.30	17.41	V

802.11ac-HT20

Channel 36

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5147.035	56.77	-25.69	34.09	48.36	74.00	17.23	V
5149.292	56.36	-25.70	34.10	47.96	74.00	17.64	H
10359.950	43.81	-33.07	37.62	39.27	68.30	24.49	H
15539.850	47.64	-28.84	39.90	36.58	74.00	26.36	H
16431.950	50.86	-27.61	40.80	37.67	68.30	17.44	H
16930.250	50.88	-27.15	41.31	36.72	68.30	17.42	V

Channel 40

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
5166.600	53.79	-25.75	34.13	45.40	68.30	14.51	H
5254.600	54.96	-25.76	34.22	46.51	68.30	13.34	V
10400.100	44.04	-33.17	37.70	39.51	68.30	24.26	H
15599.800	46.51	-28.71	39.90	35.31	74.00	27.49	V
16816.950	51.59	-27.28	41.32	37.56	68.30	16.70	V
17263.550	50.51	-26.90	40.87	36.53	68.30	17.79	V