





FCC PART 15C TEST REPORT No. I20Z70001-IOT01

for

Samsung Electronics. Co., Ltd.

Mobile phone

Model Name: SM-M115M/DS, SM-M115M

FCC ID: ZCASMM115M

with

Hardware Version: REV1.0

Software Version: M115M.001(M115MUBE0ATA8)

Issued Date: 2020-2-17

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504

Email:<u>cttl_terminals@caict.ac.cn</u>, website: <u>www.chinattl.com</u>





REPORT HISTORY

| Report Number | Revision | Description | Issue Date |
|-----------------|----------|-------------|------------|
| I20Z70001-IOT01 | Rev.0 | 1st edition | 2020-2-17 |





CONTENTS

| 1. TEST LABORATORY | 5 |
|--|----|
| 1.1. INTRODUCTION & ACCREDITATION | 5 |
| 1.2. Testing Location | 5 |
| 1.3. Testing Environment | |
| 1.4. Project data | 6 |
| 1.5. SIGNATURE | 6 |
| 2. CLIENT INFORMATION | 7 |
| 2.1. Applicant Information | 7 |
| 2.2. MANUFACTURER INFORMATION | 7 |
| 3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) | 8 |
| 3.1. About EUT | 8 |
| 3.2. INTERNAL IDENTIFICATION OF EUT | |
| 3.3. INTERNAL IDENTIFICATION OF AE | 8 |
| 3.4. NORMAL ACCESSORY SETTING | 9 |
| 3.5. GENERAL DESCRIPTION | 9 |
| 4. REFERENCE DOCUMENTS | 10 |
| 4.1. DOCUMENTS SUPPLIED BY APPLICANT | |
| 4.2. Reference Documents for testing | 10 |
| 5. TEST RESULTS | 11 |
| 5.1. SUMMARY OF TEST RESULTS | |
| 5.2. Statements | 11 |
| 5.3. EXPLANATION OF RE-USE OF TEST DATA | |
| 6. TEST FACILITIES UTILIZED | 12 |
| 7. MEASUREMENT UNCERTAINTY | |
| 7.1. PEAK OUTPUT POWER - CONDUCTED | 13 |
| 7.2. Frequency Band Edges | 13 |
| 7.3. TRANSMITTER SPURIOUS EMISSION - CONDUCTED | |
| 7.4. TRANSMITTER SPURIOUS EMISSION - RADIATED | |
| 7.5. TIME OF OCCUPANCY (DWELL TIME) | |
| 7.6. 20DB BANDWIDTH | |
| 7.7. CARRIER FREQUENCY SEPARATION | 14 |
| 7.8. AC POWERLINE CONDUCTED EMISSION | |
| ANNEX A: DETAILED TEST RESULTS | |
| A.1. Measurement Method | |
| A.2. PEAK OUTPUT POWER – CONDUCTED | |
| A.3. FREQUENCY BAND EDGES – CONDUCTED | |
| | |





| A.4. T | RANSMITTER SPURIOUS EMISSION - CONDUCTED | 25 |
|--------|--|----|
| A.5. T | RANSMITTER SPURIOUS EMISSION - RADIATED | |
| A.6. T | IME OF OCCUPANCY (DWELL TIME) | 60 |
| A.7. 2 | 0DB BANDWIDTH | 71 |
| A.8. C | ARRIER FREQUENCY SEPARATION | |
| A.9. N | IUMBER OF HOPPING CHANNELS | |
| A.10. | AC Powerline Conducted Emission | |
| ANNEX | B: ACCREDITATION CERTIFICATE | 88 |
| | | |





1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP)with lab code600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Conducted testing Location: CTTL(huayuan North Road)

Address:

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China100191

Radiated testing Location: CTTL(BDA)

Address:No.18A, Kangding Street, Beijing Economic-TechnologyDevelopment Area, Beijing, P. R. China 100176





1.3. Testing Environment

| Normal Temperature: | 15-35 ℃ |
|---------------------|----------------|
| Relative Humidity: | 20-75% |

1.4. Project data

| Testing Start Date: | 2019-12-13 |
|---------------------|------------|
| Testing End Date: | 2020-2-13 |

1.5. Signature

Æ

Wu Le (Prepared this test report)



Sun Zhenyu (Reviewed this test report)

Li Zhuofang (Approved this test report)





2. Client Information

2.1. Applicant Information

| Company Name: | Samsung Electronics. Co., Ltd. | |
|----------------|---|--|
| | R5, A Tower 22 Floor A-1,(Maetan dong) | |
| Address /Post: | 129,Samsung-ro,Yeongtong-gu, Suwon-Si, Gyeonggi-do 16677, | |
| | Korea | |
| City: | / | |
| Postal Code: | / | |
| Country: | Korea | |
| Telephone: | +82-10-4376-0326 | |
| Fax: | / | |

2.2. Manufacturer Information

| Company Name: | Samsung Electronics. Co., Ltd. | | |
|----------------|---|--|--|
| | R5, A Tower 22 Floor A-1,(Maetan dong) | | |
| Address /Post: | 129,Samsung-ro,Yeongtong-gu, Suwon-Si, Gyeonggi-do 16677, | | |
| | Korea | | |
| City: | 1 | | |
| Postal Code: | 1 | | |
| Country: | Korea | | |
| Telephone: | +82-10-4376-0326 | | |
| Fax: | 1 | | |





3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

| Description | Mobile phone |
|--------------------|-----------------------|
| Model Name | SM-M115M/DS, SM-M115M |
| FCC ID | ZCASMM115M |
| Frequency Band | ISM 2400MHz~2483.5MHz |
| Type of Modulation | GFSK/π/4 DQPSK/8DPSK |
| Number of Channels | 79 |
| Power Supply | 3.85V DC by Battery |

3.2. Internal Identification of EUT

| EUT ID* | SN or IMEI | HW Version | SW Version |
|--------------------|------------------|------------|--------------------------|
| EUT1 | 1 | REV1.0 | M115M.001(M115MUBE0ATA8) |
| EUT2 (SM-M115M/DS) | 353691110106894/ | REV1.0 | M115M.001(M115MUBE0ATA8) |
| | 353692110106892 | | |

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

| AE ID* | Description | |
|---------------|-------------|-----------------------------------|
| AE1 | Battery | 1 |
| AE2 | Battery | 1 |
| AE3 | Charger | 1 |
| AE4 | USB Cable | 1 |
| AE1 | | |
| Model | | HQ-70S |
| Manufacturer | | SCUD(Fujian) Electronics Co., Ltd |
| Capacitance | | 1 |
| Nominal volta | ige | 1 |
| AE2 | | |
| Model | | HQ-70N |
| Manufacturer | | Amperex Technology Limited |
| Capacitance | | 1 |
| Nominal volta | ige | 1 |
| AE3 | | |
| Model | | EP-TA200-JWE |
| Manufacturer | | Samsung Electronics. Co., Ltd. |
| Length of cab | le | 1 |
| | | |





| AE4 | | |
|-----------------|------------------------|---------|
| Model | EP-DR140AWE | |
| Manufacturer | LUXSHARE-ICT (VIETNAM) | LIMITED |
| Length of cable | 1 | |

*AE ID: is used to identify the test sample in the lab internally.

3.4. Normal Accessory setting

Fully charged battery should be used during the test.

3.5. General Description

The Equipment Under Test (EUT) is a model of Mobile phone with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfill the test. Samples undergoing test were selected by the Client.





4. <u>Reference Documents</u>

4.1. Documents supplied by applicant

EUT feature information is supplied by the client or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

| Reference | Title | Version |
|-------------|--|-----------|
| | FCC CFR 47, Part 15, Subpart C: | |
| | 15.205 Restricted bands of operation; | |
| FCC Part15 | 15.209 Radiated emission limits, general requirements; | 2018 |
| | 15.247 Operation within the bands 902–928MHz, | |
| | 2400–2483.5 MHz, and 5725–5850 MHz. | |
| ANSI C63.10 | American National Standard of Procedures for | June,2013 |
| ANGI 603.10 | Compliance Testing of Unlicensed Wireless Devices | June,2013 |





5. <u>Test Results</u>

5.1. Summary of Test Results

Abbreviations used in this clause:

- **P** Pass, The EUT complies with the essential requirements in the standard.
- **F** Fail, The EUT does not comply with the essential requirements in the standard
- NA Not Applicable, The test was not applicable
- NP Not Performed, The test was not performed by CTTL
- **R** Re-use test data from basic model report.

| SUMMARY OF MEASUREMENT RESULTS | Sub-clause | Verdict |
|---|------------------------|---------|
| Peak Output Power - Conducted | 15.247 (b)(1) | Р |
| Frequency Band Edges | 15.247 (d) | R |
| Transmitter Spurious Emission - Conducted | 15.247 (d) | R |
| Transmitter Spurious Emission - Radiated | 15.247, 15.205, 15.209 | R |
| Time of Occupancy (Dwell Time) | 15.247 (a) (1)(iii) | R |
| 20dB Bandwidth | 15.247 (a)(1) | R |
| Carrier Frequency Separation | 15.247 (a)(1) | R |
| Number of hopping channels | 15.247 (a)(b)(iii) | R |
| AC Powerline Conducted Emission | 15.107, 15.207 | R |

Please refer to **ANNEX A** for detail.

The measurement is made according to ANSI C63.10.

5.2. Statements

CTTL has evaluated the test cases requested by the applicant /manufacturer as listed in section 5.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.2

5.3. Explanation of re-use of test data

The Equipment Under Test (EUT) model SM-M115M/DS and SM-M115M(FCC ID: ZCASMM115M) are variants product of SM-A115M/DS(FCC ID: ZCASMA115M), according to the declaration of changes provided by the applicant and FCC KDB publication 484596 D01, spot check measurements(Peak Output Power-Conducted) were performed on SM-M115M/DS, other test results are derived from test report No. I19Z70342-IOT01.The SM-M115M/DS with Dual SIM mode is a new product for this testing. The SM-M115M with single SIM mode is a variant product of SM-M115M/DS and shares the SM-M115M/DS results.

Please refer Annex A for detail spot check verification data and reference data. the spot check test results are consistent with basic model.

For detail differences between basic model and Under Test model please refer the Declaration of Changes document.





6. <u>Test Facilities Utilized</u>

Conducted test system

| No. | Equipment | Model | Serial Number | Manufacturer | Calibratio n Period | Calibration Due date |
|-----|---------------------------|--------|------------------|-----------------|------------------------|-------------------------|
| 1 | Vector Signal Analyzer | FSQ26 | 200136 | Rohde & Schwarz | 1 year | 2020-11-29 |
| 2 | Bluetooth Tester | CBT32 | 100649 | Rohde & Schwarz | 1 year | 2020-11-29 |
| 3 | LISN | ENV216 | 825562/0 28 | R&S | 1 year | 2020-03-10 |
| 4 | Test Receiver | ESCI | 100766 | R&S | 1 year | 2020-03-20 |
| 6 | Shielding Room | S81 | / | ETS-Lindgren | / | / |

Radiated emission test system

| No. | Equipment | Model | Serial Number | Manufacturer | Calibration Period | Calibration Due date |
|-----|---|----------|------------------|-----------------|-----------------------|-------------------------|
| 1 | Test Receiver | ESU26 | 100376 | Rohde & Schwarz | 1 year | 2020-10-30 |
| 2 | BiLog Antenna | VULB9163 | 9163-514 | Schwarzbeck | 1 year | 2021-02-03 |
| 3 | Dual-Ridge Waveguide Horn Antenna | 3117 | 00139065 | ETS-Lindgren | 1 year | 2020-11-10 |
| 4 | Dual-Ridge Waveguide Horn Antenna | 3116 | 2663 | ETS-Lindgren | 1 year | 2020-05-31 |
| 5 | Vector Signal Analyzer | FSV40 | 101047 | Rohde & Schwarz | 1 year | 2020-07-20 |
| 6 | Base Station Simulator | CMW500 | 159408 | R&S | 1 year | 2020-03-03 |





7. <u>Measurement Uncertainty</u>

7.1. Peak Output Power - Conducted

Measurement Uncertainty:

| Measurement Uncertainty (k=2) | 0.66dB |
|-------------------------------|--------|
|-------------------------------|--------|

7.2. Frequency Band Edges

Measurement Uncertainty:

| Measurement Uncertainty (k=2) | 0.66dB |
|-------------------------------|--------|
|-------------------------------|--------|

7.3. Transmitter Spurious Emission - Conducted

Measurement Uncertainty:

| Frequency Range | Uncertainty (k=2) | |
|-------------------|-------------------|--|
| 30 MHz ~ 8 GHz | 1.22dB | |
| 8 GHz ~ 12.75 GHz | 1.51dB | |
| 12.7GHz ~ 26 GHz | 1.51dB | |

7.4. Transmitter Spurious Emission - Radiated

Measurement Uncertainty:

| Frequency Range | Uncertainty (k=2) | |
|-----------------|-------------------|--|
| < 1 GHz | 5.40dB | |
| > 1 GHz | 4.32dB | |

7.5. Time of Occupancy (Dwell Time)

Measurement Uncertainty:

| Measurement Uncertainty (k=2) | 0.88ms |
|-------------------------------|--------|
|-------------------------------|--------|

7.6. 20dB Bandwidth

Measurement Uncertainty:





7.7. Carrier Frequency Separation

Measurement Uncertainty:

| Measurement Uncertainty (k=2) | 61.936Hz |
|-------------------------------|----------|
|-------------------------------|----------|

7.8. AC Powerline Conducted Emission

Measurement Uncertainty:

| Measurement Uncertainty (k=2) | 3.10dB |
|-------------------------------|--------|
| | 0.100D |






ANNEX A: Detailed Test Results

A.1. Measurement Method

A.1.1. Conducted Measurements

The measurement is made according to ANSI C63.10.

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode (Transmitter, receiver or transmitter & receiver).
- 3). Set the EUT to the required channel.
- 4). Set the EUT hopping mode (hopping or hopping off).
- 5). Set the spectrum analyzer to start measurement.
- 6). Record the values. Vector Signal Analyzer




A.1.2. Radiated Emission Measurements

The measurement is made according to ANSI C63.10

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz; Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 1MHz;







A.2. Peak Output Power – Conducted

Method of Measurement: See ANSI C63.10-clause 7.8.5

a) Use the following spectrum analyzer settings:

- Span: 6MHz
- RBW: 3MHz
- VBW: 3MHz
- Sweep time: 2.5ms
- Detector function: peak
- Trace: max hold
- b) Allow trace to stabilize.
- c) Use the marker-to-peak function to set the marker to the peak of the emission.
- d) The indicated level is the peak output power.

Measurement Limit:

| Standard | Limits | | |
|------------------------|----------------|---------------|--|
| FCC Part 15.247 (b)(1) | Bandwidth≪1MHz | 30dBm (1W) | |
| | Bandwidth>1MHz | 21dBm (125mW) | |

Spot check Measurement Results:

For GFSK

| Channel | Ch 0 2402 MHz | Ch 39 2441 MHz | Ch 78 2480 MHz | Conclusion |
|--------------------------------------|------------------|-------------------|-------------------|------------|
| Peak Conducted Output Power (dBm) | 8.03 | 8.85 | 7.95 | Р |

For $\pi/4$ DQPSK

| Channel | Ch 0 2402 MHz | Ch 39 2441 MHz | Ch 78 2480 MHz | Conclusion |
|--------------------------------------|------------------|-------------------|-------------------|------------|
| Peak Conducted Output Power (dBm) | 8.91 | 9.76 | 8.41 | Р |

For 8DPSK

| Channel | Ch 0 2402 MHz | Ch 39 2441 MHz | Ch 78 2480 MHz | Conclusion |
|--------------------------------------|------------------|-------------------|-------------------|------------|
| Peak Conducted Output Power (dBm) | 9.00 | 10.15 | 8.77 | Р |

Conclusion: PASS





Ρ

Reference Measurement Results from basic model:

8.31

For GFSK

| Channel | Ch 0 | Ch 39 | Ch 78 | Conclusion |
|--------------------|----------|----------|----------|------------|
| Channer | 2402 MHz | 2441 MHz | 2480 MHz | Conclusion |
| Peak Conducted | 8.93 | 9.72 | 8.35 | Р |
| Output Power (dBm) | 0.93 | 9.72 | 0.35 | F |
| For π/4 DQPSK | | | | |
| Channel | Ch 0 | Ch 39 | Ch 78 | Conclusion |
| Channel | 2402 MHz | 2441 MHz | 2480 MHz | Conclusion |
| Peak Conducted | 8.16 | 8.99 | 7.60 | Р |
| Output Power (dBm) | 0.10 | 0.99 | 7.00 | F |
| For 8DPSK | | | | |
| Channel | Ch 0 | Ch 39 | Ch 78 | Conclusion |
| Channel | 2402 MHz | 2441 MHz | 2480 MHz | Conclusion |
| Peak Conducted | 0.21 | 0.22 | 7 90 | D |

9.23

7.80

Conclusion: PASS

Output Power (dBm)





A.3. Frequency Band Edges – Conducted

Method of Measurement: See ANSI C63.10-clause 7.8.6

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below (be sure to enter all losses between the unlicensed wireless device output and the spectrum analyzer).

- Span: 10 MHz
- Resolution Bandwidth: 100 kHz
- Video Bandwidth: 300 kHz
- Sweep Time:Auto
- Detector: Peak
- Trace: max hold

Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel.

Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not an absolute field strength measurement; it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.

Measurement Limit:

| Standard | Limit (dBc) |
|----------------------------|-------------|
| FCC 47 CFR Part 15.247 (d) | < -20 |

Measurement Result:

For GFSK

| Channel | Hopping | Band Edge Power (dBc) | | Conclusion |
|---------|-------------|------------------------|--------|------------|
| 0 | Hopping OFF | Fig.1 | -57.01 | Р |
| 0 | Hopping ON | Fig.2 | -63.38 | Р |
| 70 | Hopping OFF | Fig.3 | -64.19 | Р |
| 78 | Hopping ON | Fig.4 | -68.30 | Р |

For $\pi/4$ DQPSK

| Channel | Hopping | Band Edge Power (dBc) | | Conclusion |
|---------|-------------|------------------------|--------|------------|
| 0 | Hopping OFF | Fig.5 | -56.41 | Р |
| 0 | Hopping ON | Fig.6 | -66.23 | Р |
| 70 | Hopping OFF | Fig.7 | -63.88 | Р |
| 78 | Hopping ON | Fig.8 | -66.45 | Р |

For 8DPSK

| Channel | Hopping | Band Edge | Power (dBc) | Conclusion |
|---------|-------------|-----------|--------------|------------|
| 0 | Hopping OFF | Fig.9 | -57.74 | Р |
| 0 | Hopping ON | Fig.10 | -64.17 | Р |





| 70 | Hopping OFF | Fig.11 | -63.40 | Р |
|----|-------------|--------|--------|---|
| 78 | Hopping ON | Fig.12 | -66.56 | Р |

Conclusion: PASS

Test graphs as below




Fig.1. Frequency Band Edges: GFSK, Channel 0, Hopping Off




Fig.2. Frequency Band Edges: GFSK, Channel 0, Hopping On








Fig.3. Frequency Band Edges: GFSK, Channel 78, Hopping Off




Fig.4. Frequency Band Edges: GFSK, Channel 78, Hopping On








Fig.5. Frequency Band Edges: $\pi/4$ DQPSK, Channel 0, Hopping Off




Fig.6. Frequency Band Edges: $\pi/4$ DQPSK, Channel 0, Hopping On








Fig.7. Frequency Band Edges: π/4 DQPSK, Channel 78, Hopping Off




Fig.8. Frequency Band Edges: π/4 DQPSK, Channel 78, Hopping On








Fig.9. Frequency Band Edges: 8DPSK, Channel 0, Hopping Off




Fig.10. Frequency Band Edges: 8DPSK, Channel 0, Hopping On








Fig.11. Frequency Band Edges: 8DPSK, Channel 78, Hopping Off




Fig.12. Frequency Band Edges: 8DPSK, Channel 78, Hopping On





A.4. Transmitter Spurious Emission - Conducted

Method of Measurement: See ANSI C63.10-clause 7.8.8

Measurement Procedure – Reference Level

- 1. Set the RBW = 100 kHz.
- 2. Set the VBW = 300 kHz.
- 3. Set the span to 5-30 % greater than the EBW.
- 4. Detector = peak.
- 5. Sweep time = auto couple.
- 6. Trace mode = max hold.
- 7. Allow trace to fully stabilize.

8. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW. Next, determine the power in 100 kHz band segments outside of the authorized frequency band using the following measurement:

Measurement Procedure - Unwanted Emissions

- 1. Set RBW = 100 kHz.
- 2. Set VBW = 300 kHz.
- 3. Set span to encompass the spectrum to be examined.
- 4. Detector = peak.
- 5. Trace Mode = max hold.
- 6. Sweep = auto couple.

7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified above.

Measurement Limit:

| Standard | Limit |
|----------------------------|---|
| FCC 47 CFR Part 15.247 (d) | 20dB below peak output power in 100 kHz |
| FCC 47 CFR Fait 15.247 (d) | bandwidth |

Measurement Results:

For GFSK

| Channel | Frequency Range | Test Results | Conclusion |
|---------|------------------|--------------|------------|
| Ch 0 | Center Frequency | Fig.13 | Р |

©Copyright. All rights reserved by CTTL.





| 2402 MHz | 30 MHz ~ 1 GHz | Fig.14 | Р |
|-------------------|--|--|---|
| | 1 GHz ~ 3 GHz | Fig.15 | Р |
| | 3 GHz ~ 10 GHz | Fig.16 | Р |
| | 10 GHz ~ 26 GHz | Fig.17 | Р |
| | Center Frequency | Fig.18 | Р |
| | 30 MHz ~ 1 GHz | Fig.19 | Р |
| Ch 39 2441 MHz | 1 GHz ~ 3 GHz | Fig.20 | Р |
| | 3 GHz ~ 10 GHz | Fig.21 | Р |
| | 10 GHz ~ 26 GHz | Fig.22 | Р |
| | Center Frequency | Fig.23 | Р |
| | 30 MHz ~ 1 GHz | Fig.24 | Р |
| Ch 78 2480 MHz | 1 GHz ~ 3 GHz | Fig.25 | Р |
| 2400 10112 | 3 GHz ~ 10 GHz | Fig.26 | Р |
| | 10 GHz ~ 26 GHz | Fig.27 | Р |
| For π/4 DQPSK | | | |
| Channel | Frequency Range | Test Results | Conclusion |
| | Center Frequency | Fig.28 | Р |
| Ch 0 | 30 MHz ~ 1 GHz | Fig.29 | Р |
| 2402 MHz | 1 GHz ~ 3 GHz | Fig.30 | Р |
| 210210112 | 3 GHz ~ 10 GHz | Fig.31 | Р |
| | 10 GHz ~ 26 GHz | Fig.32 | D |
| | | 1 19.52 | P |
| | Center Frequency | Fig.33 | P P |
| | | _ | |
| Ch 39 | Center Frequency | Fig.33 | Р |
| Ch 39 2441 MHz | Center Frequency 30 MHz ~ 1 GHz | Fig.33 Fig.34 | P P |
| | Center Frequency 30 MHz ~ 1 GHz 1 GHz ~ 3 GHz | Fig.33 Fig.34 Fig.35 | P P P |
| | Center Frequency 30 MHz ~ 1 GHz 1 GHz ~ 3 GHz 3 GHz ~ 10 GHz | Fig.33 Fig.34 Fig.35 Fig.36 | P P P P |
| 2441 MHz | Center Frequency30 MHz ~ 1 GHz1 GHz ~ 3 GHz3 GHz ~ 10 GHz10 GHz ~ 26 GHz | Fig.33 Fig.34 Fig.35 Fig.36 Fig.37 | P P P P P P |
| 2441 MHz Ch 78 | Center Frequency30 MHz ~ 1 GHz1 GHz ~ 3 GHz3 GHz ~ 10 GHz10 GHz ~ 26 GHzCenter Frequency | Fig.33 Fig.34 Fig.35 Fig.36 Fig.37 Fig.38 | P P P P P P P |
| 2441 MHz | Center Frequency30 MHz ~ 1 GHz1 GHz ~ 3 GHz3 GHz ~ 10 GHz10 GHz ~ 26 GHzCenter Frequency30 MHz ~ 1 GHz | Fig.33 Fig.34 Fig.35 Fig.36 Fig.37 Fig.38 Fig.39 | P P P P P P P P P |

For 8DPSK

| Channel | Frequency Range | Test Results | Conclusion |
|------------------|------------------|--------------|------------|
| Ch 0 2402 MHz | Center Frequency | Fig.43 | Р |
| | 30 MHz ~ 1 GHz | Fig.44 | Р |
| | 1 GHz ~ 3 GHz | Fig.45 | Р |
| | 3 GHz ~ 10 GHz | Fig.46 | Р |
| | 10 GHz ~ 26 GHz | Fig.47 | Р |





| Ch 39 2441 MHz | Center Frequency | Fig.48 | Р |
|-------------------|------------------|--------|---|
| | 30 MHz ~ 1 GHz | Fig.49 | Р |
| | 1 GHz ~ 3 GHz | Fig.50 | Р |
| | 3 GHz ~ 10 GHz | Fig.51 | Р |
| | 10 GHz ~ 26 GHz | Fig.52 | Р |
| Ch 78 2480 MHz | Center Frequency | Fig.53 | Р |
| | 30 MHz ~ 1 GHz | Fig.54 | Р |
| | 1 GHz ~ 3 GHz | Fig.55 | Р |
| | 3 GHz ~ 10 GHz | Fig.56 | Р |
| | 10 GHz ~ 26 GHz | Fig.57 | Р |

Conclusion: PASS

Test graphs as below




Fig.13. Conducted spurious emission: GFSK, Channel 0,2402MHz








Fig.14. Conducted spurious emission: GFSK, Channel 0, 30MHz - 1GHz




Fig.15. Conducted spurious emission: GFSK, Channel 0, 1GHz - 3GHz








Fig.16. Conducted spurious emission: GFSK, Channel 0, 3GHz - 10GHz




Fig.17. Conducted spurious emission: GFSK, Channel 0,10GHz - 26GHz








Fig.18. Conducted spurious emission: GFSK, Channel 39, 2441MHz




Fig.19. Conducted spurious emission: GFSK, Channel 39, 30MHz - 1GHz








Fig.20. Conducted spurious emission: GFSK, Channel 39, 1GHz – 3GHz




Fig.21. Conducted spurious emission: GFSK, Channel 39, 3GHz – 10GHz








Fig.22. Conducted spurious emission: GFSK, Channel 39, 10GHz – 26GHz




Fig.23. Conducted spurious emission: GFSK, Channel 78, 2480MHz








Fig.24. Conducted spurious emission: GFSK, Channel 78, 30MHz - 1GHz




Fig.25. Conducted spurious emission: GFSK, Channel 78, 1GHz - 3GHz








Fig.26. Conducted spurious emission: GFSK, Channel 78, 3GHz - 10GHz




Fig.27. Conducted spurious emission: GFSK, Channel 78, 10GHz - 26GHz








Fig.28. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0,2402MHz




Fig.29. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0, 30MHz - 1GHz








Fig.30. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0, 1GHz - 3GHz




Fig.31. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0, 3GHz - 10GHz








Fig.32. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0,10GHz - 26GHz




Fig.33. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 2441MHz








Fig.34. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 30MHz - 1GHz




Fig.35. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 1GHz - 3GHz








Fig.36. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 3GHz - 10GHz




Fig.37. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 10GHz – 26GHz








Fig.38. Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 2480MHz




Fig.39. Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 30MHz - 1GHz








Fig.40. Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 1GHz - 3GHz




Fig.41. Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 3GHz - 10GHz








Fig.42. Conducted spurious emission: π/4 DQPSK, Channel 78, 10GHz - 26GHz




Fig.43. Conducted spurious emission: 8DPSK, Channel 0,2402MHz








Fig.44. Conducted spurious emission: 8DPSK, Channel 0, 30MHz - 1GHz




Fig.45. Conducted spurious emission: 8DPSK, Channel 0, 1GHz - 3GHz








Fig.46. Conducted spurious emission: 8DPSK, Channel 0, 3GHz - 10GHz




Fig.47. Conducted spurious emission: 8DPSK, Channel 0,10GHz - 26GHz