















































Conclusion: Pass





A.4. DTS 6-dB Signal Bandwidth

Method of Measurement: See ANSI C63.10-2013 section 11.8.1.

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) = 300 kHz.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measurement Limit:

Standard	Limit (kHz)	
FCC 47 CFR Part 15.247 (a)	≥ 500	

EUT ID: UT11a

Measurement Result:

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Verdict
11B Ant6		2412	8.04	2407.96	2416.00	PASS
	2437	8.80	2432.72	2441.52	PASS	
		2462	8.60	2457.48	2466.08	PASS
		2412	16.52	2403.72	2420.24	PASS
11G Ant6	Ant6	2437	16.52	2428.72	2445.24	PASS
		2462	16.48	2453.72	2470.20	PASS
11N20SISO		2412	17.72	2403.12	2420.84	PASS
	Ant6	2437	17.72	2428.12	2445.84	PASS
		2462	17.68	2453.12	2470.80	PASS
11AX40SISO Ant6		2422	38.16	2402.88	2441.04	PASS
	2437	38.16	2417.88	2456.04	PASS	
		2452	38.16	2432.88	2471.04	PASS
Ante 11N20MIMO Ante Ante	Ant6	2412	17.72	2403.12	2420.84	PASS
	Ant10	2412	17.68	2403.16	2420.84	PASS
	Ant6	2437	17.72	2428.12	2445.84	PASS
	Ant10	2437	17.72	2428.12	2445.84	PASS
	Ant6	2462	17.72	2453.12	2470.84	PASS
	Ant10	2462	17.72	2453.12	2470.84	PASS
	Ant6	2422	34.48	2405.04	2439.52	PASS
11N40MIMO	Ant10	2422	34.48	2404.40	2438.88	PASS
	Ant6	2437	34.48	2420.04	2454.52	PASS
	Ant10	2437	32.64	2421.88	2454.52	PASS

©Copyright. All rights reserved by CTTL.





Ant6	2452	35.04	2434.48	2469.52	PASS
Ant10	2452	35.04	2434.48	2469.52	PASS

Test graphs as below:













