



Test Report

Report No.: MTi20103015-1E1

Date of issue: Feb. 23, 2021

Applicant: Shenzhen Smarteye Digital
Electronics Co., Ltd

Product name: IP Camera

792JBU, 758JC4(W5S), 793JBU,
Model(s): 793JC4, 709JD3, 761JBU,
762JC4, 764JBU, 792JBU(W9),
Q7, 794JBU

FCC ID: ZCB-792JBU

Shenzhen Microtest Co., Ltd.
<http://www.mtitest.com>



Instructions

1. The report shall not be partially reproduced without the written consent of the laboratory;
2. The test results of this report are only responsible for the samples submitted;
3. This report is invalid without the seal and signature of the laboratory;
4. This report is invalid if transferred, altered or tampered with in any form without authorization;
5. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.



Table of Contents

1 GENERAL INFORMATION	6
1.1 DESCRIPTION OF EUT	6
1.2 OPERATION CHANNEL LIST	7
1.3 TEST CHANNEL LIST	7
1.4 ANCILLARY EQUIPMENT LIST	7
1.5 DESCRIPTION OF SUPPORT UNITS	8
2 SUMMARY OF TEST RESULTS	9
3 TEST FACILITIES AND ACCREDITATIONS.....	10
3.1 TEST LABORATORY	10
3.2 ENVIRONMENTAL CONDITIONS	10
3.3 MEASUREMENT UNCERTAINTY	10
3.4 TEST SOFTWARE	10
4 EQUIPMENT LIST	11
5 TEST RESULT	12
5.1 ANTENNA REQUIREMENT	12
5.1.1 Standard requirement	12
5.1.2 EUT antenna	12
5.2 PEAK OUTPUT POWER	13
5.2.1 Limit	13
5.2.2 Test setup	13
5.2.3 Test procedure	13
5.2.4 Test results	14
5.3 POWER SPECTRAL DENSITY	15
5.3.1 Limit	15
5.3.2 Test setup	15
5.3.3 Test procedure	15
5.3.4 Test results	16
5.4 CONDUCTED EMISSION	20
5.4.1 Limits	20
5.4.2 Test setup	20
5.4.3 Test procedure	21
5.4.4 Test results	21
5.5 RADIATED SPURIOUS	26
5.5.1 Limits	26
5.5.2 Test setup	27
5.5.3 Test procedure	28
5.5.4 Test results	29
5.5.4.1 Radiation emission	29
5.5.4.2 Band edge - radiated	33
5.5.5 Spurious Emission in Restricted Band 3260MHz-18000MHz	35
5.6 BAND EDGE - CONDUCTED	36
5.6.1 Limits	36
5.6.2 Test setup	36
5.6.3 Test procedure	36
5.6.4 Test results	37
5.7 6DB BANDWIDTH	41
5.7.1 Limit	41
5.7.2 Test setup	41
5.7.3 Test procedure	41
5.7.4 Test results	41
5.8 DUTY CYCLE	50
5.8.1 Limit	50



5.8.2	<i>Measuring instruments</i>	50
5.8.3	<i>Test setup</i>	50
5.8.4	<i>Test procedure</i>	50
5.8.5	<i>Test Results</i>	51
5.9	SPURIOUS RF CONDUCTED EMISSIONS	52
5.9.1	<i>Limit</i>	52
5.9.2	<i>Measuring instruments</i>	52
5.9.3	<i>Test setup</i>	52
5.9.4	<i>Test procedure</i>	52
5.9.5	<i>Test results</i>	52
PHOTOGRAPHS OF THE TEST SETUP		55
PHOTOGRAPHS OF THE EUT		57



TEST RESULT CERTIFICATION

Applicant's name.....	Shenzhen Smarteye Digital Electronics Co., Ltd
Address.....	#6 Northern Area, Shangxue S&T Industrial Park, Bantian, Longgang, Shenzhen
Manufacturer's Name	Shenzhen Smarteye Digital Electronics Co., Ltd
Address.....	#6 Northern Area, Shangxue S&T Industrial Park, Bantian, Longgang, Shenzhen

Product description

Product name	IP Camera
Trademark	N/A
Model Name	792JBU
Serial Model.....	758JC4(W5S), 793JBU, 793JC4, 709JD3, 761JBU, 762JC4, 764JBU, 792JBU(W9), Q7, 794JBU
Standards.....	FCC Part 15.247
Test procedure	ANSI C63.10-2013 KDB 558074 D01 D15.247 Meas Guidance v05r02

Date of Test

Date (s) of performance of tests	Nov. 16, 2020 ~ Feb. 05, 2021
Test Result.....	Pass

This device described above has been tested by Shenzhen Microtest Co., Ltd. and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Testing Engineer

:

(Danny Xu)

Technical Manager

:

(Leo Su)

Authorized Signatory

:

(Tom Xue)



1 General information

1.1 Description of EUT

Product name:	IP Camera
Model name:	792JBU
Serial model:	758JC4(W5S), 793JBU, 793JC4, 709JD3, 761JBU, 762JC4, 764JBU, 792JBU(W9), Q7, 794JBU
Model difference:	All the models are the same circuit and module, except the color and model No..
Operation frequency:	802.11b/g/n20:2412~2462 MHz 802.11n40:2422~2452 MHz
Modulation type:	IEEE 802.11b : DSSS (DBPSK, DQPSK, CCK) IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Bit Rate of transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n(20MHz) use 800 ns GI: 65.0/58.5/52.0/39.0/26.0/19.5/13.0/6.5 Mbps (MCS0~MCS7) 802.11n(40MHz) use 800 ns GI: 13.5/27/40.5/54/81/108/121.5/135Mbps
Antenna type:	External Antenna
Antenna gain:	5dBi
Max. output power:	13.50dBm
Power supply:	DC 5V from adapter AC 120V/60Hz
Adapter information:	Model: G006A0501000U Input: 100V-240V~ 50/60Hz 0.3A Output: DC 5V 1A
Hardware version:	V1.0
Software version:	V1.0
Serial number:	MTi20103015-1-S0001



1.2 Operation channel list

Channel List for 802.11b/g/n (20)

Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	11	2462
06	2437	\	\

Channel List for 802.11n (40)

Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	07	2442
04	2427	08	2447
05	2432	09	2452
06	2437	\	\

1.3 Test channel list

Channel List for 802.11b/g/n (20)

Channel	Channel	Frequency (MHz)
Low	01	2412
Middle	06	2437
High	11	2462

Channel List for 802.11n (40)

Channel	Channel	Frequency (MHz)
Low	03	2422
Middle	06	2437
High	09	2452

1.4 Ancillary equipment list

Equipment	Model	S/N	Manufacturer	Certificate type
/	/	/	/	/



1.5 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
/	/	/	/	/	/

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2 Summary of Test Results

Test procedures according to the technical standards:

No.	Standard Section	Test Item	Result	Remark
1	15.203	Antenna Requirement	Pass	
2	15.247 (b)	Peak Output Power	Pass	
3	15.247 (e)	Power Spectral Density	Pass	
4	15.207	Conducted Emission	Pass	
5	15.247 (d) & 15.209	Radiated Spurious Emission	Pass	
6	15.205	Band Edge Emission	Pass	
7	15.247 (a)(2)	6dB Bandwidth	Pass	
8	558074 D01 15.247 Meas Guidance v05r02 Chapter 6	Duty Cycle	Pass	
9	15.247(d)	Spurious RF Conducted Emissions	Pass	



3 Test Facilities and Accreditations

3.1 Test laboratory

Test Laboratory	Shenzhen Microtest Co., Ltd
Location	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao' an District, Shenzhen, Guangdong, China.
FCC Registration No.:	448573

3.2 Environmental conditions

Temperature:	15°C~35°C
Humidity	20%~75%
Atmospheric pressure	98kPa~101kPa

3.3 Measurement uncertainty

The reported uncertainty of measurement $y \pm U$ · where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ · providing a level of confidence of approximately 95 %

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated(<1G)	±4.68dB
5	All emissions, radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

3.4 Test software

Software Name	Manufacturer	Model	Version
Bluetooth and WiFi Test System	Shenzhen JS tonscent co., ltd	JS1120-3	2.5.77.0418



4 Equipment list

Equipment No.	Equipment Name	Manufacturer	Model	Serial No.	Calibration date	Due date
MTI-E043	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2020/06/04	2021/06/03
MTI-E044	TRILOG Broadband Antenna	schwarzb eck	VULB 9163	9163-133 8	2020/06/05	2021/06/04
MTI-E047	Amplifier	Hewlett-P ackard	8447F	3113A061 50	2020/06/04	2021/06/03
MTI-E089	ESG Vector Signal Generator	Agilent	N5182A	MY49060 455	2020/06/03	2021/06/02
MTI-E058	ESG Series Analog Ssignal Generator	Agilent	E4421B	GB40051 240	2020/07/03	2021/07/04
MTI-E062	PXA Signal Analyzer	Agilent	N9030A	MY51350 296	2020/06/04	2021/06/03
MTI-E066	MXA Signal Analyzer	Agilent	N9020A	MY50143 483	2020/06/04	2021/06/03
MTI-E078	Synthesized Sweeper	Agilent	83752A	3610A019 57	2020/06/04	2021/06/03
MTI-E079	DC Power Supply	Agilent	E3632A	MY40027 695	2020/06/04	2021/06/03
MTI-E045	Double Ridged Broadband Horn Antenna	schwarzb eck	BBHA 9120 D	9120D-22 78	2020/06/05	2021/06/04
MTI-E021	EMI Test Receiver	Rohde&schwarz	ESCS30	100210	2020/06/04	2021/06/03
MTI-E022	Pulse Limiter	Schwarzbe ck	VSTD 9561-F	00679	2020/06/03	2021/06/02
MTI-E023	Artificial mains network	Schwarzbe ck	NSLK 8127	NSLK 8127 #841	2020/06/04	2021/06/03
MTI-E046	Active Loop Antenna	Schwarzbe ck	FMZB 1519 B	00044	2020/06/05	2021/06/04
MTI-E048	Amplifier	Agilent	8449B	3008A024 00	2020/07/03	2021/07/04
MTI-E072	Thermometer Clock Humidity Monitor	-	HTC-1	/	2020/06/07	2021/06/06
MTI-E095	Horn Antenna	Schwarzbe ck	BBHA 9170	9170-181	2019/04/16	2021/04/15
MTI-E096	RF Power Sensor	DARE!! Instrument s	RadiPower RPR3006W	17I00015 SNO26	2019/04/16	2021/04/15

Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



5 Test Result

5.1 Antenna requirement

5.1.1 Standard requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

5.1.2 EUT antenna

The EUT antenna is External antenna (5dBi). It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.




5.2 Peak output power

5.2.1 Limit

Section	Test Item	Limit	Frequency Range (MHz)
15.247(b)(3)	Peak output power	1 watt or 30dBm	2400-2483.5

5.2.2 Test setup



5.2.3 Test procedure

The EUT was directly connected to the Power meter.



5.2.4 Test results

802.11b

Test Channel	Frequency (MHz)	Maximum Peak Conducted Output Power(dBm)	Limit (dBm)
CH01	2412	12.68	30
CH06	2437	13.50	30
CH11	2462	13.18	30

802.11g

Test Channel	Frequency (MHz)	Maximum Peak Conducted Output Power(dBm)	Limit (dBm)
CH01	2412	8.64	30
CH06	2437	11.59	30
CH11	2462	11.33	30

802.11n20

Test Channel	Frequency (MHz)	Maximum Peak Conducted Output Power(dBm)	Limit (dBm)
CH01	2412	8.64	30
CH06	2437	11.43	30
CH11	2462	11.26	30

802.11n40

Test Channel	Frequency (MHz)	Maximum Peak Conducted Output Power(dBm)	Limit (dBm)
CH03	2422	10.82	30
CH06	2437	10.91	30
CH09	2452	11.21	30




5.3 Power spectral density

5.3.1 Limit

Section	Test Item	Limit	Frequency Range (MHz)
15.247(e)	Power Spectral Density	8 dBm (in any 3kHz)	2400-2483.5

5.3.2 Test setup



5.3.3 Test procedure


- a. The EUT tested system was configured as the statements of 2.1 unless otherwise a special operating condition is specified in the follows during the testing.
- b. Set analyzer center frequency to DTS channel center frequency.
- c. Set the span to 1.5 times the DTS channel bandwidth.
- d. Set the RBW \geq 3 kHz.
- e. Set the VBW \geq 3 x RBW.
- f. Detector = peak.
- g. Sweep time = auto couple.
- h. Trace mode = max hold.
- i. Allow trace to fully stabilize.
- j. Use the peak marker function to determine the maximum amplitude level.
- k. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



5.3.4 Test results

802.11b



Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2412 MHz	-8.779	8	Pass
2437 MHz	-9.176	8	Pass
2462 MHz	-7.776	8	Pass





802.11g



Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2412 MHz	-14.926	8	Pass
2437 MHz	-12.911	8	Pass
2462 MHz	-12.672	8	Pass





802.11n20



Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2412 MHz	-15.875	8	Pass
2437 MHz	-13.418	8	Pass
2462 MHz	-13.219	8	Pass





802.11n40

Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2422 MHz	-17.115	8	Pass
2437 MHz	-16.399	8	Pass
2452 MHz	-16.961	8	Pass





5.4 Conducted emission


5.4.1 Limits

According to FCC Part 15.207(a) and KDB 174176 D01 Line Conducted FAQ v01r01.

FREQUENCY (MHz)	Class B (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note: *Decreases with the logarithm of the frequency..

5.4.2 Test setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes



5.4.3 Test procedure

a. EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b. The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

- c. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- d. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- e. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- f. LISN at least 80 cm from nearest part of EUT chassis.

For the actual test configuration, please refer to the related Item –EUT Test Photos.

5.4.4 Test results


Note:

1. All the modulation modes have been tested, the report only shows the worst mode. The worst mode is 802.11b CH06
2. Emission Level =Reading Level + Factor, Margin= Emission Level- Limit, Factor = LISN modulus + Cable Loss



Test data


EUT:	IP Camera	Model Name:	792JBU
Pressure:	1010hPa	Phase::	L
Test Voltage:	DC 5V from adapter AC 120V/60Hz	Test Mode:	TX



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.4178	32.01	9.87	41.88	57.49	-15.61	QP
2		0.4178	5.50	9.87	15.37	47.49	-32.12	AVG
3		0.5340	28.07	9.93	38.00	56.00	-18.00	QP
4		0.5340	2.00	9.93	11.93	46.00	-34.07	AVG
5		0.6540	23.28	9.95	33.23	56.00	-22.77	QP
6		0.6540	-0.66	9.95	9.29	46.00	-36.71	AVG
7		1.6100	22.26	10.02	32.28	56.00	-23.72	QP
8		1.6100	-0.21	10.02	9.81	46.00	-36.19	AVG
9		2.6300	20.88	10.07	30.95	56.00	-25.05	QP
10		2.6300	-2.65	10.07	7.42	46.00	-38.58	AVG
11		5.3379	28.79	10.20	38.99	60.00	-21.01	QP
12		5.3379	7.32	10.20	17.52	50.00	-32.48	AVG




EUT:	IP Camera	Model Name:	792JBU
Pressure:	1010hPa	Phase::	N
Test Voltage:	DC 5V from adapter AC 120V/60Hz	Test Mode:	TX



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.4778	34.58	9.91	44.49	56.38	-11.89	QP
2		0.4778	22.90	9.91	32.81	46.38	-13.57	AVG
3		0.6700	27.12	9.95	37.07	56.00	-18.93	QP
4		0.6700	14.93	9.95	24.88	46.00	-21.12	AVG
5		3.6539	33.92	10.12	44.04	56.00	-11.96	QP
6		3.6539	22.82	10.12	32.94	46.00	-13.06	AVG
7		4.3900	36.94	10.15	47.09	56.00	-8.91	QP
8		4.3900	26.46	10.15	36.61	46.00	-9.39	AVG
9		5.8578	39.99	10.23	50.22	60.00	-9.78	QP
10		5.8578	27.52	10.23	37.75	50.00	-12.25	AVG
11		23.1299	37.24	10.51	47.75	60.00	-12.25	QP
12	*	23.1299	32.73	10.51	43.24	50.00	-6.76	AVG




EUT:	IP Camera	Model Name:	792JBU
Pressure:	1010hPa	Phase:	L
Test Voltage:	DC 5V from adapter AC 240V/60Hz	Test Mode:	TX



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2620	24.34	9.75	34.09	61.37	-27.28	QP
2		0.2620	1.02	9.75	10.77	51.37	-40.60	AVG
3		0.4178	30.01	9.87	39.88	57.49	-17.61	QP
4		0.4178	4.50	9.87	14.37	47.49	-33.12	AVG
5	*	0.5340	29.07	9.93	39.00	56.00	-17.00	QP
6		0.5340	4.08	9.93	14.01	46.00	-31.99	AVG
7		1.6100	24.76	10.02	34.78	56.00	-21.22	QP
8		1.6100	2.29	10.02	12.31	46.00	-33.69	AVG
9		5.3379	25.79	10.20	35.99	60.00	-24.01	QP
10		5.3379	4.90	10.20	15.10	50.00	-34.90	AVG
11		6.7778	14.76	10.28	25.04	60.00	-34.96	QP
12		6.7778	-1.96	10.28	8.32	50.00	-41.68	AVG



EUT:	IP Camera	Model Name:	792JBU
Pressure:	1010hPa	Phase:	N
Test Voltage:	DC 5V from adapter AC 240V/60Hz	Test Mode:	TX



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	dB Over Detector	Over
1		0.2620	27.34	9.75	37.09	61.37	-24.28	QP
2		0.2620	5.17	9.75	14.92	51.37	-36.45	AVG
3	*	0.4178	32.01	9.87	41.88	57.49	-15.61	QP
4		0.4178	4.06	9.87	13.93	47.49	-33.56	AVG
5		0.6540	24.78	9.95	34.73	56.00	-21.27	QP
6		0.6540	1.64	9.95	11.59	46.00	-34.41	AVG
7		1.6100	24.76	10.02	34.78	56.00	-21.22	QP
8		1.6100	4.08	10.02	14.10	46.00	-31.90	AVG
9		5.3379	25.29	10.20	35.49	60.00	-24.51	QP
10		5.3379	0.28	10.20	10.48	50.00	-39.52	AVG
11		29.8300	14.33	10.73	25.06	60.00	-34.94	QP
12		29.8300	4.12	10.73	14.85	50.00	-35.15	AVG



5.5 Radiated spurious

5.5.1 Limits

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP




5.5.2 Test setup


Radiated emission test-up frequency below 30MHz



Radiated emission test-up frequency 30MHz~1GHz



Radiated emission test-up frequency above 1GHz





5.5.3 Test procedure

- a. EUT operating conditions. The EUT tested system was configured as the statements of 2.4 unless otherwise a special operating condition is specified in the follows during the testing.
- b. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- c. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For emission measurements above 1 GHz, the EUT shall be placed at a height of 1.5 m above the floor on a support that is RF transparent for the frequencies of interest. Final measurements for the EUT require a measurement antenna height scan of 1 m to 4 m.
- f. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- h. For the actual test configuration, please refer to the related Item –EUT Test photos.

Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported



5.5.4 Test results

5.5.4.1 Radiation emission

Below 30MHz

EUT:	IP Camera	Model Name:	792JBU
Pressure:	1010 hPa	Phase:	H
Test Mode:	TX	Test Voltage:	DC 5V from adapter AC 120V/60Hz

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State
--	--	--	--	Pass
--	--	--	--	Pass


Note:

1. For 9k-30MHz, the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = $40 \log(\text{specific distance}/\text{test distance})$ (dB).
3. Limit line = specific limits (dBuV) + distance extrapolation factor.



Between 30MHz – 1GHz


EUT:	IP Camera	Model Name:	792JBU
Pressure:	1010 hPa	Phase:	H
Test Mode:	TX	Test Voltage:	DC 5V from adapter AC 120V/60Hz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	55.8047	28.12	-14.17	13.95	40.00	-26.05	QP
2	170.1948	40.92	-16.07	24.85	43.50	-18.65	QP
3 !	237.4760	52.85	-12.49	40.36	46.00	-5.64	QP
4 *	274.1939	52.14	-11.29	40.85	46.00	-5.15	QP
5	357.9287	43.81	-9.58	34.23	46.00	-11.77	QP
6	588.9050	38.17	-5.16	33.01	46.00	-12.99	QP



EUT:	IP Camera	Model Name:	792JBU
Pressure:	1010 hPa	Phase:	V
Test Mode:	TX	Test Voltage:	DC 5V from adapter AC 120V/60Hz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	38.8878	39.62	-14.35	25.27	40.00	-14.73	QP
2	125.0066	51.34	-16.47	34.87	43.50	-8.63	QP
3 *	243.3772	53.29	-12.30	40.99	46.00	-5.01	QP
4	286.9823	44.84	-10.87	33.97	46.00	-12.03	QP
5	375.9385	43.57	-9.34	34.23	46.00	-11.77	QP
6	420.5803	46.28	-8.59	37.69	46.00	-8.31	QP

Note:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level- Limit, Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. The three modulated high, medium and low channels have been tested. The report only shows the worst mode. The worst mode is 802.11b CH06.



1GHz-25GHz

Frequency (MHz)	Read Level (dB μ V)	Cable loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Remark	Comment

Low Channel (2412 MHz)(802.11b)--Above 1G

4824.161	62.58	4.36	32.92	45.53	54.33	74.00	-19.67	Pk	Vertical
4824.161	43.56	4.36	32.92	45.53	35.31	54.00	-18.69	AV	Vertical
7236.396	60.47	5.02	37.63	45.56	57.56	74.00	-16.44	Pk	Vertical
7236.396	40.76	5.02	37.63	45.56	37.85	54.00	-16.15	AV	Vertical
4824.154	62.58	4.36	32.92	45.53	54.33	74.00	-19.67	Pk	Horizontal
4824.154	42.91	4.36	32.92	45.53	34.66	54.00	-19.34	AV	Horizontal
7236.168	63.76	5.02	37.63	45.56	60.85	74.00	-13.15	Pk	Horizontal
7236.168	42.85	5.02	37.63	45.56	39.94	54.00	-14.06	AV	Horizontal

Middle Channel (2437 MHz)(802.11b)--Above 1G

4874.112	63.30	4.41	33.01	45.76	54.96	74.00	-19.04	Pk	Vertical
4874.112	43.53	4.41	33.01	45.76	35.19	54.00	-18.81	AV	Vertical
7311.247	59.85	5.02	37.68	45.59	56.96	74.00	-17.04	Pk	Vertical
7311.247	41.33	5.02	37.68	45.59	38.44	54.00	-15.56	AV	Vertical
4874.132	63.36	4.41	33.01	45.76	55.02	74.00	-18.98	Pk	Horizontal
4874.132	44.65	4.41	33.01	45.76	36.31	54.00	-17.69	AV	Horizontal
7311.085	61.57	5.02	37.68	45.59	58.68	74.00	-15.32	Pk	Horizontal
7311.085	43.10	5.02	37.68	45.59	40.21	54.00	-13.79	AV	Horizontal

High Channel (2462 MHz)(802.11b)--Above 1G

4924.169	63.95	4.50	33.26	46.07	55.64	74.00	-18.36	Pk	Vertical
4924.169	43.81	4.50	33.26	46.07	35.50	54.00	-18.50	AV	Vertical
7386.215	61.42	5.02	37.78	45.77	58.45	74.00	-15.55	Pk	Vertical
7386.215	40.59	5.02	37.78	45.77	37.62	54.00	-16.38	AV	Vertical
4924.045	64.21	4.50	33.26	46.07	55.90	74.00	-18.10	Pk	Horizontal
4924.045	44.74	4.50	33.26	46.07	36.43	54.00	-17.57	AV	Horizontal
7386.132	60.97	5.02	37.78	45.77	58.00	74.00	-16.00	Pk	Horizontal
7386.132	42.57	5.02	37.78	45.77	39.60	54.00	-14.40	AV	Horizontal

Note:

1. Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
2. All other emissions more than 20dB below the limit.
3. The three modulated high, medium and low channels have been tested. The report only shows the worst mode. The worst mode is 802.11b.



5.5.4.2 Band edge - radiated

Frequency (MHz)	Read Level (dB μ V)	Cable loss (dB)	Antenna Factor	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Remark	Comment

802.11b									
2310.00	59.40	2.40	27.70	40.40	49.10	74	-24.90	Pk	Horizontal
2310.00	43.51	2.40	27.70	40.40	33.21	54	-20.79	AV	Horizontal
2310.00	58.58	2.40	27.70	40.40	48.28	74	-25.72	Pk	Vertical
2310.00	41.92	2.40	27.70	40.40	31.62	54	-22.38	AV	Vertical
2390.00	57.93	2.44	28.30	40.10	48.57	74	-25.43	Pk	Vertical
2390.00	41.98	2.44	28.30	40.10	32.62	54	-21.38	AV	Vertical
2390.00	57.08	2.44	28.30	40.10	47.72	74	-26.28	Pk	Horizontal
2390.00	42.01	2.44	28.30	40.10	32.65	54	-21.35	AV	Horizontal
2483.50	57.77	2.48	28.70	39.80	49.15	74	-24.85	Pk	Vertical
2483.50	43.45	2.48	28.70	39.80	34.83	54	-19.17	AV	Vertical
2483.50	59.26	2.48	28.70	39.80	50.64	74	-23.36	Pk	Horizontal
2483.50	41.38	2.48	28.70	39.80	32.76	54	-21.24	AV	Horizontal

802.11g									
2310.00	59.03	2.40	27.70	40.40	48.73	74	-25.27	Pk	Horizontal
2310.00	44.19	2.40	27.70	40.40	33.89	54	-20.11	AV	Horizontal
2310.00	56.94	2.40	27.70	40.40	46.64	74	-27.36	Pk	Vertical
2310.00	42.52	2.40	27.70	40.40	32.22	54	-21.78	AV	Vertical
2390.00	58.22	2.44	28.30	40.10	48.86	74	-25.14	Pk	Vertical
2390.00	42.49	2.44	28.30	40.10	33.13	54	-20.87	AV	Vertical
2390.00	57.83	2.44	28.30	40.10	48.47	74	-25.53	Pk	Horizontal
2390.00	44.29	2.44	28.30	40.10	34.93	54	-19.07	AV	Horizontal
2483.50	58.81	2.48	28.70	39.80	50.19	74	-23.81	Pk	Vertical
2483.50	44.32	2.48	28.70	39.80	35.70	54	-18.30	AV	Vertical
2483.50	58.71	2.48	28.70	39.80	50.09	74	-23.91	Pk	Horizontal
2483.50	41.86	2.48	28.70	39.80	33.24	54	-20.76	AV	Horizontal



802.11n20									
2310.00	57.78	2.40	27.70	40.40	47.48	74	-26.52	Pk	Horizontal
2310.00	43.70	2.40	27.70	40.40	33.40	54	-20.60	AV	Horizontal
2310.00	59.23	2.40	27.70	40.40	48.93	74	-25.07	Pk	Vertical
2310.00	42.56	2.40	27.70	40.40	32.26	54	-21.74	AV	Vertical
2390.00	57.42	2.44	28.30	40.10	48.06	74	-25.94	Pk	Vertical
2390.00	42.11	2.44	28.30	40.10	32.75	54	-21.25	AV	Vertical
2390.00	56.79	2.44	28.30	40.10	47.43	74	-26.57	Pk	Horizontal
2390.00	42.25	2.44	28.30	40.10	32.89	54	-21.11	AV	Horizontal
2483.50	58.13	2.48	28.70	39.80	49.51	74	-24.49	Pk	Vertical
2483.50	42.68	2.48	28.70	39.80	34.06	54	-19.94	AV	Vertical
2483.50	59.10	2.48	28.70	39.80	50.48	74	-23.52	Pk	Horizontal
2483.50	42.26	2.48	28.70	39.80	33.64	54	-20.36	AV	Horizontal
802.11n40									
2310.00	59.08	2.40	27.70	40.40	48.78	74	-25.22	Pk	Horizontal
2310.00	44.50	2.40	27.70	40.40	34.20	54	-19.80	AV	Horizontal
2310.00	57.26	2.40	27.70	40.40	46.96	74	-27.04	Pk	Vertical
2310.00	43.83	2.40	27.70	40.40	33.53	54	-20.47	AV	Vertical
2390.00	58.42	2.44	28.30	40.10	49.06	74	-24.94	Pk	Vertical
2390.00	42.14	2.44	28.30	40.10	32.78	54	-21.22	AV	Vertical
2390.00	57.91	2.44	28.30	40.10	48.55	74	-25.45	Pk	Horizontal
2390.00	44.10	2.44	28.30	40.10	34.74	54	-19.26	AV	Horizontal
2483.50	58.32	2.48	28.70	39.80	49.70	74	-24.30	Pk	Vertical
2483.50	44.25	2.48	28.70	39.80	35.63	54	-18.37	AV	Vertical
2483.50	58.62	2.48	28.70	39.80	50.00	74	-24.00	Pk	Horizontal
2483.50	42.14	2.48	28.70	39.80	33.52	54	-20.48	AV	Horizontal

Note:

1. All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
2. Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor.
3. All the modulation modes have been tested, and only the worst results are reflected in the report.



5.5.5 Spurious Emission in Restricted Band 3260MHz-18000MHz

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Read Level (dB μ V)	Cable loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB)	Margin (dB)	Remark	Comment
3260	60.67	3.27	30.02	38.05	55.91	74	-18.09	Pk	Vertical
3260	39.26	3.27	30.02	38.05	34.50	54	-19.50	AV	Vertical
3260	59.19	3.27	30.02	38.05	54.43	74	-19.57	Pk	Horizontal
3260	36.40	3.27	30.02	38.05	31.64	54	-22.36	AV	Horizontal
3332	60.34	3.31	30.00	37.91	55.74	74	-18.26	Pk	Vertical
3332	39.25	3.31	30.00	37.91	34.65	54	-19.35	AV	Vertical
3332	60.34	3.31	30.00	37.91	55.74	74	-18.26	Pk	Horizontal
3332	35.60	3.31	30.00	37.91	31.00	54	-23.00	AV	Horizontal
17797	43.09	8.63	44.23	39.60	56.35	74	-17.65	Pk	Vertical
17797	29.26	8.63	44.23	39.60	42.52	54	-11.48	AV	Vertical
17788	42.99	8.63	44.23	39.60	56.25	74	-17.75	Pk	Horizontal
17788	27.79	8.63	44.23	39.60	41.05	54	-12.95	AV	Horizontal




5.6 Band edge - Conducted

5.6.1 Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.6.2 Test setup



5.6.3 Test procedure


- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.




5.6.4 Test results

Test plots:

802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side






802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side






802.11n20: Band Edge, Left Side




802.11n20: Band Edge, Right Side





802.11n40: Band Edge, Left Side



802.11n40: Band Edge, Right Side





5.7 6dB bandwidth

5.7.1 Limit

Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	>= 500kHz (6dB bandwidth)	2400-2483.5

5.7.2 Test setup



5.7.3 Test procedure


- a. Set RBW= 100 kHz.
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Sweep = auto couple.
- f. Allow the trace to stabilize.
- g. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.7.4 Test results




EUT:	IP Camera	Model Name:	792JBU
Pressure:	1012 hPa	Test Voltage:	DC 5V from adapter AC 120V/60Hz
Test Mode:	TX b Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	9.107	500	Pass
Middle	2437	10.06	500	Pass
High	2462	9.098	500	Pass






TX CH 06




TX CH 11






EUT:	IP Camera	Model Name:	792JBU
Pressure:	1012 hPa	Test Voltage:	DC 5V from adapter AC 120V/60Hz
Test Mode:	TX g Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	15.73	500	Pass
Middle	2437	15.12	500	Pass
High	2462	14.97	500	Pass










EUT:	IP Camera	Model Name:	792JBU
Pressure:	1012 hPa	Test Voltage:	DC 5V from adapter AC 120V/60Hz
Test Mode:	TX n20 Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	15.66	500	Pass
Middle	2437	13.57	500	Pass
High	2462	17.34	500	Pass









EUT:	IP Camera	Model Name:	792JBU
Pressure:	1012 hPa	Test Voltage:	DC 5V from adapter AC 120V/60Hz
Test Mode:	TX n40 Mode /CH03, CH06, CH09		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2422	34.23	500	Pass
Middle	2437	34.00	500	Pass
High	2452	35.22	500	Pass







5.8 Duty Cycle

5.8.1 Limit

No limit requirement.

5.8.2 Measuring instruments

The Measuring equipment is listed in the section 4 of this test report.

5.8.3 Test setup



5.8.4 Test procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW \geq OBW if possible; otherwise, set RBW to the largest available value. Set VBW \geq RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0(b) in KDB 558074

The largest available value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Zero Span

RBW = 8MHz (the largest available value)

VBW = 8MHz (\geq RBW)

Number of points in Sweep >100

Detector function = peak

Trace = Clear write

Measure T total and Ton

Calculate Duty Cycle = Ton / T total



5.8.5 Test Results

EUT:	IP Camera	Model Name:	792JBU
Pressure:	1012 hPa	Test Voltage:	DC 5V from adapter AC 120V/60Hz
Test Mode:	TX b/g/n(20/40) Mode / CH06		

Mode	Data rate	Channel	T _{on}	T _{total}	Duty Cycle	Duty Cycle Factor (dB)	VBW Setting
802.11b	1Mbps	6	-	-	100%	0	8MHz
802.11g	6Mbps	6	-	-	100%	0	8MHz
802.11n HT20	MCS0	6	-	-	100%	0	8MHz
802.11n HT40	MCS0	6	-	-	100%	0	8MHz



5.9 Spurious RF Conducted Emissions

5.9.1 Limit

Below -20dB of the highest emission level in operating band.

5.9.2 Measuring instruments

The Measuring equipment is listed in the section 4 of this test report.

5.9.3 Test setup



5.9.4 Test procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300kHz to measure the peak field strength, and measure frequency range from 9kHz to 26.5GHz.

5.9.5 Test results

Note:


- 1: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency; The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.
- 2: The three modulated high, medium and low channels have been tested. The report only shows the worst mode. The worst mode is 802.11b CH01/06/11.



802.11b on Channel 01



802.11b on Channel 01



802.11b on Channel 01




802.11b on Channel 06







802.11b on Channel 06




802.11b on Channel 06



802.11b on Channel 11



802.11b on Channel 11



802.11b on Channel 11





Photographs of the Test Setup

Radiated emission





Conducted emission





Photographs of the EUT

See the APPENDIX 1- EUT PHOTO.

----END OF REPORT----