

# MPE REPORT

FCC ID: ZCB-801RTB

Date of issue: Sept. 13, 2018

Report Number:	MTi180904E011
Sample Description:	Battery Camera
Model(s):	801RTB, 802RTB, 803RTB, 804RTB, B1, B2, B3, B4
Applicant:	Shenzhen Smart-eye Digital Electronics Co.,Ltd
Address:	#6 Northern Zone, Shangxue S&T City, Bantian, Longgang District, Shenzhen, China
Date of Test:	Aug. 18, 2018 to Sept. 13, 2018

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

<b>TEST RESULT CERTIFICATION</b>	
Applicant's name:	Shenzhen Smart-eye Digital Electronics Co.,Ltd
Address:	#6 Northern Zone, Shangxue S&T City, Bantian, Longgang District, Shenzhen, China.
Manufacture's name:	Shenzhen Smart-eye Digital Electronics Co.,Ltd
Address:	#6 Northern Zone, Shangxue S&T City, Bantian, Longgang District, Shenzhen, China.
Product name:	Battery Camera
Trademark:	N/A
Model name:	801RTB
Series model:	802RTB, 803RTB, 804RTB, B1, B2, B3, B4
Difference in series models:	The wireless module used in the product is the same, just different in appearance and color.
RF Exposure Procedures:	KDB 447498 D01 v06

*This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.*

Tested by:



Demi Mu

Sept. 13, 2018

Reviewed by:



Blue Zheng

Sept. 13, 2018

Approved by:



Smith Chen

Sept. 13, 2018

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

### MPE Calculation Method

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = Numeric gain of the antenna relative to isotropic antenna

$\pi$  = 3.14115926

$R$  = distance between observation point and center of the radiator in cm(20cm)

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

### WIFI:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: Wifi Antenna: Metal Antenna;

WIFI antenna gain: 3dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}= 10^{(3/10)}=2$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
		Ant A	Ant A	(dBm)	(mW)	Numeric		
2412	802.11b	14.83	14±1	15	31.62278	2	0.01258	1
2437		14.15	14±1	15	31.62278	2	0.01258	1
2462		14.44	14±1	15	31.62278	2	0.01258	1
2412	802.11g	13.25	13±1	14	25.11886	2	0.00999	1
2437		13.21	13±1	14	25.11886	2	0.00999	1
2462		13.3	13±1	14	25.11886	2	0.00999	1
2412	802.11n H20	12.74	12±1	13	19.95262	2	0.00794	1
2437		12.27	12±1	13	19.95262	2	0.00794	1
2462		12.28	12±1	13	19.95262	2	0.00794	1

### Conclusion:

For the max result:  $0.01258 \leq 1.0$

----END OF REPORT----