

## RF EXPOSURE TEST

**FCC ID: ZCB620GB**

**Applied procedures / limit**

These devices are not exempted from compliance does not exceed the Commission's RF exposure guidelines. Unless a device operates at substantially low power levels, with a low gain antenna(s), supporting information is generally needed to establish the various potential operating configurations and exposure conditions of a transmitter and its antenna(s) in order to determine compliance with the RF exposure guidelines.

In order to demonstrate compliance with MPE requirement(see Section 2.1091),the following information is typically needed:

Calculation that estimates the minimum separation distance (20 cm or more) between an antenna and persons required to satisfy power density limits defined for free space.

Antenna installation and device operating instructions for installers(professional/unskilled users),and the parties responsible for ensuring compliance with the RF exposure requirement

Any caution statements and/or warning labels that are necessary in order to comply with the exposure limits Any other RF exposure related issues that may affect MPE compliance.

FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency(RF) radiation as specified in 1.1307(b).

**(A) Limits for Occupational / Controlled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

**(B) Limits for General Population / Uncontrolled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

## MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

P :power input to the antenna in Mw

EIRP :Equivalent(effective) isotropic radiated power.

S :power density mW/ cm<sup>2</sup>

G ;numeric gain of antenna relative to isotropic radiator

R :distance to centre of radiation in cm

FCC radio frequency exposure limits may be exceeded at distances closer than r cm from the antenna of this device

$$r = \sqrt{\frac{PG}{4\pi S}} = \sqrt{\frac{EIRP}{4\pi S}}$$

EIRP=10<sup>(Antenna Gain+Peak Output Power/10)</sup>

Note:

1. s=1.0 mW /cm<sup>2</sup> for limits for General Population/Uncontrolled Exposures.
2. The time averaged power over 30 minutes will be equaled Output Power.
3. The Power Density at a distance of 20cm calculated from the formula is far below the limit of 1MW/ cm<sup>2</sup>

## TEST RESULTS

Channel	Maximum Peak Conducted Output Power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Distance (cm)	Power Density (mW/ cm <sup>2</sup> )	Limit of Power Density (mW/ cm <sup>2</sup> )	Result
802.11b							
2412MHz	14.92	31.046	3dBi (1.995)	20	0.012	1	Pass
2437MHz	14.83	30.409	3dBi (1.995)	20	0.012	1	Pass
2462MHz	14.75	29.854	3dBi (1.995)	20	0.012	1	Pass
802.11g							
2412MHz	13.94	24.774	3dBi (1.995)	20	0.01	1	Pass
2437MHz	13.73	23.605	3dBi (1.995)	20	0.009	1	Pass
2462MHz	13.13	20.559	3dBi (1.995)	20	0.008	1	Pass
802.11n20							
2412MHz	12.16	16.444	3dBi (1.995)	20	0.007	1	Pass
2437MHz	12.33	17.1	3dBi (1.995)	20	0.007	1	Pass
2462MHz	12.49	17.742	3dBi (1.995)	20	0.007	1	Pass
802.11n40							
2422MHz	11.07	12.794	3dBi (1.995)	20	0.005	1	Pass
2437MHz	11.13	12.972	3dBi (1.995)	20	0.005	1	Pass
2452MHz	11.16	13.062	3dBi (1.995)	20	0.005	1	Pass