



**SGS-CSTC Standards Technical Services
(Shanghai) Co., Ltd.**

588 West Jindu Road, Songjiang District, Shanghai, China
Telephone: +86 (0) 21 6191 5666
Fax: +86 (0) 21 6191 5678
ee.shanghai@sgs.com

Report No.: SHEM150700238301
Page: 1 of 16

1 Cover Page

TEST REPORT

| | |
|---|------------------------------------|
| Application No.: | SHEM1507002383CR |
| Applicant: | FEITIAN Technologies Co., Ltd. |
| FCC ID: | ZD3FTEPASS |
| Equipment Under Test (EUT): NOTE: The following sample(s) was/were submitted and identified by the client as | |
| Product Name: | USB Token |
| Model No.(EUT): | ePass |
| Standards: | CFR 47 FCC Part 15 subpart B, 2014 |
| Date of Receipt: | July 21, 2015 |
| Date of Test: | August 04, 2015 |
| Date of Issue: | August 12, 2015 |
| Test Result: | Pass* |

* In the configuration tested, the EUT (Equipment under test) complied with the standards specified above.



Parlam Zhan
E&E Section Manager
SGS-CSTC (Shanghai) Co., Ltd.




The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

| Revision Record | | | | |
|-----------------|---------|-----------------|----------|----------|
| Version | Chapter | Date | Modifier | Remark |
| 00 | / | August 12, 2015 | / | Original |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

| | | | |
|---------------------------------|--|---|---|
| Authorized for issue by: | | | |
| Engineer | | Eddy Zong _____ Print Name |  |
| Clerk | | Susie Liu _____ Print Name |  |
| Reviewer | | Keny Xu _____ Print Name |  |

3 Test Summary

| Test | FCC Requirement | Test Method | Result |
|---|------------------------------|------------------|--------|
| Conducted Emission (150kHz to 30MHz) | CFR 47 FCC Part 15 subpart B | ANSI C63.4: 2014 | PASS |
| Radiated Emission, (30MHz to 1GHz) | CFR 47 FCC Part 15 subpart B | ANSI C63.4: 2014 | PASS |
| Radiated Emission above 1 GHz | CFR 47 FCC Part 15 subpart B | ANSI C63.4: 2014 | N/A* |

Remark:

N/A: Not Applicable.

* If the highest frequency of the internal sources of the EUT is less than 108MHz, the measurement shall only be made up to 1GHz.

4 Contents

| | Page |
|---|-----------|
| 1 COVER PAGE | 1 |
| 2 VERSION..... | 2 |
| 3 TEST SUMMARY | 3 |
| 4 CONTENTS..... | 4 |
| 5 GENERAL INFORMATION..... | 5 |
| 5.1 Client Information..... | 5 |
| 5.2 General Description of E.U.T. | 5 |
| 5.3 E.U.T Operation Environment | 5 |
| 5.4 Description of Support Units | 5 |
| 5.5 Test Mode | 6 |
| 5.6 Deviation from Standards | 6 |
| 5.7 Abnormalities from Standard Conditions | 6 |
| 5.8 Modification/Retest Record..... | 6 |
| 5.9 Test Location..... | 6 |
| 5.10 Test Facility..... | 6 |
| 6 EQUIPMENT LIST | 7 |
| 7 ELECTROMAGNETIC INTERFERENCE TEST RESULTS | 8 |
| 7.1 Conducted Emissions on Mains Terminals, 150 kHz to 30 MHz | 8 |
| 7.2 Radiated Emissions, 30MHz to 1GHz | 12 |
| 8 TEST SETUP PHOTOGRAPHS | 16 |
| 9 EUT CONSTRUCTIONAL DETAILS | 16 |

5 General Information

5.1 Client Information

| | |
|--------------------------|---|
| Applicant: | FEITIAN Technologies Co., Ltd. |
| Address of Applicant: | Floor 17th, Tower B, Huizhi Mansion, No.9 Xueqing Road Haidian District, Beijing, P.R.China |
| Manufacturer: | FEITIAN Technologies Co., Ltd. |
| Address of Manufacturer: | Floor 17th, Tower B, Huizhi Mansion, No.9 Xueqing Road Haidian District, Beijing, P.R.China |
| Factory: | FEITIAN Technologies Co., Ltd. |
| Address of Factory: | Floor 17th, Tower B, Huizhi Mansion, No.9 Xueqing Road Haidian District, Beijing, P.R.China |

5.2 General Description of E.U.T.

| | |
|----------------------|--|
| Product Description: | Connect product to PC and using management tool encrypted file |
| Operating Frequency: | 50 MHz (the Highing working frequency) |
| Power Supply: | DC 5V via USB interface |
| Test Voltage: | AC 120V 60Hz |

5.3 E.U.T Operation Environment

| | |
|-----------------------------|------------|
| Temperature Range: | 20-25°C |
| Humidity Range: | 30-60% RH |
| Atmospheric Pressure Range: | 100-102kPa |

5.4 Description of Support Units

The EUT has been tested with associated equipment below.

| Description | Manufacturer | Model No. | Supplied by |
|-------------|--------------|----------------|-------------|
| PC | Lenovo | ThinkPad X100e | SGS |
| Mouse | Lenovo | MO28UOL | SGS |

Note: For the cable details please refer to below table.

| CableType | Length, m | Shield | Metallic hood | Ferrite |
|-----------|-----------|--------|---------------|---------|
| USB Cable | 1.5 | Yes | No | No |
| AC Cable | 1.0 | Yes | No | No |
| DC Cable | 1.8 | Yes | No | No |

| Description | Manufacturer | Software name | Version no. |
|-------------|--------------|---------------|-------------|
| Encrypted | Feitian | ePass2003 | 1.0.0.1 |

5.5 Test Mode

| Test Mode | Description of Test Mode |
|----------------|--|
| Encrypted mode | Connect product to PC and using management tool encrypted file |

5.6 Deviation from Standards

None.

5.7 Abnormalities from Standard Conditions

None.

5.8 Modification/Retest Record

None.

5.9 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab

No.588 West Jindu Road, Songjiang District, Shanghai, China. 201612.

Tel: +86 21 6191 5666

Fax: +86 21 6191 5678

No tests were sub-contracted.

5.10 Test Facility

- **CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing. Date of expiry: 2017-07-14.

- **FCC – Registration No.: 402683**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered and fully described in a report filed with the Federal Communications Commission (FCC). The acceptance letter from the FCC is maintained in our files. Registration No.: 402683, Expiry Date: 2017-09-16.

- **Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1. Expiry Date: 2017-06-18.

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868, C-4336, T-2221, G-830 respectively. Date of Expiry: 2017-11-16.

6 Equipment list

| Item | Test Equipment | Manufacturer | Model No. | Serial No. | Cal. Date | Cal. Due date |
|---------------------------|--|-----------------------------|-----------|--|------------|---------------|
| Conducted Emission | | | | | | |
| 1 | EMI test receiver | Rohde & Schwarz | ESCS30 | TDGC2 | 2015-01-22 | 2016-01-21 |
| 2 | Line impedance stabilization network | SCHWARZBECK | NSLK8127 | 8127490 | 2015-01-22 | 2016-01-21 |
| 3 | Line impedance stabilization network | EMCO | 3816/2 | 00034161 | 2015-01-22 | 2016-01-21 |
| Radiated Emission | | | | | | |
| 1 | EMI test receiver | Rohde & Schwarz | ESU40 | 100109 | 2015-02-13 | 2016-02-12 |
| 2 | Loop Antenna (9KHz – 30MHz) | SCHWARZBECK | FMZB1519 | 1519-034 | 2015-02-07 | 2016-02-06 |
| 3 | Broadband UHF-VHF ANTENNA (30MHz – 1GHz) | SCHWARZBECK | VULB9168 | 9168-313 | 2015-02-07 | 2016-02-06 |
| 4 | Horn Antenna (1GHz to 18GHz) | SCHWARZBECK | BBHA9120D | 9120D-679 | 2015-02-07 | 2016-02-06 |
| 5 | Low noise Pre-amplifier (9KHz – 1GHz) | LNA6900 | TESEQ | 71033 | 2014-12-27 | 2015-12-27 |
| General Equipment | | | | | | |
| 1 | Digital pressure meter | YONGZHI | DYM3-01 | 101012 | 2015-04-13 | 2016-04-12 |
| 2 | Temperature & humidity recorder | ShangHai weather meter work | ZJ 1-2B | 0804081 0802150 0805126 0805177 | 2014-08-19 | 2015-08-18 |
| 3 | Digital Multimeter | FLUKE | 17B | 19720439 | 2015-01-22 | 2016-01-21 |

7 Electromagnetic Interference Test Results

7.1 Conducted Emissions on Mains Terminals, 150 kHz to 30 MHz

Class / Severity: Class B

Detector: Peak for pre-scan (9 kHz Resolution Bandwidth from 150 kHz to 30 MHz)

Limit:

| Frequency range (MHz) | LimitdB (μV) | |
|--------------------------|--------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

Note1: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50MHz.

Note2: The lower limit is applicable at the transition frequency.


7.1.1 E.U.T. Operation

Test mode: Encrypted mode

Pre-scan was performed with peak detected on all ports, Quasi-peak & average measurements were performed at the frequencies at which maximum peak emission level were detected.

Please see the attached Quasi-peak and Average test results.


7.1.2 Test Setup and Procedure



1. The mains terminal disturbance voltage was measured with the EUT in a shielded room.
2. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN, which was bonded to the ground reference plane in the same way as the LISN for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded
3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
4. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance was between the closest points of the LISN and the EUT. The mains lead of EUT excess 0.8m was folded back and forth parallel to the lead so as to form a horizontal bundle with a length between 0.3m and 0.4m. All other units of the EUT and associated equipment was at least 0,8 m from the LISN.


7.1.3 Measurement Data

Live Line:



| Item | Freq. | Read Level | LISN Factor | Cable Loss | Level | Limit Line | Over Limit | Detector |
|--------|--------|--------------|-------------|------------|--------------|--------------|------------|----------|
| (Mark) | (MHz) | (dB μ V) | (dB) | (dB) | (dB μ V) | (dB μ V) | (dB) | |
| 1 | 0.155 | 28.47 | 0.32 | 9.86 | 38.65 | 55.74 | -17.09 | Average |
| 2 | 0.155 | 47.32 | 0.32 | 9.86 | 57.50 | 65.74 | -8.24 | QP |
| 3 | 0.190 | 25.51 | 0.27 | 9.86 | 35.64 | 54.02 | -18.38 | Average |
| 4 | 0.190 | 38.21 | 0.27 | 9.86 | 48.34 | 64.02 | -15.68 | QP |
| 5 | 0.371 | 12.47 | 0.25 | 9.86 | 22.58 | 48.47 | -25.89 | Average |
| 6 | 0.371 | 25.06 | 0.25 | 9.86 | 35.17 | 58.47 | -23.30 | QP |
| 7 | 0.494 | 20.54 | 0.25 | 9.86 | 30.65 | 46.10 | -15.45 | Average |
| 8 | 0.494 | 29.42 | 0.25 | 9.86 | 39.53 | 56.10 | -16.57 | QP |
| 9 | 0.694 | 9.01 | 0.22 | 9.86 | 19.09 | 46.00 | -26.91 | Average |
| 10 | 0.694 | 21.26 | 0.22 | 9.86 | 31.34 | 56.00 | -24.66 | QP |
| 11 | 16.750 | 9.50 | 0.36 | 9.93 | 19.79 | 50.00 | -30.21 | Average |
| 12 | 16.750 | 18.62 | 0.36 | 9.93 | 28.91 | 60.00 | -31.09 | QP |

Neutral Line:



| Item | Freq. | Read Level | LISN Factor | Cable Loss | Level | Limit Line | Over Limit | Detector |
|--------|--------|--------------|-------------|------------|--------------|--------------|------------|----------|
| (Mark) | (MHz) | (dB μ V) | (dB) | (dB) | (dB μ V) | (dB μ V) | (dB) | |
| 1 | 0.153 | 30.01 | 0.34 | 9.86 | 40.21 | 55.82 | -15.61 | Average |
| 2 | 0.153 | 48.04 | 0.34 | 9.86 | 58.24 | 65.82 | -7.58 | QP |
| 3 | 0.200 | 26.36 | 0.29 | 9.86 | 36.51 | 53.62 | -17.11 | Average |
| 4 | 0.200 | 37.42 | 0.29 | 9.86 | 47.57 | 63.62 | -16.05 | QP |
| 5 | 0.247 | 19.92 | 0.29 | 9.86 | 30.07 | 51.86 | -21.79 | Average |
| 6 | 0.247 | 32.02 | 0.29 | 9.86 | 42.17 | 61.86 | -19.69 | QP |
| 7 | 0.417 | 14.79 | 0.30 | 9.86 | 24.95 | 47.51 | -22.56 | Average |
| 8 | 0.417 | 25.42 | 0.30 | 9.86 | 35.58 | 57.51 | -21.93 | QP |
| 9 | 0.502 | 21.22 | 0.30 | 9.86 | 31.38 | 46.00 | -14.62 | Average |
| 10 | 0.502 | 29.00 | 0.30 | 9.86 | 39.16 | 56.00 | -16.84 | QP |
| 11 | 16.839 | 10.65 | 0.41 | 9.94 | 21.00 | 50.00 | -29.00 | Average |
| 12 | 16.839 | 21.04 | 0.41 | 9.94 | 31.39 | 60.00 | -28.61 | QP |

Level = Read Level + LISN/ISN Factor + Cable Loss.

7.2 Radiated Emissions, 30MHz to 1GHz

Measurement Distance: 3m
 Class: Class B
 Detector: Peak for pre-scan (120 kHz resolution bandwidth)
 Limit:

| Frequency range MHz | Quasi-peak limits dB (μV/m) |
|--|--------------------------------|
| 30 to 88 | 40 |
| 88 to 216 | 43.5 |
| 216 to 960 | 46 |
| Above 960 | 54 |
| Note: At transitional frequencies the lower limit applies. Test distance is 3m | |


7.2.1 E.U.T. Operation

Test mode: Encrypted mode

Pre-scan was performed with peak detected on all ports, Quasi-peak measurements was performed at the frequencies at which maximum peak emission level were detected.

Please see the attached Quasi-peak test results.


7.2.2 Test Setup and Procedure



1. The radiated emissions test was conducted in a semi-anechoic chamber.
2. The EUT was connected to AC power source through a mains power outlet which was bonded to the ground reference plane; the mains cables shall drape to the ground reference plane.
3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
4. Before final measurements of radiated emissions, a pre-scan was performed in the spectrum mode with the peak detector to find out the maximum emission spectrum signature data plots of the EUT.
5. The frequencies of maximum emission were determined in the final radiated emissions measurement, the physical arrangement of the test system and associated cabling was varied in order to determine the effect on the EUT's emissions in amplitude, direction and frequency. At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the maximum disturbance. Measurements were performed for both horizontal and vertical antenna polarization.


7.2.3 Measurement Data

Vertical:



| Item | Freq. | Read Level | Antenna Factor | Preamp Factor | Cable Loss | Result Level | Limit Line | Over Limit | Detector |
|--------|--------|--------------|----------------|---------------|------------|----------------|----------------|------------|----------|
| (Mark) | (MHz) | (dB μ V) | (dB/m) | (dB) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) | |
| 1 | 30.21 | 42.50 | 12.51 | 23.72 | 0.55 | 31.84 | 40.00 | -8.16 | QP |
| 2 | 32.29 | 42.77 | 12.55 | 23.71 | 0.14 | 31.75 | 40.00 | -8.25 | QP |
| 3 | 36.24 | 39.39 | 12.73 | 23.71 | 0.20 | 28.61 | 40.00 | -11.39 | QP |
| 4 | 85.42 | 39.40 | 8.58 | 23.67 | 0.77 | 25.08 | 40.00 | -14.92 | QP |
| 5 | 187.07 | 41.24 | 11.62 | 23.62 | 1.36 | 30.60 | 43.50 | -12.90 | QP |
| 6 | 625.67 | 33.79 | 19.40 | 23.83 | 2.79 | 32.15 | 46.00 | -13.85 | QP |

Horizontal:



| Item (Mark) | Freq. (MHz) | Read Level (dBμV) | Antenna Factor (dB/m) | Preamp Factor (dB) | Cable Loss (dB) | Result Level (dBμV/m) | Limit Line (dBUV/m) | Over Limit (dB) | Detector |
|----------------|----------------|-------------------------|-----------------------------|--------------------------|-----------------------|-----------------------------|---------------------------|-----------------------|----------|
| 1 | 190.97 | 39.88 | 11.22 | 23.62 | 1.37 | 28.85 | 43.50 | -14.65 | QP |
| 2 | 335.89 | 35.74 | 13.14 | 23.68 | 1.94 | 27.14 | 46.00 | -18.86 | QP |
| 3 | 433.21 | 32.34 | 15.52 | 23.71 | 2.28 | 26.43 | 46.00 | -19.57 | QP |
| 4 | 720.62 | 28.37 | 20.74 | 23.88 | 3.01 | 28.24 | 46.00 | -17.76 | QP |
| 5 | 816.96 | 24.59 | 21.87 | 23.93 | 3.24 | 25.77 | 46.00 | -20.23 | QP |
| 6 | 913.36 | 24.32 | 22.80 | 23.94 | 3.45 | 26.63 | 46.00 | -19.37 | QP |

For radiated emission: Level = Read Level + Antenna Factor + Cable Loss – Preamp Factor.

8 Test Setup Photographs

Refer to the < ePass_Test Setup Photos-FCC >

9 EUT Constructional Details

Refer to the < ePass_External Photos > & < ePass_Internal Photos >.

--End of the Report--